



## RF Exposure Report

**Report No.:** SA151022E06A

**FCC ID:** 2AD8UFZCWM2A1

**Test Model:** WM2A-AC210m

**Received Date:** Oct. 22, 2015

**Test Date:** Dec. 02 to 16, 2015

**Issued Date:** Apr. 14, 2016

**Applicant:** Nokia Solutions and Networks.OY

**Address:** Karaportti 3, P.O. Box 226, Nokia Group, Finland.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (1):** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
<b>3 Antenna Gain</b> .....	<b>6</b>
<b>4 Calculation Result</b> .....	<b>7</b>
<b>5 Brief Summary of results</b> .....	<b>8</b>



A D T

### Release Control Record

Issue No.	Description	Date Issued
SA151022E06A	Original release.	Apr. 14, 2016



A D T

## 1 Certificate of Conformity

**Product:** Wi-Fi AP Module 802.11 ac

**Brand:** Nokia

**Test Model:** WM2A-AC210m

**Hardware Version:** AM2

**Sample Status:** MASS-PRODUCTION


**Applicant:** Nokia Solutions and Networks.OY

**Test Date:** Dec. 02 to 16, 2015

**Standards:** FCC Part 2 (Section 2.1091)  
KDB 447498 D01 GENERAL RF EXPOSURE GUIDANCE V06  
IEEE STD C95.1-2005  
FCC 47 CFR § 1.13.10

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Apr. 14, 2016  
Claire kuan / Specialist

**Approved by :**  , **Date:** Apr. 14, 2016  
May Chen / Manager

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **fixed device**.

### 3 Antenna Gain

#### WLAN – 5GHz Antenna spec.

Antenna No	PCB Chain No.	Brand	Model	Antenna Type	Gain(dBi)	Frequency (GHz to GHz)
1	U20	Galtronics	02102140-06084A4	PIFA	6.03	5.15~5.25
					6.17	5.25~5.35
					5.57	5.47~5.725
					5.18	5.725~5.85
2	U21	Galtronics	02102140-06084A1	PIFA	5.1	5.15~5.25
					4.91	5.25~5.35
					5.23	5.47~5.725
					5.73	5.725~5.85

#### Cable Spec.

Antenna No	Brand	Model	Connector Type	Cable Loss(dB)	Cable Length (cm)
1	Galtronics	LL100	MMCX	0	30.6
2	Galtronics	LL100	MMCX	0	9.1

#### 4 Calculation Result

For 2.4GHz and 5GHz (U-NII-1 band and U-NII-3 band) data was copied from the original test report (Report No.: SA151022E06)

##### For 1TX Chain 0 Mode:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	89.536	5.17	20	0.05858	1
5180-5240	182.81	6.03	20	0.14579	1
5250~5350	182.81	6.17	20	0.15057	1
5470~5725	182.39	5.57	20	0.13084	1
5745-5825	163.682	5.18	20	0.10733	1

##### For 1TX Chain 1 Mode:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	89.125	4.27	20	0.04739	1
5180-5240	196.789	5.10	20	0.12669	1
5250~5350	193.642	4.91	20	0.11932	1
5470~5725	191.867	5.23	20	0.12727	1
5745-5825	163.305	5.73	20	0.12154	1

##### For 2TX Mode:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	199.467	7.74	20	0.23583	1
5180-5240	368.481	8.59	20	0.52984	1
5250~5350	223.973	8.57	20	0.32057	1
5470~5725	242.038	8.41	20	0.33390	1
5745-5825	384.025	8.47	20	0.53714	1

**NOTE:**

2412-2462MHz : Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.74\text{dBi}$

5180-5240MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.59\text{dBi}$

5250-5350MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.57\text{dBi}$

5470-5725MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.41\text{dBi}$

5745-5825MHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.47\text{dBi}$

**Conclusion:**

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is  $0.23583 / 1 + 0.53714 / 1 = 0.773$ , which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

**5 Brief Summary of results**

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(m)	
	Occupational	General Population
2.4GHz WiFi + 5GHz WiFi	0.2	0.2

--- END ---