



RF Exposure Report

Report No.: SA150326E02C

FCC ID: 2AD8UFZPFWID01

Test Model: FWID

Received Date: Mar. 26, 2015

Test Date: Apr. 01 to 17, 2015

Issued Date: July 27, 2015

Applicant: Nokia Solutions and Networks

Address: 1455 West Shure Drive, Arlington Heights, IL 60004, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	6
4 Calculation Result (For FCC)	7
5 Calculation Result (For Canada)	8
6 Calculation Result (For Europe)	9
7 Brief Summary of results	9



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150326E02C	Original release.	July 27, 2015

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as fixed station and installations by professional service personnel device.

3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

LTE Antenna Spec.							
Antenna No	Brand	Model	Antenna Type	Antenna Connector	Gain(dBi) <Including cable loss>	Cable Length (mm)	Frequency (MHz)
Internal LTE (Main)	TongDa	T-543-8141050-6	PIFA	i-pex(MHF)	4.9	50	1710~2390 (Band 4)
Internal LTE (Aux)		T-543-8141050-7			4.6	190	1710~2390 (Band 4)
GPS Antenna Spec.							
Antenna No	Brand	Model	Antenna Type	Antenna Connector	Gain(dBi) <Including cable loss>	Cable Length (mm)	Frequency (MHz)
External GPS Ant	TongDa	T-543-8141037-9	ElecPatch	SMA Male	4.0	9140 ± 100	GPS : 1575.42 ± 3 MHz Glonass : 1602 ± 8 MHz
BT Antenna Spec.							
Antenna No	Brand	Model	Antenna Type	Antenna Connector	Gain(dBi) <Including cable loss>	Cable Length (mm)	Frequency (MHz)
Internal BT Ant	INPAQ	Fz PICO	Chip	NA	-1.22	NA	2400~2500

4 Calculation Result (For FCC)

Calculation for Maximum Conducted Power

For BT

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	8.730	-1.22	20	0.00131	1

For LTE

Frequency Band (MHz)	EIRP Power (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2112.5-2152.5	1183.9	20	0.236	1

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$BT + LTE = 0.00131 + 0.236 = 0.237$$

Therefore the maximum calculations of above situations are less than the "1" limit.

5 Calculation Result (For Canada)

Calculation for Maximum Conducted Power

For BT

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (W/m ²)	Limit (W/m ²)
2402-2480	8.730	-1.22	0.2	0.0131	5.4100

For LTE

Frequency Band (MHz)	EIRP Power (mW)	Distance (cm)	Power Density (W/m ²)	Limit (W/m ²)
2112.5-2152.5	1055.2	0.2	2.10	4.9565

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 10$

CPD = Calculation power density

LPD = Limit of power density

$BT + LTE = 0.0131/5.4100 + 2.10/4.9325 = 0.426$

Therefore the maximum calculations of above situations are less than the "1" limit.

6 Calculation Result (For Europe)

Calculation for maximum EIRP

BT

Output Power EIRP (dBm)	Output Power EIRP (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	Pass / Fail
8.82	7.621	2.391	61	Pass

LTE

Output Power EIRP (dBm)	Output Power EIRP (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	Pass / Fail
32.94	1967.886	38.418	61	Pass

Conclusion:

Both of the BT and LTE can transmit simultaneously, the formula of calculated the exposure is:

$$(CEF1 / LEF1)^2 + (CEF2 / LEF2)^2 + \dots \text{etc.} < 1$$

CEF = Calculation E-Field Strength

LEF = Limit of E-Field Strength

Therefore, the calculation of this situation is $(2.391 / 61)^2 + (38.418 / 61)^2 = 0.39817$, which is less than the "1" limit.

7 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(m)	
	Occupational	General Population
LTE FDD Band 4+ Bluetooth	0.2	0.2

--- END ---