

## RF Exposure Evaluation

### FCC Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW;

$G$  = gain of antenna in linear scale,  $\pi = 3.1416$ ;

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

FCC ID: 2AD9I-DL980QT  
IC: 24046-DL980QT

### Test Result of RF Exposure Evaluation

#### WCDMA Band II

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest (1852.4MHz)	230.144	0.05505	1.0	PASS
Middle (1880.0MHz)	249.459	0.05967	1.0	PASS
Highest (1907.6MHz)	233.346	0.05581	1.0	PASS

Remark: antenna gain=0.8 dBi, Tune-up tolerance: 23±1

#### WCDMA Band IV

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest (1712.4MHz)	169.434	0.03960	1.0	PASS
Middle (1732.4MHz)	187.932	0.04393	1.0	PASS
Highest (1752.6MHz)	189.671	0.04433	1.0	PASS

Remark: antenna gain=0.7 dBi, Tune-up tolerance: 22±1

#### WCDMA Band V

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest (826.4MHz)	246.037	0.04071	0.551	PASS
Middle (836.6MHz)	239.332	0.03960	0.558	PASS
Highest (846.6MHz)	241.546	0.03997	0.564	PASS

Remark: antenna gain=-0.8 dBi, Tune-up tolerance: 23±1

#### LTE mode

Band	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
LTE Band 2	1852.5	23.99	250.611	0.05994	1.0	PASS
LTE Band 4	1732.5	23.96	248.886	0.05817	1.0	PASS
LTE Band 12	714.5	24	251.189	0.04253	0.476	PASS

Remark: antenna gain: Band 2: 0.8dBi, Band 4: 0.7dBi, Band 12: -0.7dBi.

Tune-up tolerance: 23±1

---

FCC ID: 2AD9I-DL980QT  
IC: 24046-DL980QT

#### WiFi 2.4Gmode

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Lowest (2412MHz)	27.54	0.00613	1.0	PASS
Middle (2437MHz)	26.42	0.00590	1.0	PASS
Highest (2462MHz)	27.48	0.00613	1.0	PASS

Remark: antenna gain=0.5dBi

#### For BLE

According to 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances > 50 mm are determined by:

{[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)·10]} mW,  
for > 1500 MHz and ≤ 6 GHz

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{Exd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m) ---3m

$$\text{So pt} = (\text{Exd})^2/30 \times \text{gt}$$

Field strength =94.93 dBuV/m @3m

Ant gain =0.5dBi, so Ant numeric gain= 1.122

So pt={  $[10^{94.93/20}]/10^6 \times 3]^2/30 \times 1.122 \times 1000$  mW =0.832mW<96mW (illustrated in Appendix B)

## IC Limits

Transmitters are exempt from routine SAR and RF exposure evaluations provided that they comply with the requirements of sections 2.5.1 or 2.5.2.

### 2.5.1

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of <b>≤5 mm</b>	At separation distance of <b>10 mm</b>	At separation distance of <b>15 mm</b>	At separation distance of <b>20 mm</b>	At separation distance of <b>25 mm</b>
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of <b>30 mm</b>	At separation distance of <b>35 mm</b>	At separation distance of <b>40 mm</b>	At separation distance of <b>45 mm</b>	At separation distance of <b>≥50 mm</b>
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

### 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

FCC ID: 2AD9I-DL980QT  
IC: 24046-DL980QT

### Test Result of RF Exposure Evaluation

According to RSS-102 RF exposure section 2.5.2 is calculated.

The minimum separation distance is 20cm declared by manufacturer

#### WCDMA Band II

Channel	Output power to antenna (adjusted for tune-up tolerance mW)	Limit (mW)	Result
Lowest (1852.4MHz)	251.189	2240.99	PASS
Middle (1880.0MHz)	251.189	2263.76	PASS
Highest (1907.6MHz)	251.189	2286.42	PASS

Remark: antenna gain=0.8 dBi, Tune-up tolerance:  $23 \pm 1$

#### WCDMA Band IV

Channel	Output power to antenna (adjusted for tune-up tolerance mW)	Limit (mW)	Result
Lowest (1712.4MHz)	199.526	2123.82	PASS
Middle (1732.4MHz)	199.526	2140.74	PASS
Highest (1752.6MHz)	199.526	2157.76	PASS

Remark: antenna gain=0.7 dBi, Tune-up tolerance:  $22 \pm 1$

#### WCDMA Band V

Channel	Output power to antenna (adjusted for tune-up tolerance mW)	Limit (mW)	Result
Lowest (826.4MHz)	251.189	1290.86	PASS
Middle (836.6MHz)	251.189	1301.73	PASS
Highest (846.6MHz)	251.189	1312.34	PASS

Remark: antenna gain=-0.8 dBi, Tune-up tolerance:  $23 \pm 1$

#### LTE mode

Band	Frequency(MHz)	Output power to antenna (adjusted for tune-up tolerance mW)	Limit (mW)	Result
LTE Band 2	1852.5	251.189	2241.08	PASS
LTE Band 4	1732.5	251.189	2140.82	PASS
LTE Band 12	714.5	251.189	1168.68	PASS

Remark: antenna gain: Band 2: 0.8dBi, Band 4: 0.7dBi, Band 12: -0.7dBi.

Tune-up tolerance:  $23 \pm 1$

---

FCC ID: 2AD9I-DL980QT  
IC: 24046-DL980QT

**WIFI mode:**

Channel	Output power to antenna (adjusted for tune-up tolerance mW)	Limit mW	Result
Lowest (2412MHz)	30.90	2684.03	PASS
Middle (2437MHz)	29.65	2703.01	PASS
Highest (2462MHz)	30.83	2721.93	PASS

**BLE mode:**

Channel(MHz)	Output power to antenna (adjusted for tune-up tolerance mW)	Limit mW	Result
2480.00	1.332	2735.52	PASS

Remark:

Field strength =94.93 dBuV/m @3m

Ant gain =0.5dBi, so Ant numeric gain= 1.122

So  $pt = \{ [10^{94.93/20}] / 10^6 \times 3 \}^2 / 30 \times 1.122 \} \times 1000 \text{ mW} = 0.832 \text{ mW}$

WIFI & BLE couldn't transmit simultaneously

WIFI & 3G/4G couldn't transmit simultaneously

BT & 3G/4G couldn't transmit simultaneously

The max power density is less than SAR exempt limit, so SAR evaluation is not required.