



# RADIO TEST REPORT

Report No: STS1806172W04

Issued for

Prentke Romich Company

1022 Heyl Rd. wooster, Ohio 44691, United States

<b>Product Name:</b>	Accent 800
<b>Brand Name:</b>	Accent
<b>Model Name:</b>	ACN800-30
<b>Series Model:</b>	N/A
<b>FCC ID:</b>	2AD9PA-A80030PRC
<b>IC ID:</b>	23408-ACN80030
<b>Test Standard:</b>	FCC Part 15.407
	RSS-247 Issue 2, February 2017

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





### TEST RESULT CERTIFICATION

**Applicant's name** ..... : Prentke Romich Company  
 Address ..... : 1022 Heyl Rd. wooster, Ohio 44691, United States  
**Manufacture's Name**..... : Prentke Romich Company  
 Address ..... : 1022 Heyl Rd. wooster, Ohio 44691, United States

**Product description**

Product Name..... : Accent 800  
 Brand Name ..... : Accent  
 Model Name ..... : ACN800-30  
 Series Model..... : N/A

**Test Standards** ..... : FCC Part15.407  
 RSS-247 Issue 2, February 2017

Test procedure ..... ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC&IC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

**Date of Test** ..... :  
 Date (s) of performance of tests ..... : 28 June 2018 ~10 July 2018  
 Date of Issue..... : 13 July 2018  
 Test Result..... : **Pass**

Testing Engineer : *Chris chen*  
 \_\_\_\_\_  
 ( Chris chen )

Technical Manager : *Sean she*  
 \_\_\_\_\_  
 ( Sean she )

Authorized Signatory : *Vita Li*  
 \_\_\_\_\_  
 (Vita Li)





Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
<b>2 . GENERAL INFORMATION</b>	<b>7</b>
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
<b>3 . EMC EMISSION TEST</b>	<b>15</b>
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION AND ( BANDEGE) MEASUREMENT	19
3.2.6 FIELD STRENGTH CALCULATION	22
<b>4. CONDUCTED SPURIOUS EMISSIONS AND BANDEGE</b>	<b>43</b>
4.1 APPLIED PROCEDURES / LIMIT	43
<b>5. POWER SPECTRAL DENSITY TEST</b>	<b>45</b>
5.1 APPLIED PROCEDURES / LIMIT	45
<b>6. BANDWIDTH MEASUREMENT</b>	<b>47</b>
6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	47
6.2 OCCUPIED BANDWIDTH ( 99%) TEST APPLIED PROCEDURES / LIMIT	48
6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	49
<b>7. MAXIMUM CONDUCTED OUTPUT POWER</b>	<b>50</b>
7.1 APPLIED PROCEDURES / LIMIT	50
<b>8. AUTOMATICALLY DISCONTINUE TRANSMISSION</b>	<b>60</b>
8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	60
8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	60
<b>9. ANTENNA REQUIREMENT</b>	<b>61</b>
9.1 STANDARD REQUIREMENT	61
9.2 EUT ANTENNA	61
<b>APPENDIX - PHOTOS OF TEST SETUP</b>	<b>62</b>



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 July 2018	STS1806172W04	ALL	Initial Issue





## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

<b>FCC Part 15.407 RSS-247 Issue 2, February 2017</b>		
FCC standard	Test Item	Results
15.207 RSS-Gen Issue 5 April 2018	AC Conducted Emission	PASS
§ 15.407 (2) (26 dB) / § 15.407 (e) (6 dB) / § 15.407 (a) (99%) RSS-Gen Issue 4 nov 2014	26dB/6dB & 99% Bandwidth	PASS
15.407(a) (1).(2).(3).(4).(5) RSS-247 Issue 2, February 2017	Maximum Conducted Output Power	PASS
15.407(b)	Peak Excursion Ratio	PASS
15.407(b) & 15.209 RSS-247 Issue 2, February 2017	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(b)7 RSS-247 Issue 2, February 2017	Conducted Emission And (bandedge Emissions) Measurement	PASS
15.407(a) (1).(2).(3).(4).(5) RSS-247 Issue 2, February 2017	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204 RSS-Gen Issue 5 April 2018	Antenna Requirement	PASS

**NOTE:**

(1) "N/A" denotes test is not applicable in this Test Report

(2) all tests are according to ANSI C63.10-2013



## 1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,  
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649; FCC Registration No.: 625569

IC Registration No.: 12108A; A2LA Certificate No.: 4338.01;

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.71\text{dB}$
4	Spurious emissions,conducted	$\pm 0.63\text{dB}$
5	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 3.80\text{dB}$
6	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 3.97\text{dB}$
7	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Product Name	Accent 800	
Trade Name	Accent	
Model Name	ACN800-30	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Accent 800	
	Operation Frequency:	IEEE 802.11a/ n/ac(HT20) 5.180GHz-5.240GHz IEEE 802.11n/ac(HT40) 5.190GHz-5.230GHz IEEE 802.11ac(HT80) 5.210GHz IEEE 802.11a/ n/ac(HT20)5.260GHz-5.320GHz IEEE 802.11n/ac(HT40)5.270GHz-5.310GHz IEEE 802.11ac(HT80) 5.290GHz IEEE 802.11a/ n/ac(HT20)5.500GHz-5.700GHz IEEE 802.11n/ac(HT40)5.510GHz-5.670GHz IEEE 802.11ac(HT80) 5.530GHz-5.610GHz IEEE 802.11a/ n/ac(HT20)5.745GHz-5.825GHz IEEE 802.11a/ n/ac(HT40)5.755GHz-5.795GHz IEEE 802.11ac(HT80) 5.775GHz
	Modulation Type:	802.11a(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM):BPSK,QPSK,16-QAM,64-QAM
	Antenna Designation:	See Note 2
	Max.Output Power(Conducted):	-0.54dBm
	Duty Cycle:	>98%
	More details of EUT technical specification, please refer to the User's Manual.	
Test Channel	Please refer to the Note 1.	
Adapter	Power supply and ADP(rating): Input: AC 100V-240V, 50/60Hz, 1500mA Output: DC 18V, 3330mA	
Battery	Battery(rating): Rated Voltage: 7.6V Charge Limit: 8.7V Capacity: 6000mAh	
Hardware version number	Ver C	
Software version number	Windows 10 Pro 64-bit	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1. Operation Frequency of channel

5.180GHz-5.240GHz		5.500GHz-5.720GHz	
Channel	Frequency	Channel	Frequency
36	5180	100	5500
38	5190	102	5510
40	5200	104	5520
42	5210	108	5540
44	5220	110	5550
46	5230	112	5560
48	5240	116	5580
		118	5590
		120	5600
5.260GHz-5.320GHz			
Channel	Frequency		
52	5260	124	5620
54	5270	126	5630
56	5280	128	5640
58	5290	132	5660
60	5300	134	5670
62	5310	136	5680
64	5320	140	5700
5.745GHz-5.825GHz			
Channel	Frequency		
149	5745		
151	5755		
153	5765		
157	5785		
159	5795		
161	5805		
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n/ac (HT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	52	5260
40	5200	60	5300
48	5240	64	5320

For 802.11a/n/ac (HT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
100	5500	149	5745
116	5580	157	5785
140	5700	165	5825





For 802.11n/ac (HT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	54	5270
46	5230	62	5310

For 802.11n/ac (HT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
102	5510	151	5755
110	5550	159	5795
134	5670		

For 802.11ac (HT80)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	58	5290

For 802.11ac (HT80)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
106	5530	155	5775
122	5610		

2.

Ant.	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
A	Accent	ACN800-30	PIFA Antenna	N/A	0dBi	WLAN Ant.



## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH100&CH116&CH140	6 Mbps
Mode 4	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 5	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 6	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 8	TX IEEE 802.11ac HT20 CH52&CH60&CH64	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT20 CH100&CH116&CH140	MCS 0
Mode 10	TX IEEE 802.11ac HT20 CH100&CH116&CH140	NSS1 MCS0
Mode 11	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 12	TX IEEE 802.11n HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 13	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 14	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 15	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 16	TX IEEE 802.11ac HT40 CH54 &CH62	NSS1 MCS0
Mode 17	TX IEEE 802.11n HT40 CH102&CH110&CH134	MCS 0
Mode 18	TX IEEE 802.11ac HT40 CH102&CH110&CH134	NSS1 MCS0
Mode 19	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 20	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 21	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 22	TX IEEE 802.11ac HT80 CH58	NSS1 MCS0
Mode 23	TX IEEE 802.11ac HT80 CH106&122	NSS1 MCS0
Mode 24	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0


- Note: (1) The measurements are performed at the highest, middle, lowest available channels.  
 (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported  
 (3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report

AC Conducted Emission


Test Case	
AC Conducted Emission	Mode 25: Keeping TX + WLAN Link

**2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**

Radiated Spurious Emission Test



Conducted Emission Test





## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-2	Adapter	MEGMEET	MANGO60S	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	DC Cable	NO	100cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

## Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESCI	102086	2017.10.15	2018.10.14
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2018.11.01
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2017.10.27	2018.10.26
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	N/A	2018.03.11	2019.03.10
Temperature & Humidity	HH660	Mieo	N/A	2017.10.15	2018.10.14
Temperature & Humidity	HH660	Mieo	N/A	2017.10.15	2018.10.14
Pre-mpifier (0.1M-3GHz)	EM	EM330	60538	2018.03.11	2019.03.10
PreAmplifier (1G-26.5GHz)	Agilent	8449B	60538	2017.10.15	2018.10.14
Passive Loop (9K--30MHz)	ZHNAN	ZN3090C	16035	2018.03.11	2019.03.10
Low frequency cable	EM	R01	N/A	2018.03.11	2019.03.10
Low frequency cable	EM	R06	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R04	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R02	N/A	2018.03.11	2019.03.10
Semi-anechoic chamber	Changling	966	N/A	2017.10.15	2018.10.14
trun table	EM	SC100_1	60531	N/A	N/A
Antnna mast	EM	SC100	N/A	N/A	N/A
Max-full Antenna Corp	MF	MFA-440H	N/A	N/A	N/A
EMI Test Receiver	R&S	ESW	101535	2017.07.11	2018.07.10

## Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2017.10.15	2018.10.14
LISN	R&S	ENV216	101242	2017.10.15	2018.10.14
conduction Cable	EM	C01	N/A	2018.03.11	2019.03.10
Temperature & Humidity	Mieo	HH660	N/A	2017.10.15	2018.10.14



## RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2017.10.15	2018.10.14
Power Meter	R&S	NRP	100510	2017.10.15	2018.10.14
Spectrum Analyzer	Agilent	N9020A	MY51110105	2018.03.08	2019.03.07
Signal Analyzer	Agilent	N9020A	MY49100060	2017.10.15	2018.10.14





### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



- Note: 1.Support units were connected to second LISN.**  
**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.





### 3.1.6 TEST RESULTS


Temperature:	23°C	Relative Humidity:	61%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 25		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1540	48.75	9.79	58.54	65.78	-7.24	QP
0.1540	25.62	9.79	35.41	55.78	-20.37	AVG
0.2220	39.19	9.88	49.07	62.74	-13.67	QP
0.2220	25.30	9.88	35.18	52.74	-17.56	AVG
0.5540	35.73	9.98	45.71	56.00	-10.29	QP
0.5540	31.76	9.98	41.74	46.00	-4.26	AVG
0.6100	34.88	9.93	44.81	56.00	-11.19	QP
0.6100	31.55	9.93	41.48	46.00	-4.52	AVG
2.4420	28.07	9.80	37.87	56.00	-18.13	QP
2.4420	18.48	9.80	28.28	46.00	-17.72	AVG
19.4900	28.39	10.44	38.83	60.00	-21.17	QP
19.4900	19.58	10.44	30.02	50.00	-19.98	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit

100.0 dBuV






Temperature:	23 °C	Relative Humidity:	61%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode	Mode 25		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1582	46.33	9.77	56.10	65.56	-9.46	QP
0.1582	29.64	9.77	39.41	55.56	-16.15	AVG
0.2220	39.40	9.96	49.36	62.74	-13.38	QP
0.2220	24.43	9.96	34.39	52.74	-18.35	AVG
0.4460	35.26	10.02	45.28	56.95	-11.67	QP
0.4460	28.78	10.02	38.80	46.95	-8.15	AVG
0.6100	34.27	9.91	44.18	56.00	-11.82	QP
0.6100	30.71	9.91	40.62	46.00	-5.38	AVG
1.7700	32.62	9.85	42.47	56.00	-13.53	QP
1.7700	23.50	9.85	33.35	46.00	-12.65	AVG
19.7260	27.60	10.45	38.05	60.00	-21.95	QP
19.7260	18.63	10.45	29.08	50.00	-20.92	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit

100.0 dBuV



### 3.2 RADIATED EMISSION AND ( BANDEDGE) MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band; limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dB $\mu$ V/m)	RA (dB $\mu$ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

### 3.2.7 TEST RESULTS (Between 9KHz – 30 MHz)

Temperature:	25.5°C	Relative Humidity:	62%
Test Voltage :	DC 7.6V from battery	Polarization :	--
Test Mode :	TX Mode		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})(\text{dB})$ ;

Limit line = specific limits(dBuv) + distance extrapolation factor.



**3.2.8 TEST RESULTS (Between 30MHz – 1GHz)**


Temperature	25.5 °C	Relative Humidity	62%
Test Voltage	DC 7.6V from battery	Polarization	Horizontal
Test Mode	Mode 1-24(Mode 1-6M worst mode)		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
48.8430	49.47	-20.89	28.58	40.00	-11.42	QP
67.4381	50.44	-24.16	26.28	40.00	-13.72	QP
100.2286	44.93	-19.17	25.76	43.50	-17.74	QP
150.0107	38.96	-17.97	20.99	43.50	-22.51	QP
300.3672	44.24	-14.81	29.43	46.00	-16.57	QP
552.8831	37.57	-6.71	30.86	46.00	-15.14	QP

Remark:

1. Margin = Result (Result =Reading + Factor )–Limit

80.0 dBuV/m






Temperature	25.5°C	Relative Humidity	62%
Test Voltage	DC 7.6V from battery	Polarization	Vertical
Test Mode	Mode 1-24(Mode 1-6M worst mode)		

Frequency (MHz)	Reading (dBUV)	Correct Factor(dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
30.6374	31.88	-11.52	20.36	40.00	-19.64	QP
73.6170	48.56	-23.59	24.97	40.00	-15.03	QP
95.7622	46.99	-19.61	27.38	43.50	-16.12	QP
175.0363	44.38	-19.38	25.00	43.50	-18.50	QP
400.4318	42.94	-11.22	31.72	46.00	-14.28	QP
965.5421	30.82	-0.14	30.68	54.00	-23.32	QP

Remark:

1. Margin = Result (Result =Reading + Factor )–Limit

80.0 dBUV/m







**3.2.9 TEST RESULTS (Above 1000 MHz)**

**Band I 5150-5250MHz**

Band I(5.15-5.25) GHz										
Frequency (MHz)	Reading	Amplifier	Loss	Antenna	Corrected	Emission	Limit (dBuV/m)	Margin	Detector	Comment
	(dBuV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)		(dB)		
Low Channel (802.11a/ 5180 MHz)										
3250.06	44.96	44.70	6.70	28.20	-9.80	35.16	74.00	-38.84	PK	Vertical
3250.06	41.19	44.70	6.70	28.20	-9.80	31.39	54.00	-22.61	AV	Vertical
3257.22	43.97	44.70	6.70	28.20	-9.80	34.17	74.00	-39.83	PK	Horizontal
3257.22	41.69	44.70	6.70	28.20	-9.80	31.89	54.00	-22.11	AV	Horizontal
3987.41	38.86	44.20	7.90	29.70	-6.60	32.26	74.00	-41.74	PK	Vertical
3987.41	36.29	44.20	7.90	29.70	-6.60	29.69	54.00	-24.31	AV	Vertical
3982.35	39.00	44.20	7.90	29.70	-6.60	32.40	74.00	-41.60	PK	Horizontal
3982.35	36.06	44.20	7.90	29.70	-6.60	29.46	54.00	-24.54	AV	Horizontal
7223.69	37.43	43.50	11.40	35.50	3.40	40.83	74.00	-33.17	PK	Vertical
7223.69	33.76	43.50	11.40	35.50	3.40	37.16	54.00	-16.84	AV	Vertical
7236.12	36.68	43.50	11.40	35.50	3.40	40.08	74.00	-33.92	PK	Horizontal
7236.12	34.64	43.50	11.40	35.50	3.40	38.04	54.00	-15.96	AV	Horizontal
10360.00	39.27	44.50	13.80	38.80	8.10	47.37	74.00	-26.63	PK	Vertical
10360.00	36.72	44.50	13.80	38.80	8.10	44.82	54.00	-9.18	AV	Vertical
10360.07	39.60	44.50	13.80	38.80	8.10	47.70	74.00	-26.30	PK	Horizontal
10360.07	37.17	44.50	13.80	38.80	8.10	45.27	54.00	-8.73	AV	Horizontal
11025.01	34.18	43.60	14.30	39.50	10.20	44.38	74.00	-29.62	PK	Vertical
11025.01	30.14	43.60	14.30	39.50	10.20	40.34	54.00	-13.66	AV	Vertical
11031.73	33.06	43.60	14.30	39.50	10.20	43.26	74.00	-30.74	PK	Horizontal
11031.73	29.85	43.60	14.30	39.50	10.20	40.05	54.00	-13.95	AV	Horizontal
13282.10	31.96	42.60	15.90	38.90	12.20	44.16	74.00	-29.84	PK	Vertical
13282.10	29.09	42.60	15.90	38.90	12.20	41.29	54.00	-12.71	AV	Vertical
13288.15	32.25	42.60	15.90	38.90	12.20	44.45	74.00	-29.55	PK	Horizontal
13288.15	29.59	42.60	15.90	38.90	12.20	41.79	54.00	-12.21	AV	Horizontal



Mid Channel (802.11a/ 5200 MHz)										
3249.52	43.81	44.70	6.70	28.20	-9.80	34.01	74.00	-39.99	PK	Vertical
3249.52	41.11	44.70	6.70	28.20	-9.80	31.31	54.00	-22.69	AV	Vertical
3265.11	44.28	44.70	6.70	28.20	-9.80	34.48	74.00	-39.52	PK	Horizontal
3265.11	42.20	44.70	6.70	28.20	-9.80	32.40	54.00	-21.60	AV	Horizontal
3984.18	39.36	44.20	7.90	29.70	-6.60	32.76	74.00	-41.24	PK	Vertical
3984.18	35.79	44.20	7.90	29.70	-6.60	29.19	54.00	-24.81	AV	Vertical
3986.77	39.17	44.20	7.90	29.70	-6.60	32.57	74.00	-41.43	PK	Horizontal
3986.77	36.85	44.20	7.90	29.70	-6.60	30.25	54.00	-23.75	AV	Horizontal
7219.25	36.97	43.50	11.40	35.50	3.40	40.37	74.00	-33.63	PK	Vertical
7219.25	34.39	43.50	11.40	35.50	3.40	37.79	54.00	-16.21	AV	Vertical
7220.80	36.83	43.50	11.40	35.50	3.40	40.23	74.00	-33.77	PK	Horizontal
7220.80	34.51	43.50	11.40	35.50	3.40	37.91	54.00	-16.09	AV	Horizontal
10400.27	39.72	44.50	13.80	38.80	8.10	47.82	74.00	-26.18	PK	Vertical
10400.27	37.08	44.50	13.80	38.80	8.10	45.18	54.00	-8.82	AV	Vertical
10400.11	39.04	44.50	13.80	38.80	8.10	47.14	74.00	-26.86	PK	Horizontal
10400.11	36.43	44.50	13.80	38.80	8.10	44.53	54.00	-9.47	AV	Horizontal
11019.78	33.10	43.60	14.30	39.50	10.20	43.30	74.00	-30.70	PK	Vertical
11019.78	30.88	43.60	14.30	39.50	10.20	41.08	54.00	-12.92	AV	Vertical
11034.32	33.94	43.60	14.30	39.50	10.20	44.14	74.00	-29.86	PK	Horizontal
11034.32	31.05	43.60	14.30	39.50	10.20	41.25	54.00	-12.75	AV	Horizontal
13299.53	31.53	42.60	15.90	38.90	12.20	43.73	74.00	-30.27	PK	Vertical
13299.53	29.65	42.60	15.90	38.90	12.20	41.85	54.00	-12.15	AV	Vertical
13296.20	31.91	42.60	15.90	38.90	12.20	44.11	74.00	-29.89	PK	Horizontal
13296.20	28.93	42.60	15.90	38.90	12.20	41.13	54.00	-12.87	AV	Horizontal



High Channel (802.11 a/ 5240 MHz)										
3250.16	44.77	44.70	6.70	28.20	-9.80	34.97	74.00	-39.03	PK	Vertical
3250.16	40.99	44.70	6.70	28.20	-9.80	31.19	54.00	-22.81	AV	Vertical
3264.28	45.25	44.70	6.70	28.20	-9.80	35.45	74.00	-38.55	PK	Horizontal
3264.28	40.85	44.70	6.70	28.20	-9.80	31.05	54.00	-22.95	AV	Horizontal
3994.56	38.66	44.20	7.90	29.70	-6.60	32.06	74.00	-41.94	PK	Vertical
3994.56	36.38	44.20	7.90	29.70	-6.60	29.78	54.00	-24.22	AV	Vertical
3980.40	39.23	44.20	7.90	29.70	-6.60	32.63	74.00	-41.37	PK	Horizontal
3980.40	36.67	44.20	7.90	29.70	-6.60	30.07	54.00	-23.93	AV	Horizontal
7217.80	36.94	43.50	11.40	35.50	3.40	40.34	74.00	-33.66	PK	Vertical
7217.80	34.29	43.50	11.40	35.50	3.40	37.69	54.00	-16.31	AV	Vertical
7219.21	36.85	43.50	11.40	35.50	3.40	40.25	74.00	-33.75	PK	Horizontal
7219.21	34.25	43.50	11.40	35.50	3.40	37.65	54.00	-16.35	AV	Horizontal
10479.95	39.42	44.50	13.80	38.80	8.10	47.52	74.00	-26.48	PK	Vertical
10479.95	36.10	44.50	13.80	38.80	8.10	44.20	54.00	-9.80	AV	Vertical
10480.40	38.75	44.50	13.80	38.80	8.10	46.85	74.00	-27.15	PK	Horizontal
10480.40	36.97	44.50	13.80	38.80	8.10	45.07	54.00	-8.93	AV	Horizontal
11024.55	33.16	43.60	14.30	39.50	10.20	43.36	74.00	-30.64	PK	Vertical
11024.55	30.54	43.60	14.30	39.50	10.20	40.74	54.00	-13.26	AV	Vertical
11020.20	33.60	43.60	14.30	39.50	10.20	43.80	74.00	-30.20	PK	Horizontal
11020.20	30.38	43.60	14.30	39.50	10.20	40.58	54.00	-13.42	AV	Horizontal
13287.86	32.53	42.60	15.90	38.90	12.20	44.73	74.00	-29.27	PK	Vertical
13287.86	29.06	42.60	15.90	38.90	12.20	41.26	54.00	-12.74	AV	Vertical
13290.46	32.70	42.60	15.90	38.90	12.20	44.90	74.00	-29.10	PK	Horizontal
13290.46	29.15	42.60	15.90	38.90	12.20	41.35	54.00	-12.65	AV	Horizontal

**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (HT-20), 802.11ac (HT-40), 802.11ac (HT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



**Band II 5250-5350MHz**

Band II(5.25-5.35) GHz										
Frequency (MHz)	Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limit (dBuV/m)	Margin	Detector	Comment
	(dBuV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)		(dB)		
Low Channel (802.11 a/ 5260 MHz)										
3246.52	44.07	44.70	6.70	28.20	-9.80	34.27	74.00	-39.73	PK	Vertical
3246.52	40.75	44.70	6.70	28.20	-9.80	30.95	54.00	-23.05	AV	Vertical
3257.93	44.76	44.70	6.70	28.20	-9.80	34.96	74.00	-39.04	PK	Horizontal
3257.93	41.55	44.70	6.70	28.20	-9.80	31.75	54.00	-22.25	AV	Horizontal
3987.05	39.65	44.20	7.90	29.70	-6.60	33.05	74.00	-40.95	PK	Vertical
3987.05	36.19	44.20	7.90	29.70	-6.60	29.59	54.00	-24.41	AV	Vertical
3989.55	40.00	44.20	7.90	29.70	-6.60	33.40	74.00	-40.60	PK	Horizontal
3989.55	36.06	44.20	7.90	29.70	-6.60	29.46	54.00	-24.54	AV	Horizontal
7228.50	36.77	43.50	11.40	35.50	3.40	40.17	74.00	-33.83	PK	Vertical
7228.50	34.60	43.50	11.40	35.50	3.40	38.00	54.00	-16.00	AV	Vertical
7235.61	36.81	43.50	11.40	35.50	3.40	40.21	74.00	-33.79	PK	Horizontal
7235.61	33.87	43.50	11.40	35.50	3.40	37.27	54.00	-16.73	AV	Horizontal
10520.04	39.76	44.50	13.90	38.80	8.20	47.96	74.00	-26.04	PK	Vertical
10520.04	36.02	44.50	13.90	38.80	8.20	44.22	54.00	-9.78	AV	Vertical
10520.05	39.58	44.50	13.90	38.80	8.20	47.78	74.00	-26.22	PK	Horizontal
10520.05	36.06	44.50	13.90	38.80	8.20	44.26	54.00	-9.74	AV	Horizontal
11032.93	33.09	43.60	14.30	39.50	10.20	43.29	74.00	-30.71	PK	Vertical
11032.93	30.52	43.60	14.30	39.50	10.20	40.72	54.00	-13.28	AV	Vertical
11031.44	32.71	43.60	14.30	39.50	10.20	42.91	74.00	-31.09	PK	Horizontal
11031.44	30.39	43.60	14.30	39.50	10.20	40.59	54.00	-13.41	AV	Horizontal
13293.59	32.54	42.60	15.90	38.90	12.20	44.74	74.00	-29.26	PK	Vertical
13293.59	29.78	42.60	15.90	38.90	12.20	41.98	54.00	-12.02	AV	Vertical
13291.96	31.63	42.60	15.90	38.90	12.20	43.83	74.00	-30.17	PK	Horizontal
13291.96	28.72	42.60	15.90	38.90	12.20	40.92	54.00	-13.08	AV	Horizontal



Mid Channel (802.11 a/ 5300 MHz)										
3246.95	44.54	44.70	6.70	28.20	-9.80	34.74	74.00	-39.26	PK	Vertical
3246.95	41.75	44.70	6.70	28.20	-9.80	31.95	54.00	-22.05	AV	Vertical
3249.02	44.26	44.70	6.70	28.20	-9.80	34.46	74.00	-39.54	PK	Horizontal
3249.02	41.07	44.70	6.70	28.20	-9.80	31.27	54.00	-22.73	AV	Horizontal
3992.21	39.61	44.20	7.90	29.70	-6.60	33.01	74.00	-40.99	PK	Vertical
3992.21	36.65	44.20	7.90	29.70	-6.60	30.05	54.00	-23.95	AV	Vertical
3992.28	38.88	44.20	7.90	29.70	-6.60	32.28	74.00	-41.72	PK	Horizontal
3992.28	37.11	44.20	7.90	29.70	-6.60	30.51	54.00	-23.49	AV	Horizontal
7219.51	37.38	43.50	11.40	35.50	3.40	40.78	74.00	-33.22	PK	Vertical
7219.51	34.46	43.50	11.40	35.50	3.40	37.86	54.00	-16.14	AV	Vertical
7223.88	37.68	43.50	11.40	35.50	3.40	41.08	74.00	-32.92	PK	Horizontal
7223.88	34.47	43.50	11.40	35.50	3.40	37.87	54.00	-16.13	AV	Horizontal
10600.28	39.39	44.50	13.80	38.80	8.10	47.49	74.00	-26.51	PK	Vertical
10600.28	35.73	44.50	13.80	38.80	8.10	43.83	54.00	-10.17	AV	Vertical
10599.98	39.31	44.50	13.80	38.80	8.10	47.41	74.00	-26.59	PK	Horizontal
10599.98	36.87	44.50	13.80	38.80	8.10	44.97	54.00	-9.03	AV	Horizontal
11034.68	33.99	43.60	14.30	39.50	10.20	44.19	74.00	-29.81	PK	Vertical
11034.68	30.86	43.60	14.30	39.50	10.20	41.06	54.00	-12.94	AV	Vertical
11017.98	33.55	43.60	14.30	39.50	10.20	43.75	74.00	-30.25	PK	Horizontal
11017.98	30.11	43.60	14.30	39.50	10.20	40.31	54.00	-13.69	AV	Horizontal
13291.43	31.84	42.60	15.90	38.90	12.20	44.04	74.00	-29.96	PK	Vertical
13291.43	29.01	42.60	15.90	38.90	12.20	41.21	54.00	-12.79	AV	Vertical
13282.59	32.09	42.60	15.90	38.90	12.20	44.29	74.00	-29.71	PK	Horizontal
13282.59	30.01	42.60	15.90	38.90	12.20	42.21	54.00	-11.79	AV	Horizontal



High Channel (802.11 a/ 5320 MHz)										
3256.77	44.92	44.70	6.70	28.20	-9.80	35.12	74.00	-38.88	PK	Vertical
3256.77	41.36	44.70	6.70	28.20	-9.80	31.56	54.00	-22.44	AV	Vertical
3261.22	44.72	44.70	6.70	28.20	-9.80	34.92	74.00	-39.08	PK	Horizontal
3261.22	41.99	44.70	6.70	28.20	-9.80	32.19	54.00	-21.81	AV	Horizontal
3997.01	39.88	44.20	7.90	29.70	-6.60	33.28	74.00	-40.72	PK	Vertical
3997.01	37.01	44.20	7.90	29.70	-6.60	30.41	54.00	-23.59	AV	Vertical
3984.36	39.86	44.20	7.90	29.70	-6.60	33.26	74.00	-40.74	PK	Horizontal
3984.36	35.79	44.20	7.90	29.70	-6.60	29.19	54.00	-24.81	AV	Horizontal
7235.85	37.79	43.50	11.40	35.50	3.40	41.19	74.00	-32.81	PK	Vertical
7235.85	33.52	43.50	11.40	35.50	3.40	36.92	54.00	-17.08	AV	Vertical
7225.76	37.49	43.50	11.40	35.50	3.40	40.89	74.00	-33.11	PK	Horizontal
7225.76	34.77	43.50	11.40	35.50	3.40	38.17	54.00	-15.83	AV	Horizontal
10640.14	39.08	44.50	13.80	38.80	8.10	47.18	74.00	-26.82	PK	Vertical
10640.14	36.16	44.50	13.80	38.80	8.10	44.26	54.00	-9.74	AV	Vertical
10640.09	39.41	44.50	13.80	38.80	8.10	47.51	74.00	-26.49	PK	Horizontal
10640.09	36.53	44.50	13.80	38.80	8.10	44.63	54.00	-9.37	AV	Horizontal
11027.32	32.80	43.60	14.30	39.50	10.20	43.00	74.00	-31.00	PK	Vertical
11027.32	30.31	43.60	14.30	39.50	10.20	40.51	54.00	-13.49	AV	Vertical
11031.70	33.19	43.60	14.30	39.50	10.20	43.39	74.00	-30.61	PK	Horizontal
11031.70	30.41	43.60	14.30	39.50	10.20	40.61	54.00	-13.39	AV	Horizontal
13297.28	32.14	42.70	18.00	37.10	12.40	44.54	74.00	-29.46	PK	Vertical
13297.28	29.11	42.70	18.00	37.10	12.40	41.51	54.00	-12.49	AV	Vertical
13295.43	32.73	42.70	18.00	37.10	12.40	45.13	74.00	-28.87	PK	Horizontal
13295.43	29.70	42.70	18.00	37.10	12.40	42.10	54.00	-11.90	AV	Horizontal

**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (HT-20), 802.11ac (HT-40), 802.11ac (HT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



**Band III 5470-5725MHz**

Band III(5.47-5.725) GHz										
Frequency (MHz)	Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limit (dBuV/m)	Margin	Detector	Comment
	(dBuV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)		(dB)		
Low Channel (802.11 a/ 5500 MHz)										
3253.55	44.34	44.70	6.70	28.20	-9.80	34.54	74.00	-39.46	PK	Vertical
3253.55	41.77	44.70	6.70	28.20	-9.80	31.97	54.00	-22.03	AV	Vertical
3252.11	45.05	44.70	6.70	28.20	-9.80	35.25	74.00	-38.75	PK	Horizontal
3252.11	40.78	44.70	6.70	28.20	-9.80	30.98	54.00	-23.02	AV	Horizontal
3992.26	40.06	44.20	7.90	29.70	-6.60	33.46	74.00	-40.54	PK	Vertical
3992.26	35.67	44.20	7.90	29.70	-6.60	29.07	54.00	-24.93	AV	Vertical
3989.31	39.15	44.20	7.90	29.70	-6.60	32.55	74.00	-41.45	PK	Horizontal
3989.31	36.02	44.20	7.90	29.70	-6.60	29.42	54.00	-24.58	AV	Horizontal
7220.04	36.58	43.50	11.40	35.50	3.40	39.98	74.00	-34.02	PK	Vertical
7220.04	34.53	43.50	11.40	35.50	3.40	37.93	54.00	-16.07	AV	Vertical
7227.15	37.52	43.50	11.40	35.50	3.40	40.92	74.00	-33.08	PK	Horizontal
7227.15	34.29	43.50	11.40	35.50	3.40	37.69	54.00	-16.31	AV	Horizontal
10342.88	39.46	44.50	13.80	38.80	8.10	47.56	74.00	-26.44	PK	Vertical
10342.88	36.72	44.50	13.80		-30.70	6.02	54.00	-47.98	AV	Vertical
10351.84	38.92	44.50	13.80	38.80	8.10	47.02	74.00	-26.98	PK	Horizontal
10351.84	36.90	44.50	13.80	38.80	8.10	45.00	54.00	-9.00	AV	Horizontal
11000.39	34.11	43.60	14.30	39.50	10.20	44.31	74.00	-29.69	PK	Vertical
11000.39	30.95	43.60	14.30	39.50	10.20	41.15	54.00	-12.85	AV	Vertical
11000.20	33.38	43.60	14.30	39.50	10.20	43.58	74.00	-30.42	PK	Horizontal
11000.20	30.73	43.60	14.30	39.50	10.20	40.93	54.00	-13.07	AV	Horizontal
13285.20	32.25	42.60	15.90	38.90	12.20	44.45	74.00	-29.55	PK	Vertical
13285.20	29.03	42.60	15.90	38.90	12.20	41.23	54.00	-12.77	AV	Vertical
13296.40	32.91	42.60	15.90	38.90	12.20	45.11	74.00	-28.89	PK	Horizontal
13296.40	28.60	42.60	15.90	38.90	12.20	40.80	54.00	-13.20	AV	Horizontal



Mid Channel (802.11 a/ 5580 MHz)										
3261.49	44.51	44.70	6.70	28.20	-9.80	34.71	74.00	-39.29	PK	Vertical
3261.49	41.59	44.70	6.70	28.20	-9.80	31.79	54.00	-22.21	AV	Vertical
3251.76	44.89	44.70	6.70	28.20	-9.80	35.09	74.00	-38.91	PK	Horizontal
3251.76	41.60	44.70	6.70	28.20	-9.80	31.80	54.00	-22.20	AV	Horizontal
3998.27	38.76	44.20	7.90	29.70	-6.60	32.16	74.00	-41.84	PK	Vertical
3998.27	36.74	44.20	7.90	29.70	-6.60	30.14	54.00	-23.86	AV	Vertical
3992.47	40.06	44.20	7.90	29.70	-6.60	33.46	74.00	-40.54	PK	Horizontal
3992.47	35.99	44.20	7.90	29.70	-6.60	29.39	54.00	-24.61	AV	Horizontal
7229.59	36.70	43.50	11.40	35.50	3.40	40.10	74.00	-33.90	PK	Vertical
7229.59	34.37	43.50	11.40	35.50	3.40	37.77	54.00	-16.23	AV	Vertical
7227.56	37.36	43.50	11.40	35.50	3.40	40.76	74.00	-33.24	PK	Horizontal
7227.56	33.71	43.50	11.40	35.50	3.40	37.11	54.00	-16.89	AV	Horizontal
10384.35	39.32	44.50	13.80	38.80	8.10	47.42	74.00	-26.58	PK	Vertical
10384.35	36.43	44.50	13.80	38.80	8.10	44.53	54.00	-9.47	AV	Vertical
10394.48	39.18	44.50	13.80	38.80	8.10	47.28	74.00	-26.72	PK	Horizontal
10394.48	35.86	44.50	13.80	38.80	8.10	43.96	54.00	-10.04	AV	Horizontal
11160.27	34.18	43.60	14.30	39.50	10.20	44.38	74.00	-29.62	PK	Vertical
11160.27	29.86	43.60	14.30	39.50	10.20	40.06	54.00	-13.94	AV	Vertical
11160.22	33.82	43.60	14.30	39.50	10.20	44.02	74.00	-29.98	PK	Horizontal
11160.22	30.10	43.60	14.30	39.50	10.20	40.30	54.00	-13.70	AV	Horizontal
13292.57	32.20	42.60	15.90	38.90	12.20	44.40	74.00	-29.60	PK	Vertical
13292.57	29.21	42.60	15.90	38.90	12.20	41.41	54.00	-12.59	AV	Vertical
13291.89	32.96	42.60	15.90	38.90	12.20	45.16	74.00	-28.84	PK	Horizontal
13291.89	29.59	42.60	15.90	38.90	12.20	41.79	54.00	-12.21	AV	Horizontal





High Channel (802.11 a/ 5700 MHz)										
3254.87	44.07	44.70	6.70	28.20	-9.80	34.27	74.00	-39.73	PK	Vertical
3254.87	41.78	44.70	6.70	28.20	-9.80	31.98	54.00	-22.02	AV	Vertical
3251.50	43.93	44.70	6.70	28.20	-9.80	34.13	74.00	-39.87	PK	Horizontal
3251.50	42.03	44.70	6.70	28.20	-9.80	32.23	54.00	-21.77	AV	Horizontal
3997.36	38.75	44.20	7.90	29.70	-6.60	32.15	74.00	-41.85	PK	Vertical
3997.36	36.01	44.20	7.90	29.70	-6.60	29.41	54.00	-24.59	AV	Vertical
3987.89	39.77	44.20	7.90	29.70	-6.60	33.17	74.00	-40.83	PK	Horizontal
3987.89	36.46	44.20	7.90	29.70	-6.60	29.86	54.00	-24.14	AV	Horizontal
7233.61	37.75	43.50	11.40	35.50	3.40	41.15	74.00	-32.85	PK	Vertical
7233.61	34.10	43.50	11.40	35.50	3.40	37.50	54.00	-16.50	AV	Vertical
7236.36	36.46	43.50	11.40	35.50	3.40	39.86	74.00	-34.14	PK	Horizontal
7236.36	34.70	43.50	11.40	35.50	3.40	38.10	54.00	-15.90	AV	Horizontal
10466.13	38.98	44.50	13.80	38.80	8.10	47.08	74.00	-26.92	PK	Vertical
10466.13	36.26	44.50	13.80	38.80	8.10	44.36	54.00	-9.64	AV	Vertical
10463.15	39.21	44.50	13.80	38.80	8.10	47.31	74.00	-26.69	PK	Horizontal
10463.15	36.24	44.50	13.80	38.80	8.10	44.34	54.00	-9.66	AV	Horizontal
11399.94	33.90	43.60	14.30	39.50	10.20	44.10	74.00	-29.90	PK	Vertical
11399.94	30.62	43.60	14.30	39.50	10.20	40.82	54.00	-13.18	AV	Vertical
11400.22	32.97	43.60	14.30	39.50	10.20	43.17	74.00	-30.83	PK	Horizontal
11400.22	30.76	43.60	14.30	39.50	10.20	40.96	54.00	-13.04	AV	Horizontal
13290.17	32.98	42.60	15.90	38.90	12.20	45.18	74.00	-28.82	PK	Vertical
13290.17	29.51	42.60	15.90	38.90	12.20	41.71	54.00	-12.29	AV	Vertical
13296.41	32.49	42.60	15.90	38.90	12.20	44.69	74.00	-29.31	PK	Horizontal
13296.41	29.97	42.60	15.90	38.90	12.20	42.17	54.00	-11.83	AV	Horizontal

**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (HT-20), 802.11ac (HT-40), 802.11ac (HT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



**Band IV(5.725-5.850) GHz**

Band IV(5.725-5.85) GHz										
Frequency (MHz)	Reading	Amplifier	Loss	Antenna	Orrected	Emission	Limit (dBuV/m)	Margin	Detector	Comment
	(dBuV)	(dB)	(dB)	(dB/m)	Factor	Factor		Level (dBμV/m)		
Low Channel (802.11 a/ 5745 MHz)										
3263.51	43.90	44.70	6.70	28.20	-9.80	34.10	74.00	-39.90	PK	Vertical
3263.51	41.89	44.70	6.70	28.20	-9.80	32.09	54.00	-21.91	AV	Vertical
3256.83	43.80	44.70	6.70	28.20	-9.80	34.00	74.00	-40.00	PK	Horizontal
3256.83	41.36	44.70	6.70	28.20	-9.80	31.56	54.00	-22.44	AV	Horizontal
3994.50	39.48	44.20	7.90	29.70	-6.60	32.88	74.00	-41.12	PK	Vertical
3994.50	36.97	44.20	7.90	29.70	-6.60	30.37	54.00	-23.63	AV	Vertical
3998.36	39.69	44.20	7.90	29.70	-6.60	33.09	74.00	-40.91	PK	Horizontal
3998.36	36.75	44.20	7.90	29.70	-6.60	30.15	54.00	-23.85	AV	Horizontal
7233.48	37.41	43.50	11.40	35.50	3.40	40.81	74.00	-33.19	PK	Vertical
7233.48	34.40	43.50	11.40	35.50	3.40	37.80	54.00	-16.20	AV	Vertical
7229.64	36.97	43.50	11.40	35.50	3.40	40.37	74.00	-33.63	PK	Horizontal
7229.64	33.62	43.50	11.40	35.50	3.40	37.02	54.00	-16.98	AV	Horizontal
10505.05	40.14	44.50	13.90	38.80	8.20	48.34	74.00	-25.66	PK	Vertical
10505.05	36.12	44.50	13.90	38.80	8.20	44.32	54.00	-9.68	AV	Vertical
10515.16	39.96	44.50	13.90	38.80	8.20	48.16	74.00	-25.84	PK	Horizontal
10515.16	37.00	44.50	13.90	38.80	8.20	45.20	54.00	-8.80	AV	Horizontal
11490.37	33.48	43.60	14.30	39.50	10.20	43.68	74.00	-30.32	PK	Vertical
11490.37	30.99	43.60	14.30	39.50	10.20	41.19	54.00	-12.81	AV	Vertical
11490.24	33.33	43.60	14.30	39.50	10.20	43.53	74.00	-30.47	PK	Horizontal
11490.24	30.20	43.60	14.30	39.50	10.20	40.40	54.00	-13.60	AV	Horizontal
13299.49	32.12	42.60	15.90	38.90	12.20	44.32	74.00	-29.68	PK	Vertical
13299.49	28.70	42.60	15.90	38.90	12.20	40.90	54.00	-13.10	AV	Vertical
13297.07	32.43	42.60	15.90	38.90	12.20	44.63	74.00	-29.37	PK	Horizontal
13297.07	29.81	42.60	15.90	38.90	12.20	42.01	54.00	-11.99	AV	Horizontal



Mid Channel (802.11 a/ 5785 MHz)										
3253.14	44.30	44.70	6.70	28.20	-9.80	34.50	74.00	-39.50	PK	Vertical
3253.14	41.81	44.70	6.70	28.20	-9.80	32.01	54.00	-21.99	AV	Vertical
3257.52	43.84	44.70	6.70	28.20	-9.80	34.04	74.00	-39.96	PK	Horizontal
3257.52	40.94	44.70	6.70	28.20	-9.80	31.14	54.00	-22.86	AV	Horizontal
3981.47	39.60	44.20	7.90	29.70	-6.60	33.00	74.00	-41.00	PK	Vertical
3981.47	36.37	44.20	7.90	29.70	-6.60	29.77	54.00	-24.23	AV	Vertical
3997.55	39.30	44.20	7.90	29.70	-6.60	32.70	74.00	-41.30	PK	Horizontal
3997.55	35.86	44.20	7.90	29.70	-6.60	29.26	54.00	-24.74	AV	Horizontal
7222.72	37.75	43.50	11.40	35.50	3.40	41.15	74.00	-32.85	PK	Vertical
7222.72	33.50	43.50	11.40	35.50	3.40	36.90	54.00	-17.10	AV	Vertical
7235.10	37.09	43.50	11.40	35.50	3.40	40.49	74.00	-33.51	PK	Horizontal
7235.10	33.70	43.50	11.40	35.50	3.40	37.10	54.00	-16.90	AV	Horizontal
10588.32	39.72	44.50	13.80	38.80	8.10	47.82	74.00	-26.18	PK	Vertical
10588.32	36.10	44.50	13.80	38.80	8.10	44.20	54.00	-9.80	AV	Vertical
10595.72	39.58	44.50	13.80	38.80	8.10	47.68	74.00	-26.32	PK	Horizontal
10595.72	36.72	44.50	13.80	38.80	8.10	44.82	54.00	-9.18	AV	Horizontal
11570.25	34.00	43.60	14.30	39.50	10.20	44.20	74.00	-29.80	PK	Vertical
11570.25	29.94	43.60	14.30	39.50	10.20	40.14	54.00	-13.86	AV	Vertical
11570.39	33.50	43.60	14.30	39.50	10.20	43.70	74.00	-30.30	PK	Horizontal
11570.39	29.67	43.60	14.30	39.50	10.20	39.87	54.00	-14.13	AV	Horizontal
13289.09	33.00	42.60	15.90	38.90	12.20	45.20	74.00	-28.80	PK	Vertical
13289.09	28.57	42.60	15.90	38.90	12.20	40.77	54.00	-13.23	AV	Vertical
13283.32	32.02	42.60	15.90	38.90	12.20	44.22	74.00	-29.78	PK	Horizontal
13283.32	29.58	42.60	15.90	38.90	12.20	41.78	54.00	-12.22	AV	Horizontal



High Channel (802.11 a/ 5825 MHz)										
3258.27	44.86	44.70	6.70	28.20	-9.80	35.06	74.00	-38.94	PK	Vertical
3258.27	41.06	44.70	6.70	28.20	-9.80	31.26	54.00	-22.74	AV	Vertical
3258.60	43.89	44.70	6.70	28.20	-9.80	34.09	74.00	-39.91	PK	Horizontal
3258.60	41.01	44.70	6.70	28.20	-9.80	31.21	54.00	-22.79	AV	Horizontal
3989.89	38.72	44.20	7.90	29.70	-6.60	32.12	74.00	-41.88	PK	Vertical
3989.89	36.70	44.20	7.90	29.70	-6.60	30.10	54.00	-23.90	AV	Vertical
3999.13	39.86	44.20	7.90	29.70	-6.60	33.26	74.00	-40.74	PK	Horizontal
3999.13	35.98	44.20	7.90	29.70	-6.60	29.38	54.00	-24.62	AV	Horizontal
7235.62	36.74	43.50	11.40	35.50	3.40	40.14	74.00	-33.86	PK	Vertical
7235.62	34.17	43.50	11.40	35.50	3.40	37.57	54.00	-16.43	AV	Vertical
7218.67	37.31	43.50	11.40	35.50	3.40	40.71	74.00	-33.29	PK	Horizontal
7218.67	33.96	43.50	11.40	35.50	3.40	37.36	54.00	-16.64	AV	Horizontal
10636.95	39.77	44.50	13.80	38.80	8.10	47.87	74.00	-26.13	PK	Vertical
10636.95	36.96	44.50	13.80	38.80	8.10	45.06	54.00	-8.94	AV	Vertical
10640.19	39.75	44.50	13.80	38.80	8.10	47.85	74.00	-26.15	PK	Horizontal
10640.19	35.75	44.50	13.80	38.80	8.10	43.85	54.00	-10.15	AV	Horizontal
11650.14	33.68	43.60	14.30	39.50	10.20	43.88	74.00	-30.12	PK	Vertical
11650.14	30.66	43.60	14.30	39.50	10.20	40.86	54.00	-13.14	AV	Vertical
11650.16	32.81	43.60	14.30	39.50	10.20	43.01	74.00	-30.99	PK	Horizontal
11650.16	30.23	43.60	14.30	39.50	10.20	40.43	54.00	-13.57	AV	Horizontal
13289.09	32.96	42.70	18.00	37.10	12.40	45.36	74.00	-28.64	PK	Vertical
13289.09	29.25	42.70	18.00	37.10	12.40	41.65	54.00	-12.35	AV	Vertical
13288.10	32.55	42.70	18.00	37.10	12.40	44.95	74.00	-29.05	PK	Horizontal
13288.10	29.16	42.70	18.00	37.10	12.40	41.56	54.00	-12.44	AV	Horizontal

**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (HT-20), 802.11ac (HT-40), 802.11ac (HT-80) the worst case is 802.11n (HT-20).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
4. Pre-scan both the SISO and MIMO mode, only the worst-case results were reported.



### 3.2.10 Band Edge

#### Band I&II(5.15-5.35)GHz

Band I&II(5.15-5.35)GHz										
Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11a BW20MHz										
5150	40.69	44.20	8.98	31.60	-3.62	37.07	74	-36.93	Peak	Vertical
5150	29.53	44.20	8.98	31.60	-3.62	25.91	54	-28.09	AVG	Vertical
5150	39.67	44.20	8.98	31.60	-3.62	36.05	74	-37.95	Peak	Horizontal
5150	30.44	44.20	8.98	31.60	-3.62	26.82	54	-27.18	AVG	Horizontal
5350	43.35	44.20	9.35	31.60	-3.25	40.10	74	-33.90	Peak	Vertical
5350	27.88	44.20	9.35	31.60	-3.25	24.63	54	-29.37	AVG	Vertical
5350	41.20	44.20	9.35	31.60	-3.25	37.95	74	-36.05	Peak	Horizontal
5350	29.46	44.20	9.35	31.60	-3.25	26.21	54	-27.79	AVG	Horizontal
802.11n BW20MHz										
5150	39.59	44.20	8.98	31.60	-3.62	35.97	74	-38.03	Peak	Vertical
5150	30.67	44.20	8.98	31.60	-3.62	27.05	54	-26.95	AVG	Vertical
5150	38.65	44.20	8.98	31.60	-3.62	35.03	74	-38.97	Peak	Horizontal
5150	30.16	44.20	8.98	31.60	-3.62	26.54	54	-27.46	AVG	Horizontal
5350	46.31	44.20	9.35	31.60	-3.25	43.06	74	-30.94	Peak	Vertical
5350	30.90	44.20	9.35	31.60	-3.25	27.65	54	-26.35	AVG	Vertical
5350	40.42	44.20	9.35	31.60	-3.25	37.17	74	-36.83	Peak	Horizontal
5350	27.92	44.20	9.35	31.60	-3.25	24.67	54	-29.33	AVG	Horizontal
802.11n BW40MHz										
5150	41.62	44.20	8.98	31.60	-3.62	38.00	74	-36.00	Peak	Vertical
5150	31.24	44.20	8.98	31.60	-3.62	27.62	54	-26.38	AVG	Vertical
5150	40.27	44.20	8.98	31.60	-3.62	36.65	74	-37.35	Peak	Horizontal
5150	28.08	44.20	8.98	31.60	-3.62	24.46	54	-29.54	AVG	Horizontal
5350	44.03	44.20	9.35	31.60	-3.25	40.78	74	-33.22	Peak	Vertical
5350	28.49	44.20	9.35	31.60	-3.25	25.24	54	-28.76	AVG	Vertical
5350	37.83	44.20	9.35	31.60	-3.25	34.58	74	-39.42	Peak	Horizontal
5350	28.27	44.20	9.35	31.60	-3.25	25.02	54	-28.98	AVG	Horizontal



802.11ac BW20MHz										
5150	41.50	44.20	8.98	31.60	-3.62	37.88	74	-36.12	Peak	Vertical
5150	31.60	44.20	8.98	31.60	-3.62	27.98	54	-26.02	AVG	Vertical
5150	41.32	44.20	8.98	31.60	-3.62	37.70	74	-36.30	Peak	Horizontal
5150	28.67	44.20	8.98	31.60	-3.62	25.05	54	-28.95	AVG	Horizontal
5350	43.41	44.20	9.35	31.60	-3.25	40.16	74	-33.84	Peak	Vertical
5350	28.62	44.20	9.35	31.60	-3.25	25.37	54	-28.63	AVG	Vertical
5350	40.43	44.20	9.35	31.60	-3.25	37.18	74	-36.82	Peak	Horizontal
5350	29.17	44.20	9.35	31.60	-3.25	25.92	54	-28.08	AVG	Horizontal
802.11ac BW40MHz										
5150	41.87	44.20	8.98	31.60	-3.62	38.25	74	-35.75	Peak	Vertical
5150	28.27	44.20	8.98	31.60	-3.62	24.65	54	-29.35	AVG	Vertical
5150	41.68	44.20	8.98	31.60	-3.62	38.06	74	-35.94	Peak	Horizontal
5150	30.78	44.20	8.98	31.60	-3.62	27.16	54	-26.84	AVG	Horizontal
5350	43.77	44.20	9.35	31.60	-3.25	40.52	74	-33.48	Peak	Vertical
5350	31.26	44.20	9.35	31.60	-3.25	28.01	54	-25.99	AVG	Vertical
5350	39.91	44.20	9.35	31.60	-3.25	36.66	74	-37.34	Peak	Horizontal
5350	30.83	44.20	9.35	31.60	-3.25	27.58	54	-26.42	AVG	Horizontal
802.11ac BW80MHz										
5150	41.01	44.20	8.98	31.60	-3.62	37.39	74	-36.61	Peak	Vertical
5150	31.75	44.20	8.98	31.60	-3.62	28.13	54	-25.87	AVG	Vertical
5150	38.09	44.20	8.98	31.60	-3.62	34.47	74	-39.53	Peak	Horizontal
5150	30.10	44.20	8.98	31.60	-3.62	26.48	54	-27.52	AVG	Horizontal
5350	44.41	44.20	9.35	31.60	-3.25	41.16	74	-32.84	Peak	Vertical
5350	31.77	44.20	9.35	31.60	-3.25	28.52	54	-25.48	AVG	Vertical
5350	39.32	44.20	9.35	31.60	-3.25	36.07	74	-37.93	Peak	Horizontal
5350	30.82	44.20	9.35	31.60	-3.25	27.57	54	-26.43	AVG	Horizontal



**Band III 5470-5725MHz**

Band III(5.47-5.725 GHz)										
Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11a BW20MHz										
5470	39.23	44.20	9.67	32.00	-2.53	36.70	74	-37.30	Peak	Vertical
5470	28.98	44.20	9.67	32.00	-2.53	26.45	54	-27.55	AVG	Vertical
5470	40.86	44.20	9.67	32.00	-2.53	38.33	74	-35.67	Peak	Horizontal
5470	28.74	44.20	9.67	32.00	-2.53	26.21	54	-27.79	AVG	Horizontal
5725	44.51	44.20	10.00	32.00	-2.20	42.31	74	-31.69	Peak	Vertical
5725	29.53	44.20	10.00	32.00	-2.20	27.33	54	-26.67	AVG	Vertical
5725	39.27	44.20	10.00	32.00	-2.20	37.07	74	-36.93	Peak	Horizontal
5725	31.82	44.20	10.00	32.00	-2.20	29.62	54	-24.38	AVG	Horizontal
802.11n BW20MHz										
5470	39.55	44.20	9.67	32.00	-2.53	37.02	74	-36.98	Peak	Vertical
5470	27.44	44.20	9.67	32.00	-2.53	24.91	54	-29.09	AVG	Vertical
5470	39.69	44.20	9.67	32.00	-2.53	37.16	74	-36.84	Peak	Horizontal
5470	31.04	44.20	9.67	32.00	-2.53	28.51	54	-25.49	AVG	Horizontal
5725	42.47	44.20	10.00	32.00	-2.20	40.27	74	-33.73	Peak	Vertical
5725	29.28	44.20	10.00	32.00	-2.20	27.08	54	-26.92	AVG	Vertical
5725	39.79	44.20	10.00	32.00	-2.20	37.59	74	-36.41	Peak	Horizontal
5725	29.52	44.20	10.00	32.00	-2.20	27.32	54	-26.68	AVG	Horizontal
802.11n BW40MHz										
5470	39.19	44.20	9.67	32.00	-2.53	36.66	74	-37.34	Peak	Vertical
5470	28.06	44.20	9.67	32.00	-2.53	25.53	54	-28.47	AVG	Vertical
5470	41.92	44.20	9.67	32.00	-2.53	39.39	74	-34.61	Peak	Horizontal
5470	28.95	44.20	9.67	32.00	-2.53	26.42	54	-27.58	AVG	Horizontal
5725	43.04	44.20	10.00	32.00	-2.20	40.84	74	-33.16	Peak	Vertical
5725	28.12	44.20	10.00	32.00	-2.20	25.92	54	-28.08	AVG	Vertical
5725	39.28	44.20	10.00	32.00	-2.20	37.08	74	-36.92	Peak	Horizontal
5725	29.36	44.20	10.00	32.00	-2.20	27.16	54	-26.84	AVG	Horizontal



802.11ac BW20MHz										
5470	41.55	44.20	9.67	32.00	-2.53	39.02	74	-34.98	Peak	Vertical
5470	30.55	44.20	9.67	32.00	-2.53	28.02	54	-25.98	AVG	Vertical
5470	38.42	44.20	9.67	32.00	-2.53	35.89	74	-38.11	Peak	Horizontal
5470	30.94	44.20	9.67	32.00	-2.53	28.41	54	-25.59	AVG	Horizontal
5725	44.83	44.20	10.00	32.00	-2.20	42.63	74	-31.37	Peak	Vertical
5725	29.85	44.20	10.00	32.00	-2.20	27.65	54	-26.35	AVG	Vertical
5725	39.23	44.20	10.00	32.00	-2.20	37.03	74	-36.97	Peak	Horizontal
5725	31.22	44.20	10.00	32.00	-2.20	29.02	54	-24.98	AVG	Horizontal
802.11ac BW40MHz										
5470	40.58	44.20	9.67	32.00	-2.53	38.05	74	-35.95	Peak	Vertical
5470	30.65	44.20	9.67	32.00	-2.53	28.12	54	-25.88	AVG	Vertical
5470	39.86	44.20	9.67	32.00	-2.53	37.33	74	-36.67	Peak	Horizontal
5470	31.63	44.20	9.67	32.00	-2.53	29.10	54	-24.90	AVG	Horizontal
5725	43.86	44.20	10.00	32.00	-2.20	41.66	74	-32.34	Peak	Vertical
5725	29.47	44.20	10.00	32.00	-2.20	27.27	54	-26.73	AVG	Vertical
5725	37.81	44.20	10.00	32.00	-2.20	35.61	74	-38.39	Peak	Horizontal
5725	28.80	44.20	10.00	32.00	-2.20	26.60	54	-27.40	AVG	Horizontal
802.11ac BW80MHz										
5470	41.93	44.20	9.67	32.00	-2.53	39.40	74	-34.60	Peak	Vertical
5470	27.50	44.20	9.67	32.00	-2.53	24.97	54	-29.03	AVG	Vertical
5470	38.54	44.20	9.67	32.00	-2.53	36.01	74	-37.99	Peak	Horizontal
5470	29.72	44.20	9.67	32.00	-2.53	27.19	54	-26.81	AVG	Horizontal
5725	46.53	44.20	10.00	32.00	-2.20	44.33	74	-29.67	Peak	Vertical
5725	29.49	44.20	10.00	32.00	-2.20	27.29	54	-26.71	AVG	Vertical
5725	40.23	44.20	10.00	32.00	-2.20	38.03	74	-35.97	Peak	Horizontal
5725	27.98	44.20	10.00	32.00	-2.20	25.78	54	-28.22	AVG	Horizontal





**Band IV(5.725-5.85 GHz)**

Band IV(5.725-5.85 GHz)										
Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11a BW20MHz										
5725	41.98	44.20	10.00	32.00	-2.20	39.78	74	-34.22	Peak	Vertical
5725	29.89	44.20	10.00	32.00	-2.20	27.69	54	-26.31	AVG	Vertical
5725	40.29	44.20	10.00	32.00	-2.20	38.09	74	-35.91	Peak	Horizontal
5725	30.53	44.20	10.00	32.00	-2.20	28.33	54	-25.67	AVG	Horizontal
5850	44.11	44.20	10.20	32.00	-2.00	42.11	74	-31.89	Peak	Vertical
5850	30.95	44.20	10.20	32.00	-2.00	28.95	54	-25.05	AVG	Vertical
5850	42.07	44.20	10.20	32.00	-2.00	40.07	74	-33.93	Peak	Horizontal
5850	31.75	44.20	10.20	32.00	-2.00	29.75	54	-24.25	AVG	Horizontal
802.11n BW20MHz										
5725	39.87	44.20	10.00	32.00	-2.20	37.67	74	-36.33	Peak	Vertical
5725	31.76	44.20	10.00	32.00	-2.20	29.56	54	-24.44	AVG	Vertical
5725	39.97	44.20	10.00	32.00	-2.20	37.77	74	-36.23	Peak	Horizontal
5725	30.19	44.20	10.00	32.00	-2.20	27.99	54	-26.01	AVG	Horizontal
5850	46.83	44.20	10.20	32.00	-2.00	44.83	74	-29.17	Peak	Vertical
5850	30.94	44.20	10.20	32.00	-2.00	28.94	54	-25.06	AVG	Vertical
5850	41.53	44.20	10.20	32.00	-2.00	39.53	74	-34.47	Peak	Horizontal
5850	31.62	44.20	10.20	32.00	-2.00	29.62	54	-24.38	AVG	Horizontal
802.11n BW40MHz										
5725	38.66	44.20	10.00	32.00	-2.20	36.46	74	-37.54	Peak	Vertical
5725	27.91	44.20	10.00	32.00	-2.20	25.71	54	-28.29	AVG	Vertical
5725	42.06	44.20	10.00	32.00	-2.20	39.86	74	-34.14	Peak	Horizontal
5725	29.81	44.20	10.00	32.00	-2.20	27.61	54	-26.39	AVG	Horizontal
5850	46.15	44.20	10.20	32.00	-2.00	44.15	74	-29.85	Peak	Vertical
5850	30.77	44.20	10.20	32.00	-2.00	28.77	54	-25.23	AVG	Vertical
5850	38.08	44.20	10.20	32.00	-2.00	36.08	74	-37.92	Peak	Horizontal
5850	31.50	44.20	10.20	32.00	-2.00	29.50	54	-24.50	AVG	Horizontal



802.11ac BW20MHz										
5725	39.54	44.20	10.00	32.00	-2.20	37.34	74	-36.66	Peak	Vertical
5725	29.60	44.20	10.00	32.00	-2.20	27.40	54	-26.60	AVG	Vertical
5725	39.98	44.20	10.00	32.00	-2.20	37.78	74	-36.22	Peak	Horizontal
5725	31.55	44.20	10.00	32.00	-2.20	29.35	54	-24.65	AVG	Horizontal
5850	45.71	44.20	10.20	32.00	-2.00	43.71	74	-30.29	Peak	Vertical
5850	30.14	44.20	10.20	32.00	-2.00	28.14	54	-25.86	AVG	Vertical
5850	38.14	44.20	10.20	32.00	-2.00	36.14	74	-37.86	Peak	Horizontal
5850	29.21	44.20	10.20	32.00	-2.00	27.21	54	-26.79	AVG	Horizontal
802.11ac BW40MHz										
5725	40.48	44.20	10.00	32.00	-2.20	38.28	74	-35.72	Peak	Vertical
5725	28.45	44.20	10.00	32.00	-2.20	26.25	54	-27.75	AVG	Vertical
5725	41.88	44.20	10.00	32.00	-2.20	39.68	74	-34.32	Peak	Horizontal
5725	28.93	44.20	10.00	32.00	-2.20	26.73	54	-27.27	AVG	Horizontal
5850	44.29	44.20	10.20	32.00	-2.00	42.29	74	-31.71	Peak	Vertical
5850	28.05	44.20	10.20	32.00	-2.00	26.05	54	-27.95	AVG	Vertical
5850	39.47	44.20	10.20	32.00	-2.00	37.47	74	-36.53	Peak	Horizontal
5850	30.08	44.20	10.20	32.00	-2.00	28.08	54	-25.92	AVG	Horizontal
802.11ac BW80MHz										
5725	41.45	44.20	10.00	32.00	-2.20	39.25	74	-34.75	Peak	Vertical
5725	29.31	44.20	10.00	32.00	-2.20	27.11	54	-26.89	AVG	Vertical
5725	38.10	44.20	10.00	32.00	-2.20	35.90	74	-38.10	Peak	Horizontal
5725	31.83	44.20	10.00	32.00	-2.20	29.63	54	-24.37	AVG	Horizontal
5850	45.16	44.20	10.20	32.00	-2.00	43.16	74	-30.84	Peak	Vertical
5850	27.59	44.20	10.20	32.00	-2.00	25.59	54	-28.41	AVG	Vertical
5850	40.83	44.20	10.20	32.00	-2.00	38.83	74	-35.17	Peak	Horizontal
5850	29.33	44.20	10.20	32.00	-2.00	27.33	54	-26.67	AVG	Horizontal

## 4. CONDUCTED SPURIOUS EMISSIONS AND BANDEGE

### 4.1 APPLIED PROCEDURES / LIMIT

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

#### 4.1.1 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	1000 KHz/3000 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 5700 to 5725 MHz Upper Band Edge: 5850 to 5870 MHz
RB / VB (emission in restricted band)	1000 KHz/3000 KHz
Trace-Mode:	Max hold

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

### 4.1.3 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1000 kHz. In order to make an accurate measurement, set the span greater than RBW.

### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

### 4.1.5 TEST RESULTS

Data See Appendix A





## 5. POWER SPECTRAL DENSITY TEST

### 5.1 APPLIED PROCEDURES / LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 5.1.1 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB D02 General UNII Test Procedures New Rules v01r03.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz.

Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used.

The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set  $RBW \geq 1/T$ , where  $T$  is defined in section II.B.I.a).
- b) Set  $VBW \geq 3 RBW$ .
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log (500\text{kHz}/RBW)$  to the measured result, whereas  $RBW (< 500 \text{ kHz})$  is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10 \log (1\text{MHz}/RBW)$  to the measured result, whereas  $RBW (< 1 \text{ MHz})$  is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since  $RBW=100 \text{ KHZ}$  is available on nearly all spectrum analyzers.

### 5.1.2 DEVIATION FROM STANDARD

No deviation.

### 5.1.3 TEST SETUP



### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

### 5.1.5 TEST RESULTS

Data see Appendix B



## 6. BANDWIDTH MEASUREMENT

### 6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

See list of measuring instruments of this test report.


#### 6.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW  $\geq$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 6.1.5 TEST RESULTS

Data see Appendix C

## 6.2 OCCUPIED BANDWIDTH ( 99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth:

### 6.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW  $\geq 3 \cdot$  RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

### 6.2.2 DEVIATION FROM STANDARD

No deviation.

### 6.2.3 TEST SETUP



### 6.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 6.2.5 TEST RESULTS

Data See Appendix C



### 6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

#### 6.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
  - a) Set RBW = 100 kHz.
  - b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
  - c) Detector = Peak.
  - d) Trace mode = max hold.
  - e) Sweep = auto couple.
  - f) Allow the trace to stabilize.
  - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 6.3.2 DEVIATION FROM STANDARD

No deviation.

#### 6.3.3 TEST SETUP



#### 6.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 6.3.5 TEST RESULTS

Data see Appendix D



## 7. MAXIMUM CONDUCTED OUTPUT POWER

### 7.1 APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz, if transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or $11 \text{ dBm} + 10 \log (26 \text{ dB emission bandwidth})$	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	

- For devices in the 5.15-5.25 GHz band, the maximum e.i.r.p. shall not exceed  $200 \text{ mW}$  or  $10 + 10 \log_{10} B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz.
- For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, The maximum conducted output power shall not exceed  $250 \text{ mW}$  or  $11 + 10 \log_{10} B$ , dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- The maximum conducted output power shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information

RSS-247 Issue 2, February 2017				
Section	Test Item	Limit	Frequency Range (MHz)	Result
6.2.1.1	Peak Output Power	200 mW or $10 + 10 \log_{10} B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz	5150-5250	PASS
6.2.2.1 6.2.3.1		The lesser of 250 mW or $11 \text{ dBm} + 10 \log (26 \text{ dB emission bandwidth})$	5250-5350 5470-5725	
6.2.4.1		1 watt	5725-5825	


**7.1.1 TEST PROCEDURE**

The EUT was directly connected to the Power Sensor&PC

**7.1.2 DEVIATION FROM STANDARD**

No deviation.

**7.1.3 TEST SETUP**



**7.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.



## 7.1.5 TEST RESULTS

### Band I (5.15-5.25GHz)


Band I (5.15-5.25GHz)				
Test Channel	Frequency (MHz)	PK Power (dBm)	AV Power (dBm)	LIMIT (dBm)
802.11a				
36	5180	-0.54	-2.47	23.98/23.00
40	5200	-1.08	-3.01	23.98/23.00
48	5240	-1.29	-3.57	23.98/23.00
802.11n(HT20)				
36	5180	-1.15	-2.87	23.98/23.00
40	5200	-1.59	-3.40	23.98/23.00
48	5240	-1.91	-3.86	23.98/23.00
802.11n(HT40)				
38	5190	-2.15	-3.99	23.98/23.00
46	5230	-2.31	-4.79	23.98/23.00
802.11ac(HT20)				
36	5180	-1.55	-3.28	23.98/23.00
40	5200	-1.73	-4.10	23.98/23.00
48	5240	-2.08	-4.51	23.98/23.00
802.11ac(HT40)				
38	5190	-2.19	-4.56	23.98/23.00
46	5230	-2.55	-4.15	23.98/23.00
802.11ac(HT80)				
42	5210	-2.56	-4.29	23.98/23.00

**Note:**

1. For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 0.25 W/200mW.



802.11ac HT80(5210MHz)



**Band II (5.25-5.35GHz)**


<b>Band II(5.25-5.35GHz)</b>				
Test Channel	Frequency (MHz)	PK Power (dBm)	AV Power (dBm)	LIMIT (dBm)
802.11a				
52	5260	-0.73	-2.40	23.98
60	5300	-1.31	-2.90	23.98
64	5320	-1.23	-2.78	23.98
802.11n(HT20)				
52	5260	-0.97	-3.19	23.98
60	5300	-1.52	-3.63	23.98
64	5320	-1.49	-3.68	23.98
802.11n(HT40)				
54	5270	-2.34	-4.67	23.98
62	5310	-2.69	-4.42	23.98
802.11ac(HT20)				
52	5260	-1.31	-3.50	23.98
60	5300	-1.95	-3.82	23.98
64	5320	-1.70	-3.24	23.98
802.11ac(HT40)				
54	5270	-2.38	-3.95	23.98
62	5310	-2.73	-5.15	23.98
802.11ac(HT80)				
58	5290	-2.75	-4.58	23.98

**Note:**

1. For mobile and portable client devices in the 5.25-5.35 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 0.25 W.



802.11ac HT80(5290MHz)



**Band III (5.47-5.725GHz)**

<b>Band9 III(5.47-5.725GHz)</b>				
Test Channel	Frequency (MHz)	PK Power (dBm)	AV Power (dBm)	LIMIT (dBm)
802.11a				
100	5500	-0.84	-2.43	23.98
116	5580	-1.16	-3.12	23.98
140	5700	-1.31	-3.62	23.98
802.11n(HT20)				
100	5500	-1.48	-3.87	23.98
116	5580	-1.72	-3.67	23.98
140	5700	-1.94	-4.21	23.98
802.11n(HT40)				
102	5510	-1.81	-3.48	23.98
110	5550	-2.05	-4.19	23.98
134	5670	-2.12	-4.01	23.98
802.11ac(HT20)				
100	5500	-1.61	-4.10	23.98
116	5580	-1.92	-3.93	23.98
140	5700	-2.09	-3.66	23.98
802.11ac(HT40)				
102	5510	-1.97	-4.15	23.98
110	5550	-2.09	-4.08	23.98
134	5670	-2.26	-4.17	23.98
802.11ac(HT80)				
106	5530	-2.64	-4.14	23.98
122	5610	-2.93	-4.63	23.98


## Note:

1. For mobile and portable client devices in the 5.47-5.725 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 0.25 W.






### 802.11ac HT80(5530MHz)



### 802.11ac HT80(5610MHz)



**Band IV (5.725-5.85GHz)**


<b>Band IV (5.725-5.85GHz)</b>				
Test Channel	Frequency (MHz)	PK Power (dBm)	AV Power (dBm)	LIMIT (dBm)
802.11a				
149	5745	-1.18	-3.40	30
157	5785	-1.45	-3.87	30
165	5825	-1.49	-3.43	30
802.11n(HT20)				
149	5745	-1.49	-3.45	30
157	5785	-1.74	-3.76	30
165	5825	-1.67	-4.04	30
802.11n(HT40)				
151	5755	-2.31	-4.62	30
159	5795	-2.67	-4.28	30
802.11ac(HT20)				
149	5745	-1.85	-3.44	30
157	5785	-2.15	-4.64	30
165	5825	-2.06	-3.74	30
802.11ac(HT40)				
151	5755	-2.36	-4.65	30
159	5795	-2.66	-4.50	30
802.11ac(HT80)				
155	5775	-3.72	-6.02	30

Note:

1. For the band 5.745-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W.



802.11ac HT80(5775MHz)





## 8. AUTOMATICALLY DISCONTINUE TRANSMISSION

### 8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### 8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission





## 9. ANTENNA REQUIREMENT

### 9.1 STANDARD REQUIREMENT

15.203 and RSS-Gen Issue 5 requirement: For intentional device, according to 15.203 and RSS-Gen Issue 5: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



### 9.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.



## APPENDIX - PHOTOS OF TEST SETUP

### Radiated Measurement Photos





### Conducted Measurement Photos



※※※※※END OF THE REPORT※※※※※