




# RF TEST REPORT



Report No.: 16070815-FCC-R3

Supersede Report No.: N/A

Applicant	MOBIWIRE MOBILES (NINGBO) CO.,LTD	
Product Name	4G LTE SMARTPHONE	
Model No.	N503	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	August 09 to September 05, 2016	
Issue Date	September 07, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	16070815-FCC-R3
Page	3 of 54

This page has been left blank intentionally.

# CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH.....	10
6.3 MAXIMUM OUTPUT POWER .....	16
6.4 POWER SPECTRAL DENSITY.....	20
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS .....	24
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	30
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND .....	36
ANNEX A. TEST INSTRUMENT.....	42
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	43
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	49
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	53
ANNEX E. DECLARATION OF SIMILARITY.....	54

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070815-FCC-R3	NONE	Original	September 07, 2016

## 2. Customer information

Applicant Name	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Applicant Add	No.999,Dacheng East Road,Fenghua City,Zhejiang
Manufacturer	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Manufacturer Add	No.999,Dacheng East Road,Fenghua City,Zhejiang

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

## 4. Equipment under Test (EUT) Information

Description of EUT:	4G LTE SMARTPHONE
Main Model:	N503
Serial Model:	N/A
Date EUT received:	August 08, 2016
Test Date(s):	August 09 to September 05, 2016
Equipment Category :	DTS
Antenna Gain:	GSM850: 0dBi PCS1900: 1dBi UMTS-FDD Band V: 0dBi UMTS-FDD Band II: 1dBi LTE Band IV: 0.5dBi Bluetooth/BLE/WIFI: -3dBi GPS: -3dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
Input Power:	Adapter: Model: S005UA0500100 Input: AC100-240V~50/60Hz,150mA Output: DC 5.0V,1000mA Battery: Spec: 3.8V,2270mAh(8.63Wh)

Test Report No.	16070815-FCC-R3
Page	7 of 54

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
RF Operating Frequency (ies):	LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7 ~ 2154.3 MHz
	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	WIFI: 802.11n(40M): 2422-2452 MHz
	Bluetooth& BLE: 2402-2480 MHz
	GPS: 1575.42 MHz
	802.11b: 8.63dBm
	802.11g: 8.61dBm
Max. Output Power:	802.11n(20M): 8.73dBm
	802.11n(40M): 8.54dBm
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	Power Port, Earphone Port, USB Port
Trade Name :	Noblex
GPRS/EGPRS Multi-slot class	8/10/12
FCC ID:	2ADA4N503

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-



## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 3 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI/GPS, the gain is -3dBi.

A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is 0dBi for GSM850, 1dBi for PCS1900, 0dBi for UMTS-FDD Band V, 1dBi for UMTS-FDD Band II.

A permanently attached PIFA antenna for LTE Band IV, the gain is 0.5dBi for LTE Band IV.

**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	September 01, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS Gen(4.6.1)	a)	6dB BW ≥ 500kHz; 20dB BW ≥ 500kHz;	<input checked="" type="checkbox"/>
	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> <li>Set RBW = 100 kHz.</li> <li>Set the video bandwidth (VBW) ≥ 3 × RBW.</li> <li>Detector = Peak.</li> <li>Trace mode = max hold.</li> <li>Sweep = auto couple.</li> <li>Allow the trace to stabilize.</li> <li>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</li> </ol> <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> <li>Set RBW = 1%-5% OBW.</li> <li>Set the video bandwidth (VBW) ≥ 3 x RBW.</li> <li>Set the span range between 2 times and 5 times of the OBW.</li> <li>Sweep time=Auto, Detector=PK, Trace=Max hold.</li> <li>Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst-</li> </ol>		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

### Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	11.59	15.28	≥ 0.5
	Mid	2437	12.11	15.83	≥ 0.5
	High	2462	11.65	15.38	≥ 0.5
802.11g	Low	2412	15.87	19.07	≥ 0.5
	Mid	2437	16.56	19.65	≥ 0.5
	High	2462	15.85	19.00	≥ 0.5
802.11n (20M)	Low	2412	16.47	19.51	≥ 0.5
	Mid	2437	17.82	19.76	≥ 0.5
	High	2462	11.35	19.60	≥ 0.5
802.11n (40M)	Low	2422	35.01	40.64	≥ 0.5
	Mid	2437	36.51	41.22	≥ 0.5
	High	2452	23.79	40.05	≥ 0.5

## Test Plots


### 6dB Bandwidth measurement result



802.11b 6dB Bandwidth - Low CH 2412




802.11b 6dB Bandwidth - Mid CH 2437




802.11b 6dB Bandwidth - High CH 2462




802.11g 6dB Bandwidth - Low CH 2412




802.11g 6dB Bandwidth - Mid CH 2437




802.11g 6dB Bandwidth - High CH 2462



802.11n20 6dB Bandwidth - Low CH 2412




802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422




802.11n40 6dB Bandwidth - Mid CH 2437



802.11n40 6dB Bandwidth - High CH 2452


## 20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - Low CH 2412




802.11b 20dB Bandwidth - Mid CH 2437




802.11b 20dB Bandwidth - High CH 2462




802.11g 20dB Bandwidth - Low CH 2412




802.11g 20dB Bandwidth - Mid CH 2437




802.11g 20dB Bandwidth - High CH 2462



802.11n20 20dB Bandwidth - Low CH 2412




802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437



802.11n40 20dB Bandwidth - High CH 2452

### 6.3 Maximum Output Power

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	August 29, 2016
Tested By :	Loren Luo

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $<50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq 1$ Watt	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set span to at least 1.5 times the OBW.</li> <li>- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.</li> <li>- c) Set VBW <math>\geq 3 \times</math> RBW.</li> <li>- d) Number of points in sweep <math>\geq 2 \times</math> span / RBW. (This gives bin-to-bin spacing <math>\leq</math> RBW/2, so that narrowband signals are not lost between frequency bins.)</li> <li>- e) Sweep time = auto.</li> <li>- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.</li> <li>- g) If transmit duty cycle <math>&lt; 98</math> %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum</li> </ul>
----------------	---



	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle <math>\geq 98\%</math>, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> <li>- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.</li> <li>- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot      Yes (See below)             N/A

**Output Power measurement result**

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	8.31	30	Pass
		Mid	2437	<b>8.63</b>	30	Pass
		High	2462	8.51	30	Pass
	802.11g	Low	2412	8.48	30	Pass
		Mid	2437	<b>8.61</b>	30	Pass
		High	2462	8.36	30	Pass
	802.11n (20M)	Low	2412	8.27	30	Pass
		Mid	2437	<b>8.73</b>	30	Pass
		High	2462	8.48	30	Pass
	802.11n (40M)	Low	2422	<b>8.54</b>	30	Pass
		Mid	2437	8.16	30	Pass
		High	2452	8.24	30	Pass

**Test Plots**

**The Average Power**




802.11b - AV Output power - Low CH 2412




802.11b - AV Output power - Mid CH 2437



802.11b - AV Output power - High CH 2462




802.11g - AV Output power - Low CH 2412



802.11g - AV Output power - Mid CH 2437



802.11g - AV Output power - High CH 2462



802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437




802.11n20 - AV Output power - High CH 2462



802.11n40 - AV Output power - Low CH 2422




802.11n40 - AV Output power - Mid CH 2437



802.11n40 - AV Output power - High CH 2452

## 6.4 Power Spectral Density

Temperature	22°C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	September 29, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure <ul style="list-style-type: none"> <li>- a) Set analyzer center frequency to DTS channel center frequency.</li> <li>- b) Set the span to 1.5 times the DTS bandwidth.</li> <li>- c) Set the RBW to: <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>- d) Set the VBW <math>\geq 3 \times \text{RBW}</math>.</li> <li>- e) Detector = peak.</li> <li>- f) Sweep time = auto couple.</li> <li>- g) Trace mode = max hold.</li> <li>- h) Allow trace to fully stabilize.</li> <li>- i) Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A

**Power Spectral Density measurement result**

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-11.542	8	Pass
		Mid	2437	-10.697	8	Pass
		High	2462	-10.268	8	Pass
	802.11g	Low	2412	-15.487	8	Pass
		Mid	2437	-15.156	8	Pass
		High	2462	-11.750	8	Pass
	802.11n (20M)	Low	2412	-16.240	8	Pass
		Mid	2437	-14.371	8	Pass
		High	2462	-14.099	8	Pass
	802.11n (40M)	Low	2422	-15.840	8	Pass
		Mid	2437	-16.544	8	Pass
		High	2452	-18.790	8	Pass

**Test Plots**

**Power Spectral Density measurement result**




PSD - Low CH 2412 - 802.11b



PSD - Mid CH 2437 - 802.11b




PSD - High CH 2462 - 802.11b




PSD - Low CH 2412 - 802.11g




PSD - Mid CH 2437 - 802.11g




PSD - High CH 2462 - 802.11g



PSD - Low CH 2412 - 802.11n20




PSD - Mid CH 2437 - 802.11n20



PSD - High CH 2472 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 - 802.11n40



PSD - High CH 2452 - 802.11n40

## 6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	August 16, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	<p>The diagram illustrates the test setup for radiated emissions. It features a Turn Table with EUT &amp; Support Units on top, positioned 0.8/1.5m from the Ground Plane. An Ant. Tower is positioned 3m from the Turn Table. A 1-4m Variable antenna is attached to the tower. A Test Receiver is connected to the antenna.</p>
------------	---

Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> </ul>
----------------	---



Test Report No.	16070815-FCC-R3
Page	25 of 54



	<ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below:           <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A  
 Test Plot      Yes (See below)             N/A

**Test Plots**

**Band Edge measurement result**

<p>       * Att 5 dB * RBW 1 MHz        * VBW 3 MHz * M2[1] 50.45 dBµV        Batt Ref 102.0 dBµV SWT 2.5ms 2.391440000 GHz        Limit Check Line Limit 74        1Pk Max 90 dBµV        80 dBµV        Limit 74        60 dBµV        50 dBµV        40 dBµV        Tdf 20 dBµV        10 dBµV        M1 M2        F1 F2        CF 2.39 GHz Span 80.0 MHz        Date: 16.AUG.2016 16:59:12     </p>	<p>       * Att 5 dB * RBW 1 MHz        * VBW 3 MHz * M1[1] 49.70 dBµV        Batt Ref 102.0 dBµV SWT 2.5ms 2.506260000 GHz        Limit Check Line Limit 74        1Pk Max 90 dBµV        80 dBµV        70 dBµV        60 dBµV        50 dBµV        40 dBµV        Tdf 20 dBµV        10 dBµV        M1        F1        CF 2.4835 GHz Span 80.0 MHz        Date: 16.AUG.2016 18:01:27     </p>
<p>Band Edge, Left Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11b</p>	<p>Band Edge, Right Side (Average) - 802.11b</p>



Band Edge, Left Side (Peak) - 802.11g  
**Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz**



Band Edge, Right Side (Peak) - 802.11g  
**Note: F1 is frequency 2483.5MHz**

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11g  
**Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz**

Band Edge, Right Side (Average) - 802.11g  
**Note: F1 is frequency 2483.5MHz**



Band Edge, Left Side (Peak) - 802.11n20  
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20  
 Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n20  
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11n20  
 Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n40  
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11n40  
 Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n40  
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11n40  
 Note: F1 is frequency 2483.5MHz

## 6.6 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	August 11, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [μ] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<input checked="" type="checkbox"/>														
		<table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>		Frequency ranges (MHz)	Limit (dBμV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBμV)												
				QP	Average												
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															

Test Setup	<p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	--

Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>
-----------	---


Test Report No.	16070815-FCC-R3
Page	31 of 54

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot      Yes (See below)             N/A

**Test Mode:** Transmitting Mode




**Test Data**

**Phase Line Plot at 120Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1617	22.77	QP	10.03	32.80	65.38	-32.58
2	L1	0.1617	10.62	AVG	10.03	20.65	55.38	-34.73
3	L1	0.2007	23.68	QP	10.03	33.71	63.58	-29.87
4	L1	0.2007	9.43	AVG	10.03	19.46	53.58	-34.12
5	L1	0.2397	22.73	QP	10.03	32.76	62.11	-29.35
6	L1	0.2397	9.22	AVG	10.03	19.25	52.11	-32.86
7	L1	0.3255	23.48	QP	10.03	33.51	59.57	-26.06
8	L1	0.3255	11.55	AVG	10.03	21.58	49.57	-27.99
9	L1	1.7716	29.74	QP	10.04	39.78	56.00	-16.22
10	L1	1.7716	13.93	AVG	10.04	23.97	46.00	-22.03
11	L1	2.5095	26.17	QP	10.05	36.22	56.00	-19.78
12	L1	2.5095	12.84	AVG	10.05	22.89	46.00	-23.11



<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------




**Test Data**

**Phase Neutral Plot at 120Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.1578	24.23	QP	10.02	34.25	65.58	-31.33
2	N	0.1578	12.91	AVG	10.02	22.93	55.58	-32.65
3	N	0.2046	21.12	QP	10.02	31.14	63.42	-32.28
4	N	0.2046	10.37	AVG	10.02	20.39	53.42	-33.03
5	N	1.7529	29.34	QP	10.04	39.38	56.00	-16.62
6	N	1.7529	11.37	AVG	10.04	21.41	46.00	-24.59
7	N	2.4042	28.75	QP	10.04	38.79	56.00	-17.21
8	N	2.4042	10.52	AVG	10.04	20.56	46.00	-25.44
9	N	4.7277	20.31	QP	10.07	30.38	56.00	-25.62
10	N	4.7277	5.64	AVG	10.07	15.71	46.00	-30.29
11	N	25.6941	17.09	QP	10.35	27.44	60.00	-32.56
12	N	25.6941	14.39	AVG	10.35	24.74	50.00	-25.26

**Test Mode:** Transmitting Mode




*Test Data*

**Phase Line Plot at 240Vac, 60Hz**

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1968	21.35	QP	10.03	31.38	63.74	-32.36
2	L1	0.1968	8.32	AVG	10.03	18.35	53.74	-35.39
3	L1	0.2358	19.03	QP	10.03	29.06	62.24	-33.18
4	L1	0.2358	8.97	AVG	10.03	19.00	52.24	-33.24
5	L1	0.3879	23.66	QP	10.03	33.69	58.11	-24.42
6	L1	0.3879	14.67	AVG	10.03	24.70	48.11	-23.41
7	L1	1.7529	24.32	QP	10.04	34.36	56.00	-21.64
8	L1	1.7529	8.00	AVG	10.04	18.04	46.00	-27.96
9	L1	13.8654	29.36	QP	10.21	39.57	60.00	-20.43
10	L1	13.8654	13.50	AVG	10.21	23.71	50.00	-26.29
11	L1	25.6941	17.90	QP	10.41	28.31	60.00	-31.69
12	L1	25.6941	14.17	AVG	10.41	24.58	50.00	-25.42

**Test Mode:** Transmitting Mode



**Test Data**

**Phase Neutral Plot at 240Vac, 60Hz**


No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.3528	24.42	QP	10.02	34.44	58.90	-24.46
2	N	0.3528	19.28	AVG	10.02	29.30	48.90	-19.60
3	N	0.4308	23.52	QP	10.02	33.54	57.24	-23.70
4	N	0.4308	14.34	AVG	10.02	24.36	47.24	-22.88
5	N	0.8403	26.65	QP	10.03	36.68	56.00	-19.32
6	N	0.8403	13.94	AVG	10.03	23.97	46.00	-22.03
7	N	1.7451	29.54	QP	10.04	39.58	56.00	-16.42
8	N	1.7451	13.31	AVG	10.04	23.35	46.00	-22.65
9	N	2.6304	30.48	QP	10.05	40.53	56.00	-15.47
10	N	2.6304	14.49	AVG	10.05	24.54	46.00	-21.46
11	N	13.4169	28.97	QP	10.18	39.15	60.00	-20.85
12	N	13.4169	17.11	AVG	10.18	27.29	50.00	-22.71

## 6.7 Radiated Spurious Emissions & Restricted Band

Temperature	22°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	August 13, 2016
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<input checked="" type="checkbox"/>
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
88 – 216	150												
216 960	200												
Above 960	500												
b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down      <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>											
c)	<p>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</p>	<input checked="" type="checkbox"/>											

<p>Test Setup</p>	
<p>Procedure</p>	<ol style="list-style-type: none"> <li>1. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:             <ol style="list-style-type: none"> <li>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</li> <li>b. The EUT was then rotated to the direction that gave the maximum emission.</li> <li>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</li> </ol> </li> <li>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> <li>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</li> </ol>
<p>Remark</p>	<p>Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.</p>
<p>Result</p>	<p><input checked="" type="checkbox"/> Pass      <input type="checkbox"/> Fail</p>

Test Data     Yes       N/A  
 Test Plot     Yes (See below)       N/A

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------

(Below 1GHz)




**Test Data**

**Vertical Polarity Plot @3m**

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	H	35.8747	29.21	peak	-4.58	24.63	40.00	-15.37	100	360
2	H	42.8998	32.29	peak	-9.53	22.76	40.00	-17.24	100	246
3	H	93.7685	32.20	peak	-12.44	19.76	43.50	-23.74	100	73
4	H	207.8501	40.84	peak	-8.81	32.03	43.50	-11.47	100	152
5	H	281.9946	32.26	peak	-7.72	24.54	46.00	-21.46	100	18
6	H	625.0780	28.17	peak	0.42	28.59	46.00	-17.41	100	195

**(Below 1GHz)**



**Test Data**

**Horizontal Polarity Plot @3m**

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	V	53.6932	44.81	peak	-13.61	31.20	40.00	-8.80	100	120
2	V	94.7601	45.03	peak	-12.19	32.84	43.50	-10.66	100	321
3	V	129.0146	32.62	peak	-7.87	24.75	43.50	-18.75	100	28
4	V	161.4742	34.35	peak	-8.40	25.95	43.50	-17.55	100	204
5	V	202.8104	42.29	peak	-8.76	33.53	43.50	-9.97	100	96
6	V	231.7179	34.13	peak	-9.02	25.11	46.00	-20.89	100	0

### Above 1GHz

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------

#### Low Channel (2422 MHz)(n40 mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4844	38.69	AV	V	33.8	6.86	32.69	46.66	54	-7.34
4844	38.02	AV	H	33.8	6.86	32.69	45.99	54	-8.01
4844	47.67	PK	V	33.8	6.86	32.69	55.64	74	-18.36
4844	47.52	PK	H	33.8	6.86	32.69	55.49	74	-18.51
17916	23.64	AV	V	45.12	11.57	32.11	48.22	54	-5.78
17916	22.81	AV	H	45.12	11.57	32.11	47.39	54	-6.61
17916	41.56	PK	V	45.12	11.57	32.11	66.14	74	-7.86
17916	40.37	PK	H	45.12	11.57	32.11	64.95	74	-9.05

#### Middle Channel (2437 MHz) (n20 mode worst case)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4874	38.74	AV	V	33.6	6.82	32.71	46.45	54	-7.55
4874	37.95	AV	H	33.6	6.82	32.71	45.66	54	-8.34
4874	47.59	PK	V	33.6	6.82	32.71	55.3	74	-18.7
4874	47.26	PK	H	33.6	6.82	32.71	54.97	74	-19.03
17908	24.01	AV	V	45.17	11.63	32.18	48.63	54	-5.37
17908	22.98	AV	H	45.17	11.63	32.18	47.6	54	-6.4
17908	41.87	PK	V	45.17	11.63	32.18	66.49	74	-7.51
17908	40.64	PK	H	45.17	11.63	32.18	65.26	74	-8.74



**High Channel (2452 MHz) (b mode worst case)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4924	39.02	AV	V	33.83	6.95	32.79	47.01	54	-6.99
4924	38.21	AV	H	33.83	6.95	32.79	46.2	54	-7.8
4924	48.15	PK	V	33.83	6.95	32.79	56.14	74	-17.86
4924	47.67	PK	H	33.83	6.95	32.79	55.66	74	-18.34
17897	24.23	AV	V	45.19	11.61	32.24	48.79	54	-5.21
17897	22.63	AV	H	45.19	11.61	32.24	47.19	54	-6.81
17897	41.84	PK	V	45.19	11.61	32.24	66.4	74	-7.6
17897	40.88	PK	H	45.19	11.61	32.24	65.44	74	-8.56

**Note:**

- 1, The testing has been conformed to  $10 \times 2462 \text{MHz} = 24,620 \text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>

**Annex B. EUT and Test Setup Photographs**

**Annex B.i. Photograph: EUT External Photo**



Whole Package View




Adapter - Front View




EUT - Front View




EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

**Annex B.ii. Photograph: EUT Internal Photo**




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View



Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard with Shielding - Rear View



Mainboard without Shielding - Rear View



Small Board – Front View




Small Board - Rear View



LCD – Front View



LCD – Rear View



GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE/GPS - Antenna View



LTE Antenna View


**Annex B.iii. Photograph: Test Setup Photo**




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz




## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK


#### Block Configuration Diagram for AC Line Conducted Emissions



**Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .**



**Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .**



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
MOBIWIRE MOBILES (NINGBO) CO.,LTD	Adapter	S005UA0500100	CBA3000AH0C1

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	CBA3000AH0C1

Test Report No.	16070815-FCC-R3
Page	53 of 54

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report No.	16070815-FCC-R3
Page	54 of 54

## Annex E. DECLARATION OF SIMILARITY

N/A