

RADIO TEST REPORT

Report No: STS1703216F03

Issued for

MOBIWIRE MOBILES (NINGBO) CO.,LTD

No.999, Dacheng East Road, Fenghua City, Zhejiang, China

| | |
|-----------------------|-----------------|
| Product Name: | 3G Featurephone |
| Brand Name: | Mobiwire |
| Model Name: | XB52U |
| Series Model: | N/A |
| FCC ID: | 2ADA4XB52U |
| Test Standard: | FCC Part 15.247 |

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from BZT, All Test Data Presented in this report is only applicable to presented Test sample.

BZT Testing Technology Co., Ltd

Add. : Buliding 17, Xinghua Road Xingwei industrial Park Fuyong,
Baoan District, Shenzhen, Guangdong, China

TEST RESULT CERTIFICATION

Applicant's name: MOBIWIRE MOBILES (NINGBO) CO.,LTD

Address: No.999, Dacheng East Road, Fenghua City, Zhejiang, China

Manufacture's Name: MOBIWIRE MOBILES (NINGBO) CO.,LTD

Address: No.999, Dacheng East Road, Fenghua City, Zhejiang, China

Product description

Product name: 3G Featurephone

Brand name: Mobiwire

Model and/or type reference .: XB52U

Series Model.....: N/A

Standards: FCC Part15.247

Test procedure ANSI C63.10-2013

This device described above has been tested by BZT, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BZT, this document may be altered or revised by BZT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests: 27 Mar. 2017 ~ 01 Apr. 2017

Date of Issue: 05 Apr. 2017

Test Result.....: **Pass**

Testing Engineer :



(Leo li)

Technical Manager :



(Tony liu)

Authorized Signatory :



(Vita Li)

| Table of Contents | Page |
|---|-------------|
| 1. SUMMARY OF TEST RESULTS | 6 |
| 1.1 TEST FACTORY | 7 |
| 1.2 MEASUREMENT UNCERTAINTY | 7 |
| 2. GENERAL INFORMATION | 8 |
| 2.1 GENERAL DESCRIPTION OF EUT | 8 |
| 2.2 DESCRIPTION OF TEST MODES | 10 |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 11 |
| 2.4 DESCRIPTION OF SUPPORT UNITS | 12 |
| 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS | 13 |
| 3. EMC EMISSION TEST | 14 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 14 |
| 3.2 RADIATED EMISSION MEASUREMENT | 18 |
| 4. CONDUCTED SPURIOUS & BAND EDGE EMISSION | 29 |
| 4.1 APPLIED PROCEDURES / LIMIT | 29 |
| 4.2 TEST PROCEDURE | 29 |
| 4.3 DEVIATION FROM STANDARD | 29 |
| 4.4 TEST SETUP | 29 |
| 4.5 EUT OPERATION CONDITIONS | 29 |
| 4.6 TEST RESULTS | 30 |
| 5. POWER SPECTRAL DENSITY TEST | 42 |
| 5.1 APPLIED PROCEDURES / LIMIT | 42 |
| 5.2 TEST PROCEDURE | 42 |
| 5.3 DEVIATION FROM STANDARD | 42 |
| 5.4 TEST SETUP | 42 |
| 5.5 EUT OPERATION CONDITIONS | 42 |
| 5.6 TEST RESULTS | 43 |
| 6. BANDWIDTH TEST | 51 |
| 6.1 APPLIED PROCEDURES / LIMIT | 51 |
| 6.2 TEST PROCEDURE | 51 |
| 6.3 DEVIATION FROM STANDARD | 51 |
| 6.4 TEST SETUP | 51 |
| 6.5 EUT OPERATION CONDITIONS | 51 |
| 6.6 TEST RESULTS | 52 |
| 7. PEAK OUTPUT POWER TEST | 60 |

| Table of Contents | Page |
|--|-------------|
| 7.1 APPLIED PROCEDURES / LIMIT | 60 |
| 7.2 TEST PROCEDURE | 60 |
| 7.3 DEVIATION FROM STANDARD | 60 |
| 7.4 TEST SETUP | 60 |
| 7.5 EUT OPERATION CONDITIONS | 60 |
| 7.6 TEST RESULTS | 61 |
| 8. ANTENNA REQUIREMENT | 62 |
| 8.1 STANDARD REQUIREMENT | 62 |
| 8.2 EUT ANTENNA | 62 |
| APPENDIX - PHOTOS OF TEST SETUP | 63 |

Revision History

| Rev. | Issue Date | Report NO. | Effect Page | Contents |
|------|--------------|---------------|-------------|---------------|
| 00 | 05 Apr. 2017 | STS1703216F03 | ALL | Initial Issue |
| | | | | |

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 DTS Meas Guidance v03r05

| FCC Part 15.247,Subpart C | | | |
|----------------------------------|---|----------|--------|
| Standard Section | Test Item | Judgment | Remark |
| 15.207 | Conducted Emission | PASS | |
| 15.247 (a)(2) | 6dB Bandwidth | PASS | |
| 15.247 (b)(3) | Output Power | PASS | |
| 15.247 (c) | Radiated Spurious Emission | PASS | |
| 15.247 (d) | Conducted Spurious & Band Edge Emission | PASS | |
| 15.247 (e) | Power Spectral Density | PASS | |
| 15.205 | Restricted Band Edge Emission | PASS | |
| Part 15.247(d)/part 15.209(a) | Band Edge Emission | PASS | |
| 15.203 | Antenna Requirement | PASS | |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) all tests are according to ANSI C63.10-2013 .

1.1 TEST FACTORY

BZT Testing Technology Co., Ltd
 Add. : Buliding 17, Xinghua Road Xingwei industrial Park Fuyong,
 Baoan District, Shenzhen, Guangdong, China

FCC Registration No.: 701733

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|--|-------------------------|
| 1 | Conducted Emission (9KHz-150KHz) | $\pm 2.88\text{dB}$ |
| 2 | Conducted Emission (150KHz-30MHz) | $\pm 2.67\text{dB}$ |
| 3 | RF power,conducted | $\pm 0.70\text{dB}$ |
| 4 | Spurious emissions,conducted | $\pm 1.19\text{dB}$ |
| 5 | All emissions,radiated(<30M) (9KHz-30MHz) | $\pm 2.45\text{dB}$ |
| 6 | All emissions,radiated(<1G) 30MHz-200MHz | $\pm 2.83\text{dB}$ |
| 7 | All emissions,radiated(<1G) 200MHz-1000MHz | $\pm 2.94\text{dB}$ |
| 8 | All emissions,radiated(>1G) | $\pm 3.03\text{dB}$ |
| 9 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 10 | Humidity | $\pm 2\%$ |

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | | |
|-------------------------|--|---|
| Equipment | 3G Featurephone | |
| Trade Name | Mobiwire | |
| Model Name | XB52U | |
| Series Model | N/A | |
| Model Difference | N/A | |
| Product Description | The EUT is a 3G Featurephone | |
| | Operation Frequency: | 802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz |
| | Modulation Type: | CCK/BPSK/QPSK/16QAM |
| | Bit Rate of Transmitter: | 802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n(20MHz): 65/58.5/52/39/26/19.5/13/6.5 Mbps 802.11n(40MHz): 135/121.5/108/81/54/40.5/37/13.5 Mbps |
| | Number Of Channel: | 802.11b/g/n20: 11CH 802.11n 40: 7CH |
| | Antenna Designation: | Please see Note 3. |
| | Antenna Gain (dBi): | -1dbi |
| | Duty Cycle: | >98% |
| | Channel List | Please refer to the Note 2. |
| Adapter | Input: AC100-240V, 200mA, 50/60 Hz Output: DC 5V, 550mA | |
| Battery | Rated Voltage: 3.7V capacity :800mAh | |
| Hardware version number | V00 | |
| Software version number | UP249_XB52U_Digicel_debug_FCC | |
| Connecting I/O Port(s) | Please refer to the User's Manual | |

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

| Operation Frequency of channel | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| 802.11b/g/n(20MHz) | | Channel List for 802.11n(40MHz) | |
| Channel | Frequency | Channel | Frequency |
| 01 | 2412 | 03 | 2422 |
| 02 | 2417 | 04 | 2427 |
| 03 | 2422 | 05 | 2432 |
| 04 | 2427 | 06 | 2437 |
| 05 | 2432 | 07 | 2442 |
| 06 | 2437 | 08 | 2447 |
| 07 | 2442 | 09 | 2452 |
| 08 | 2447 | | |
| 09 | 2452 | | |
| 10 | 2457 | | |
| 11 | 2462 | | |

3

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

2.4GHz Test Frequency:

| For 802.11b/g/n (HT20) | | For 802.11n (HT40) | |
|------------------------|------------|--------------------|------------|
| Channel | Freq.(MHz) | Channel | Freq.(MHz) |
| 01 | 2412 | 03 | 2422 |
| 06 | 2437 | 06 | 2437 |
| 11 | 2462 | 09 | 2452 |

3

| Ant | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | NOTE |
|-----|----------|------------|--------------|-----------|------------|--------------|
| 1 | Mobiwire | XB52U | PIFA Antenna | N/A | -1 | WIFI Antenna |

2.2 DESCRIPTION OF TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Worst Mode | Description | Data Rate |
|------------|---------------------------|-----------|
| Mode 1 | TX IEEE 802.11b CH1 | 1 Mbps |
| Mode 2 | TX IEEE 802.11b CH6 | 1 Mbps |
| Mode 3 | TX IEEE 802.11 b CH11 | 1 Mbps |
| Mode 4 | TX IEEE 802.11g CH1 | 6 Mbps |
| Mode 5 | TX IEEE 802.11g CH6 | 6 Mbps |
| Mode 6 | TX IEEE 802.11g CH11 | 6 Mbps |
| Mode 7 | TX IEEE 802.11n HT20 CH1 | MCS 0 |
| Mode 8 | TX IEEE 802.11n HT20 CH6 | MCS 0 |
| Mode 9 | TX IEEE 802.11n HT20 CH11 | MCS 0 |
| Mode 10 | TX IEEE 802.11n HT40 CH3 | MCS 0 |
| Mode 11 | TX IEEE 802.11n HT40 CH6 | MCS 0 |
| Mode 12 | TX IEEE 802.11n HT40 CH9 | MCS 0 |

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
- (3) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

AC Conducted Emission


| Test Case | |
|-----------------------|-------------------------|
| AC Conducted Emission | Mode13: Keeping WIFI TX |

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set



conduction Test Set



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Serial No. | Note |
|------|-----------------|-----------|------------------|------------|------|
| E-1 | 3G Featurephone | Mobiwire | XB52U | N/A | EUT |
| E-2 | Adapter | Mobiwire | A31A-050055U-US1 | N/A | N/A |
| E-3 | Earphone | N/A | N/A | N/A | N/A |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|--|--------------|--------|------|
| C-1 | USB Cable shielded line (Charging) | NO | 100cm | N/A |
| C-2 | Unshielded Cable | NO | 110cm | N/A |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|-----------------------|--------------|------------------|----------------|------------------|------------------|
| Spectrum Analyzer | Agilent | E4407B | MY50140340 | 2016.10.23 | 2017.10.22 |
| Test Receiver | R&S | ESCI | 101427 | 2016.10.23 | 2017.10.22 |
| Bilog Antenna | TESEQ | CBL6111D | 34678 | 2014.11.24 | 2017.11.23 |
| Horn Antenna | Schwarzbeck | BBHA 9120D(1201) | 9120D-1343 | 2015.03.05 | 2018.03.04 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | 9170-0741 | 2016.03.06 | 2019.03.05 |
| 50Ω Coaxial Switch | Anritsu | MP59B | 6200264416 | 2016.06.06 | 2017.06.05 |
| PreAmplifier | Agilent | 8449B | 60538 | 2016.10.23 | 2017.10.22 |
| Loop Antenna | EMCO | 6502 | 9003-2485 | 2016.03.06 | 2019.03.05 |
| Preamplifier | Agilent | 8449B | 60538 | 2016.10.23 | 2017.10.22 |
| Low frequency cable | EM | R01 | N/A | NCR | NCR |
| High frequency cable | SCHWARZBECK | AK9515H | SN-96286/96287 | NCR | NCR |
| Semi-anechoic chamber | Changling | 966 | N/A | 2016.10.23 | 2017.10.22 |

Conduction Test equipment

| Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|-------------------|--------------|----------|------------|------------------|------------------|
| EMI Test Receiver | R&S | ESPI | 102086 | 2016.10.23 | 2017.10.22 |
| LISN | R&S | ENV216 | 101242 | 2016.10.23 | 2017.10.22 |
| LISN | EMCO | 3810/2NM | 000-23625 | 2016.10.23 | 2017.10.22 |
| Conduction Cable | EM | C01 | N/A | NCR | NCR |
| Shielding Room | Changling | 854 | N/A | 2016.10.23 | 2017.10.22 |

RF Connected Test

| Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|---------------------|--------------|----------|---------------|------------------|------------------|
| USB RF power sensor | DARE | RPR3006W | 15I00041SNO03 | 2016.10.23 | 2017.10.22 |
| Spectrum Analyzer | Agilent | E4407B | MY50140340 | 2016.10.23 | 2017.10.22 |
| Signal Analyzer | Agilent | N9020A | MY49100060 | 2016.10.23 | 2017.10.22 |

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a) limit in the table below has to be followed.

| FREQUENCY (MHz) | Conducted Emission limit (dBuV) | |
|-----------------|---------------------------------|-----------|
| | Quasi-peak | Average |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |

3.1.2 TEST PROCEDURE

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.5 TEST RESULT

| | | | |
|---------------|--------------|--------------------|---------|
| Temperature: | 23.1 °C | Relative Humidity: | 61% |
| Pressure: | 1010hPa | Phase: | L |
| Test Voltage: | AC 120V/60Hz | Test Mode: | Mode 13 |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 0.1900 | 40.84 | 9.23 | 50.07 | 64.04 | -13.97 | QP |
| 0.1900 | 23.52 | 9.23 | 32.75 | 54.04 | -21.29 | AVG |
| 0.3780 | 31.99 | 9.37 | 41.36 | 58.32 | -16.96 | QP |
| 0.3780 | 18.13 | 9.37 | 27.50 | 48.32 | -20.82 | AVG |
| 0.5500 | 28.13 | 9.17 | 37.30 | 56.00 | -18.70 | QP |
| 0.5500 | 16.55 | 9.17 | 25.72 | 46.00 | -20.28 | AVG |
| 1.7380 | 30.96 | 9.22 | 40.18 | 56.00 | -15.82 | QP |
| 1.7380 | 17.99 | 9.22 | 27.21 | 46.00 | -18.79 | AVG |
| 4.9420 | 26.65 | 9.27 | 35.92 | 56.00 | -20.08 | QP |
| 4.9420 | 15.44 | 9.27 | 24.71 | 46.00 | -21.29 | AVG |
| 16.4740 | 28.06 | 9.60 | 37.66 | 60.00 | -22.34 | QP |
| 16.4740 | 19.50 | 9.60 | 29.10 | 50.00 | -20.90 | AVG |

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit




| | | | |
|---------------|--------------|--------------------|---------|
| Temperature: | 23.1 °C | Relative Humidity: | 61% |
| Pressure: | 1010hPa | Phase: | N |
| Test Voltage: | AC 120V/60Hz | Test Mode: | Mode 13 |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|--------|
| 0.1860 | 41.52 | 9.23 | 50.75 | 64.21 | -13.46 | QP |
| 0.1860 | 24.66 | 9.23 | 33.89 | 54.21 | -20.32 | AVG |
| 0.2940 | 32.01 | 9.14 | 41.15 | 60.41 | -19.26 | QP |
| 0.2940 | 18.33 | 9.14 | 27.47 | 50.41 | -22.94 | AVG |
| 1.6540 | 27.84 | 9.22 | 37.06 | 56.00 | -18.94 | QP |
| 1.6540 | 16.63 | 9.22 | 25.85 | 46.00 | -20.15 | AVG |
| 3.2260 | 27.39 | 9.26 | 36.65 | 56.00 | -19.35 | QP |
| 3.2260 | 15.58 | 9.26 | 24.84 | 46.00 | -21.16 | AVG |
| 8.4820 | 27.30 | 9.39 | 36.69 | 60.00 | -23.31 | QP |
| 8.4820 | 15.88 | 9.39 | 25.27 | 50.00 | -24.73 | AVG |
| 28.2380 | 29.92 | 9.90 | 39.82 | 60.00 | -20.18 | QP |
| 28.2380 | 16.49 | 9.90 | 26.39 | 50.00 | -23.61 | AVG |

Remark:

- All readings are Quasi-Peak and Average values.
- Margin = Result (Result = Reading + Factor) - Limit



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

| Frequencies (MHz) | Field Strength (micovolts/meter) | Measurement Distance (meters) |
|-------------------|----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

| FREQUENCY (MHz) | (dBuV/m) (at 3M) | |
|-----------------|------------------|---------|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

| Spectrum Parameter | Setting |
|---------------------------------------|-------------------------------|
| Attenuation | Auto |
| Detector | Peak |
| Start Frequency | 1000 MHz(Peak/AV) |
| Stop Frequency | 10th carrier hamonic(Peak/AV) |
| RB / VB (emission in restricted band) | 1 MHz /3MHz |

For Band edge

| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Detector | Peak |
| Start/Stop Frequency | Lower Band Edge: 2300 to 2422 MHz Upper Band Edge: 2452 to 2500 MHz |
| RB / VB (emission in restricted band) | 1 MHz /3MHz |

| Receiver Parameter | Setting |
|------------------------|--------------------------------------|
| Start ~ Stop Frequency | 9kHz~90kHz / RB 200Hz for PK & AV |
| Start ~ Stop Frequency | 90kHz~110kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 110kHz~490kHz / RB 200Hz for PK & AV |
| Start ~ Stop Frequency | 490kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

3.2.2 TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz
- b. The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 TEST RESULT

9KHz-30MHz

| | | | |
|--------------|----------|--------------------|----------------------|
| Temperature: | 20 °C | Relative Humidity: | 48% |
| Pressure: | 1010 hPa | Test Voltage: | DC 3.7V From Battery |
| Test Mode: | TX Mode | Polarization: | -- |

| Freq. (MHz) | Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | State P/F | Test Result |
|----------------|---------------------|-------------------|----------------|--------------|----------------|
| -- | -- | -- | -- | -- | PASS |
| -- | -- | -- | -- | -- | PASS |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


(30MHz - 1000MHz)

| | | | |
|--------------|---|--------------------|----------------------|
| Temperature: | 26 °C | Relative Humidity: | 60% |
| Pressure: | 1010 hPa | Test Voltage: | DC 3.7V From Battery |
| Test Mode: | Mode 1/2/3/4/5/6/7/8/9/10/11/12 (Mode 2-1M worst mode) | Polarization: | Horizontal |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 47.8260 | 42.61 | -20.36 | 22.25 | 40.00 | -17.75 | QP |
| 99.8777 | 35.68 | -19.20 | 16.48 | 43.50 | -27.02 | QP |
| 250.3012 | 37.18 | -16.29 | 20.89 | 46.00 | -25.11 | QP |
| 350.4768 | 33.50 | -13.57 | 19.93 | 46.00 | -26.07 | QP |
| 463.9696 | 37.61 | -9.99 | 27.62 | 46.00 | -18.38 | QP |
| 750.1083 | 35.80 | -3.56 | 32.24 | 46.00 | -13.76 | QP |

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit




| | | | |
|--------------|---|--------------------|----------------------|
| Temperature: | 26 °C | Relative Humidity: | 60% |
| Pressure: | 1010 hPa | Test Voltage: | DC 3.7V From Battery |
| Test Mode: | Mode 1/2/3/4/5/6/7/8/9/10/11/12 (Mode 2-1M worst mode) | Polarization: | Vertical |

| Frequency (MHz) | Reading (dBuV) | Correct Factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 31.3992 | 41.38 | -11.91 | 29.47 | 40.00 | -10.53 | QP |
| 36.6375 | 43.55 | -14.59 | 28.96 | 40.00 | -11.04 | QP |
| 91.1746 | 40.17 | -20.07 | 20.10 | 43.50 | -23.40 | QP |
| 140.8351 | 34.60 | -17.55 | 17.05 | 43.50 | -26.45 | QP |
| 222.9502 | 44.22 | -18.93 | 25.29 | 46.00 | -20.71 | QP |
| 750.1083 | 32.39 | -3.56 | 28.83 | 46.00 | -17.17 | QP |

Remark:.

1. Margin = Result (Result = Reading + Factor) – Limit



(1000MHz-25GHz) Restricted band and Spurious emission Requirements

802.11b Low Channel

| Frequency (MHz) | Reading (dBμV) | Amplifier (dB) | Loss (dB) | Antenna | Corrected | Emission | | Margin (dB) | Detector Type | Comment |
|------------------------|-------------------|-------------------|--------------|------------------|----------------|-------------------|--------------------|----------------|------------------|------------|
| | | | | Factor (dB/m) | Factor (dB) | Level (dBμV/m) | Limits (dBμV/m) | | | |
| Low Channel (2412 MHz) | | | | | | | | | | |
| 3264.70 | 47.99 | 44.70 | 6.70 | 28.20 | -9.80 | 38.19 | 74.00 | -35.81 | PK | Vertical |
| 3264.70 | 38.74 | 44.70 | 6.70 | 28.20 | -9.80 | 28.94 | 54.00 | -25.06 | AV | Vertical |
| 3264.62 | 48.75 | 44.70 | 6.70 | 28.20 | -9.80 | 38.95 | 74.00 | -35.05 | PK | Horizontal |
| 3264.62 | 38.47 | 44.70 | 6.70 | 28.20 | -9.80 | 28.67 | 54.00 | -25.33 | AV | Horizontal |
| 4824.40 | 58.94 | 44.20 | 9.04 | 31.60 | -3.56 | 55.38 | 74.00 | -18.62 | PK | Vertical |
| 4824.40 | 39.39 | 44.20 | 9.04 | 31.60 | -3.56 | 35.83 | 54.00 | -18.17 | AV | Vertical |
| 4824.52 | 59.17 | 44.20 | 9.04 | 31.60 | -3.56 | 55.61 | 74.00 | -18.39 | PK | Horizontal |
| 4824.52 | 38.14 | 44.20 | 9.04 | 31.60 | -3.56 | 34.58 | 54.00 | -19.42 | AV | Horizontal |
| 5359.79 | 44.96 | 44.20 | 9.86 | 32.00 | -2.34 | 42.62 | 74.00 | -31.38 | PK | Vertical |
| 5359.79 | 38.32 | 44.20 | 9.86 | 32.00 | -2.34 | 35.98 | 54.00 | -18.02 | AV | Vertical |
| 5359.75 | 46.28 | 44.20 | 9.86 | 32.00 | -2.34 | 43.94 | 74.00 | -30.06 | PK | Horizontal |
| 5359.75 | 37.34 | 44.20 | 9.86 | 32.00 | -2.34 | 35.00 | 54.00 | -19.00 | AV | Horizontal |
| 7235.97 | 51.92 | 43.50 | 11.40 | 35.50 | 3.40 | 55.32 | 74.00 | -18.68 | PK | Vertical |
| 7235.97 | 32.93 | 43.50 | 11.40 | 35.50 | 3.40 | 36.33 | 54.00 | -17.67 | AV | Vertical |
| 7235.68 | 51.80 | 43.50 | 11.40 | 35.50 | 3.40 | 55.20 | 74.00 | -18.80 | PK | Horizontal |
| 7235.68 | 33.06 | 43.50 | 11.40 | 35.50 | 3.40 | 36.46 | 54.00 | -17.54 | AV | Horizontal |
| 11035.95 | 40.80 | 43.60 | 14.30 | 39.50 | 10.20 | 51.00 | 74.00 | -23.00 | PK | Vertical |
| 11035.95 | 31.14 | 43.60 | 14.30 | 39.50 | 10.20 | 41.34 | 54.00 | -12.66 | AV | Vertical |
| 11036.24 | 39.85 | 43.60 | 14.30 | 39.50 | 10.20 | 50.05 | 74.00 | -23.95 | PK | Horizontal |
| 11036.24 | 30.11 | 43.60 | 14.30 | 39.50 | 10.20 | 40.31 | 54.00 | -13.69 | AV | Horizontal |
| 13299.18 | 40.89 | 42.60 | 15.90 | 38.90 | 12.20 | 53.09 | 74.00 | -20.91 | PK | Vertical |
| 13299.18 | 28.54 | 42.60 | 15.90 | 38.90 | 12.20 | 40.74 | 54.00 | -13.26 | AV | Vertical |
| 13299.44 | 41.07 | 42.60 | 15.90 | 38.90 | 12.20 | 53.27 | 74.00 | -20.73 | PK | Horizontal |
| 13299.44 | 28.61 | 42.60 | 15.90 | 38.90 | 12.20 | 40.81 | 54.00 | -13.19 | AV | Horizontal |
| 15999.74 | 40.94 | 42.70 | 18.00 | 37.10 | 12.40 | 53.34 | 74.00 | -20.66 | PK | Vertical |
| 15999.74 | 28.64 | 42.70 | 18.00 | 37.10 | 12.40 | 41.04 | 54.00 | -12.96 | AV | Vertical |
| 15999.65 | 40.81 | 42.70 | 18.00 | 37.10 | 12.40 | 53.21 | 74.00 | -20.79 | PK | Horizontal |
| 15999.65 | 30.03 | 42.70 | 18.00 | 37.10 | 12.40 | 42.43 | 54.00 | -11.57 | AV | Horizontal |
| 17997.68 | 30.78 | 42.70 | 19.40 | 46.50 | 23.20 | 53.98 | 74.00 | -20.02 | PK | Vertical |
| 17997.68 | 18.74 | 42.70 | 19.40 | 46.50 | 23.20 | 41.94 | 54.00 | -12.06 | AV | Vertical |
| 17997.74 | 30.74 | 42.70 | 19.40 | 46.50 | 23.20 | 53.94 | 74.00 | -20.06 | PK | Horizontal |
| 17997.74 | 18.89 | 42.70 | 19.40 | 46.50 | 23.20 | 42.09 | 54.00 | -11.91 | AV | Horizontal |

802.11b Mid Channel

| Frequency (MHz) | Reading (dBμV) | Amplifier (dB) | Loss (dB) | Antenna | Corrected | Emission | Limits (dBμV/m) | Margin (dB) | Detector Type | Comment |
|------------------------|-------------------|-------------------|--------------|------------------|----------------|-------------------|--------------------|----------------|------------------|------------|
| | | | | Factor (dB/m) | Factor (dB) | Level (dBμV/m) | | | | |
| Low Channel (2437 MHz) | | | | | | | | | | |
| 3264.81 | 49.11 | 44.70 | 6.70 | 28.20 | -9.80 | 39.31 | 74.00 | -34.69 | PK | Vertical |
| 3264.81 | 38.09 | 44.70 | 6.70 | 28.20 | -9.80 | 28.29 | 54.00 | -25.71 | AV | Vertical |
| 3264.85 | 48.14 | 44.70 | 6.70 | 28.20 | -9.80 | 38.34 | 74.00 | -35.66 | PK | Horizontal |
| 3264.85 | 38.79 | 44.70 | 6.70 | 28.20 | -9.80 | 28.99 | 54.00 | -25.01 | AV | Horizontal |
| 4874.52 | 59.25 | 44.20 | 9.04 | 31.60 | -3.56 | 55.69 | 74.00 | -18.31 | PK | Vertical |
| 4874.52 | 38.91 | 44.20 | 9.04 | 31.60 | -3.56 | 35.35 | 54.00 | -18.65 | AV | Vertical |
| 4874.49 | 58.39 | 44.20 | 9.04 | 31.60 | -3.56 | 54.83 | 74.00 | -19.17 | PK | Horizontal |
| 4874.49 | 39.11 | 44.20 | 9.04 | 31.60 | -3.56 | 35.55 | 54.00 | -18.45 | AV | Horizontal |
| 5359.87 | 45.00 | 44.20 | 9.86 | 32.00 | -2.34 | 42.66 | 74.00 | -31.34 | PK | Vertical |
| 5359.87 | 37.76 | 44.20 | 9.86 | 32.00 | -2.34 | 35.42 | 54.00 | -18.58 | AV | Vertical |
| 5359.60 | 46.56 | 44.20 | 9.86 | 32.00 | -2.34 | 44.22 | 74.00 | -29.78 | PK | Horizontal |
| 5359.60 | 38.06 | 44.20 | 9.86 | 32.00 | -2.34 | 35.72 | 54.00 | -18.28 | AV | Horizontal |
| 7310.92 | 51.87 | 43.50 | 11.40 | 35.50 | 3.40 | 55.27 | 74.00 | -18.73 | PK | Vertical |
| 7310.92 | 32.64 | 43.50 | 11.40 | 35.50 | 3.40 | 36.04 | 54.00 | -17.96 | AV | Vertical |
| 7310.70 | 50.93 | 43.50 | 11.40 | 35.50 | 3.40 | 54.33 | 74.00 | -19.67 | PK | Horizontal |
| 7310.70 | 32.53 | 43.50 | 11.40 | 35.50 | 3.40 | 35.93 | 54.00 | -18.07 | AV | Horizontal |
| 9747.76 | 40.39 | 43.60 | 14.30 | 39.50 | 10.20 | 50.59 | 74.00 | -23.41 | PK | Vertical |
| 9747.76 | 30.26 | 43.60 | 14.30 | 39.50 | 10.20 | 40.46 | 54.00 | -13.54 | AV | Vertical |
| 9748.21 | 40.97 | 43.60 | 14.30 | 39.50 | 10.20 | 51.17 | 74.00 | -22.83 | PK | Horizontal |
| 9748.21 | 29.71 | 43.60 | 14.30 | 39.50 | 10.20 | 39.91 | 54.00 | -14.09 | AV | Horizontal |
| 13299.24 | 41.08 | 42.60 | 15.90 | 38.90 | 12.20 | 53.28 | 74.00 | -20.72 | PK | Vertical |
| 13299.24 | 28.54 | 42.60 | 15.90 | 38.90 | 12.20 | 40.74 | 54.00 | -13.26 | AV | Vertical |
| 13299.25 | 40.21 | 42.60 | 15.90 | 38.90 | 12.20 | 52.41 | 74.00 | -21.59 | PK | Horizontal |
| 13299.25 | 29.22 | 42.60 | 15.90 | 38.90 | 12.20 | 41.42 | 54.00 | -12.58 | AV | Horizontal |
| 15999.85 | 40.03 | 42.70 | 18.00 | 37.10 | 12.40 | 52.43 | 74.00 | -21.57 | PK | Vertical |
| 15999.85 | 28.64 | 42.70 | 18.00 | 37.10 | 12.40 | 41.04 | 54.00 | -12.96 | AV | Vertical |
| 15999.68 | 39.81 | 42.70 | 18.00 | 37.10 | 12.40 | 52.21 | 74.00 | -21.79 | PK | Horizontal |
| 15999.68 | 29.85 | 42.70 | 18.00 | 37.10 | 12.40 | 42.25 | 54.00 | -11.75 | AV | Horizontal |
| 17997.70 | 30.73 | 42.70 | 19.40 | 46.50 | 23.20 | 53.93 | 74.00 | -20.07 | PK | Vertical |
| 17997.70 | 19.14 | 42.70 | 19.40 | 46.50 | 23.20 | 42.34 | 54.00 | -11.66 | AV | Vertical |
| 17997.66 | 30.43 | 42.70 | 19.40 | 46.50 | 23.20 | 53.63 | 74.00 | -20.37 | PK | Horizontal |
| 17997.66 | 18.80 | 42.70 | 19.40 | 46.50 | 23.20 | 42.00 | 54.00 | -12.00 | AV | Horizontal |

802.11b High Channel

| Frequency (MHz) | Reading (dBμV) | Amplifier (dB) | Loss (dB) | Antenna | Corrected | Emission | | Margin (dB) | Detector Type | Comment |
|------------------------|-------------------|-------------------|--------------|------------------|----------------|-------------------|--------------------|----------------|------------------|------------|
| | | | | Factor (dB/m) | Factor (dB) | Level (dBμV/m) | Limits (dBμV/m) | | | |
| Low Channel (2462 MHz) | | | | | | | | | | |
| 3264.63 | 47.95 | 44.70 | 6.70 | 28.20 | -9.80 | 38.15 | 74.00 | -35.85 | PK | Vertical |
| 3264.63 | 39.55 | 44.70 | 6.70 | 28.20 | -9.80 | 29.75 | 54.00 | -24.25 | AV | Vertical |
| 3264.76 | 47.84 | 44.70 | 6.70 | 28.20 | -9.80 | 38.04 | 74.00 | -35.96 | PK | Horizontal |
| 3264.76 | 38.53 | 44.70 | 6.70 | 28.20 | -9.80 | 28.73 | 54.00 | -25.27 | AV | Horizontal |
| 4924.55 | 58.44 | 44.20 | 9.04 | 31.60 | -3.56 | 54.88 | 74.00 | -19.12 | PK | Vertical |
| 4924.55 | 38.54 | 44.20 | 9.04 | 31.60 | -3.56 | 34.98 | 54.00 | -19.02 | AV | Vertical |
| 4924.45 | 59.38 | 44.20 | 9.04 | 31.60 | -3.56 | 55.82 | 74.00 | -18.18 | PK | Horizontal |
| 4924.45 | 38.74 | 44.20 | 9.04 | 31.60 | -3.56 | 35.18 | 54.00 | -18.82 | AV | Horizontal |
| 5359.82 | 45.88 | 44.20 | 9.86 | 32.00 | -2.34 | 43.54 | 74.00 | -30.46 | PK | Vertical |
| 5359.82 | 37.55 | 44.20 | 9.86 | 32.00 | -2.34 | 35.21 | 54.00 | -18.79 | AV | Vertical |
| 5359.71 | 45.32 | 44.20 | 9.86 | 32.00 | -2.34 | 42.98 | 74.00 | -31.02 | PK | Horizontal |
| 5359.71 | 37.12 | 44.20 | 9.86 | 32.00 | -2.34 | 34.78 | 54.00 | -19.22 | AV | Horizontal |
| 7385.74 | 51.92 | 43.50 | 11.40 | 35.50 | 3.40 | 55.32 | 74.00 | -18.68 | PK | Vertical |
| 7385.74 | 32.85 | 43.50 | 11.40 | 35.50 | 3.40 | 36.25 | 54.00 | -17.75 | AV | Vertical |
| 7385.84 | 51.64 | 43.50 | 11.40 | 35.50 | 3.40 | 55.04 | 74.00 | -18.96 | PK | Horizontal |
| 7385.84 | 33.78 | 43.50 | 11.40 | 35.50 | 3.40 | 37.18 | 54.00 | -16.82 | AV | Horizontal |
| 9847.78 | 41.13 | 43.60 | 14.30 | 39.50 | 10.20 | 51.33 | 74.00 | -22.67 | PK | Vertical |
| 9847.78 | 30.08 | 43.60 | 14.30 | 39.50 | 10.20 | 40.28 | 54.00 | -13.72 | AV | Vertical |
| 9848.07 | 39.93 | 43.60 | 14.30 | 39.50 | 10.20 | 50.13 | 74.00 | -23.87 | PK | Horizontal |
| 9848.07 | 30.67 | 43.60 | 14.30 | 39.50 | 10.20 | 40.87 | 54.00 | -13.13 | AV | Horizontal |
| 13299.16 | 39.89 | 42.70 | 18.00 | 37.10 | 12.40 | 52.29 | 74.00 | -21.71 | PK | Vertical |
| 13299.16 | 28.54 | 42.70 | 18.00 | 37.10 | 12.40 | 40.94 | 54.00 | -13.06 | AV | Vertical |
| 13299.49 | 40.40 | 42.70 | 18.00 | 37.10 | 12.40 | 52.80 | 74.00 | -21.20 | PK | Horizontal |
| 13299.49 | 28.81 | 42.70 | 18.00 | 37.10 | 12.40 | 41.21 | 54.00 | -12.79 | AV | Horizontal |
| 17997.77 | 31.13 | 42.70 | 19.40 | 46.50 | 23.20 | 54.33 | 74.00 | -19.67 | PK | Vertical |
| 17997.77 | 20.06 | 42.70 | 19.40 | 46.50 | 23.20 | 43.26 | 54.00 | -10.74 | AV | Vertical |
| 17997.62 | 30.66 | 42.70 | 19.40 | 46.50 | 23.20 | 53.86 | 74.00 | -20.14 | PK | Horizontal |
| 17997.62 | 19.16 | 42.70 | 19.40 | 46.50 | 23.20 | 42.36 | 54.00 | -11.64 | AV | Horizontal |

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Scan with 802.11b, 802.11g, 802.11n (HT-20), 802.11n (HT-40) the worst case is 802.11b.

Emission Level = Meter Reading + Factor

Margin = Limit - Emission Level

3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

3.2.6 TEST RESULTS (Band edge Requirements)

| Frequency (MHz) | Reading (dB μ V) | Amplifier (dB) | Loss (dB) | Antenna | Corrected | Emission | | Margin (dB) | Detector | |
|--------------------|-------------------------|-------------------|--------------|------------------|----------------|-------------------------|--------------------------|----------------|----------|------------|
| | | | | Factor (dB/m) | Factor (dB) | Level (dB μ V/m) | Limits (dB μ V/m) | | Type | Comment |
| 802.11b | | | | | | | | | | |
| 2400.00 | 67.71 | 43.80 | 4.91 | 25.90 | -12.99 | 54.72 | 74.00 | -19.28 | PK | Vertical |
| 2400.00 | 52.99 | 43.80 | 4.91 | 25.90 | -12.99 | 40.00 | 54.00 | -14.00 | AV | Vertical |
| 2400.00 | 69.26 | 43.80 | 4.91 | 25.90 | -12.99 | 56.27 | 74.00 | -17.73 | PK | Horizontal |
| 2400.00 | 53.56 | 43.80 | 4.91 | 25.90 | -12.99 | 40.57 | 54.00 | -13.43 | AV | Horizontal |
| 2483.50 | 69.55 | 43.80 | 5.12 | 25.90 | -12.78 | 56.77 | 74.00 | -17.23 | PK | Vertical |
| 2483.50 | 52.19 | 43.80 | 5.12 | 25.90 | -12.78 | 39.41 | 54.00 | -14.59 | AV | Vertical |
| 2483.50 | 70.45 | 43.80 | 5.12 | 25.90 | -12.78 | 57.67 | 74.00 | -16.33 | PK | Horizontal |
| 2483.50 | 52.67 | 43.80 | 5.12 | 25.90 | -12.78 | 39.89 | 54.00 | -14.11 | AV | Horizontal |
| 802.11g | | | | | | | | | | |
| 2400.00 | 66.66 | 43.80 | 4.91 | 25.90 | -12.99 | 53.67 | 74.00 | -20.33 | PK | Vertical |
| 2400.00 | 52.31 | 43.80 | 4.91 | 25.90 | -12.99 | 39.32 | 54.00 | -14.68 | AV | Vertical |
| 2400.00 | 66.02 | 43.80 | 4.91 | 25.90 | -12.99 | 53.03 | 74.00 | -20.97 | PK | Horizontal |
| 2400.00 | 54.44 | 43.80 | 4.91 | 25.90 | -12.99 | 41.45 | 54.00 | -12.55 | AV | Horizontal |
| 2483.50 | 66.47 | 43.80 | 5.12 | 25.90 | -12.78 | 53.69 | 74.00 | -20.31 | PK | Vertical |
| 2483.50 | 53.56 | 43.80 | 5.12 | 25.90 | -12.78 | 40.78 | 54.00 | -13.22 | AV | Vertical |
| 2483.50 | 65.40 | 43.80 | 5.12 | 25.90 | -12.78 | 52.62 | 74.00 | -21.38 | PK | Horizontal |
| 2483.50 | 52.47 | 43.80 | 5.12 | 25.90 | -12.78 | 39.69 | 54.00 | -14.31 | AV | Horizontal |
| 802.11n20 | | | | | | | | | | |
| 2400.00 | 67.29 | 43.80 | 4.91 | 25.90 | -12.99 | 54.30 | 74.00 | -19.70 | PK | Vertical |
| 2400.00 | 52.12 | 43.80 | 4.91 | 25.90 | -12.99 | 39.13 | 54.00 | -14.87 | AV | Vertical |
| 2400.00 | 66.26 | 43.80 | 4.91 | 25.90 | -12.99 | 53.27 | 74.00 | -20.73 | PK | Horizontal |
| 2400.00 | 54.41 | 43.80 | 4.91 | 25.90 | -12.99 | 41.42 | 54.00 | -12.58 | AV | Horizontal |
| 2483.50 | 65.67 | 43.80 | 5.12 | 25.90 | -12.78 | 52.89 | 74.00 | -21.11 | PK | Vertical |
| 2483.50 | 52.34 | 43.80 | 5.12 | 25.90 | -12.78 | 39.56 | 54.00 | -14.44 | AV | Vertical |
| 2483.50 | 66.20 | 43.80 | 5.12 | 25.90 | -12.78 | 53.42 | 74.00 | -20.58 | PK | Horizontal |
| 2483.50 | 53.45 | 43.80 | 5.12 | 25.90 | -12.78 | 40.67 | 54.00 | -13.33 | AV | Horizontal |

| Frequency (MHz) | Reading (dB μ V) | Amplifier (dB) | Loss (dB) | Antenna | Corrected | Emission | Limits (dB μ V/m) | Margin (dB) | Detector Type | Comment |
|---|-------------------------|-------------------|--------------|------------------|----------------|-------------------------|--------------------------|----------------|------------------|------------|
| | | | | Factor (dB/m) | Factor (dB) | Level (dB μ V/m) | | | | |
| 802.11n40 | | | | | | | | | | |
| 2400.00 | 66.40 | 43.80 | 4.91 | 25.90 | -12.99 | 53.41 | 74.00 | -20.59 | PK | Vertical |
| 2400.00 | 53.43 | 43.80 | 4.91 | 25.90 | -12.99 | 40.44 | 54.00 | -13.56 | AV | Vertical |
| 2400.00 | 65.90 | 43.80 | 4.91 | 25.90 | -12.99 | 52.91 | 74.00 | -21.09 | PK | Horizontal |
| 2400.00 | 54.24 | 43.80 | 4.91 | 25.90 | -12.99 | 41.25 | 54.00 | -12.75 | AV | Horizontal |
| 2483.50 | 66.31 | 43.80 | 5.12 | 25.90 | -12.78 | 53.53 | 74.00 | -20.47 | PK | Vertical |
| 2483.50 | 52.93 | 43.80 | 5.12 | 25.90 | -12.78 | 40.15 | 54.00 | -13.85 | AV | Vertical |
| 2483.50 | 65.50 | 43.80 | 5.12 | 25.90 | -12.78 | 52.72 | 74.00 | -21.28 | PK | Horizontal |
| 2483.50 | 52.38 | 43.80 | 5.12 | 25.90 | -12.78 | 39.60 | 54.00 | -14.40 | AV | Horizontal |
| <p>Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Low measurement frequencies is range from 2300 to 2422 MHz, high measurement frequencies is range from 2452 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2300-2422 MHz and 2452-2500 MHz.</p> | | | | | | | | | | |

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 APPLIED PROCEDURES / LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

| Spectrum Parameter | Setting |
|---------------------------------------|---------------------------------|
| Detector | Peak |
| Start/Stop Frequency | 30 MHz to 10th carrier harmonic |
| RB / VB (emission in restricted band) | 100 KHz/300 KHz |
| Trace-Mode: | Max hold |


For Band edge

| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Detector | Peak |
| Start/Stop Frequency | Lower Band Edge: 2300 to 2422 MHz Upper Band Edge: 2452 to 2500 MHz |
| RB / VB (emission in restricted band) | 100 KHz/300 KHz |
| Trace-Mode: | Max hold |

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


4.6 TEST RESULTS

| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX b Mode /CH01, CH06, CH11 | | |

CH 01




CH 06




Band edge

CH 01




CH 11




| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX g Mode /CH01, CH06, CH11 | | |

CH 01




CH06




Band edge

CH 01




CH11




| | | | |
|--------------|----------------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX n Mode(20M) /CH01, CH06, CH11 | | |


CH 01



CH 06




CH 11




Band edge


CH 01




CH 11



CH06




CH09




Band edge

CH03



CH 09



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

| FCC Part15.247) , Subpart C | | | | |
|-----------------------------|------------------------|------------------------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(e) | Power Spectral Density | ≤ 8 dBm (RBW ≥ 3 KHz) | 2400-2483.5 | PASS |

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS


| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX b Mode /CH01, CH06, CH11 | | |

| Frequency | Power Density (dBm/3kHz) | Limit (dBm) | Result |
|-----------|--------------------------|-------------|--------|
| 2412 MHz | -4.424 | ≤8 | PASS |
| 2437 MHz | -4.197 | ≤8 | PASS |
| 2462 MHz | -4.748 | ≤8 | PASS |


TX CH01



TX CH06




TX CH11




| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX g Mode /CH01, CH06, CH11 | | |

| Frequency | Power Density (dBm/3kHz) | Limit (dBm) | Result |
|-----------|--------------------------|-------------|--------|
| 2412 MHz | -8.766 | ≤8 | PASS |
| 2437 MHz | -8.623 | ≤8 | PASS |
| 2462 MHz | -9.839 | ≤8 | PASS |


TX CH01



TX CH06




TX CH11




| | | | |
|--------------|----------------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX n Mode(20M) /CH01, CH06, CH11 | | |

| Frequency | Power Density (dBm/3kHz) | Limit (dBm) | Result |
|-----------|--------------------------|-------------|--------|
| 2412 MHz | -9.137 | ≤8 | PASS |
| 2437 MHz | -8.791 | ≤8 | PASS |
| 2462 MHz | -9.899 | ≤8 | PASS |


TX CH01



TX CH06




TX CH11




| | | | |
|--------------|----------------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1015 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX n Mode(40M) /CH03, CH06, CH09 | | |

| Frequency | Power Density (dBm/3kHz) | Limit(dBm) | Result |
|-----------|--------------------------|------------|--------|
| 2422 MHz | -15.378 | ≤8 | PASS |
| 2437 MHz | -14.039 | ≤8 | PASS |
| 2452 MHz | -14.990 | ≤8 | PASS |


TX CH03



TX CH06



TX CH09



6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

| FCC Part 15.247, Subpart C | | | | |
|----------------------------|-----------|---|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2) | Bandwidth | $\geq 500\text{KHz}$ (6dB bandwidth) | 2400-2483.5 | PASS |


6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


6.6 TEST RESULTS

| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1012 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX b Mode /CH01, CH06, CH11 | | |


Remark: PEAK DETECTOR IS USED

| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2412 MHz | 10.04 | ≥500KHz | PASS |
| 2437 MHz | 10.03 | ≥500KHz | PASS |
| 2462 MHz | 9.555 | ≥500KHz | PASS |


TX CH 01



TX CH 06




TX CH 11




| | | | |
|--------------|-----------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1012 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX g Mode /CH01, CH06, CH11 | | |

| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2412 MHz | 15.41 | ≥500KHz | PASS |
| 2437 MHz | 15.33 | ≥500KHz | PASS |
| 2462 MHz | 15.46 | ≥500KHz | PASS |


TX CH 01



TX CH 06




TX CH 11




| | | | |
|--------------|----------------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1012 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX n Mode(20M) /CH01, CH06, CH11 | | |

| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2412 MHz | 15.14 | ≥500KHz | PASS |
| 2437 MHz | 15.68 | ≥500KHz | PASS |
| 2462 MHz | 15.35 | ≥500KHz | PASS |


TX CH 01



TX CH 06




TX CH 11




| | | | |
|--------------|----------------------------------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1012 hPa | Test Voltage: | DC 3.7V |
| Test Mode: | TX n Mode(40M) /CH03, CH06, CH09 | | |

| Frequency | 6dB Bandwidth (MHz) | Channel Separation (KHz) | Result |
|-----------|---------------------|--------------------------|--------|
| 2422 MHz | 35.18 | ≥500KHz | PASS |
| 2437 MHz | 35.17 | ≥500KHz | PASS |
| 2452 MHz | 35.19 | ≥500KHz | PASS |


TX CH 03



TX CH 06



TX CH 09



7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

| FCC Part 15.247, Subpart C | | | | |
|----------------------------|--------------|-----------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) | Output Power | 1 watt or 30dBm | 2400-2483.5 | PASS |

7.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor&PC

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

| | | | |
|--------------|----------|--------------------|---------|
| Temperature: | 25 °C | Relative Humidity: | 60% |
| Pressure: | 1012 hPa | Test Voltage: | DC 3.7V |

| TX 802.11b Mode | | | | |
|------------------------|-----------|------------------------|----------|-------|
| Test Channel | Frequency | Conducted Output Power | | LIMIT |
| | (MHz) | Peak(dBm) | AVG(dBm) | dBm |
| CH01 | 2412 | 18.74 | 17.83 | 30 |
| CH06 | 2437 | 18.75 | 17.63 | 30 |
| CH11 | 2462 | 18.72 | 17.60 | 30 |

| TX 802.11g Mode | | | | |
|------------------------|-----------|------------------------|----------|-------|
| Test Channel | Frequency | Conducted Output Power | | LIMIT |
| | (MHz) | Peak(dBm) | AVG(dBm) | dBm |
| CH01 | 2412 | 16.18 | 14.55 | 30 |
| CH06 | 2437 | 16.15 | 14.52 | 30 |
| CH11 | 2462 | 16.32 | 14.78 | 30 |

| TX 802.11n20 Mode | | | | |
|--------------------------|-----------|------------------------|----------|-------|
| Test Channel | Frequency | Conducted Output Power | | LIMIT |
| | (MHz) | Peak(dBm) | AVG(dBm) | dBm |
| CH01 | 2412 | 16.12 | 14.52 | 30 |
| CH06 | 2437 | 16.11 | 14.50 | 30 |
| CH11 | 2462 | 16.32 | 14.72 | 30 |

| TX 802.11n40 Mode | | | | |
|--------------------------|-----------|------------------------|----------|-------|
| Test Channel | Frequency | Conducted Output Power | | LIMIT |
| | (MHz) | Peak(dBm) | AVG(dBm) | dBm |
| CH03 | 2422 | 14.38 | 13.12 | 30 |
| CH06 | 2437 | 14.29 | 13.05 | 30 |
| CH09 | 2452 | 14.23 | 13.01 | 30 |

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA


The EUT antenna is Internal PIFA Antenna. It comply with the standard requirement.

APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos



Conducted Measurement Photos



*****END OF THE REPORT*****