8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for Genera	l Population/Uncontrolled	Exposure
--------------------------	---------------------------	----------

Frequency Range Power Density (S)	
(MHz)	(mW/cm2)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

- $S = PG/4\pi R^2$
- S = Power density
- P = power input to antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- \mathbf{R} = distance to the center of radiation of the antenna.

Note:

- 1. Manufacturer declared that the maximum antenna gain is 3.0dBi for TX.
- 2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
- 3. Only record worst case data.

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. FCC ID: 2ADACNEOX6

Report No.: LCS1409160706E

802.11b		
Conducted Peak output Power in dBm	14.74	dBm
Max. Conducted Peak output Power in mW	29.7852	mW
Prediction distance	20	cm
Prediction frequency	2462	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)	2.0	
Power density at prediction frequency(S)	0.01186	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1	mW/cm ²

802.11g

00=1118		
Conducted Peak output Power in dBm	12.53	dBm
Max. Conducted Peak output Power in mW		mW
Prediction distance	20	cm
Prediction frequency	2437	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)		
Power density at prediction frequency(S)	0.00713	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1	mW/cm ²

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.. $Page \ 2 \ of \ 3$

Conducted Peak output Power in dBm	12.44	dBm
Max. Conducted Peak output Power in mW	17.5388	mW
Prediction distance	20	cm
Prediction frequency	2437	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)	2.0	
Power density at prediction frequency(S)	0.00698	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1	mW/cm ²

802.11n-HT20

802.11n-HT40

Conducted Peak output Power in dBm	8.81	dBm
Max. Conducted Peak output Power in mW		mW
Prediction distance	20	cm
Prediction frequency	2437	MHz
Antenna Gain(typical)	3.0	dBi
Antenna Gain(numeric)	2.0	
Power density at prediction frequency(S)	0.00303	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1	mW/cm ²

8.2 Test Results

The power density level worst case at 20 cm is below the uncontrolled exposure limit.