

MPE/RF EXPOSURE TEST REPORT FCC CFR 47 Part 1.1310

Report No.: CATA11-U3 Rev A (FCC MPE)

Company: Catapult Sports Pty Ltd

Model: B001



MPE/RF EXPOSURE TEST REPORT

Company: Catapult Sports Pty Ltd

Model: B001

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: CATA11-U3 Rev A (FCC MPE)

This report supersedes: NONE

Applicant: Catapult Sports Pty Ltd Company

75-83 High St Prahran Melbourne, Victoria 3181

Australia

Issue Date: 21st July 2022

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.

575 Boulder Court Pleasanton California 94566 USA

Phone: +1 (925) 462-0304 Fax: +1 (925) 462-0306 www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: Catapult Sports Pty Ltd B001

To: FCC CFR 47 Part 1.1310
Serial #: CATA11-U3 Rev A

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/($4*\pi*d^2$)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10 ^ (G (dBi)/10)$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

The following technologies never operate simultaneously

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm²) @ 20cm	Power Density Limit (mW/cm²)	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm²) @ Safe Distance
2400.0 - 2483.5 (BLE)	1.0	1.26	1.542	1.43	0.00036	1.00	0.378	0.00036
3993.6 (UWB)	-0.15	0.97	-16.98	0.02	0.000004	1.00	0.04	0.000004
4492.8 (UWB)	-0.15	0.97	-14.69	0.03	0.00001	1.00	0.05	0.00001
6489.6 (UWB)	-0.15	0.97	-7.41	0.18	0.00003	1.00	0.12	0.00003

NOTE: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

NOTE: MPE exemption applies for the B001 as the EIRP is <20mW

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.

Issue Date: 21st July 2022 Page: 3 of 4





575 Boulder Court Pleasanton, California 94566, USA Tel: +1 (925) 462 0304 Fax: +1 (925) 462 0306 www.micomlabs.com