



10/04/2017

Telecommunication Certification Body
UL VS Ltd
Unit 3, Horizon
Wade Road
Kingsland Business Park
Basingstoke
Hampshire
RG24 8AH
United Kingdom

**RF Exposure Considerations for the
Kontakt Micro-Location Sp z o.o.
Kontakt.io Smart Beacon 2**

FCC ID: 2ADAO-SB2-V250

Analysis for FCC SAR Test Exemption

The FCC requires that the device meet the requirements of KDB 447498 D01 v06 to be eligible for SAR test exemption.

The Kontakt.io Smart Beacon 2 Bluetooth Low Energy device operates in the 2400 to 2480MHz operating bands.

The following FCC Rule Parts and procedures are applicable:

- Part 2.1093 – Radiofrequency radiation exposure evaluation: portable devices
- Part 15.247(b)(3) - *For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.*
- Part 15.247(b)(4) - *The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.*
- KDB447498 D01 *Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies*

SAR Exemption Calculation

The following formula as given in KDB 487497 D01 v06, section 4.3.1 is used to calculate if the device meets the FCC SAR exemption requirements.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$
* $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Parameters

Max output conducted power: 6.0dBm (3.98mW) {from Tune Up Spec.}

Separation distance: ≤ 5 mm

{in accordance with KDB 447498 D01 section 4.3.1, point 1)}

Frequency: 2.402GHz

Calculation

At 5mm Separation distance

$$(4.0\text{mW} / 5\text{mm}) \times \sqrt{2.480} \leq 3$$

$$0.8 \times 1.58 = 1.264$$

1.3 is < 3.0 limit for 1-g head SAR

Conclusion

Thus for portable usage, the SAR exclusion condition is fulfilled and SAR evaluation is not required for a separation distance of 5mm or more.