



FCC RADIO TEST REPORT

FCC ID: 2ADBRE1200

Of

Product Name: Feature phone

Brand Name: KALIHO. K-CEL. K-TEN

Model No.: E1200

Series Model: P1000,K109

Test Report Number: STS1409062F01

Issued for

Shenzhen Kaliho Technology Development Limited

19F. Block A, Stars plaza, HuaQiang North Road, FuTian District, Shenzhen,China

Issued by

Shenzhen STS Test Services Co., Ltd.

**1/F A, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong,
Baoan District, Shenzhen, China**

TEL: +86-755 3688 6288

FAX: +86-755 3688 6277

E-mail:sts@stsapp.com

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Kaliho Technology Development Limited
Address : 19F. Block A, Stars plaza, HuaQiang North Road, FuTian District, Shenzhen, China
Manufacturer's Name : Shenzhen Kaliho Technology Development Limited
Address : Floor 4, Flat F, XingHui Technology industrial park, Huaning West Rd., Dalang Street, Longhua, Baoan district, Shenzhen, China
Product name : Feature phone
Band name : KALIHO. K-CEL. K-TEN
Model and/or type reference .. : E1200, P1000, K109
Standards : FCC Part 22H and 24E
Test procedure : ANSI C63.10-2009

This device described above has been tested by STS and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests ... Sep. 30, 2014 ~ Oct. 12, 2014

Date of Issue Otc. 13, 2014

Test Result **Pass**

Testing Engineer : 

(Tony Liu)

Technical Manager : 

(Vita Li)



Authorized Signatory : 

(Bovey Yang)

TABLE OF CONTENTS

1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY.....	6
1.5 MEASUREMENT INSTRUMENTS.....	6
1.6 SPECIAL ACCESSORIES.....	6
1.7 EQUIPMENT MODIFICATIONS	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE.....	7
2.3 GENERAL TECHNICAL REQUIREMENTS	7
2.4 CONFIGURATION OF EUT SYSTEM.....	8
3. SUMMARY OF TEST RESULTS.....	9
4. DESCRIPTION OF TEST MODES.....	9
5. OUTPUT POWER	10
5.1 CONDUCTED OUTPUT POWER.....	10
5.2 RADIATED OUTPUT POWER	11
6. SPURIOUS EMISSION	14
6.1 CONDUCTED SPURIOUS EMISSION.....	14
6.2 RADIATED SPURIOUS EMISSION.....	16
7. FREQUENCY STABILITY	20
7.1 MEASUREMENT METHOD	20
7.2 PROVISIONS APPLICABLE.....	20
7.3 MEASUREMENT RESULT.....	21
8. OCCUPIED BANDWIDTH	23
8.1 MEASUREMENT METHOD	23
8.2 PROVISIONS APPLICABLE.....	23

8.3 MEASUREMENT RESULT	23
9.1 MEASUREMENT METHOD	24
9.2 PROVISIONS APPLICABLE.....	24
9.3 MEASUREMENT RESULT	24
10. BAND EDGE.....	25
10.1 MEASUREMENT METHOD	25
10.2 PROVISIONS APPLICABLE	25
10.3 MEASUREMENT RESULT	25
APPENDIX I.....	26
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION.....	26
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)	32
EMISSION BANDWIDTH (-26dbc).....	32
APPENDIX III.....	37
TEST PLOTS FOR BAND EDGES.....	37
APPENDIX IV.....	40
PHOTOGRAPHS OF TEST SETUP	40

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	Feature phone
Hardware version:	w2_jlk_v1.4.3
Software version:	W2_JLK_V1.5.0
FCC ID:	2ADBRE1200
Frequency Bands:	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input type="checkbox"/> GSM 900 <input type="checkbox"/> DCS 1800 (Non-U.S. Bands) U.S. Bands: <input type="checkbox"/> UMTS FDD Band II <input type="checkbox"/> UMTS FDD Band V Non-U.S. Bands: <input type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band VIII
Bluetooth	Frequency:2402 – 2480 MHz Modulation: GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps),8-DPSK(3Mbps)
Antenna:	Integrated Antenna
Antenna gain:	0 dBi
Power Supply:	DC 3.7V by battery or DC 5.0V supplied by adapter
Battery parameter:	DC 3.7V/1000mAh
Adapter Input:	AC180-240V, 50-60Hz, 150mA
Adapter Output:	DC 5.0V, 500mA
Extreme Vol. Limits:	DC3.4 V to 4.2 V (Nominal DC3.7 V)
Extreme Temp. Tolerance	-10°C to +50°C
** Note: The High Voltage 4.2V and Low Voltage 3.4V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.	

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ADBRE1200** filing to comply with the FCC Part 22H&24E.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China.

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.10: 2009.

FCC Registration No.: 842334

1.5 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CALIBRATION DATE	NEXT CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2014.6.25	2015.6.26
TEST RECEIVER	R&S	ESCI	A0304218	2014.6.25	2015.6.26
COMMUNICATION TESTER	AGILENT	8960	3104A03367	2014.7.20	2015.7.21
COMMUNICATION TESTER	R&S	CMU200	A0304247	2014.7.20	2015.7.21
TEST RECEIVER	R&S	FCKL1528	A0304230	2014.6.25	2015.6.26
LISN	SCHWARZBECK	NSLK8127	A0304233	2014.6.25	2015.6.26
CLIMATE CHAMBER	ALBATROSS	--	--	2014.6.25	2015.6.26
Loop Antenna	Daze	ZN30900N	SEL0097	2014.6.25	2015.6.26
Biological Antenna	A.H. Systems Inc.	SAS-521-4	N/A	2014.4.25	2015.4.26
Horn Antenna	EM	EM-AH-10180	N/A	2014.4.25	2015.4.26

1.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description		FCC Rules
1	Output Power	Conducted output power	22.913(a) / 24.232 (b)
		Radiated output power	
2	Spurious Emission	Conducted spurious emission	2.1051 / 22.917 / 24.238
		Radiated spurious emission	
3	Frequency Stability		2.1055 /24.235
4	Occupied Bandwidth		2.1049 (h)(i)
5	Emission Bandwidth		22.917(b) / 24.238 (b)
6	Band Edge		22.917(b) / 24.238 (b)

2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System



Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	Feature phone	E1200	FCC ID: 2ADBRE1200	EUT

*Note: All the accessories have been used during the test.
the following "EUT" in setup diagram means EUT system.*

3. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result
1	Output Power	Conducted Output Power	22.913(a) / 24.232 (b)	Pass
		Radiated Output Power		
2	Spurious Emission	Conducted Spurious Emission	2.1051 / 22.917 / 24.238	Pass
		Radiated Spurious Emission		
3	Mains Conducted Emission		15.107 / 15.207	Pass
4	Frequency Stability		2.1055 /24.235	Pass
5	Occupied Bandwidth		2.1049 (h)(i)	Pass
6	Emission Bandwidth		22.917(b) / 24.238 (b)	Pass
7	Band Edge		22.917(b) / 24.238 (b)	Pass

4. DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM850 and GSM1900 frequency band.

Note: GSM850, GSM, during the test.

the worst condition (GSM 850) be recorded in the test report if no other modes test data.

5. OUTPUT POWER

5.1 CONDUCTED OUTPUT POWER

5.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(EDGE850, EDGE1900) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

5.1.2 MEASUREMENT RESULT

Conducted Output Power Limits for GSM 850 MHZ

Mode	Nominal Peak Power	Tolerance(dB)
GSM850	32 dBm	+/- 1

Conducted Output Power Limits for PCS 1900 MHZ

Mode	Nominal Peak Power	Tolerance(dB)
GSM1900	29 dBm	+/- 1

GSM 850:

Mode	Frequency (MHz)	Peak Power
GSM850	824.2	32.61
	836.6	32.73
	848.8	32.45

PCS 1900:

Mode	Frequency (MHz)	Peak Power
GSM1900	1850.2	29.56
	1880	29.79
	1909.8	29.65

5.2 RADIATED OUTPUT POWER

5.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- 1 In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as $AR_{pl} = P_{in} + 2.15 - P_r$. The AR_{pl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + AR_{pl}$
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- 6 Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.
9. Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies,

"Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Mode	Nominal Peak Power
GSM 850	<=38.45 dBm (7W)
PCS 1900	<=33 dBm (2W)

5.2.3 MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850 MHZ				
Mode	Frequency	Result		Conclusion
		Max. Peak ERP (dBm)	Polarization Of Max. ERP	
GSM850	824.2	28.58	Horizontal	Pass
	824.2	29.38	Vertical	Pass
	836.6	28.05	Horizontal	Pass
	836.6	26.89	Vertical	Pass
	848.8	29.06	Horizontal	Pass
	848.8	30.15	Vertical	Pass

Radiated Power (E.I.R.P) for PCS 1900 MHZ				
Mode	Frequency	Result		Conclusion
		Max. Peak E.I.R.P.(dBm)	Polarization Of Max. E.I.R.P.	
PCS1900	1850.2	25.57	Horizontal	Pass
	1850.2	26.35	Vertical	Pass
	1880.0	25.86	Horizontal	Pass
	1880.0	27.54	Vertical	Pass
	1909.8	25.65	Horizontal	Pass
	1909.8	27.65	Vertical	Pass

6. SPURIOUS EMISSION

6.1 CONDUCTED SPURIOUS EMISSION

6.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.

2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz	
Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Typical Channels for testing of PCS 1900 MHz	
Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

6.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

6.1.3 MEASUREMENT RESULT

PLEASE REFER TO : APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

Note:

1. Below 30MHZ no Spurious found and The GSM modes is the worst condition.
2. As no emission found in standby or receive mode, no recording in this report.


6.2 RADIATED SPURIOUS EMISSION

6.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS850, GPRS1900)at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = Rx \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107$ (dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of

the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: $\text{Power} = P_{\text{Mea}} + A_{Rpl}$

6.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:

6.2.3 MEASUREMENT RESULT

GSM 850:

The Worst Test Results Channel 128/824.2 MHz					
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1648.379	-35.35	-4.65	-40	-13.00	Horizontal
2471.322	-36.57	-2.1	-38.67	-13.00	Horizontal
4118.454	-31.48	11.8	-19.68	-13.00	Horizontal
1648.379	-38.68	-4.65	-43.33	-13.00	Vertical
2471.322	-41.24	-2.1	-43.34	-13.00	Vertical
4118.454	-40.58	11.8	-28.78	-13.00	Vertical
The Worst Test Results Channel 190/836.6 MHz					
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1673.317	-36.67	-4.97	-41.64	-13.00	Horizontal
2506.234	-42.28	-2.1	-44.38	-13.00	Horizontal
3339.401	-36.29	3.46	-32.83	-13.00	Horizontal
1673.317	-37.68	-4.97	-42.65	-13.00	Vertical
2506.234	-32.48	-2.1	-34.58	-13.00	Vertical
3339.401	-36.29	3.46	-32.83	-13.00	Vertical
The Worst Test Results Channel 251/848.8 MHz					
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1698.254	-35.57	-4.94	-40.51	-13.00	Horizontal
2541.147	-43.46	-2.02	-45.48	-13.00	Horizontal
3384.835	-45.87	3.49	-42.38	-13.00	Horizontal
1698.254	-35.42	-4.94	-40.36	-13.00	Vertical
2541.147	-41.52	-2.02	-43.54	-13.00	Vertical
3384.835	-37.12	3.49	-33.63	-13.00	Vertical

Note: Below 30MHz no Spurious found and The GSM modes is the worst condition.

1900:

The Worst Test Results for Channel 512/1850.2MHz

Frequency(MHz)	Power(dBm)	ARPL (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1793.017	-36.69	-3.54	-40.23	-13.00	Horizontal
3720.698	-43.69	13.01	-30.68	-13.00	Horizontal
5543.641	-42.79	14.7	-28.09	-13.00	Horizontal
1793.017	-34.68	-3.54	-38.22	-13.00	Vertical
3720.698	-45.58	13.01	-32.57	-13.00	Vertical
5543.641	-41.89	14.7	-27.19	-13.00	Vertical

The Worst Test Results for Channel 661/1880.0MHz

Frequency(MHz)	Power(dBm)	ARPL (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1822.943	-36.75	-3.48	-40.23	-13.00	Horizontal
3763.092	-52.23	13.8	-38.43	-13.00	Horizontal
5628.429	-43.57	15.4	-28.17	-13.00	Horizontal
1822.943	-31.59	-3.48	-35.07	-13.00	Vertical
3763.092	-43.06	13.8	-29.26	-13.00	Vertical
5628.429	-33.59	15.4	-18.19	-13.00	Vertical

The Worst Test Results for Channel 810/1909.8MHz

Frequency(MHz)	Power(dBm)	ARPL (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1967.581	-32.79	-3.26	-36.05	-13.00	Horizontal
3847.88	-45.56	12.4	-33.16	-13.00	Horizontal
5713.217	-37.29	15.75	-21.54	-13.00	Horizontal
1967.581	-32.84	-3.26	-36.1	-13.00	Vertical
3847.88	-45.39	12.4	-32.99	-13.00	Vertical
5713.217	-38.09	15.75	-22.34	-13.00	Vertical

Note: Below 30MHz no Spurious found and The GSM modes is the worst condition.

7. FREQUENCY STABILITY

7.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 . Measure the carrier frequency at room temperature.
- 2 .Subject the EUT to overnight soak at -10°C.
- 3 .With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band , channel 190 for GSM 850 band and channel 4183 for UMTS band V measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 .Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 .Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 .Subject the EUT to overnight soak at +50°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 .Repeat the above measurements at 10°C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 .At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

7.2 PROVISIONS APPLICABLE

7.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

7.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

7.3 MEASUREMENT RESULT

Frequency Error Against Voltage for GSM 850 band		
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.4	23	0.028
3.7	43	0.051
4.2	36	0.043

Frequency Error Against Temperature for GSMS850 band		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	23	0.028
0	32	-0.038
10	25	0.030
20	13	-0.016
30	18	-0.022
40	10	0.012
50	26	0.031

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for GSM1900 band		
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.4	23	0.012
3.7	19	0.010
4.2	25	0.013

Frequency Error Against Temperature for GSM1900 band		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	27	0.014
0	9	0.005
10	25	0.013
20	19	0.010
30	32	0.017
40	9	0.005
50	23	0.012

Note: The EUT doesn't work below -10

8. OCCUPIED BANDWIDTH

8.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

8.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

8.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM 850 band		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
Low Channel	824.2	257.78
Middle Channel	836.6	244.18
High Channel	848.8	239.81

Occupied Bandwidth (99%) for GSM1900 band		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
Low Channel	1850.2	244.89
Middle Channel	1880.0	248.15
High Channel	1909.8	245.63

9. EMISSION BANDWIDTH

9.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

9.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

9.3 MEASUREMENT RESULT

Emission Bandwidth (-26dBc) for GSM850 band		
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)
Low Channel	824.2	315.00
Middle Channel	836.6	318.30
High Channel	848.8	313.29

Emission Bandwidth (-26dBc) for GSM1900 band		
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)
Low Channel	1850.2	315.72
Middle Channel	1880.0	314.56
High Channel	1909.8	308.00

10. BAND EDGE

10.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

10.2 PROVISIONS APPLICABLE

as Specified in FCC rules of 22.917(b) and 24.238(b)


10.3 MEASUREMENT RESULT

Please refers to Appendix III for compliance test plots for band edges


APPENDIX I

TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION


CONDUCTED EMISSION IN GSM 850 BAND
Conducted Emission Transmitting Mode CH 128 30MHz – 10GHz



Conducted Emission Transmitting Mode CH 190 30MHz – 10GHz





Conducted Emission Transmitting Mode CH 251 30MHz – 10GHz





CONDUCTED EMISSION IN GSM1900 BAND



Conducted Emission Transmitting Mode CH 512 30MHz – 20GHz



Conducted Emission Transmitting Mode CH 661 30MHz – 20GHz




Conducted Emission Transmitting Mode CH 810 30MHz – 20GHz




APPENDIX II
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)
EMISSION BANDWIDTH (-26dBC)

Occupied Bandwidth (99%) GSM 850 BAND CH 128




Transmit Freq Error 238.217 Hz
x dB Bandwidth 315.003 kHz

Occupied Bandwidth (99%) GSM 850 BAND CH 190



Transmit Freq Error 1.902 kHz
x dB Bandwidth 318.296 kHz

Occupied Bandwidth (99%) GSM 850 BAND CH 251




Transmit Freq Error -941.991 Hz
x dB Bandwidth 313.292 kHz

Occupied Bandwidth (99%) PCS 1900 BAND CH 512

* Agilent

R T




Transmit Freq Error 1.607 kHz
x dB Bandwidth 315.718 kHz

Occupied Bandwidth (99%) PCS 1900 BAND CH 661


* Agilent

R T



Transmit Freq Error -1.864 kHz
x dB Bandwidth 314.561 kHz


Occupied Bandwidth (99%) PCS 1900 BAND CH 810




Transmit Freq Error -1.603 kHz
x dB Bandwidth 307.998 kHz

APPENDIX III
TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251



Low Band Edge PCS 1900 BAND CH 512





High Band Edge PCS 1900 BAND CH 810



APPENDIX IV

PHOTOGRAPHS OF TEST SETUP

RADIATED SPURIOUS EMISSION



----END OF REPORT----