

*Testing Tomorrow's Technology*

**Application**

**For**

**Part 2, Subpart J, Paragraph 2.907 Equipment Authorization of Certification for an Intentional Radiator per Part 15, Subpart E, paragraphs 15.401, 15.403, 15.405 and 15.407**

**And**

**RSS-247 Issue 1 of Industry Canada**

**For the**

**Acuity Brands Lighting Inc. and  
Acuity Brands Technology Services, Inc.**


**Model: ACWIFI001**

**FCC ID: 2ADCB-ACWIFI001  
IC: 6715A-ACWIFI001**

**UST Project: 16-0141  
Issue Date: September 23, 2016**

Total Pages in This Report: 266

**3505 Francis Circle Alpharetta, GA 30004  
PH: 770-740-0717 Fax: 770-740-1508  
[www.ustech-lab.com](http://www.ustech-lab.com)**



Testing Tomorrow's Technology

I certify that I am authorized to sign for the Test Agency and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

US TECH (Agent Responsible For Test):

By: Alan Ghasiani

Name: 

Title: Compliance Engineer – President

Date September 23, 2016



NVLAP LAB CODE 200162-0

**This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of US Tech. The results contained in this report are subject to the adequacy and representative character of the sample provided. This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government.**

**3505 Francis Circle Alpharetta, GA 30004  
PH: 770-740-0717 Fax: 770-740-1508  
[www.ustech-lab.com](http://www.ustech-lab.com)**



## Table of Contents

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
<b>1</b>	<b>General Information</b>	<b>15</b>
1.1	Purpose of this Report	15
1.2	Characterization of Test Sample	15
1.3	Product Description	15
1.4	Configuration of Tested System	16
1.5	Test Facility	16
1.6	Related Submittals	16
<b>2</b>	<b>Tests and Measurements</b>	<b>18</b>
2.1	Test Equipment	18
2.2	Modifications to EUT Hardware	19
2.3	Number of Measurements for Intentional Radiators (15.31(m))	20
2.4	Frequency Range of Radiated Measurements (Part 15.33)	20
2.4.1	Intentional Radiator	20
2.4.2	Unintentional Radiator	20
2.5	Measurement Detector Function and Bandwidth (Part 15.35)	21
2.5.1	Detector Function and Associated Bandwidth	21
2.5.2	Corresponding Peak and Average Requirements	21
2.5.3	Pulsed Transmitter Averaging	21
2.6	Duty Cycle Verification (Part 15.35 (c))	22
2.7	EUT Antenna Requirements (Part 15.203)	30
2.8	Maximum Peak Conducted Output Power (Part 15.407 (a) (1,2,3))	31
2.9	Power Spectral Density (Part 15.407(a) (1-5)) (IC RSS 247 5.1, 5.2)	36
2.10	Restricted Bands of Operation (Part 15.205)	85
2.11	Intentional Radiator, Power Line Conducted Emissions (Part 15.207)	85
2.12	Intentional Radiator, Radiated Emissions (Part 15.209, 15.407) (IC RSS 247, 6.2)	87
2.12.1	Spurious Emissions, Radiated Measurements	88
2.12.2	Spurious Emissions Radiated Measurements, Antenna 1	90
2.12.3	Spurious Emissions Radiated Measurements, Antenna 2	98
2.12.4	Undesirable emissions (Part 15.407(b))	106
2.13	Undesired Emissions (Part 15.407(b))	164
	For compliance to RSS-247 in the band 5725-5850 MHz, emissions at frequencies from the band edges to 10 MHz above or below the band edges shall not exceed -17 dBm/MHz e.i.r.p. For emissions at frequencies more than 10 MHz above or below the band edges, the emissions power shall not exceed -27 dBm/MHz. ...	183
2.14	Unwanted Emissions in the Restricted Bands (Part 15.205, 15.209)	192
2.14.1	Antenna 1 Measurements	193
2.14.2	Antenna 2 Measurements	212

2.15 Six (6) dB Bandwidth per Part 15.407(e), ..... 231  
2.16 99% Occupied Bandwidth (15.407(a), IC RSS 247, 6.4) ..... 238  
2.17 Frequency Stability ..... 265  
2.18 Measurement Uncertainty ..... 266  
    2.18.1 Conducted Emissions Measurement Uncertainty ..... 266  
    2.18.2 Radiated Emissions Measurement Uncertainty ..... 266

**List of Figures**

<b><u>Figures</u></b>	<b><u>Title</u></b>	<b><u>Page</u></b>
Figure 1.	Block Diagram of Test Configuration .....	17
Figure 2.	802.11a(20), Ch 36 6 Mbps .....	22
Figure 3.	802.11a(20), Ch 36, 72 Mbps .....	23
Figure 4.	802.11n(20), Ch 36, MCS0 .....	24
Figure 5.	802.11n(20), Ch 36, MCS7 .....	25
Figure 6.	802.11a(40), Ch 38, 6 Mbps .....	26
Figure 7.	802.11a(40), Ch 38, 72 Mbps .....	27
Figure 8.	802.11n(40), Ch 38, MCS0 .....	28
Figure 9.	802.11n(40), Ch 38, MCS7 .....	29
Figure 10.	Antenna Conducted Output Power, 802.11a Channel 36 .....	41
Figure 11.	Antenna Conducted Output Power, 802.11a 5.22 GHz .....	42
Figure 12.	Antenna Conducted Output Power, 802.11a Channel 48 .....	43
Figure 13.	Antenna Conducted Output Power, 802.11a Channel 52 .....	44
Figure 14.	Antenna Conducted Output Power, 802.11a 5.28 GHz .....	45
Figure 15.	Antenna Conducted Output Power, 802.11a Channel 64 .....	46
Figure 16.	Antenna Conducted Output Power, 802.11a Channel 100 .....	47
Figure 17.	Antenna Conducted Output Power, 802.11a Channel 112 .....	48
Figure 18.	Antenna Conducted Output Power, 802.11a Channel 132 .....	49
Figure 19.	Antenna Conducted Output Power, 802.11a Channel 140 .....	50
Figure 20.	Antenna Conducted Output Power, 802.11a Channel 149 .....	51
Figure 21.	Antenna Conducted Output Power, 802.11a 5.785 GHz .....	52
Figure 22.	Antenna Conducted Output Power, 802.11a Channel 165 .....	53
Figure 23.	Antenna Conducted Output Power, 802.11n Channel 36 .....	54
Figure 24.	Antenna Conducted Output Power, 802.11n 5.22 GHz .....	55
Figure 25.	Antenna Conducted Output Power, 802.11n Channel 48 .....	56
Figure 26.	Antenna Conducted Output Power, 802.11n Channel 52 .....	57
Figure 27.	Antenna Conducted Output Power, 802.11n 5.28 GHz .....	58
Figure 28.	Antenna Conducted Output Power, 802.11n Channel 64 .....	59
Figure 29.	Antenna Conducted Output Power, 802.11n Channel 100 .....	60

Figure 30. Antenna Conducted Output Power, 802.11n Channel 112 ..... 61  
Figure 31. Antenna Conducted Output Power, 802.11n Channel 132 ..... 62  
Figure 32. Antenna Conducted Output Power, 802.11n Channel 140 ..... 63  
Figure 33. Antenna Conducted Output Power, 802.11n Channel 149 ..... 64  
Figure 34. Antenna Conducted Output Power, 802.11n 5.785 GHz ..... 65  
Figure 35. Antenna Conducted Output Power, 802.11n Channel 165 ..... 66  
Figure 36. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 38  
..... 67  
Figure 37. Antenna Conducted Output Power, 802.11a with 40 MHz BW ..... 68  
Figure 38. Antenna Conducted Output Power, 802.11a with 40 MHz BW ..... 69  
Figure 39. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 62  
..... 70  
Figure 40. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel  
102..... 71  
Figure 41. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel  
110..... 72  
Figure 42. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel  
134..... 73  
Figure 43. Antenna Conducted Output Power, 802.11a with 40 MHz BW ..... 74  
Figure 44. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel  
159..... 75  
Figure 45. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 38  
..... 76  
Figure 46. Antenna Conducted Output Power, 802.11n with 40 MHz BW ..... 77  
Figure 47. Antenna Conducted Output Power, 802.11n with 40 MHz BW ..... 78  
Figure 48. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 62  
..... 79  
Figure 49. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel  
102..... 80  
Figure 50. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel  
110..... 81  
Figure 51. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel  
134..... 82  
Figure 52. Antenna Conducted Output Power, 802.11n with 40 MHz BW ..... 83  
Figure 53. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel  
159..... 84  
Figure 54. Antenna Conducted Emissions Channel 36 802.11a, Part 1 ..... 107  
Figure 55. Antenna Conducted Emissions Channel 36 802.11a, Part 2 ..... 108  
Figure 56. Antenna Conducted Emissions Channel 36 802.11a, Part 3 ..... 109  
Figure 57. Antenna Conducted Emissions Channel 48 802.11a, Part 1 ..... 110  
Figure 58. Antenna Conducted Emissions Channel 48 802.11a, Part 2 ..... 111  
Figure 59. Antenna Conducted Emissions Channel 48 802.11a, Part 3 ..... 112

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

Figure 60. Antenna Conducted Emissions Channel 64 802.11a, Part 1 ..... 113  
Figure 61. Antenna Conducted Emissions Channel 64 802.11a, Part 2 ..... 114  
**Figure 62. Antenna Conducted Emissions Channel 64 802.11a, Part 3 ..... 115**  
Figure 63. Antenna Conducted Emissions Channel 100 802.11a, Part 1 ..... 116  
Figure 64. Antenna Conducted Emissions Channel 100 802.11a, Part 2 ..... 117  
Figure 65. Antenna Conducted Emissions Channel 100 802.11a, Part 3 ..... 118  
Figure 66. Antenna Conducted Emissions Channel 140 802.11a, Part 1 ..... 119  
Figure 67. Antenna Conducted Emissions Channel 140 802.11a, Part 2 ..... 120  
Figure 68. Antenna Conducted Emissions Channel 140 802.11a, Part 3 ..... 121  
Figure 69. Antenna Conducted Emissions Channel 149 802.11a, Part 1 ..... 122  
Figure 70. Antenna Conducted Emissions Channel 149 802.11a, Part 2 ..... 123  
Figure 71. Antenna Conducted Emissions Channel 149 802.11a, Part 3 ..... 124  
Figure 72. Antenna Conducted Emissions Channel 165 802.11a, Part 1 ..... 125  
Figure 73. Antenna Conducted Emissions Channel 165 802.11a, Part 2 ..... 126  
Figure 74. Antenna Conducted Emissions Channel 165 802.11a, Part 3 ..... 127  
Figure 75. Antenna Conducted Emissions Channel 36 802.11n, Part 1 ..... 128  
Figure 76. Antenna Conducted Emissions Channel 36 802.11n, Part 2 ..... 129  
Figure 77. Antenna Conducted Emissions Channel 36 802.11n, Part 3 ..... 130  
Figure 78. Antenna Conducted Emissions Channel 48 802.11n, Part 1 ..... 131  
Figure 79. Antenna Conducted Emissions Channel 48 802.11n, Part 2 ..... 132  
Figure 80. Antenna Conducted Emissions Channel 48 802.11n, Part 3 ..... 133  
Figure 81. Antenna Conducted Emissions Channel 64 802.11n, Part 1 ..... 134  
Figure 82. Antenna Conducted Emissions Channel 64 802.11n, Part 2 ..... 135  
Figure 83. Antenna Conducted Emissions Channel 64 802.11n, Part 3 ..... 136  
Figure 84. Antenna Conducted Emissions Channel 100 802.11n, Part 1 ..... 137  
Figure 85. Antenna Conducted Emissions Channel 100 802.11n, Part 2 ..... 138  
Figure 86. Antenna Conducted Emissions Channel 100 802.11n, Part 3 ..... 139  
Figure 87. Antenna Conducted Emissions Channel 140 802.11n, Part 1 ..... 140  
Figure 88. Antenna Conducted Emissions Channel 140 802.11n, Part 2 ..... 141  
Figure 89. Antenna Conducted Emissions Channel 140 802.11n, Part 3 ..... 142  
Figure 90. Antenna Conducted Emissions Channel 149 802.11n, Part 1 ..... 143  
Figure 91. Antenna Conducted Emissions Channel 149 802.11n, Part 2 ..... 144  
Figure 92. Antenna Conducted Emissions Channel 149 802.11n, Part 3 ..... 145  
Figure 93. Antenna Conducted Emissions Channel 165 802.11n, Part 1 ..... 146  
Figure 94. Antenna Conducted Emissions Channel 165 802.11n, Part 2 ..... 147  
Figure 95. Antenna Conducted Emissions Channel 165 802.11n, Part 3 ..... 148  
Figure 96. Antenna Conducted Emissions Channel 38 802.11n, Part 1 ..... 149  
Figure 97. Antenna Conducted Emissions Channel 38 802.11n, Part 2 ..... 150  
Figure 98. Antenna Conducted Emissions Channel 38 802.11n, Part 3 ..... 151  
Figure 99. Antenna Conducted Emissions Channel 62 802.11n, Part 1 ..... 152  
Figure 100. Antenna Conducted Emissions Channel 62 802.11n, Part 2 ..... 153  
Figure 101. Antenna Conducted Emissions Channel 62 802.11n, Part 3 ..... 154

Figure 102. Antenna Conducted Emissions Channel 102 802.11n, Part 1 ..... 155  
Figure 103. Antenna Conducted Emissions Channel 102 802.11n, Part 2 ..... 156  
Figure 104. Antenna Conducted Emissions Channel 102 802.11n, Part 3 ..... 157  
Figure 105. Antenna Conducted Emissions Channel 110 802.11n, Part 1 ..... 158  
Figure 106. Antenna Conducted Emissions Channel 110 802.11n, Part 2 ..... 159  
Figure 107. Antenna Conducted Emissions Channel 110 802.11n, Part 3 ..... 160  
Figure 108. Antenna Conducted Emissions Channel 159 802.11n, Part 1 ..... 161  
Figure 109. Antenna Conducted Emissions Channel 159 802.11n, Part 2 ..... 162  
Figure 110. Antenna Conducted Emissions Channel 159 802.11n, Part 3 ..... 163  
Figure 111. 5.15 GHz Band Edge Compliance, 802.11a ..... 165  
Figure 112. 5.25 GHz Band Edge Compliance, 802.11a ..... 166  
Figure 113. 5.35 GHz Band Edge Compliance, 802.11a ..... 167  
Figure 114. 5.47 GHz Band Edge Compliance, 802.11a ..... 168  
Figure 115. 5.725 GHz Band Edge Compliance, 802.11a ..... 169  
Figure 116. 5.15 GHz Band Edge Compliance 802.11a 40 MHz BW ..... 170  
Figure 117. 5.25 GHz Band Edge Compliance 802.11a 40 MHz BW ..... 171  
Figure 118. 5.35 GHz Band Edge Compliance 802.11a 40 MHz BW ..... 172  
Figure 119. 5.47 GHz Band Edge Compliance 802.11a 40 MHz BW ..... 173  
Figure 120. 5.15 GHz Band Edge Compliance, 802.11n ..... 174  
Figure 121. 5.25 GHz Band Edge Compliance, 802.11n ..... 175  
Figure 122. 5.35 GHz Band Edge Compliance, 802.11n ..... 176  
Figure 123. 5.47 GHz Band Edge Compliance, 802.11n ..... 177  
Figure 124. 5.725 GHz Band Edge Compliance, 802.11n ..... 178  
Figure 125. 5.15 GHz Band Edge Compliance 802.11n 40 MHz BW ..... 179  
Figure 126. 5.25 GHz Band Edge Compliance 802.11n 40 MHz BW ..... 180  
Figure 127. 5.35 GHz Band Edge Compliance 802.11n 40 MHz BW ..... 181  
Figure 128. 5.47 GHz Band Edge Compliance 802.11n 40 MHz BW ..... 182  
Figure 129. 802.11a 5.725 GHz Band edge ..... 184  
Figure 130. 802.11n 5.725 GHz Band edge ..... 185  
Figure 131. 802.11a(40) 5.725 GHz Band Edge ..... 186  
Figure 132. 802.11n(40) 5.725 GHz Band edge ..... 187  
Figure 133. 802.11a 5.85 GHz Band edge ..... 188  
Figure 134. 802.11n 5.85 GHz Band edge ..... 189  
Figure 135. 802.11a(40), 5.85 GHz Band edge ..... 190  
Figure 136. 802.11n(40), 5.85 GHz Bandedge ..... 191  
Figure 137. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11a –  
Peak ..... 193  
Figure 138. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11a -  
Average ..... 194  
Figure 139. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11a –  
Peak ..... 195



Figure 140. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11a - Average ..... 196

Figure 141. Restricted Band 5.35 – 5.46 GHz operating on Channel 100, 802.11a – Peak..... 197

Figure 142. Restricted Band 5.35- 5.46 GHz operating on Channel 100, 802.11a - Average ..... 198

Figure 143. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11n - Peak..... 199

Figure 144. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11n – Average ..... 200

Figure 145. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11n - Peak..... 201

Figure 146. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11n – Average ..... 202

Figure 147. Restricted Band 5.35 - 5.46 GHz operating on Channel 100, 802.11n - Peak..... 203

Figure 148. Restricted Band 5.35 - 5.46 GHz operating on Channel 100, 802.11n – Average ..... 204

Figure 149. Restricted Band 4.5 - 5.15 GHz operating on Channel 38, 802.11n 40 MHz BW – Peak..... 205

Figure 150. Restricted Band 4.5 - 5.15 GHz operating on Channel 38, 802.11n 40 MHz BW – Average ..... 206

Figure 151. Restricted Band 5.35 - 5.46 GHz operating on Channel 62, 802.11n 40 MHz BW – Peak..... 207

Figure 152. Restricted Band 5.35 - 5.46 GHz operating on Channel 62, 802.11n 40 MHz BW – Average ..... 208

Figure 153. Restricted Band 5.35 - 5.46 GHz operating on Channel 102, 802.11n 40 MHz BW – Peak..... 210

Figure 154. Restricted Band 5.35 - 5.46 GHz operating on Channel 102, 802.11n 40 MHz BW – Average ..... 211

Figure 155. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11a – Peak..... 212

Figure 156. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11a - Average ..... 213

Figure 157. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11a – Peak..... 214

Figure 158. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11a - Average ..... 215

Figure 159. Restricted Band 5.35 – 5.46 GHz operating on Channel 100, 802.11a – Peak..... 216

Figure 160. Restricted Band 5.35- 5.46 GHz operating on Channel 100, 802.11a - Average ..... 217

Figure 161. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11n - Peak..... 218  
Figure 162. Restricted Band 4.5 - 5.15 GHz operating on Channel 36, 802.11n – Average ..... 219  
Figure 163. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11n - Peak..... 220  
Figure 164. Restricted Band 5.35 - 5.46 GHz operating on Channel 64, 802.11n – Average ..... 221  
Figure 165. Restricted Band 5.35 - 5.46 GHz operating on Channel 100, 802.11n - Peak..... 222  
Figure 166. Restricted Band 5.35 - 5.46 GHz operating on Channel 100, 802.11n – Average ..... 223  
Figure 167. Restricted Band 4.5 - 5.15 GHz operating on Channel 38, 802.11n 40 MHz BW – Peak..... 224  
Figure 168. Restricted Band 4.5 - 5.15 GHz operating on Channel 38, 802.11n 40 MHz BW – Average ..... 225  
Figure 169. Restricted Band 5.35 - 5.46 GHz operating on Channel 62, 802.11n 40 MHz BW – Peak..... 226  
Figure 170. Restricted Band 5.35 - 5.46 GHz operating on Channel 62, 802.11n 40 MHz BW – Average ..... 227  
Figure 171. Restricted Band 5.35 - 5.46 GHz operating on Channel 102, 802.11n 40 MHz BW – Peak..... 228  
Figure 172. Restricted Band 5.35 - 5.46 GHz operating on Channel 102, 802.11n 40 MHz BW – Average ..... 229  
Figure 173. Six dB Bandwidth 802.11a - 15.407 - Low Channel..... 232  
Figure 174. Six dB Bandwidth 802.11a - 15.407 - High Channel..... 233  
Figure 175. Six dB Bandwidth 802.11n - 15.407 - Low Channel..... 234  
Figure 176. Six dB Bandwidth 802.11n - 15.407 - High Channel..... 235  
Figure 177. Six dB Bandwidth 802.11n - 15.407 - High Channel (40MHz) ..... 236  
Figure 178. Six dB Bandwidth 802.11a - 15.407 - High Channel (40MHz) ..... 237  
Figure 179. 26 dB BW and OBW -802.11a- Channel 36..... 241  
Figure 180. 26 dB BW and OBW -802.11a- Channel 48..... 242  
Figure 181. 26 dB BW and OBW -802.11a- Channel 52..... 243  
Figure 182. 26 dB BW and OBW -802.11a- Channel 64..... 244  
Figure 183. 26 dB BW and OBW -802.11a- Channel 100..... 245  
Figure 184. 26 dB BW and OBW -802.11a- Channel 112..... 246  
Figure 185. 26 dB BW and OBW -802.11a- Channel 132..... 247  
Figure 186. 26 dB BW and OBW -802.11a- Channel 140..... 248  
Figure 187. 26 dB BW and OBW -802.11a (40 MHz) Channel 38 ..... 249  
Figure 188. 26 dB BW and OBW -802.11a (40 MHz) Channel 62 ..... 250  
Figure 189. 26 dB BW and OBW -802.11a (40MHz) Channel 102 ..... 251  
Figure 190. 26 dB BW and OBW -802.11a (40 MHz) Channel 110 ..... 252

Figure 191. 26 dB BW and OBW -802.11n- Channel 36..... 253  
 Figure 192. 26 dB BW and OBW -802.11n- Channel 48..... 254  
 Figure 193. 26 dB BW and OBW -802.11n- Channel 52..... 255  
 Figure 194. 26 dB BW and OBW -802.11n- Channel 64..... 256  
 Figure 195. 26 dB BW and OBW -802.11n- Channel 100..... 257  
 Figure 196. 26 dB BW and OBW -802.11n- Channel 112..... 258  
 Figure 197. 26 dB BW and OBW -802.11n- Channel 132..... 259  
 Figure 198. 26 dB BW and OBW -802.11n- Channel 140..... 260  
 Figure 199. 26 dB BW and OBW -802.11n 40 MHz BW- Channel 38..... 261  
 Figure 200. 26 dB BW and OBW -802.11n 40 MHz BW - Channel 62..... 262  
 Figure 201. 26 dB BW and OBW -802.11n 40 MHz BW - Channel 102..... 263  
 Figure 202. 26 dB BW and OBW -802.11n 40 MHz BW - Channel 110..... 264

**List of Tables**

<b><u>Table</u></b>	<b><u>Title</u></b>	<b><u>Page</u></b>
Table 1.	EUT and Peripherals.....	17
Table 2.	Test Instruments .....	18
Table 3.	Number of Test Frequencies for Intentional Radiators.....	20
Table 4.	Allowed Antenna(s) .....	30
Table 5.	Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11a.....	32
Table 6.	Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11n.....	33
Table 7.	Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11a 40 MHz BW.....	34
Table 8.	Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11n 40 MHz BW.....	35
Table 9.	Power Spectral Density for 802.11a in the Lower Frequency Bands .....	37
Table 10.	Power Spectral Density for 802.11a in the Upper Frequency Bands .....	37
Table 11.	Power Spectral Density for 802.11n in the Lower Frequency Bands .....	38
Table 12.	Power Spectral Density for 802.11n in the Upper Frequency Bands .....	38
Table 13.	Power Spectral Density for 802.11a 40 MHz BW in the Lower Frequency Bands.....	39
Table 14.	Power Spectral Density for 802.11a 40 MHz BW in the Upper Frequency Bands.....	39
Table 15.	Power Spectral Density for 802.11n 40 MHz BW in the Lower Frequency Bands.....	40
Table 16.	Power Spectral Density for 802.11n 40 MHz BW in the Upper Frequency Bands.....	40
Table 17.	Transmitter Power Line Conducted Emissions Test Data, Part 15.207 ...	86
Table 18.	Intentional Radiator, Spurious Radiated Emissions (Part 15.209), .....	88
Table 19.	Intentional Radiator, Spurious Radiated Emissions (Part 15.209), .....	88

Table 20. Intentional Radiator, Spurious Radiated Emissions (Part 15.209), above 1 GHz..... 89  
Table 21. Peak Radiated Fundamental & Harmonic Emissions, 802.11a..... 90  
Table 22. Average Radiated Fundamental & Harmonic Emissions 802.11a..... 91  
Table 23. Peak Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW ..... 92  
Table 24. Average Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW ..... 93  
Table 25. Peak Radiated Fundamental & Harmonic Emissions, 802.11n..... 94  
Table 26. Average Radiated Fundamental & Harmonic Emissions 802.11n..... 95  
Table 27. Peak Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW ..... 96  
Table 28. Average Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW ..... 97  
Table 29. Peak Radiated Fundamental & Harmonic Emissions, 802.11a..... 98  
Table 30. Average Radiated Fundamental & Harmonic Emissions 802.11a..... 99  
Table 31. Peak Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW ..... 100  
Table 32. Average Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW ..... 101  
Table 33. Peak Radiated Fundamental & Harmonic Emissions, 802.11n..... 102  
Table 34. Average Radiated Fundamental & Harmonic Emissions 802.11n..... 103  
Table 35. Peak Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW ..... 104  
Table 36. Average Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW ..... 105  
Table 37. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11a – Peak..... 193  
Table 38. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11a – Average.... 194  
Table 39. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Peak..... 195  
Table 40. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 196  
Table 41. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Peak..... 197  
Table 42. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 198  
Table 43. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n – Peak..... 199  
Table 44. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n – Average.... 200  
Table 45. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Peak..... 201  
Table 46. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 202  
Table 47. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Average.. 203  
Table 48. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Average.. 205  
Table 49. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n 40 MHz BW – Peak..... 206  
Table 50. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n 40 MHz BW – Average ..... 207

Table 51. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Peak..... 208  
Table 52. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Average ..... 209  
Table 53. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Peak..... 210  
Table 54. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Average ..... 211  
Table 55. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11a – Peak ..... 212  
Table 56. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11a – Average.... 213  
Table 57. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Peak..... 214  
Table 58. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 215  
Table 59. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Peak..... 216  
Table 60. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 217  
Table 61. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n – Peak ..... 218  
Table 62. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n – Average.... 219  
Table 63. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Peak ..... 220  
Table 64. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11a – Average.. 221  
Table 65. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Average.. 222  
Table 66. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n – Average.. 223  
Table 67. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n 40 MHz BW – Peak..... 224  
Table 68. Radiated Restricted Band 4.5 GHz to 5.15 GHz, 802.11n 40 MHz BW – Average ..... 225  
Table 69. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Peak..... 226  
Table 70. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Average ..... 227  
Table 71. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Peak..... 228  
Table 72. Radiated Restricted Band 5.35 GHz to 5.46 GHz, 802.11n 40 MHz BW – Average ..... 229  
Table 73. Six (6) dB Bandwidth..... 231  
Table 74. 26 dB Bandwidth and 99% Occupied Bandwidth for 802.11a ..... 238  
Table 75. 26 dB Bandwidth and 99% Occupied Bandwidth for 802.11n ..... 239  
Table 76. 26 dB Bandwidth and 99% Occupied Bandwidth for 802.11a 40 MHz BW ..... 240  
Table 77. 26 dB Bandwidth and 99% Occupied Bandwidth for 802.11n 40 MHz BW ..... 240  
Table 78. Frequency Deviation/Stability @ 802.11a Mode, Channel 36 ..... 265

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

### **List of Attachments**

Agency Agreement  
Application Forms  
Letter of Confidentiality  
Equipment Label(s)  
Block Diagram(s)  
Schematic(s)  
Test Configuration Photographs  
Internal Photographs  
External Photographs  
Antenna Photographs  
Theory of Operation  
RF Exposure  
User's Manual

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **1 General Information**

### **1.1 Purpose of this Report**

This report is prepared as a means of conveying test results and information concerning the suitability of this exact product for public distribution according to the FCC Rules and Regulations Part 15, Section 407 and IC RSS 247 Issue 1.

### **1.2 Characterization of Test Sample**

The sample used for testing was received by US Tech on June 31, 2016 in good operating condition.

### **1.3 Product Description**

The Equipment Under Test (EUT) is the Acuity Brands Technology Services, Inc. Model ACWIFI001 radio module. The ACWIFI001 radio module is an embedded wireless internet connectivity module that operates in the 2.4 and 5.0 GHz spectrums.

The EUT does have two antennas, however it can only broadcast on one or the other; never both at the same time. The antenna uses an RF switch that will attenuate the signal to the antenna that is not being used for transmission.

The 2.4 GHz Wi-Fi feature has been tested and results reported in a separate report.

Antenna Gain: 3.38 dBi (Flex trace), 2.4 dBi (Omni)

Modulation: DSSS

Bandwidth: 20 MHz and 40 MHz modulation

Maximum Output Power: a mode: 17.8 dBm (max)  
a mode (40MHz ): 16.8 dBm (max),  
n mode 17.8 dBm (max)  
n mode (40MHz): 16.5 dBm

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## 1.4 Configuration of Tested System

The Test Sample was tested per *ANSI C63.10:2013, Procedures for Compliance Testing of Unlicensed Wireless Devices(2013)* and following KDB 789033 D02 General U-NII Test Procedures New Rules v01r02.

A list of EUT and Peripherals is found in Table 1 below. A block diagram of the tested system is shown in Figure 1. Test configuration photographs are provided in separate Appendices.

## 1.5 Test Facility

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA 30004. This site has been fully described and registered with the FCC. Its designation number is 186022. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number 9900A-1.

## 1.6 Related Submittals

The EUT is subject to the following FCC authorizations:

a) Certification under section 15.247 as a transmitter. A separate test report has been provided for this evaluation.


No other related submittals apply.



**Table 1. EUT and Peripherals**

PERIPHERAL MANUFACTURER.	MODEL NUMBER	SERIAL NUMBER	FCC ID:	CABLES P/D
Acuity Brands Technology Services, Inc	ACWIFI001 SIP Application Module	Engineering Sample	2ADCB-ACWIFI001 (pending) 6715A-ACWIFI001 (pending)	N/A
Antenna See antenna details	--	--	--	--

U= Unshielded  
 S= Shielded  
 P= Power  
 D= Data



**Figure 1. Block Diagram of Test Configuration**

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

## 2 Tests and Measurements

### 2.1 Test Equipment

The table below lists test equipment used to evaluate this product. Model numbers, serial numbers and their calibration status are indicated.

**Table 2. Test Instruments**

TEST INSTRUMENT	MODEL NUMBER	MANUFACTURER	SERIAL NUMBER	CALIBRATION DUE DATE
SPECTRUM ANALYZER	8566B	HEWLETT-PACKARD	2410A00109	8/30/2016
SPECTRUM ANALYZER	DSA815	RIGOL	DSA8A18030 0138	6/30/2017
SPECTRUM ANALYZER	E4407B	AGILENT	US41442935	2/11/2017
LOOP ANTENNA	SAS-200/562	A.H. Systems	142	9/28/2017
BICONICAL ANTENNA	3110B	EMCO	9306-1708	11/24/2016
LOG PERIODIC ANTENNA	3146	EMCO	9110-3236	11/19/2016
LOG PERIODIC ANTENNA	3146	EMCO	9305-3600	10/01/2016
HORN ANTENNA	SAS-571	A.H. Systems	605	8/25/2017
HORN ANTENNA	3115	EMCO	9107-3723	10/8/2016
HORN ANTENNA	3116	EMCO	9505-2255	1/27/2017

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

AMPLIFIER	11975A	HEWLETT-PACKARD	2517A00647	12/05/2016
HARMONIC MIXER	11970K	HEWLETT-PACKARD	2332A01241	Not Required
PRE-AMPLIFIER	8449B	HEWLETT-PACKARD	3008A00480	12/01/2016
PRE-AMPLIFIER	8447D	HEWLETT-PACKARD	1937A02980	12/02/2016
LISN x 2	9247-50-TS-50-N	SOLAR ELECTRONICS	955824 and 955825	11/30/2016

Note: The calibration interval of the above test instruments are 12 months unless stated otherwise and all calibrations are traceable to NIST/USA.

## 2.2 Modifications to EUT Hardware

No physical modifications were made by US Tech in order to bring the EUT into compliance with FCC Part 15, Subpart C Intentional Radiator Limits for the transmitter portion of the EUT or the Subpart B Unintentional Radiator Limits (Receiver and Digital Device) Requirements.

### 2.3 Number of Measurements for Intentional Radiators (15.31(m))

Measurements of intentional radiators or receivers shall be performed and reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in Table 3 below.

**Table 3. Number of Test Frequencies for Intentional Radiators**

Frequency Range over which the device operates	Number of Frequencies	Location in the Range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near the top 1 near the bottom
Greater than 10 MHz	3	1 near top 1 near middle 1 near bottom

Because the EUT operates at 5.15 GHz to 5.85 MHz, at least 3 test frequencies were used.

### 2.4 Frequency Range of Radiated Measurements (Part 15.33)

#### 2.4.1 Intentional Radiator

The spectrum shall be investigated for the intentional radiator from the lowest RF signal generated in the EUT, without going below 9 kHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency generated or 40 GHz, whichever is the lowest.

#### 2.4.2 Unintentional Radiator

For the digital device, an unintentional radiator, the frequency range shall be 30 MHz to 1000 MHz, or to 5 times the highest internal clock frequency.

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **2.5 Measurement Detector Function and Bandwidth (Part 15.35)**

The radiated and conducted emissions limits shown herein are based on the following:

### **2.5.1 Detector Function and Associated Bandwidth**

On frequencies below 1000 MHz, the limits herein are based upon measurement equipment employing a CISPR Quasi-peak detector function and related measurement bandwidths (i.e. 9 kHz from 150 kHz to 30 MHz and 120 kHz from 30 MHz to 1000 MHz). Alternatively, measurements may be made with equipment employing a peak detector function as long as the same bandwidths specified for the Quasi-peak device are used.

### **2.5.2 Corresponding Peak and Average Requirements**

Above 1000 MHz, radiated limits are based on measuring instrumentation employing an average detector function. When average radiated emissions are specified there is also a corresponding Peak requirement, as measured using a peak detector, of 20 dB greater than the average limit. For all measurements above 1000 MHz the Resolution Bandwidth shall be at least 1 MHz.

### **2.5.3 Pulsed Transmitter Averaging**

When the radiated emissions limit is expressed as an average value, and the transmitter is pulsed, the measured field strength shall be determined by applying a Duty Cycle Correction Factor based upon dividing the total ON time during the first 100 ms period by 100 ms (or by the period if less than 100 ms). The duty cycle may be expressed logarithmically in dB.

NOTE: If the transmitter was programmed to transmit at >98% duty cycle, then, wherever applicable (where the detection mode was AVG) the duty cycle factor calculated will be applied.

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

## 2.6 Duty Cycle Verification (Part 15.35 (c))




Figure 2. 802.11a(20), Ch 36 6 Mbps

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 3. 802.11a(20), Ch 36, 72 Mbps

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 4. 802.11n(20), Ch 36, MCS0



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 5. 802.11n(20), Ch 36, MCS7



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 7. 802.11a(40), Ch 38, 72 Mbps

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 8. 802.11n(40), Ch 38, MCS0

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 9. 802.11n(40), Ch 38, MCS7

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

## 2.7 EUT Antenna Requirements (Part 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. Only the antenna(s) listed in Table 4 will be used with this module.

**Table 4. Allowed Antenna(s)**

REPORT REFERENCE	MANUFACTURER	TYPE OF ANTENNA	MODEL	GAIN dBi	TYPE OF CONNECTOR
Antenna 1	Laird	Flex trace	MAF95310 Mini NanoBlade	3.38	u.fl
Antenna 2	Laird	Omni	DCF5151C- FNM	2.4	N-type to u.fl

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **2.8 Maximum Peak Conducted Output Power (Part 15.407 (a) (1,2,3))**

The transmitter was programmed to operate at a maximum output power across the bandwidth. The EUT is considered a client device.

Peak power within the transmitting bands was measured per FCC KDB Publication 789033 D02 and ANSI C63.10 section 12.3.2.2 as an Antenna Conducted test with a spectrum analyzer by connecting the spectrum analyzer directly, via a short RF cable, and attenuators to the antenna output terminals on the EUT. The spectrum analyzer was set for an impedance of  $50 \Omega$  with the RBW set to 1 MHz, the VBW  $\geq 3 \cdot$ RBW, and span large enough to encompass the entire 99 % bandwidth and the channel power was integrated over the whole band. Peak antenna conducted output power is tabulated in the table below.


US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 5. Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11a**

Frequency of Fundamental (MHz)	Peak Test Data (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Verdict
5180	13.39	23.98	23.00	Pass
5220	12.35	23.98	23.00	Pass
5240	12.31	23.98	23.00	Pass
5260	13.66	23.98	23.98	Pass
5280	12.94	23.98	23.98	Pass
5320	16.20	23.98	23.98	Pass
5500	15.92	23.98	23.98	Pass
5560	14.41	23.98	23.98	Pass
5660	14.51	23.98	23.98	Pass
5700	16.08	23.98	23.98	Pass
5745	15.19	30.00	30.00	Pass
5785	10.29	30.00	30.00	Pass
5825	15.85	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2017

Tested By  
 Signature:  Name: George Yang




US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 6. Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11n**

Frequency of Fundamental (MHz)	Peak Test Data (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Verdict
5180	14.46	23.98	23.00	Pass
5220	11.57	23.98	23.00	Pass
5240	14.52	23.98	23.00	Pass
5260	12.29	23.98	23.98	Pass
5280	13.18	23.98	23.98	Pass
5320	17.25	23.98	23.98	Pass
5500	16.79	23.98	23.98	Pass
5560	14.51	23.98	23.98	Pass
5660	14.69	23.98	23.98	Pass
5700	16.92	23.98	23.98	Pass
5745	16.08	30.00	30.00	Pass
5785	11.36	30.00	30.00	Pass
5825	16.46	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2017

Tested By  
 Signature:  Name: George Yang

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:


FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

**Table 7. Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11a 40 MHz BW**

Frequency of Fundamental (MHz)	Test Data (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Verdict
5190	15.61	23.98	23.00	Pass
5230	12.15	23.98	23.00	Pass
5270	12.34	23.98	23.00	Pass
5310	15.66	23.98	23.98	Pass
5510	11.59	23.98	23.98	Pass
5550	14.99	23.98	23.98	Pass
5670	11.92	23.98	23.98	Pass
5755	11.46	23.98	23.98	Pass
5795	16.10	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By

Signature: 

Name: George Yang

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:


FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

**Table 8. Antenna Conducted Output Power per 15.407 (a) (1,2,3) for 802.11n 40 MHz BW**

Frequency of Fundamental (MHz)	Test Data (dBm)	FCC Limit (dBm)	IC Limit (dBm)	Verdict
5190	14.86	23.98	23.00	Pass
5230	14.86	23.98	23.00	Pass
5270	13.38	23.98	23.00	Pass
5310	15.40	23.98	23.98	Pass
5510	12.15	23.98	23.98	Pass
5550	16.45	23.98	23.98	Pass
5670	12.75	23.98	23.98	Pass
5755	11.23	23.98	23.98	pass
5795	15.81	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By

Signature: 

Name: George Yang

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **2.9 Power Spectral Density (Part 15.407(a) (1-5)) (IC RSS 247 5.1, 5.2)**

The transmitter was placed into a continuous mode of operation at all applicable frequencies. The measurements were performed per the procedures of FCC KDB Procedure 789033 D02 and ANSI C63.10 section 12.5. The RBW was set to 1 MHz and the Video Bandwidth was set to  $\geq 3 \cdot \text{RBW}$ . The span was set to encompass the OBW. The averaging detector was used on the spectrum analyzer was used to determine the maximum PSD over the corresponding bandwidth

In the operating bands 5.15 – 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band.

In the operating band 5.725 - 5.85 GHz the maximum conducted output power spectral density shall not exceed 30 dBm in any 500 kHz band. Since the spectrum analyzer used for testing does not have a 500 kHz RBW, the RBW was set to 1 MHz for a worst case testing configuration.

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001


**Table 9. Power Spectral Density for 802.11a in the Lower Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/1 MHz)	IC Limit (dBm/1 MHz)	Verdict
5180	6.78	11.00	10.00	Pass
5220	7.20	11.00	10.00	Pass
5240	5.84	11.00	10.00	Pass
5260	8.69	11.00	11.00	Pass
5280	7.90	11.00	11.00	Pass
5320	10.59	11.00	11.00	Pass
5500	10.87	11.00	11.00	Pass
5560	9.10	11.00	11.00	Pass
5660	9.40	11.00	11.00	Pass
5700	10.57	11.00	11.00	Pass

**Table 10. Power Spectral Density for 802.11a in the Upper Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/500 kHz)	IC Limit (dBm/500 kHz)	Verdict
5745	9.55	30.00	30.00	Pass
5785	3.96	30.00	30.00	Pass
5825	10.59	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By  
 Signature:  Name: George Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 11. Power Spectral Density for 802.11n in the Lower Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/1 MHz)	IC Limit (dBm/1 MHz)	Verdict
5180	6.45	11.00	10.00	Pass
5220	7.40	11.00	10.00	Pass
5240	6.11	11.00	10.00	Pass
5260	7.06	11.00	11.00	Pass
5280	6.11	11.00	11.00	Pass
5320	10.77	11.00	11.00	Pass
5500	8.72	11.00	11.00	Pass
5560	9.41	11.00	11.00	Pass
5660	9.38	11.00	11.00	Pass
5700	10.08	11.00	11.00	Pass


**Table 12. Power Spectral Density for 802.11n in the Upper Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/500 kHz)	IC Limit (dBm/500 kHz)	Verdict
5745	7.74	30.00	30.00	Pass
5785	6.47	30.00	30.00	Pass
5825	8.79	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By

Signature:



Name: George Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001


**Table 13. Power Spectral Density for 802.11a 40 MHz BW in the Lower Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/1 MHz)	IC Limit (dBm/1 MHz)	Verdict
5190	8.36	11.00	10.00	Pass
5230	4.64	11.00	10.00	Pass
5270	4.91	11.00	10.00	Pass
5310	8.05	11.00	11.00	Pass
5510	4.52	11.00	11.00	Pass
5550	7.50	11.00	11.00	Pass
5670	4.37	11.00	11.00	Pass

**Table 14. Power Spectral Density for 802.11a 40 MHz BW in the Upper Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/500 kHz)	IC Limit (dBm/500 kHz)	Verdict
5755	3.35	30.00	30.00	Pass
5795	8.80	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By  
 Signature:  Name: George Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 15. Power Spectral Density for 802.11n 40 MHz BW in the Lower Frequency Bands**


Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/1 MHz)	IC Limit (dBm/1 MHz)	Verdict
5190	6.83	11.00	10.00	Pass
5230	7.60	11.00	10.00	Pass
5270	4.70	11.00	10.00	Pass
5310	6.54	11.00	11.00	Pass
5510	6.14	11.00	11.00	Pass
5550	8.00	11.00	11.00	Pass
5670	5.52	11.00	11.00	Pass

**Table 16. Power Spectral Density for 802.11n 40 MHz BW in the Upper Frequency Bands**

Frequency (MHz)	Test Data (dBm/1 MHz)	FCC Limit (dBm/500 kHz)	IC Limit (dBm/500 kHz)	Verdict
5755	2.92	30.00	30.00	Pass
5795	7.81	30.00	30.00	Pass

Test Date: December 5-16, 2016, January 12-13, 2016

Tested By

Signature: 

Name: George Yang



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 10. Antenna Conducted Output Power, 802.11a Channel 36

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 11. Antenna Conducted Output Power, 802.11a 5.22 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 12. Antenna Conducted Output Power, 802.11a Channel 48

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 13. Antenna Conducted Output Power, 802.11a Channel 52

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 14. Antenna Conducted Output Power, 802.11a 5.28 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 15. Antenna Conducted Output Power, 802.11a Channel 64

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 16. Antenna Conducted Output Power, 802.11a Channel 100



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 17. Antenna Conducted Output Power, 802.11a Channel 112



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 18. Antenna Conducted Output Power, 802.11a Channel 132

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 19. Antenna Conducted Output Power, 802.11a Channel 140

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 20. Antenna Conducted Output Power, 802.11a Channel 149

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 21. Antenna Conducted Output Power, 802.11a 5.785 GHz

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 22. Antenna Conducted Output Power, 802.11a Channel 165

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 23. Antenna Conducted Output Power, 802.11n Channel 36

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 24. Antenna Conducted Output Power, 802.11n 5.22 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 25. Antenna Conducted Output Power, 802.11n Channel 48



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 26. Antenna Conducted Output Power, 802.11n Channel 52

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 27. Antenna Conducted Output Power, 802.11n 5.28 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 28. Antenna Conducted Output Power, 802.11n Channel 64

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 29. Antenna Conducted Output Power, 802.11n Channel 100

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 30. Antenna Conducted Output Power, 802.11n Channel 112



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 31. Antenna Conducted Output Power, 802.11n Channel 132

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 32. Antenna Conducted Output Power, 802.11n Channel 140

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 33. Antenna Conducted Output Power, 802.11n Channel 149



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 34. Antenna Conducted Output Power, 802.11n 5.785 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 35. Antenna Conducted Output Power, 802.11n Channel 165

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 36. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 38

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 37. Antenna Conducted Output Power, 802.11a with 40 MHz BW  
5.23 GHz

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 38. Antenna Conducted Output Power, 802.11a with 40 MHz BW  
 5.27 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 39. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 62

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 40. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 102

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 41. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 110



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 42. Antenna Conducted Output Power, 802.11a with 40 MHz BW Channel 134

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 43. Antenna Conducted Output Power, 802.11a with 40 MHz BW  
5.758 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 44. Antenna Conducted Output Power, 802.11a with 40 MHz BW  
Channel 159

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 45. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 38

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 46. Antenna Conducted Output Power, 802.11n with 40 MHz BW  
5.230 GHz

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




Figure 47. Antenna Conducted Output Power, 802.11n with 40 MHz BW  
 5.270 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 48. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 62



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 49. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 102



US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 50. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 110

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 51. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 134

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 52. Antenna Conducted Output Power, 802.11n with 40 MHz BW  
5.758 GHz

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001




Figure 53. Antenna Conducted Output Power, 802.11n with 40 MHz BW Channel 159

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **2.10 Restricted Bands of Operation (Part 15.205)**

Only spurious emissions can fall in the frequency bands of Part 15.205. The field strength of these spurious cannot exceed the limits of 15.209. Radiated harmonics and other Spurious are examined for this requirement, see the sections that follow.

## **2.11 Intentional Radiator, Power Line Conducted Emissions (Part 15.207)**

The EUT is designed to operate with an input voltage of 3.3 VDC. An evaluation board was used during testing and it supplied the necessary 3.3 VDC voltage to the EUT. The EUT is considered to be indirectly connected to the AC mains during normal operation. Power line conducted emissions testing was performed to ensure that with the EUT in operation (exercising all transmitter functions), the complete system continues to meet the applicable requirements for Part 15.207. These measurements were completed and are displayed below.

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 17. Transmitter Power Line Conducted Emissions Test Data, Part 15.207**


150 KHz to 30 MHz						
Test: Power Line Conducted Emissions				Client: Acuity Brands Technology Services, Inc.		
Project: 16-0139				Model: ACWIFI001		
Frequency (MHz)	Test Data (dBuV)	LISN+CL-PA (dB)	Results (dBuV)	AVG Limits (dBuV)	Margin (dB)	Detector PK, QP, or AVG
Positive lead						
0.1675	60.70	0.50	61.20	65.1*	3.9	QP
0.1675	32.87	0.50	33.37	55.1	21.7	AVG
0.6075	32.60	0.32	32.92	46.0	13.1	PK
4.9466	39.62	0.40	40.02	46.0	6.0	PK
6.6660	47.67	0.43	48.10	50.0	1.9	QP
10.3833	40.12	0.54	40.66	50.0	9.3	QP
24.9160	29.87	0.90	30.77	50.0	19.2	PK
Negative lead						
0.1517	59.66	0.42	60.08	65.9*	5.8	QP
0.1517	31.00	0.42	31.42	55.9	24.5	AVG
0.6666	35.86	0.15	36.01	46.0	10.0	PK
4.9533	36.03	0.28	36.31	46.0	9.7	QP
6.6250	47.71	0.31	48.02	50.0	2.0	QP
10.0000	43.51	0.40	43.91	50.0	6.1	PK
26.0833	32.69	0.73	33.42	50.0	16.6	PK

(\*)= Quasi Peak limit applied.

**SAMPLE CALCULATION at 0.1628 MHz:**

Magnitude of Measured Frequency	39.40	dBuV
+ Cable Loss+ LISN Loss	0.49	dB
=Corrected Result	39.89	dBuV
Limit	55.30	dBuV
-Corrected Result	39.89	dBuV
Margin	15.40	dB

Test Date: November 30, 2016

Tested By  
 Signature: 

Name: George Yang

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

## **2.12 Intentional Radiator, Radiated Emissions (Part 15.209, 15.407) (IC RSS 247, 6.2)**

Radiated Spurious measurements: the EUT was placed into a continuous transmit mode of operation (>98% duty cycle) and tested per FCC KDB Publication 789033 D02 General UNII Test Procedures New Rules v01r02 and ANSI C63.10:2013. A preliminary scan was performed on the EUT to find signal frequencies that were caused by the transmitter part of the device. To obtain worse case results the EUT was tested in X, Y, and Z axis or in the orientation of normal operation if the device is designed to operation in a fixed position.

Radiated measurements were then performed between the frequency range of 9KHz (or lowest frequency used/generated by the device) up to the tenth harmonic of the device (no greater than 40 GHz). In the band below 30 MHz a resolution bandwidth (RBW) of 200 Hz or 9 kHz was used, emissions below 1 GHz were tested with a RBW of 120 KHz and emissions above 1 GHz were tested with a RBW of 1 MHz. All video bandwidth settings were at least three times the RBW value.

The EUT was investigated to Part 15.209, General requirements for unwanted spurious emissions.

The conducted spurious method as described in KDB 789033 D02 was used to investigate all other emissions emanating from the antenna port. Conducted Spurious measurements: the EUT was put into a continuous-transmit mode of operation (>98% duty cycle) and tested for conducted out of band emissions emanating from the antenna port over the frequency range of 30 MHz to 40 GHz. A conducted scan was performed on the EUT to identify and record spurious signals that were related to the transmitter.

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

### 2.12.1 Spurious Emissions, Radiated Measurements

Radiated emissions per Part 15.209 were performed to address the concerns of unwanted emissions that may radiate from the EUT cabinet, control circuits, or power leads. The results for this test can be found below.

**Table 18. Intentional Radiator, Spurious Radiated Emissions (Part 15.209), 9 kHz to 1000 MHz**

9 kHz to 30 MHz							
Test: Radiated Emissions				Client: Acuity Brands			
Project: 16-0141				Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuv)	AF+CA-AMP (dB/m)	Results (dBuV/m)	QP Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or QP
All emissions found were greater than 20dB from the limit.							

**Table 19. Intentional Radiator, Spurious Radiated Emissions (Part 15.209), 30 MHz to 1000 MHz**

30 MHz to 1000 MHz							
Test: Radiated Emissions				Client: Acuity Brands			
Project: 16-0141				Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuv)	AF+CA-AMP (dB/m)	Results (dBuV/m)	QP Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or QP
30.00	40.86	-13.82	27.04	40.0	3m./VERT	13.0	QP
48.28	49.61	-16.61	33.00	40.0	3m./VERT	7.0	PK
191.93	46.99	-11.57	35.42	43.5	3m./HORZ	8.1	PK
216.00	50.01	-13.52	36.49	43.5	3m./HORZ	7.0	PK
290.00	48.15	-10.22	37.93	46.0	3m./HORZ	8.1	PK
214.00	47.18	-14.02	33.16	43.5	3m./VERT	10.3	PK
314.00	44.61	-9.73	34.88	46.0	3m./VERT	11.1	PK
All otheremissions found were greater than 20dB from the limit.							

Sample Calculation at 30.00 MHz:

Magnitude of Measured Frequency	40.86	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	-13.82	dB/m
Corrected Result	27.04	dBuV/m



US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001


**Table 20. Intentional Radiator, Spurious Radiated Emissions (Part 15.209), above 1 GHz**

1 GHz to 40 GHz							
Test: Radiated Emissions				Client: Acuity Brands			
Project: 16-0141				Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	QP Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or QP
1588.00	53.44	-7.82	45.62	54.0	3.0m./HORZ	8.4	PK
1637.50	47.59	-7.36	40.23	54.0	3.0m./VERT	13.8	PK
Fundamental and Harmonic emissions are presented in the tables that follow. No other emissions were seen greater than 20 dB from the limit.							

Sample Calculation at 1588.00 MHz:

Magnitude of Measured Frequency	53.44	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	-07.82	dB/m
Corrected Result	45.62	dBuV/m

Test Date: August 1, 2016

Tested By  
 Signature:  Name: George Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

## 2.12.2 Spurious Emissions Radiated Measurements, Antenna 1

EUT fitted with Flex trace antenna.

**Table 21. Peak Radiated Fundamental & Harmonic Emissions, 802.11a**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	72.42	0.0	40.23	112.65	--	3.0m./HORZ	--	PK
Channel 48								
5240.00	71.52	0.0	40.47	111.99	--	3.0m./HORZ	--	PK
Channel 52								
5260.00	70.09	0.0	40.47	110.56	--	3.0m./HORZ	--	PK
Channel 64								
5320.00	72.81	0.0	40.56	113.37	--	3.0m./HORZ	--	PK
Channel 100								
5500.00	71.76	0.0	40.78	112.54	--	3.0m./HORZ	--	PK
Channel 140								
5700.00	72.78	0.0	41.83	114.61	--	3.0m./HORZ	--	PK
Channel 149								
5745.00	70.27	0.0	41.69	111.96	--	3.0m./HORZ	--	PK
Channel 165								
5825.00	68.85	0.0	41.71	110.56	--	3.0m./HORZ	--	PK


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5180.00 MHz:

Magnitude of Measured Frequency	72.42	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
Additional Factor	0.00	dB
Corrected Result	112.65	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 22. Average Radiated Fundamental & Harmonic Emissions 802.11a**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	62.05	0.0	40.23	102.28	--	3.0m./HORZ	--	AVG
Channel 48								
5240.00	61.30	0.0	40.47	101.77	--	3.0m./HORZ	--	AVG
Channel 52								
5260.00	62.15	0.0	40.47	102.62	--	3.0m./HORZ	--	AVG
Channel 64								
5320.00	64.32	0.0	40.56	104.88	--	3.0m./HORZ	--	AVG
Channel 100								
5500.00	63.31	0.0	40.78	104.09	--	3.0m./HORZ	--	AVG
Channel 140								
5700.00	63.31	0.0	41.83	105.14	--	3.0m./HORZ	--	AVG
Channel 149								
5745.00	60.83	0.0	41.69	102.52	--	3.0m./HORZ	--	AVG
Channel 165								
5825.00	60.14	0.0	41.71	101.85	--	3.0m./HORZ	--	AVG


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
- The Duty Cycle was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	62.05	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
Additional Factor	0.00	dB
Corrected Result	102.28	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 23. Peak Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	65.79	0.0	40.23	106.02	--	3.0m./HORZ	--	PK	
Channel 62									
5310	69.86	0.0	40.56	110.42	--	3.0m./HORZ	--	PK	
Channel 102									
5510	68.39	0.0	40.81	109.20	--	3.0m./HORZ	--	PK	
Channel 110									
5550	68.02	0.0	40.81	108.83	--	3.0m./HORZ	--	PK	
Channel 159									
5795	67.43	0.0	41.69	109.12	--	3.0m./HORZ	--	PK	


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5190.00 MHz:

Magnitude of Measured Frequency	65.79	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
Additional Factor	0.00	dB
Corrected Result	106.02	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 24. Average Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	56.84	0.0	40.23	97.07	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 62									
5310	59.16	0.0	40.56	99.72	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 102									
5510	57.93	0.0	40.81	98.74	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 110									
5550	57.27	0.0	40.81	98.08	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 159									
5795	58.09	0.0	41.69	99.78	--	3.0m./HORZ	--	<b>AVG</b>	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No harmonics detected, all other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
4. The Duty Cycle factor was not applied.

Sample Calculation at 5190.00 MHz:

Magnitude of Measured Frequency	56.84	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	<u>0.00</u>	<u>dB</u>
Corrected Result	97.07	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 25. Peak Radiated Fundamental & Harmonic Emissions, 802.11n**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 36									
5180.00	72.51	0.0	40.57	113.08	--	3.0m./HORZ	--	PK	
Channel 48									
5240.00	71.96	0.0	40.47	112.43	--	3.0m./HORZ	--	PK	
Channel 52									
5260.00	72.12	0.0	40.47	112.59	--	3.0m./HORZ	--	PK	
Channel 64									
5320.00	72.47	0.0	40.56	113.03	--	3.0m./HORZ	--	PK	
Channel 100									
5500.00	71.37	0.0	40.78	112.15	--	3.0m./HORZ	--	PK	
Channel 140									
5700.00	72.12	0.0	41.69	113.81	--	3.0m./HORZ	--	PK	
Channel 149									
5745.00	71.46	0.0	41.69	113.15	--	3.0m./HORZ	--	PK	
Channel 165									
5825.00	72.11	0.0	41.71	113.82	--	3.0m./HORZ	--	PK	


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No harmonics detected, all other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5180.00 MHz:

Magnitude of Measured Frequency	72.51	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	113.08	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 26. Average Radiated Fundamental & Harmonic Emissions 802.11n**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	61.54	0.0	40.57	102.11	--	3.0m./HORZ	--	AVG
Channel 48								
5240.00	60.33	0.0	40.47	100.80	--	3.0m./HORZ	--	AVG
Channel 52								
5260.00	61.13	0.0	40.47	101.60	--	3.0m./HORZ	--	AVG
Channel 64								
5320.00	60.93	0.0	40.56	101.49	--	3.0m./HORZ	--	AVG
Channel 100								
5500.00	59.76	0.0	40.78	100.54	--	3.0m./HORZ	--	AVG
Channel 140								
5700.00	60.54	0.0	41.69	102.23	--	3.0m./HORZ	--	AVG
Channel 149								
5745.00	60.37	0.0	41.69	102.06	--	3.0m./HORZ	--	AVG
Channel 165								
5825.00	60.78	0.0	41.71	102.49	--	3.0m./HORZ	--	AVG


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
- The Duty Cycle was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	61.54	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	102.11	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 27. Peak Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	71.11	0.0	40.23	111.34	--	3.0m./HORZ	--	PK	
Channel 62									
5310	69.92	0.0	40.47	110.39	--	3.0m./HORZ	--	PK	
Channel 102									
5510	68.28	0.0	40.78	109.06	--	3.0m./HORZ	--	PK	
Channel 110									
5550	68.89	0.0	41.96	110.85	--	3.0m./HORZ	--	PK	
Channel 159									
5795	65.54	0.0	41.69	107.23	--	3.0m./HORZ	--	PK	


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5190.00MHz:

Magnitude of Measured Frequency	71.11	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
Additional Factor	0.00	dB
Corrected Result	111.34	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang



US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 28. Average Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	59.05	0.0	40.23	99.28	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 62									
5310	55.74	0.0	40.47	96.21	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 102									
5510	54.96	0.0	40.78	95.74	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 110									
5550	56.49	0.0	41.96	98.45	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 159									
5795	54.12	0.0	41.69	95.81	--	3.0m./HORZ	--	<b>AVG</b>	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
4. The Duty Cycle was not applied.

Sample Calculation at 5190.00MHz:

Magnitude of Measured Frequency	59.05	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	<u>0.00</u>	<u>dB</u>
Corrected Result	99.28	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

### 2.12.3 Spurious Emissions Radiated Measurements, Antenna 2

EUT fitted with Omni antenna.

**Table 29. Peak Radiated Fundamental & Harmonic Emissions, 802.11a**

Test: FCC Part 15, Para 15.209, 15.407(a)					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 36									
5180.00	71.29	0.0	40.57	111.86	--	3.0m./HORZ	--	PK	
Channel 48									
5240.00	71.81	0.0	40.47	112.28	--	3.0m./HORZ	--	PK	
Channel 52									
5260.00	71.36	0.0	40.47	111.83	--	3.0m./HORZ	--	PK	
Channel 64									
5320.00	72.63	0.0	40.56	113.19	--	3.0m./HORZ	--	PK	
Channel 100									
5500.00	70.37	0.0	40.78	111.15	--	3.0m./HORZ	--	PK	
Channel 140									
5700.00	71.44	0.0	41.69	113.13	--	3.0m./HORZ	--	PK	
Channel 149									
5745.00	70.65	0.0	41.69	112.34	--	3.0m./HORZ	--	PK	
Channel 165									
5825.00	70.69	0.0	41.71	112.40	--	3.0m./HORZ	--	PK	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	71.29	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	111.86	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 30. Average Radiated Fundamental & Harmonic Emissions 802.11a**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	62.10	0.0	40.57	102.67	--	3.0m./HORZ	--	AVG
Channel 48								
5240.00	62.80	0.0	40.47	103.27	--	3.0m./HORZ	--	AVG
Channel 52								
5260.00	62.37	0.0	40.47	102.84	--	3.0m./HORZ	--	AVG
Channel 64								
5320.00	64.92	0.0	40.56	105.48	--	3.0m./HORZ	--	AVG
Channel 100								
5500.00	62.00	0.0	40.78	102.78	--	3.0m./HORZ	--	AVG
Channel 140								
5700.00	64.42	0.0	41.69	106.11	--	3.0m./HORZ	--	AVG
Channel 149								
5745.00	61.69	0.0	41.69	103.38	--	3.0m./HORZ	--	AVG
Channel 165								
5825.00	62.54	0.0	41.71	104.25	--	3.0m./HORZ	--	AVG


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
- The Duty Cycle was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	62.10	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	102.67	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 31. Peak Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	69.77	0.0	40.23	110.00	--	3.0m./HORZ	--	PK	
Channel 62									
5310	70.45	0.0	40.56	111.01	--	3.0m./HORZ	--	PK	
Channel 102									
5510	67.23	0.0	40.81	108.04	--	3.0m./HORZ	--	PK	
Channel 110									
5550	67.92	0.0	40.81	108.73	--	3.0m./HORZ	--	PK	
Channel 159									
16650	67.07	0.0	41.69	108.76	--	3.0m./HORZ	--	PK	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5190.00MHz:

Magnitude of Measured Frequency	69.77	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	0.00	dB
Corrected Result	110.00	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 32. Average Radiated Fundamental & Harmonic Emissions 802.11a 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	61.38	0.0	40.23	101.61	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 62									
5310	62.00	0.0	40.56	102.56	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 102									
5510	59.76	0.0	40.81	100.57	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 110									
5550	60.35	0.0	40.81	101.16	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 159									
5795	58.72	0.0	41.69	100.41	--	3.0m./HORZ	--	<b>AVG</b>	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
4. The Duty Cycle was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	61.38	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	<u>0.00</u>	<u>dB</u>
Corrected Result	101.61	dBuV/m

Test Date: July 29, 2016

Tested By

Signature: 

Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 33. Peak Radiated Fundamental & Harmonic Emissions, 802.11n**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	72.40	0.0	40.57	112.97	--	3.0m./HORZ	--	PK
Channel 48								
5240.00	72.15	0.0	40.47	112.62	--	3.0m./HORZ	--	PK
Channel 52								
5260.00	74.44	0.0	40.47	114.91	--	3.0m./HORZ	--	PK
Channel 64								
5320.00	74.91	0.0	40.56	115.47	--	3.0m./HORZ	--	PK
Channel 100								
5500.00	72.11	0.0	40.78	112.89	--	3.0m./HORZ	--	PK
Channel 140								
5700.00	72.55	0.0	41.83	114.38	--	3.0m./HORZ	--	PK
Channel 149								
5745.00	72.41	0.0	41.69	114.10	--	3.0m./HORZ	--	PK
Channel 165								
5825.00	72.55	0.0	41.71	114.26	--	3.0m./HORZ	--	PK


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	72.40	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	112.97	dBuV/m

Test Date: July 29, 2016 & August 1, 2016

Tested By

Signature:  Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 34. Average Radiated Fundamental & Harmonic Emissions 802.11n**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc			
Project: 16-0141					Model: ACWIFI001			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Channel 36								
5180.00	61.38	0.0	40.57	101.95	--	3.0m./HORZ	--	AVG
Channel 48								
5240.00	61.00	0.0	40.47	101.47	--	3.0m./HORZ	--	AVG
Channel 52								
5260.00	63.48	0.0	40.47	103.95	--	3.0m./HORZ	--	AVG
Channel 64								
5320.00	64.26	0.0	40.56	104.82	--	3.0m./HORZ	--	AVG
Channel 100								
5500.00	61.29	0.0	40.78	102.07	--	3.0m./HORZ	--	AVG
Channel 140								
5700.00	61.84	0.0	41.83	103.67	--	3.0m./HORZ	--	AVG
Channel 149								
5745.00	61.35	0.0	41.69	103.04	--	3.0m./HORZ	--	AVG
Channel 165								
5825.00	61.91	0.0	41.71	103.62	--	3.0m./HORZ	--	AVG


- (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
- No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
- The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
- The Duty Cycle correction factor was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	61.38	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.57	dB/m
Additional Factor	0.00	dB
Corrected Result	101.95	dBuV/m

Test Date: July 29, 2016 & August 1, 2016

Tested By

Signature:  Name: George, Yang

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 35. Peak Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	71.25	0.0	40.23	111.48	--	3.0m./HORZ	--	PK	
Channel 62									
5310	70.99	0.0	40.47	111.46	--	3.0m./HORZ	--	PK	
Channel 102									
5510	69.92	0.0	40.78	110.70	--	3.0m./HORZ	--	PK	
Channel 110									
5550	70.27	0.0	41.96	112.23	--	3.0m./HORZ	--	PK	
Channel 159									
5795	70.21	0.0	41.69	111.90	--	3.0m./HORZ	--	PK	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	71.25	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	0.00	dB
Corrected Result	111.48	dBuV/m

Test Date: July 29, 2016 & August 1, 2016

Tested By

Signature:  Name: George, Yang



US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001

**Table 36. Average Radiated Fundamental & Harmonic Emissions 802.11n 40 MHz BW**

Test: FCC Part 15, Para 15.209, 15.407					Client: Acuity Brands Technology Services, Inc				
Project: 16-0141					Model: ACWIFI001				
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode	
Channel 38									
5190	59.45	0.0	40.23	99.68	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 62									
5310	59.13	0.0	40.47	99.60	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 102									
5510	58.39	0.0	40.78	99.17	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 110									
5550	58.47	0.0	41.96	100.43	--	3.0m./HORZ	--	<b>AVG</b>	
Channel 159									
5795	58.22	0.0	41.69	99.91	--	3.0m./HORZ	--	<b>AVG</b>	


1. (\*) Falls within the restricted bands of Part 15.205. Limits based on Part 15.209 & 15.407.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10<sup>th</sup> harmonic
3. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.
4. The Duty Cycle correction factor was not applied.

Sample Calculation at 5180.00MHz:

Magnitude of Measured Frequency	59.45	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain	40.23	dB/m
<u>Additional Factor</u>	0.00	dB
Corrected Result	99.68	dBuV/m

Test Date: July 29, 2016 & August 1, 2016

Tested By

Signature:  Name: George, Yang

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:


FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001

---

### **2.12.4 Undesirable emissions (Part 15.407(b))**

The conducted output power (in dBm) was recorded. The maximum transmit antenna gain in dBi was added to determine the EIRP level. The appropriate maximum ground reflection factor to the EIRP level, 6 dB for frequencies  $\leq 30$  MHz, 4.7 dB for frequencies between 30 MHz – 1000 MHz, and 0 dB for frequencies  $> 1000$  MHz, was also added to the EIRP calculation. The results are converted and compared to the applicable field strength level to show compliance. The data is presented below.

The test procedure was based on ANSI C63.10:2013 and KDB 789033 D02 v01r02.




**Figure 54. Antenna Conducted Emissions Channel 36 802.11a, Part 1**

$EIRP = -59.67 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -51.57 \text{ dBm}$

Limit =  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin =  $-27 \text{ dBm/MHz} - (-51.57) \text{ dBm/MHz} = 24.6 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 14.6 \text{ dB}$




**Figure 55. Antenna Conducted Emissions Channel 36 802.11a, Part 2**

$EIRP = -37.61 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -34.21 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-34.21) \text{ dBm/MHz} = 7.2 \text{ dB}$




**Figure 56. Antenna Conducted Emissions Channel 36 802.11a, Part 3**

$EIRP = -68.80 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -65.40 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-65.40) \text{ dBm/MHz} = 38.4 \text{ dB}$




**Figure 57. Antenna Conducted Emissions Channel 48 802.11a, Part 1**

EIRP= -49.46 dBm + 3.4 dBi (applied antenna gain) + 4.7 dB (ground reflection factor)= -41.36 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz - (-41.36) dBm/MHz= 14.4 dB- 10 dB (correction factor for RBW: 120 k to 1 MHz) = 4.4 dB



**Figure 58. Antenna Conducted Emissions Channel 48 802.11a, Part 2**


$EIRP = -37.11 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -33.71 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-33.71) \text{ dBm/MHz} = 6.7 \text{ dB}$

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 59. Antenna Conducted Emissions Channel 48 802.11a, Part 3**

EIRP= -68.70 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.30 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.30) dBm/MHz = 38.3 dB






**Figure 60. Antenna Conducted Emissions Channel 64 802.11a, Part 1**

$EIRP = -49.22 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.12 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-41.12) \text{ dBm/MHz} = 14.12 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.1 \text{ dB}$



**Figure 61. Antenna Conducted Emissions Channel 64 802.11a, Part 2**


$EIRP = -36.78 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -33.38 \text{ dBm}$

Limit=  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin=  $-27 \text{ dBm/MHz} - (-33.38) \text{ dBm/MHz} = 6.4 \text{ dB}$

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001



**Figure 62. Antenna Conducted Emissions Channel 64 802.11a, Part 3**


$EIRP = -68.80 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -65.40 \text{ dBm}$

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.40) dBm/MHz = 38.4 dB

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001



**Figure 63. Antenna Conducted Emissions Channel 100 802.11a, Part 1**


$EIRP = -49.54 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.44 \text{ dBm}$

Limit =  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin =  $-27 \text{ dBm/MHz} - (-41.44) \text{ dBm/MHz} = 14.4 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.4 \text{ dB}$

US Tech Test Report:  
FCC ID:  
IC:  
Test Report Number:  
Issue Date:  
Customer:  
Model:

FCC Part 15 Certification/ RSS 247  
2ADCB-ACWIFI001  
6715A-ACWIFI001  
16-0141  
September 23, 2016  
Acuity Brands  
ACWIFI001



**Figure 64. Antenna Conducted Emissions Channel 100 802.11a, Part 2**


$EIRP = -39.39 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -35.99 \text{ dBm}$

Limit =  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin =  $-27 \text{ dBm/MHz} - (-35.99) \text{ dBm/MHz} = 8.9 \text{ dB}$

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 65. Antenna Conducted Emissions Channel 100 802.11a, Part 3**

$EIRP = -68.80 \text{ dBm} + 3.4 \text{ dBi (max antenna gain)} + 0 \text{ dB (ground reflection factor)} = -65.4 \text{ dBm}$

Limit =  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin =  $-27 \text{ dBm/MHz} - (-65.4) \text{ dBm/MHz} = 38.4 \text{ dB}$




**Figure 66. Antenna Conducted Emissions Channel 140 802.11a, Part 1**

$EIRP = -49.61 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.51 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-41.51) \text{ dBm/MHz} = 14.5 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.5 \text{ dB}$



**Figure 67. Antenna Conducted Emissions Channel 140 802.11a, Part 2**

$EIRP = -37.96 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -34.56 \text{ dBm}$


Limit =  $-27 \text{ dBm/MHz (15.407 (b))}$

Margin =  $-27 \text{ dBm/MHz} - (-34.56) \text{ dBm/MHz} = 7.6 \text{ dB}$



US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 68. Antenna Conducted Emissions Channel 140 802.11a, Part 3**

EIRP= -68.70 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.30 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.30) dBm/MHz= 38.3 dB




**Figure 69. Antenna Conducted Emissions Channel 149 802.11a, Part 1**

EIRP= -49.24 dBm + 3.4 dBi (applied antenna gain) + 4.7 dB (ground reflection factor)= -41.14 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz - (-41.14) dBm/MHz= 14.1 dB- 10 dB (correction factor for RBW: 120 k to 1 MHz) = 4.1 dB



**Figure 70. Antenna Conducted Emissions Channel 149 802.11a, Part 2**


EIRP= -37.51 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -34.11 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-34.11) dBm/MHz = 7.1 dB

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 71. Antenna Conducted Emissions Channel 149 802.11a, Part 3**

EIRP= -68.90 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.50 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.50) dBm/MHz= 38.5 dB




**Figure 72. Antenna Conducted Emissions Channel 165 802.11a, Part 1**

$EIRP = -49.44 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.34 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-41.34) \text{ dBm/MHz} = 14.3 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.3 \text{ dB}$



**Figure 73. Antenna Conducted Emissions Channel 165 802.11a, Part 2**


$EIRP = -38.12 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -34.72 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-34.72) \text{ dBm/MHz} = 7.7 \text{ dB}$

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 74. Antenna Conducted Emissions Channel 165 802.11a, Part 3**

EIRP= -69.00 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.60 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.60) dBm/MHz= 38.6 dB




**Figure 75. Antenna Conducted Emissions Channel 36 802.11n, Part 1**

$EIRP = -49.11 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.01 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-41.01) \text{ dBm/MHz} = 14.0 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.0 \text{ dB}$





**Figure 76. Antenna Conducted Emissions Channel 36 802.11n, Part 2**


EIRP= -36.54 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -33.14 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-33.14) dBm/MHz= 6.1 dB

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 77. Antenna Conducted Emissions Channel 36 802.11n, Part 3**

EIRP= -68.60 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.20 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.20) dBm/MHz= 38.2 dB




**Figure 78. Antenna Conducted Emissions Channel 48 802.11n, Part 1**

EIRP= -49.43 dBm + 3.4 dBi (applied antenna gain) + 4.7 dB (ground reflection factor)= -41.33 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz - (-41.33) dBm/MHz= 14.3 dB- 10 dB (correction factor for RBW: 120 k to 1 MHz) = 4.3 dB




**Figure 79. Antenna Conducted Emissions Channel 48 802.11n, Part 2**

$EIRP = -36.48 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -33.08 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-33.08) \text{ dBm/MHz} = 6.1 \text{ dB}$




**Figure 80. Antenna Conducted Emissions Channel 48 802.11n, Part 3**

Note: Large signal seen in the above figure is the fundamental emission

$EIRP = -68.60 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -65.20 \text{ dBm}$

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.20) dBm/MHz= 38.2 dB




**Figure 81. Antenna Conducted Emissions Channel 64 802.11n, Part 1**

$EIRP = -49.43 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 4.7 \text{ dB (ground reflection factor)} = -41.33 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-41.33) \text{ dBm/MHz} = 14.3 \text{ dB} - 10 \text{ dB (correction factor for RBW: 120 k to 1 MHz)} = 4.3 \text{ dB}$



**Figure 82. Antenna Conducted Emissions Channel 64 802.11n, Part 2**


$EIRP = -36.37 \text{ dBm} + 3.4 \text{ dBi (applied antenna gain)} + 0 \text{ dB (ground reflection factor)} = -32.97 \text{ dBm}$

$Limit = -27 \text{ dBm/MHz (15.407 (b))}$

$Margin = -27 \text{ dBm/MHz} - (-32.97) \text{ dBm/MHz} = 5.9 \text{ dB}$

US Tech Test Report:  
 FCC ID:  
 IC:  
 Test Report Number:  
 Issue Date:  
 Customer:  
 Model:

FCC Part 15 Certification/ RSS 247  
 2ADCB-ACWIFI001  
 6715A-ACWIFI001  
 16-0141  
 September 23, 2016  
 Acuity Brands  
 ACWIFI001




**Figure 83. Antenna Conducted Emissions Channel 64 802.11n, Part 3**

EIRP= -68.70 dBm + 3.4 dBi (applied antenna gain) + 0 dB (ground reflection factor)= -65.30 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz – (-65.30) dBm/MHz= 38.3 dB





**Figure 84. Antenna Conducted Emissions Channel 100 802.11n, Part 1**

EIRP= -49.17 dBm + 3.4 dBi (applied antenna gain) + 4.7 dB (ground reflection factor)= -41.07 dBm

Limit= -27 dBm/MHz (15.407 (b))

Margin= -27 dBm/MHz - (-41.07) dBm/MHz= 14.1 dB- 10 dB (correction factor for RBW: 120 k to 1 MHz) = 4.1 dB