	e. LIGHT AND HUMIDITY AS SPECIFIED IN UL EXPOSURE TEST	MATERIAL: A. ACRYLIC SILK SCREEN PRINT ON CLEANED PHOTO CONTROL BASE PLASTIC DIRECTLY B. SCREEN PRINTING INK #710 FROM ESAY CHEMCIAL MFG. LTD. C. ALLOW INK TO AIR DRY SUFFICIENTLY BEFORE DISTURBING PRINTED AREA D002"THICK POLYESTER WITH 3M #400 OR #7921 ACRYLIC E. ADHESIVE: BACKING: SILICONE RELEASE LINER FACE COLOR: WHITE WITH BLACK INK F. ENVIRONMENTAL: c. TEMPERATURE RANGE: -40°C TO +85°C d. ADHESIVE, MATERIAL AND INK SHALL BE RESISTANT TO UV DEGRADATION		
ER#	XXX 696	LEANED TLY ESAY ESAY TTLY 400 DR 400 DR K INK K INK C BE RESIS		
DATE	- OUTDOOR	TANT TO UV	M/N: ACVIFI001 FCC ID: 2ADCB-ACVIFI001 IC: 6715A-ACWIF1001	
REL	D		TF1001	
REVISIONS	RELEASE			
BY 6		1. NOTE: 1. NOT	1.00	
APP		NUTE: 1. MUDEL 1. MUDEL 0.200" CH 0.200" CH 2. VULTA 2. VULTA 3. LUAD 4. ASSEM 4. ASSEM 5. REPLA 5. REPLA		
NONE	PRW STAFF	TE: MODEL NUMBER (REVERSE PRINTING) 200° CHARACTER HEIGHT. VOLTAGE/FREQUENCY RATING, 0.093° C LOAD RATING (HID) 0.093° CHARACTER ASSEMBLED IN CHINA, 0.093° CHARACTER ASSEMBLED IN CHINA, 0.093° CHARACT REPLACE MM/DD/YYYY WITH DATE OF NUFACTURE IN MONTH/DAY/YEAR FORM	0.50 RADIUS	
	e property of A	VERSE PI GHT. 0.093″ C 0.093″ C NA, 0.093″ C NA, 0.093	0.05 ×	_
	Lighting Group, Inc. Copierty of American Electric Lighting a division of Acuity Lighting Group, Inc. Copies are issued in strict confidence and skill not be reproduced <u>DIDENSIBING</u> IN INCLES the pasts for the manufacture or sale of approaches without permiss with TOLERANCES BELOW UNLESS OTHERVISE NOTED FRACTION± 1/64 DECIMAL± .005 ANGLE± 1° RPS American BANGLE± 1° RPS Areas Bandards and ShEET DRAWN MATERIAL, GAGES, AND DRAWN MATERIAL, GAGES, AND DRAWN DRIL SIZES EXCLUED APPROVED DATE 3/15/16 STALF		AMERICAN ELECTRIC LIGHTING	ייי דח יזרווד חחאי
	a, division of Acuity shall not be reproduced JDULAR FCC 1002-00302-001	CHARACTER HEIGHT. ? HEIGHT. TER HEIGHT. MAT. 0.093"	LIGHTING DRAWING	

US Tech FCC ID: IC: Test Report Number: Issue Date: Customer: Model: FCC Part 15/IC RSS Certification 2ADCB-ACWIFI001 6715A-ACWIFI001 16-0139 September 23, 2016 Acuity Brands ACWIFI001

## LABEL LOCATION

