Acuity Brands Lighting, Inc. One Lithonia Way Conyers, GA 30012-3957 Tel: 770 922 9000 www.acuitybrands.com

Request for FCC Modular Approval

August 24, 2021

Federal Communications Commission Equipment Authorization Branch 7435 Oakland Mills Road Columbia, MD 21046

Dear Sir or Madam:

I certify that all exhibits contained within this filing properly describe the device or system for which certification is sought. I further certify that all requirements for modular approval have been met. At this time, I would like to request formal approval for Equipment Certification of the Modular Device, HALEON BTP.

For reference, the Modular Approval Checklist is attached.

Sincerely,

In fla

Name: Alex Bahk Title: Lead RF Engineer



Acuity Brands Lighting, Inc. One Lithonia Way Conyers, GA 30012-3957 Tel: 770 922 9000 www.acuitybrands.com

Modular Approval Requirement	Yes	No	Details
(i) The radio elements of the modular transmitter must have	x		
their own shielding. The physical crystal and tuning			
capacitors may be located external to the shielded radio			
elements.			
(ii) The modular transmitter must have buffered	x		
modulation/data inputs (if such inputs are provided) to ensure			
that the module will comply with part 15 requirements under			
conditions of excessive data rates or over-modulation.			
(iii) The modular transmitter must have its own power supply	x		
regulation.			
(iv) The modular transmitter must comply with the antenna	х		
and transmission system requirements of §§ 15.203, 15.204(b)			
and 15.204(c). The antenna must either be permanently			
attached or employ a "unique" antenna coupler (at all			
connections between the module and the antenna, including			
the cable). The "professional installation" provision of §			
15.203 is not applicable to modules but can apply to limited			
modular approvals under paragraph (b) of this section.			
(v) The modular transmitter must be tested in a stand-alone	x		
configuration, <i>i.e.</i> , the module must not be inside another			
device during testing for compliance with part 15			
requirements. Unless the transmitter module will be battery			
powered, it must comply with the AC line conducted			
requirements found in § 15.207. AC or DC power lines and			
data input/output lines connected to the module must not			
contain ferrites, unless they will be marketed with the module			
(see § 15.27(a)). The length of these lines shall be the length			
typical of actual use or, if that length is unknown, at least 10			
centimeters to insure that there is no coupling between the			
case of the module and supporting equipment. Any			
accessories, peripherals, or support equipment connected to			
the module during testing shall be unmodified and			
commercially available (see § 15.31(i)).			
(vi) The modular transmitter must be equipped with either a	x		
permanently affixed label or must be capable of electronically			
displaying its FCC identification number.			
(vii) The modular transmitter must comply with any specific	x		
rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide			
adequate instructions along with the module to explain any			
such requirements. A copy of these instructions must be			
included in the application for equipment authorization.			
(viii) The modular transmitter must comply with any	x		
applicable RF exposure requirements in its final	~		
configuration.			
configuration.	I	1	