

rLSXR

1720

000-251356

INPUT: 120-277 VAC 50/60Hz
MAX LOAD: 16A Electronic Ballast
20A Tungsten, Ballast, General Purpose
1/2 HP Motor
0-10 DIM: 100 mA SINK
Temp -10C to 50C @20A; -10C to 60C @12A
Suitable for Plenum Mounting
FCC ID: 2ADCB-RMODIT, IC: 6715C-RMODIT

THE ENCLOSED DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

BLK - HOT
WHT - NEUTRAL
BLU - SWITCHED OUT
VIO - DIM 0-10V
GRY - DIM-
GRN - GROUND

CAUTION:

Risk of Electric Shock - More than one disconnect switch may be required to de-energize the equipment before servicing. For supply connections, use 14 AWG or larger wires rated for at least 75°C.
CU ONLY

E326029



3D62
ENERGY
MGMT EQPT

Factory ID:74

Assembled In MEX

1.800.535.2465
AcuityControls.com

AcuityControls

nLight