



RF EXPOSURE Test Report

Report No.: MTi210330008-05E3

Date of issue: July 30, 2021

Applicant: EKEN GROUP LIMITED

Product name: Smart Video Doorbell

Model(s): T8, K8, K6, K7, K9, V8, T6, T9,
V6, V9

FCC ID: 2ADDG-T8

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



TEST RESULT CERTIFICATION

Applicant's name.....:	EKEN GROUP LIMITED
Address.....:	Room 2511-2512, Meilan Business Center Qianjin Two Road, XiXiang, Baoan District Shenzhen, Guangdong China
Manufacturer's Name	Shenzhen Puge Electronics Co., Ltd.
Address.....:	2F Building E, No. 1 LingXia Road, FengHuang Community, FuYong Street, BaoAn District, Shenzhen.

Product description

Product name	Smart Video Doorbell
Trademark	N/A
Model Name	T8
Serial Model	K8, K6, K7, K9, V8, T6, T9, V6, V9
Standards.....:	N/A
Test procedure.....:	KDB 447498 D01 v06


Date of Test

Date (s) of performance of tests	May 10, 2021 ~ July 20, 2021
Test Result.....:	Pass


This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Testing Engineer : 

 (Danny Xu)

Technical Manager : 

 (Leo Su)

Authorized Signatory : 

 (Tom Xue)



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Antenna Type: monopole Antenna;

WIFI antenna gain: 1dBi

433.92MHz:

Operation Frequency: 433.92MHz

Power density limited: 1mW/ cm²

Antenna Type: spring Antenna;

WIFI antenna gain: 1dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(1/10)}=1.26$

2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna Gain Numeric	Evaluation result at 20cm Power density(mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power				
				(dBm)	(mW)			
				Ant A	Ant A	Ant A	Ant A	
2412	802.11b	14.89	15±1	16	39.810717	1.26	0.00998	1
2437		15.11	15±1	16	39.810717	1.26	0.00998	1
2462		14.57	15±1	16	39.810717	1.26	0.00998	1
2412	802.11g	11.30	11±1	12	15.848932	1.26	0.00397	1
2437		13.21	13±1	14	25.118864	1.26	0.00630	1
2462		12.39	13±1	14	25.118864	1.26	0.00630	1
2412	802.11n H20	11.27	11±1	12	15.848932	1.26	0.00397	1
2437		13.24	13±1	14	25.118864	1.26	0.00630	1
2462		12.65	13±1	14	25.118864	1.26	0.00630	1
2422	802.11n H40	12.23	12±1	13	19.952623	1.26	0.00500	1
2437		12.39	12±1	13	19.952623	1.26	0.00500	1
2452		12.27	12±1	13	19.952623	1.26	0.00500	1



Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits	
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)	
		Ant A	Ant A	(dBm)	(mW)	Numeric			
433.92	ASK	-6	-6±1	Ant A	Ant A	Ant A	Ant A	0.0001	1

Conclusion:

For the max result: $0.00998+0.0001=0.01008 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----