

Tune up procedure

The output power setting of EUT is set in the factory and followed the max average level in below. There is no tune up procedure except factory default setting.

GSM 850

GSM(GMSK): 32dBm±1dB

GPRS/ (GMSK)

1 TX Slot: 32dBm±1dB

2 TX Slots: 32dBm±1dB

3 TX Slots: 30dBm±1dB

4 TX Slots: 29dBm±1dB

GSM 1900

GSM(GMSK): 28dBm±1dB

GPRS (GMSK)

1 TX Slot: 28dBm±1dB

2 TX Slots: 27dBm±1dB

3 TX Slots: 26dBm±1dB

4 TX Slots: 25dBm±1dB

WCDMA850

WCDMA: 23dBm±1dB

HSDPA: 22dBm±1dB

HSUPA: 22dBm±1dB

Wi-Fi

802.11b: 14dBm ± 1dB

802.11g: 13dBm ± 2dB

802.11n20: 13dBm ± 2dB

802.11n40: 12dBm ± 1dB

BT: 4dBm±1.5dB

BLE: -3dBm±1.5dB

By:

Zhang Lijing
(Signature)

Zhang Lijing

(Print name)

Title:

MANAGER

Date:

2015/11/12

On behalf of:

WUXI IDATA TECHNOLOGY COMPANY LTD.

Telephone:

0755-26966621-603
