



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0) Date : Oct 21, 2018

Application No. : LW029880(5)

Applicant : Kondor Limited
Radar Way
Christchurch Business Park
Christchurch, BH23, 4FL
United Kingdom

Sample Description :	Sample Description	Model No.
	Kitsound: District Qi Charge Headphone	KSDISBK

Date Received : Sep 13, 2018

Test Period : Sep 15, 2018 – Oct 20, 2018

Test Requested : FCC Certification for FCC Part 15, subpart C
ISED Certification for License-exempt Device


Test Method : 47 CFR Part 15 (10-1-17 Edition),
ANSI C63.10 – 2013,
ANSI C63.4 – 2014
RSS-247 Issue 2,
RSS-Gen Issue 5,

Test Engineer : Mr. Leung Shu Kan, Ken

Conclusion : The submitted sample was found to comply with technical requirement of FCC Part 15 Subpart C, section 15.247, and ISED Canada Radio Standards Specification RSS-247 Issue 2.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Manager
Electrical Division

Page 1 of 70

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Table of Contents

Table of Contents	2
1 Product Information	4
1.1 General Information.....	4
1.2 Technical Information.....	4
1.3 Associated Electric Accessories Information	5
1.4 Associated Cables	5
2.0 Equipment Units Tested (EUT).....	5
3.0 Location of Test Facility.....	5
4.0 List of test equipment, supporting equipment and cables.....	6
4.1 Test equipment.....	6
4.2 Supporting equipment.....	7
4.3 Cables.....	7
4.4 Software	7
5.0 Measurement Uncertainty.....	7
6.0 Measurement	8
6.1 General Test condition.....	8
6.2 Number of hopping frequency	8
6.2.1 Measurement	8
6.2.2 Final Result	8
6.3 Band-edge measurement.....	9
6.3.1 Measurement.....	9
6.3.2 Final Result	10
6.4 Carrier Frequency Separation	11
6.4.1 Measurement.....	11
6.4.2 Final Result	11
6.5 Time of occupancy (dwell time)	12
6.5.1 Measurement.....	12
6.5.2 Final Result	12
6.6 Output Power	13
6.6.1 Measurement.....	13
6.6.2 Final Result	13
6.7 Occupied Bandwidth.....	14
6.7.1 Measurement.....	14
6.7.2 Final Result	14
6.8 Conducted Spurious emission (Transmitter).....	15
6.8.1 Measurement.....	15
6.8.2 Final Result	15
6.9 Radiated Spurious emission (Transmitter).....	16
6.9.1 Measurement.....	16
6.9.2 Final Result	17

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.10	Conducted Emission.....	18
6.10.1	Measurement.....	18
6.10.2	Final Result.....	18
6.11	Frequency Stability.....	19
6.11.1	Measurement.....	19
6.11.2	Final Result.....	19
7.0	Frequency Hopping System Requirement.....	20
APPENDIX A	Test Result.....	23

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

1 Product Information

1.1 General Information

Product Description:	Model:
Kitsound: District Qi Charge Headphone	KSDISBK

Primary function : Receive the audio signal from player by Bluetooth communication

Power supply : DC 3.7V (Li-ion rechargeable), DC 5.0V (micro-USB)

RF related function : Bluetooth communication for audio communication

Electric Accessories sold with : Qi Charging base with DC 5.0V micro USB input

Interconnection cable associated sold with : NIL

Operating condition : Not specified

Model difference : Not applicable

Remark : NIL

1.2 Technical Information

Operating Frequency : 2402 – 2480MHz

Digital Modulation : FHSS

Modulation : GFSK, $\pi/4$ QDPSK, 8DPSK

Number of Channel : 79

Channel Bandwidth : 1MHz

Occupied Bandwidth : 1.20MHz

Signal Type : Data

Number of Antenna : One

Antenna Type : PCB Type Antenna

Antenna Gain : 1.0 dBi

Rated Input Voltage : DC 3.7V (Li-ion rechargeable), DC 5.0V (micro-USB)

RF Technology Used : Bluetooth 4.0+EDR (non BLE)

Simplex or Duplex : Half-duplex

Adaptivity : FHSS adaptivity

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

1.3 Associated Electric Accessories Information

Qi Charging base with DC5.0V micro USB input

1.4 Associated Cables

NIL

2.0 Equipment Units Tested (EUT)

Product Description : Kitsound: District Qi Charge Headphone
Model : KSDISBK
Serial No. : Not specified
Sample Type : Production Sample and engineering sample
Sample No. : RW032027-006(9)
Rationale of selection : Only one model number

3.0 Location of Test Facility

CMA Industrial Development Foundation Ltd.
Room 1302, Yan Hing Centre,
9-13 Wong Chuk Yeung,
Fo Tan, Shatin,
New Territories
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

4.0 List of test equipment, supporting equipment and cables

4.1 Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCS30	100001	01 Feb 2019	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	100152	07 Dec 2018	1Year
Spectrum Analyzer	R&S	FSV40	100964	08 Feb 2019	1Year
Spectrum Analyzer	Rohde & Schwarz	FSP30	100628	27 Mar 2019	1Year
Broadband Antenna	Schaffner	CBL6112B	2692	28 Mar 2019	2Years
Loop Antenna	EMCO	6502	00056620	25 Jan 2020	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	21 Dec 2018	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	21 Dec 2018	2Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	01 Aug 2020	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	01 Aug 2020	2Years
Coaxial Cable	Schaffner	RG 213/U	N/A	17 May 2019	1Year
Coaxial Cable	Suhner	RG 214/U	N/A	17 May 2019	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	21 Dec 2018	1Year
LISN	Rohde & Schwarz	ENV216	101323	16 Jan 2019	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	23 Oct 2019	1Year
Rohde & Schwarz TS8997 Testing System					
Spectrum Analyzer	Rohde & Schwarz	FSV 40	101190	08 Aug 2019	1Year
Vector Generator	Rohde & Schwarz	SMBV100A	262024	08 Aug 2019	1Year
Generator	Rohde & Schwarz	SMB100A	103230	08 Aug 2019	1Year
OSP	Rohde & Schwarz	OSP	OSP120 V02	08 Aug 2019	1Year

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

4.2 Supporting equipment

Equipment Name	Manufacturer	Model	Serial	Provided by
CSR control module	CSR	CSR-USB-SP1	Not labelled	Applicant
USB charger	Apple	A1299	Not labelled	CMA

Remark: *only used for configure engineering mode

4.3 Cables

Cable Type	Length	Shielding	Ferrite used	Provided by
USB Cable*	1m	Not shielded	No	CMA

Remark: *only used for configure engineering mode

4.4 Software

Software Name	Version	Function	Provided by
CSR BlueSuite – BlueTest3	V2.6.8	Configure Engineering mode	Applicant

Remark: *only used for configure engineering mode

5.0 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~1000MHz (Horizontal)	4.94dB
200MHz ~1000MHz (Vertical)	4.97dB
1GHz ~6GHz	4.52dB
6GHz ~18GHz	4.58dB

Line-conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz~30MHz	2.80dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.0 Measurement

6.1 General Test condition

Temperature : 27.3 °C
 Test Voltage : DC3.7V and 120Vac (Charging mode)
 Humidity : 50.0%
 Atmosphere Pressure : 101.1kPa

6.2 Number of hopping frequency

6.2.1 Measurement

Requirement : FCC Part 15 § 15.247(a)(1)(iii) and RSS-247 §5.1(d)
 Measuring procedure : ANSI C63.10:2013, clause 7.8.3
 Span : 83.5MHz
 RBW : 300kHz
 VBW : 300kHz
 Frequency range : 2.4000 – 2.4835GHz
 Modulation tested : GFSK
 Packet Type tested : DH5
 Additional measuring procedure : Nil

6.2.2 Final Result

No. of hopping channels measured	Limit	Result	Worst case mode
79	≥ 15	PASS	GFSK and DH5

Remark: Detail test result and equipment setting refer to appendix A, A3

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.3 Band-edge measurement

6.3.1 Measurement

Requirement : FCC Part 15 §15.247(d) and RSS-247 §5.5
Measuring procedure : ANSI C63.10:2013, section 7.8.6 and 6.10
Hopping mode : Enabled and Disable
RBW : 100kHz
VBW : 300kHz
Frequency range : 2310 – 2400MHz and 2483.5 – 2500MHz
Modulation tested : GFSK, $\pi/4$ QDPSK, 8DPSK
Packet Type tested : DH5
Channel tested for non-hopping mode : 2402MHz for lowed band edge and 2480MHz for higher band edge
Additional measuring procedure : For lower band edge (2400MHz)

1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental
2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2310 – 2400MHz to measure the bandedge reading
3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB

For Upper bandedge (2483.5MHz)

1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental
2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2483.5 – 2500MHz to measure the bandedge reading
3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.3.2 Final Result

Banded frequency for lower bandedge (Worst Case)	Worst case (dBc) ²	Detector	Limit ¹ (dBc)	Result	Worst case
2399.775000MHz	51.4	Peak	≥20.0	PASS	GFSK and DH5
Bandedge frequency for higher bandedge (Worst Case)	Worst case in (dBc) ²	Detector	Limit ¹	Result	Worst case
2494.825000MHz	54.6	Peak	≥20.0	PASS	GFSK and DH5

Remark: 1) The limit is based on the transmitter demonstrated compliance with peak conducted power limit on section 6.4.2 of this report.

2) The Worst case dBc is the peak values measured in procedure 1 minus the worst case bandedge emission

3) Detail test result and equipment setting refer to appendix A, A4-7, A12-13, A16-17

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.4 Carrier Frequency Separation

6.4.1 Measurement

Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(b)
 Measuring procedure : ANSI C63.10:2013, section 7.8.2
 Hopping mode : Enabled
 RBW : 300kHz
 VBW : 300kHz
 Frequency range : 2440 – 2443MHz¹
 Modulation tested : GFSK²
 Packet Type tested : DH5
 Additional measuring procedure : Nil
 Remark : 1) Since the measured value is more than 1.5 times of limit, only middle channel is measured.
 2) Since the modulation and packet type does not affect the channel separation, GFSK and DH5 are selected as represented modulation and data type

6.4.2 Final Result

Carrier Frequency Separation	Limit ¹	Result	Worst case mode
1.009900MHz	≥0.844200MHz	PASS	GFSK and DH5

Remark: 1) Limit is 2/3 of the 20dB bandwidth in section 6.7 and conducted peak power is less than 0.125W in section 6.6 of this report.

2) Detail test result and equipment setting refer to appendix A, A18-20

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.5 Time of occupancy (dwell time)

6.5.1 Measurement

- Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
- Measuring procedure : ANSI C63.10:2013, section 7.8.4
- Hopping mode : Disable
- RBW : 500kHz
- VBW : 1MHz
- Modulation tested : GFSK¹
- Packet Type tested : DH1, DH3, DH5
- Channel tested for non-hopping mode : 2441MHz
- Additional measuring procedure :
 - 1) Setup engineering sample to channel 2441MHz and DH1 packet size to perform the measurement according to ANSI C63.10, section 7.8.4
 - 2) Find the worst case packet size
 - 3) Repeat procedure1 with the worst case packet size for channel 2402MHz and 2480MHz
- Remark : 1) Since the modulation does not affect the dwell time, GFSK is selected as represented modulation.

6.5.2 Final Result

Dwell time (worst case)	Limit	Result	Worst case mode
312.540ms	≤400ms	PASS	GFSK and DH5

Remark: 1) Detail test result and equipment setting refer to appendix A, A8-10

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.6 Output Power

6.6.1 Measurement

Requirement : FCC Part 15 §15.247(b) (1) and RSS-247 §5.4
 Measuring procedure : ANSI C63.10:2013, section 7.8.5
 Hopping mode : Disable
 Modulation tested : GFSK, $\pi/4$ QPSK, 8DPSK
 Packet Type tested : DH5¹
 Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
 Additional measuring procedure : Nil
 Remark : 1) Since the packet size does not affect the output power, DH5 is selected as represented packet size.

6.6.2 Final Result

(a) Maximum peak conducted output power

Maximum peak conducted output power	Limit(s) ¹	Result	Modulation
6.4dBm	≤ 21.0 dBm	PASS	GFSK
6.4dBm	≤ 21.0 dBm	PASS	$\pi/4$ QPSK
6.4dBm	≤ 21.0 dBm	PASS	8DPSK

Remark: 1) 0.125W (21.0dBm) limit is used for 2/3 20dB bandwidth requirement for channel separation.

2) Detail test result and equipment setting refer to appendix A, A11, A14, A15

(b) Maximum peak e.i.r.p.(for RSS-247)

Maximum peak e.i.r.p. ¹	Limit(s) ²	Result	Modulation
7.4dBm	≤ 27.0 dBm	PASS	GFSK
7.4dBm	≤ 27.0 dBm	PASS	$\pi/4$ QPSK
7.4dBm	≤ 27.0 dBm	PASS	8DPSK

Remark: 1) Maximum peak e.i.r.p. = Maximum peak conducted output power + antenna gain (dBi)

2) Maximum peak e.i.r.p. limit = Maximum peak conducted output power limit + 6dBi

3) Detail test result and equipment setting refer to appendix A, A11, A14, A15

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.7 Occupied Bandwidth

6.7.1 Measurement

- Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
- Measuring procedure : ANSI C63.10:2013, section 7.8.7 and 6.9.2
- Hopping mode : Disable
- Modulation tested : GFSK, $\pi/4$ QPSK, 8DPSK
- Packet Type tested : DH5¹
- Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
- Additional measuring procedure : Nil
- Remark : 1) Since the packet size does not affect the bandwidth, DH5 is selected as represented packet size.

6.7.2 Final Result

20dB bandwidth	99% OBW	Modulation
0.952300MHz	0.876990MHz	GFSK
1.266300MHz	1.201160MHz	$\pi/4$ QPSK
1.251800MHz	1.164979MHz	8DPSK

Remark: 1) Detail test result and equipment setting refer to appendix A, A30 - 39

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.8 Conducted Spurious emission (Transmitter)

6.8.1 Measurement

Requirement	:	FCC Part 15 §15.247(d) and RSS-247 §5.5
Measuring procedure	:	ANSI C63.10:2013, section 5.5, 5.6, 7.8.8 and 11.12.2.1
Hopping mode	:	Disable
RBW	:	Refer to pre-measurement and final measurement setting
Detector	:	Refer to pre-measurement and final measurement setting
Modulation tested	:	GFSK ¹
Packet Type tested	:	DH5 ²
Channel tested for non-hopping mode	:	2402MHz, 2441MHz, 2480MHz
Additional measuring procedure	:	<ol style="list-style-type: none"> 1) Setup engineering sample to channel 2402MHz to perform the measurement according to ANSI C63.10, section 7.8.8 with pre-measurement setting 2) If the pre-measurement is over the limit, the final measurement is performed for the specific frequency according to final measurement setting or restricted band frequency 3) For non-restricted band frequency, peak detector and 100kHz RBW will be used for final measurement. 4) Repeat the procedure 1 to 3 for channel frequency of 2441MHz and 2480MHz
Remark	:	<ol style="list-style-type: none"> 1) Since the GFSK generates a higher SPD with power level, GFSK is selected as represented modulation for testing. 2) Since DH5 generates a higher dwell time, DH5 is selected as representative packet size for testing

6.8.2 Final Result

Worst case spurious emission frequency	Worst case spurious emission power ¹	Limit ²	Margin	Result	Worst case mode
2376.250MHz	-46.3dBm	-41.2dBm	-5.1dB	PASS	GFSK and DH5

- Remark: 1) Spurious emission power = measured conducted power + antenna gain(dBi) + ground reflection factor according to ANSI C63.10 section 11.12.2.2 for restricted band emission.
- 2) For restricted band emission, limit = restricted band field strength limit (dBuV/m) + 4.7dB – 104.8dB according to ANSI C63.10 section 11.12.2.2 For non-restricted band, limit = SPD/100kHz – 20dB.
- 3) Detail test result and equipment setting refer to appendix A, A21-29

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.9 Radiated Spurious emission (Transmitter)

6.9.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Bluetooth hopping + charging mode with GFSK modulation and DH5packet type are selected as worst case mode for spurious radiated emission test from cabinet. Other non-bluetooth operating mode such as charging mode and Aux-in mode for digital part of EUT may be tested.

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.9.2 Final Result

a) Test mode: Bluetooth hopping

Polarization	Frequency (MHz)	Reading at 3m (dB μ V)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)	Detector (PK/QP/AV)
V	2400.000	67.9	-4.7	63.2	74.0	-10.8	Peak
V	2400.000	51.0	-4.7	46.3	54.0	-7.7	Average
V	2483.500	57.7	-4.7	53.0	54.0	-1.0	Peak
V	4803.892	40.0	2.3	42.3	54.0	-11.7	Peak
V	4880.977	39.9	2.3	42.2	54.0	-11.8	Peak
V	4960.216	41.9	2.8	44.7	54.0	-9.3	Peak
V	7206.030	40.8	9.6	50.4	54.0	-3.6	Peak
H	7323.475	44.3	9.6	53.9	54.0	-0.1	Peak
H	7439.586	44.0	9.6	53.6	54.0	-0.4	Peak

Remark: 1) Field Strength = Reading + transducer factor.

2) Other emission with more than 20dB margin are not reported in this report.

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.10 Conducted Emission

6.10.1 Measurement

Requirement : FCC Part 15 §15.207(a) and RSS-Gen, clause 8.8
 Measuring procedure : ANSI C63.4:2014, section 7.3
 Test mode : Bluetooth Hopping + charging mode
 RBW : 9kHz
 VBW : 30kHz
 Modulation tested : GFSK¹
 Packet Type tested : DH5
 Additional measuring procedure : Nil
 Remark : Nil

6.10.2 Final Result

Worst case conducted emission frequency	Worst case conducted emission	Limit	Margin	Detector	Lines	Worst case mode	Result
0.4785MHz	36.47dBμV	46.36dBμV	-9.89dB	AV	L	charging	PASS

Remark: 1) Detail test result and equipment setting refer to appendix A, A40-41

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

6.11 Frequency Stability

6.11.1 Measurement

Requirement : RSS-Gen, clause 8.11
 Measuring procedure : ANSI C63.4:2014, section 6.8 and RSS Gen clause 6.11
 Test mode : Non-hopping mode without modulation
 RBW : 500Hz
 VBW : 3kHz
 Modulation tested : GFSK
 Packet Type tested : DH5
 Additional measuring procedure : Nil
 Remark : Nil

6.11.2 Final Result

Test Temperature (°C)	Test Channel (MHz)	Measured Channel Frequency (MHz)	Frequency range of 80% of channel bandwidth	Result
20	2402.00000	2401.98260	2401.60000 – 2402.40000	PASS
20	2441.00000	2440.98260	2440.60000 – 2441.40000	PASS
20	2480.00000	2479.98260	2479.60000 – 2480.40000	PASS
-20	2402.00000	2401.98550	2401.60000 – 2402.40000	PASS
-20	2441.00000	2440.98550	2440.60000 – 2441.40000	PASS
-20	2480.00000	2479.98550	2479.60000 – 2480.40000	PASS
50	2402.00000	2401.98220	2401.60000 – 2402.40000	PASS
50	2441.00000	2440.98220	2440.60000 – 2441.40000	PASS
50	2480.00000	2479.98220	2479.60000 – 2480.40000	PASS

Remark: 1) Test Voltage: DC 3.7V
 2) Channel Bandwidth: 1MHz

Test Voltage	Test Channel (MHz)	Measured Channel Frequency (MHz)	Frequency range of 80% of channel bandwidth	Result
DC 3.7V	2402.00000	2401.98260	2401.60000 – 2402.40000	PASS
DC 3.7V	2441.00000	2440.98260	2440.60000 – 2441.40000	PASS
DC 3.7V	2480.00000	2479.98260	2479.60000 – 2480.40000	PASS
DC 3.15V	2402.00000	2401.99550	2401.60000 – 2402.40000	PASS
DC 3.15V	2441.00000	2440.99548	2440.60000 – 2441.40000	PASS
DC 3.15V	2480.00000	2479.99551	2479.60000 – 2480.40000	PASS

FCC ID: 2ADFF-KSDISBK
 IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Remark: 1) Test temperature: 20°C
2) Channel Bandwidth: 1MHz

7.0 Frequency Hopping System Requirement

Test Requirement: Section 15.247(a)(1), (g), (h) and RSS-247, section 5.1 requirement

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom order list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmissions bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1) and RSS-247 section 5.1(a)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stage: 9
- Length of pseudorandom sequence: $2^9-1=511$ bits
- Longest sequence of zero: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page 21 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

An example of Pseudorandom Frequency Hopping Sequence as following:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g) and RSS-247 section 5.1 2nd paragraph

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h) and RSS-247 section 5.1 3rd paragraph

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in effort to avoid the simultaneous occupancy of the individual hopping frequencies by multiple transmitter.

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

APPENDIX A Test Result

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page 23 of 26

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

FCC Part 47 §15.247 2400-2483.5 MHz 2016

DUT Information

Frequencies

BT CH 0 (2402 MHz)	BT CH 1 (2403 MHz)	BT CH 2 (2404 MHz)
BT CH 3 (2405 MHz)	BT CH 4 (2406 MHz)	BT CH 5 (2407 MHz)
BT CH 6 (2408 MHz)	BT CH 7 (2409 MHz)	BT CH 8 (2410 MHz)
BT CH 9 (2411 MHz)	BT CH 10 (2412 MHz)	BT CH 11 (2413 MHz)
BT CH 12 (2414 MHz)	BT CH 13 (2415 MHz)	BT CH 14 (2416 MHz)
BT CH 15 (2417 MHz)	BT CH 16 (2418 MHz)	BT CH 17 (2419 MHz)
BT CH 18 (2420 MHz)	BT CH 19 (2421 MHz)	BT CH 20 (2422 MHz)
BT CH 21 (2423 MHz)	BT CH 22 (2424 MHz)	BT CH 23 (2425 MHz)
BT CH 24 (2426 MHz)	BT CH 25 (2427 MHz)	BT CH 26 (2428 MHz)
BT CH 27 (2429 MHz)	BT CH 28 (2430 MHz)	BT CH 29 (2431 MHz)
BT CH 30 (2432 MHz)	BT CH 31 (2433 MHz)	BT CH 32 (2434 MHz)
BT CH 33 (2435 MHz)	BT CH 34 (2436 MHz)	BT CH 35 (2437 MHz)
BT CH 36 (2438 MHz)	BT CH 37 (2439 MHz)	BT CH 38 (2440 MHz)
BT CH 39 (2441 MHz)	BT CH 40 (2442 MHz)	BT CH 41 (2443 MHz)
BT CH 42 (2444 MHz)	BT CH 43 (2445 MHz)	BT CH 44 (2446 MHz)
BT CH 45 (2447 MHz)	BT CH 46 (2448 MHz)	BT CH 47 (2449 MHz)
BT CH 48 (2450 MHz)	BT CH 49 (2451 MHz)	BT CH 50 (2452 MHz)
BT CH 51 (2453 MHz)	BT CH 52 (2454 MHz)	BT CH 53 (2455 MHz)
BT CH 54 (2456 MHz)	BT CH 55 (2457 MHz)	BT CH 56 (2458 MHz)
BT CH 57 (2459 MHz)	BT CH 58 (2460 MHz)	BT CH 59 (2461 MHz)
BT CH 60 (2462 MHz)	BT CH 61 (2463 MHz)	BT CH 62 (2464 MHz)
BT CH 63 (2465 MHz)	BT CH 64 (2466 MHz)	BT CH 65 (2467 MHz)
BT CH 66 (2468 MHz)	BT CH 67 (2469 MHz)	BT CH 68 (2470 MHz)
BT CH 69 (2471 MHz)	BT CH 70 (2472 MHz)	BT CH 71 (2473 MHz)
BT CH 72 (2474 MHz)	BT CH 73 (2475 MHz)	BT CH 74 (2476 MHz)
BT CH 75 (2477 MHz)	BT CH 76 (2478 MHz)	BT CH 77 (2479 MHz)
BT CH 78 (2480 MHz)		

Hardware Setup: WMS Measurements\TS8997

Spectrum Analyzer:	SA FSV 40 (SA FSV 40) @ VISA (ADR TCPIP::192.168.48.148::inst0::instr), SN 1321.3008K39/101190, FW 2.30 SP4
Vector Generator:	VG SMBV100A (VG SMBV100A) @ VISA (ADR TCPIP::192.168.48.149::inst0::instr), SN 262024, FW 3.1.19.8- 3.20.281.28.7
Generator:	SMB100A (SMB100A) @ VISA (ADR TCPIP::192.168.48.152::inst0::instr), SN 103230, FW 3.20.390.24 / Drv:Rev 2.21.0, 07/2016, CVI 2015

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

OSP:

OSP-B157W (OSP-B157W) @ VISA (ADR
TCP/IP::192.168.48.157::inst0::instr), SN 1527.1144.03 / 101057,
FW 1.23.0.2

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A2 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Hopping Frequencies (GFSK and DH5)

Channels

Channels	Limit Min	Limit Max	Result
79	15	---	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	<= 299.000 kHz
VBW	200.000 kHz	>= 200.000 kHz
SweepPoints	418	~ 418
Sweeptime	1.060 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	57 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.29 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Band Edge low (GFSK and DH5)

Result

DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2421.175000	2.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2374.025000	-49.6	22.4	-27.2	PASS
2340.875000	-50.2	22.9	-27.2	PASS
2340.825000	-50.3	23.1	-27.2	PASS
2359.175000	-50.4	23.2	-27.2	PASS
2359.225000	-50.8	23.6	-27.2	PASS
2374.075000	-51.0	23.7	-27.2	PASS
2373.975000	-51.3	24.1	-27.2	PASS
2373.025000	-51.7	24.5	-27.2	PASS
2368.125000	-51.8	24.6	-27.2	PASS
2373.075000	-51.9	24.7	-27.2	PASS
2372.925000	-52.0	24.8	-27.2	PASS
2375.825000	-52.2	25.0	-27.2	PASS
2375.775000	-52.2	25.0	-27.2	PASS
2371.125000	-52.2	25.0	-27.2	PASS
2338.175000	-52.3	25.1	-27.2	PASS

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level × Fail

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
Sweeptime	1.800 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

SweepPoints	1670	~ 1670
Sweeptime	1.670 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	150 / max. 150	max. 150
Stable	0 / 3	3
Max Stable Difference	3.76 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A6 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Band Edge high (GFSK and DH5)

Result

DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2420.175000	2.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2494.825000	-51.8	24.6	-27.2	PASS
2496.125000	-51.8	24.6	-27.2	PASS
2496.175000	-52.0	24.8	-27.2	PASS
2494.875000	-52.2	25.0	-27.2	PASS
2499.825000	-53.0	25.8	-27.2	PASS
2499.875000	-53.3	26.1	-27.2	PASS
2492.125000	-53.5	26.3	-27.2	PASS
2494.775000	-53.6	26.4	-27.2	PASS
2492.075000	-53.7	26.5	-27.2	PASS
2488.075000	-54.0	26.7	-27.2	PASS
2488.125000	-54.1	26.8	-27.2	PASS
2485.925000	-54.3	27.0	-27.2	PASS
2496.075000	-54.4	27.2	-27.2	PASS
2483.975000	-54.5	27.2	-27.2	PASS
2486.975000	-54.5	27.3	-27.2	PASS

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level × Fail

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	150 / max. 150	max. 150
Stable	0 / 3	3
Max Stable Difference	1.33 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A9 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Time of Channel Occupancy (2441 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	133.490	400.000	0.000	-16.0	PASS



— Trace — Threshold

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
Sweeptime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Time of Channel Occupancy(2) (2441 MHz; GFSK and 2-DH5)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	267.710	400.000	0.000	-16.0	PASS



— Trace — Threshold

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Time of Channel Occupancy(3) (2441 MHz; GFSK and 3-DH5)

Result

DUT Frequency (MHz)	Time (ms)	Limit Max (ms)	Limit Min (ms)	Threshold (dBm)	Result
2441.000000	312.540	400.000	0.000	-16.0	PASS



— Trace — Threshold

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	0.000 dBm	0.000 dBm
Attenuation	10.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 ms	0.000 ms

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

RF output power (2402 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2402.000000	1.5	21.0	2.5	77.742	PASS



— Gated Trace
 — Overall
 — Limit

FCC ID: 2ADFF-KSDISBK
 IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Band Edge low (2402 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2402.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2402.175000	0.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.775000	-50.6	21.4	-29.2	PASS
2399.725000	-50.9	21.6	-29.2	PASS
2399.825000	-51.0	21.7	-29.2	PASS
2399.975000	-51.1	21.9	-29.2	PASS
2399.625000	-51.1	21.9	-29.2	PASS
2399.675000	-51.2	21.9	-29.2	PASS
2399.925000	-51.8	22.6	-29.2	PASS
2399.575000	-52.2	22.9	-29.2	PASS
2399.875000	-52.2	23.0	-29.2	PASS
2399.475000	-52.3	23.1	-29.2	PASS
2399.525000	-52.6	23.4	-29.2	PASS
2399.425000	-53.9	24.6	-29.2	PASS
2399.375000	-55.1	25.9	-29.2	PASS
2399.325000	-57.9	28.6	-29.2	PASS
2399.175000	-58.6	29.4	-29.2	PASS

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level × Fail

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.09 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A16 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)


Date : Oct 21, 2018

RF output power (2441 MHz; GFSK and DH5)

Test according to FCC title 47 part 15 §15.247(b), KDB 558074 D01 DTS Meas Guidance v03r05 and ANSI C63.10

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2441.000000	6.4	21.0	7.4	77.868	PASS



— Gated Trace — Overall — Limit

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

RF output power (2480 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2480.000000	5.6	21.0	6.6	76.965	PASS



— Gated Trace
 — Overall
 — Limit

FCC ID: 2ADFF-KSDISBK
 IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Band Edge high (2480 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2480.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2479.875000	1.7

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.525000	-55.0	26.7	-28.3	PASS
2493.925000	-57.4	29.1	-28.3	PASS
2493.875000	-57.9	29.6	-28.3	PASS
2492.025000	-58.1	29.8	-28.3	PASS
2493.975000	-58.1	29.8	-28.3	PASS
2483.725000	-58.3	30.0	-28.3	PASS
2492.075000	-58.3	30.0	-28.3	PASS
2483.575000	-58.4	30.1	-28.3	PASS
2483.675000	-58.5	30.2	-28.3	PASS
2483.625000	-58.7	30.4	-28.3	PASS
2492.325000	-58.7	30.4	-28.3	PASS
2483.775000	-58.7	30.4	-28.3	PASS
2492.175000	-58.8	30.5	-28.3	PASS
2498.275000	-58.8	30.5	-28.3	PASS
2492.675000	-58.9	30.6	-28.3	PASS

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level × Fail

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.03 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Carrier Frequency Separation (2402 MHz; 4.000 dBm; 1 MHz)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2402.000000	1.009900	0.937293	---	2401.995050	2403.004950



(

Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Trace	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	22 / max. 150	max. 150

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Stable	10 / 10	10
Max Stable Difference	0.07 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A23 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Carrier Frequency Separation (2441 MHz; 4.000 dBm; 1 MHz)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2441.000000	1.009900	0.937293	---	2440.995050	2442.004950



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Stable	10 / 10	10
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

Carrier Frequency Separation (2479 MHz; 4.000 dBm; 1 MHz)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2479.000000	1.009900	0.937293	---	2478.995050	2480.004950



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	20 / max. 150	max. 150

FCC ID: 2ADFF-KSDISBK

IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Stable	10 / 10	10
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A27 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Tx Spurious Emission (2402 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2402.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
2399.750000	-36.7	11.2	-25.5
2298.750000	-53.4	12.2	-41.2
2298.250000	-53.5	12.3	-41.2
2497.750000	-53.8	12.6	-41.2
2498.250000	-53.8	12.6	-41.2
2297.750000	-54.1	12.9	-41.2
2496.250000	-54.7	13.5	-41.2
2496.750000	-54.8	13.6	-41.2
2499.750000	-55.6	14.4	-41.2
2498.750000	-55.7	14.5	-41.2
2299.250000	-56.0	14.8	-41.2
2495.750000	-56.0	14.8	-41.2
2350.250000	-56.1	14.9	-41.2
2350.750000	-56.2	15.0	-41.2
2497.250000	-56.3	15.1	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	18000.000000	2	2
18000.000000	26000.000000	2	2

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level — Threshold × Critical × Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK

Page A30 of 70

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Tx Spurious Emission (2441 MHz; 4 GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2441.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
2337.250000	-47.2	-49.9	-41.2	8.7	PASS
7322.750000	-44.6	-48.1	-41.2	6.9	PASS

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7322.750000	-44.6	3.4	-41.2
7322.250000	-44.7	3.5	-41.2
7323.750000	-45.0	3.8	-41.2
7323.250000	-45.0	3.8	-41.2
7324.250000	-46.8	5.6	-41.2
2337.250000	-47.2	6.0	-41.2
2337.750000	-47.2	6.0	-41.2
2336.750000	-47.3	6.1	-41.2
7321.750000	-49.3	8.1	-41.2
2338.250000	-50.5	9.3	-41.2
2363.250000	-50.7	9.5	-41.2
2363.750000	-50.8	9.6	-41.2
2493.250000	-51.0	9.8	-41.2
2362.750000	-51.1	9.9	-41.2
2493.750000	-51.2	10.0	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	18000.000000	2	2
18000.000000	26000.000000	2	2

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level — Threshold x Critical
x Final Critical ◆ Fail ◆ Pass

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.33 dB	0.50 dB

Final Measurement 2

Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	~ 3.000 MHz
SweepPoints	10001	~ 10001
SweepTime	1.000 s	1.000 s
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Tx Spurious Emission (2480 MHz; GFSK and DH5)

Result

DUT Frequency (MHz)	Result
2480.000000	PASS

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
2376.250000	-43.6	-46.3	-41.2	5.1	PASS
2483.750000	-43.7	-56.5	-41.2	15.3	PASS
7439.750000	-43.0	-46.6	-41.2	5.4	PASS

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7439.750000	-43.0	1.8	-41.2
7439.250000	-43.3	2.1	-41.2
7440.250000	-43.4	2.2	-41.2
7440.750000	-43.5	2.3	-41.2
2376.250000	-43.6	2.4	-41.2
2483.750000	-43.7	2.5	-41.2
2376.750000	-43.7	2.5	-41.2
2375.750000	-44.0	2.8	-41.2
2377.250000	-47.0	5.8	-41.2
7438.750000	-47.5	6.3	-41.2
2375.250000	-48.4	7.2	-41.2
7441.250000	-49.9	8.7	-41.2
7441.750000	-50.0	8.8	-41.2
2484.250000	-50.8	9.6	-41.2
2484.750000	-52.4	11.2	-41.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1000.000000	1	1
1000.000000	2400.000000	2	2
2400.000000	2483.500000	2	2
2483.500000	7000.000000	2	2
7000.000000	18000.000000	2	2
18000.000000	26000.000000	2	2

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



— Limit — Sum Level — Threshold × Critical
◆ Final Critical ◆ Fail ◆ Pass

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	19400	~ 19400
SweepTime	19.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Pre Measurement 2

Setting	Instrument Value	Target Value
RBW	1.000 MHz	<= 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	2800	~ 2800
SweepTime	2.800 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.09 dB	0.50 dB

Final Measurement 2

Setting	Instrument Value	Target Value
Span	ZeroSpan	ZeroSpan
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	~ 3.000 MHz
SweepPoints	10001	~ 10001
SweepTime	1.000 s	1.000 s
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

20dB bandwidth



2402MHz, GFSK



2402MHz, $\pi/4$ DQPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2402MHz, 8DPSK



2441MHz, GFSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2441MHz, $\pi/4$ DQPSK



2441MHz, 8DPSK

FCC ID: 2ADFF-KSDISBK
 IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2480MHz, GFSK



2480MHz, $\pi/4$ DQPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2480MHz, 8DPSK

FCC ID: 2ADFF-KSDISBK
 IC: 23562-KSDISBK



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AW0062807(0)

Date : Oct 21, 2018

99% Occupied bandwidth



2402MHz, GFSK



2402MHz, $\pi/4$ DQPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2402MHz, 8DPSK



2441MHz, GFSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2441MHz, $\pi/4$ DQPSK



2441MHz, 8DPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2480MHz, GFSK



2480MHz, $\pi/4$ DQPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018



2480MHz, 8DPSK

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

Conducted Emission


1) Bluetooth mode + charging mode



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0062807(0)

Date : Oct 21, 2018

EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCC-QP		
Trace2:	FCC-AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	213 kHz	29.24 N gnd	-33.84
1 Quasi Peak	429 kHz	32.01 L1 gnd	-25.25
2 Average	429 kHz	23.82 L1 gnd	-23.45
1 Quasi Peak	469.5 kHz	34.30 L1 gnd	-22.21
2 Average	478.5 kHz	36.47 L1 gnd	-9.89
2 Average	1.0355 MHz	22.42 L1 gnd	-23.57
1 Quasi Peak	1.184 MHz	24.29 L1 gnd	-31.70
1 Quasi Peak	1.3145 MHz	26.32 L1 gnd	-29.67
2 Average	1.508 MHz	25.42 L1 gnd	-20.57
1 Quasi Peak	3.0605 MHz	27.65 L1 gnd	-28.34
2 Average	3.0605 MHz	22.93 L1 gnd	-23.07
2 Average	4.055 MHz	20.78 L1 gnd	-25.21
1 Quasi Peak	4.9145 MHz	24.17 L1 gnd	-31.83
2 Average	10.2695 MHz	15.86 L1 gnd	-34.13
1 Quasi Peak	10.373 MHz	28.86 L1 gnd	-31.13
2 Average	17.6225 MHz	30.67 L1 gnd	-19.32
1 Quasi Peak	17.6495 MHz	41.75 L1 gnd	-18.24
1 Quasi Peak	17.8745 MHz	43.63 L1 gnd	-16.37
2 Average	18.122 MHz	31.53 L1 gnd	-18.46

***** End of Report *****

FCC ID: 2ADFF-KSDISBK
IC: 23562-KSDISBK