



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AY0051051(8) Date: Sep 13, 2019

Application No. : LY026333(6)

Applicant : KONDOR LIMITED  
CHRISTCHURCH BUSINESS PARK, RADAR WAY,  
BH23 4FL. UK

Sample Description : One(1) item of submitted sample stated to be

Product Description : ENGAGE 2 WIRELESS HEADPHONES WITH ANC  
Model : KSENGA2  
Sample registration No. : RY022415-002(5)  
Radio Frequency : 2402 – 2480MHz  
Supply voltage : DC3.7V (Li-ion rechargeable battery)  
DC5.0V (Charging pad)  
No. of submitted sample : 1

FCC ID : 2ADFF-KSENGA2

Date Received : Aug 13, 2019


Evaluation Period : Sep 05, 2018 – Sep 12, 2018

Evaluation Method : 447498 D01 General RF Exposure Guidance v06 - RF Exposure Procedure and  
Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The source-based time-averaged maximum conducted power of Bluetooth operation  
were satisfied RF exposure requirements.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-pong, Andrew  
Manager

Page 1 of 2

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmateesting.org](http://www.cmateesting.org).  
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : [info@cmateesting.org](mailto:info@cmateesting.org) Web Site : <http://www.cmateesting.org>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AY0051051(8)

Date: Sep 13, 2019

### Simultaneous power

No Simultaneous transmission

### RF Exposure Evaluation

According to KDB 447498 D01 clause 4.3.1 a), transmission from 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f(\text{GHz})} \right]$$

### Calculation

- Frequency : 2.480GHz
- Max. peak conducted output power , including tune-up tolerance : 0.07mW
- Minimum test separation distances : <5mm

where

-f(GHz) is the RF channel transmit frequency in GHz.

-Power and distance are rounded to the nearest mW and mm before calculation.

-The result is rounded to two decimal place for comparison.

Substitute above reading for calculation.

$$[(\text{mW}) / (\text{mm})] \times \sqrt{\text{GHz}}$$

Result = 0.022

Requirements:  $\leq 3.00$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

### Conclusion

The corresponding SAR test exclusion threshold was satisfied 4.3.1a) requirements. Measurement or numerical simulation is not required.

\*\*\*\*\* End of Evaluation \*\*\*\*\*