



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AW0005891(1) Date: Jan 16, 2018

Application No. : LV041517

Applicant : Kondor Limited

Sample Description : One(1) item of submitted sample stated to be

Product Description : Myjack2 bluetooth receiver  
Model : KSMYJACK2BK  
Sample registration No. : RV041777  
Radio Frequency : 2402 – 2480MHz  
Supply voltage : DC 3.7V  
No. of submitted sample : 2

FCC ID : 2ADFFKSMYJACK2

Date Received : December 16, 2017


Evaluation Period : December 28-29, 2017

Evaluation Method : 447498 D01 General RF Exposure Guidance v06 - RF Exposure Procedure and Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The maximum simultaneous power of Bluetooth operation were satisfied RF exposure requirements.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-pong, Andrew  
Manager  
Electrical Division

Page 1 of 2

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com)  
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## RF EXPOSURE EVALUATION

Report No. : AW0005891(1)

Date: Jan 16, 2018

### Simultaneous power

Not applicable because only Bluetooth transmitter installed on the device

### RF Exposure Evaluation

According to KDB 447498 D01 clause 4.3.1 a), transmission from 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

### Calculation

-Frequency : 2.480GHz  
-Max. power of channel in EIRP , including tune-up tolerance : 0.00933mW  
-Minimum test separation distances : <5mm

where

-f(GHz) is the RF channel transmit frequency in GHz.

-Power and distance are rounded to the nearest mW and mm before calculation.

-The result is rounded to two decimal place for comparison.

Substitute above reading for calculation.

$$[(\text{mW}) / (\text{mm})] \times \sqrt{\text{GHz}}$$

Result = 0.00

Requirements:  $\leq 3.00$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

### Conclusion

The corresponding SAR test exclusion threshold was satisfied 4.3.1a) requirements. Measurement or numerical simulation is not required.

\*\*\*\*\* End of Evaluation \*\*\*\*\*