

TEST REPORT

of

FCC Part 15 Subpart C

☒ New Application; ☐ Class I PC; ☐ Class II PC

Product : Dual Band Gigabit 802.11ac Wi-Fi Router

Brand: B Communications Ltd (BCOM)



Model: FZBOX1200AC

Model Difference: N/A

FCC ID: 2ADGL-FZ1200AC

FCC Rule Part: §15.247, Cat: DTS

Applicant: B Communications Pty Ltd

Address: 175 Heytesbury Rd ,Subiaco , WA 6008,
Australia

Test Performed by:
International Standards Laboratory

<Lung-Tan LAB>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-3;

*Address:

No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd.

Lung-Tan Hsiang, Tao Yuan County 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-14LR267FCDTS-R1

Issue Date : 2014/11/17

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.



VERIFICATION OF COMPLIANCE

Applicant: B Communications Pty Ltd

Product Description: Dual Band Gigabit 802.11ac Wi-Fi Router

Brand Name: B Communications Ltd (BCOM) 

Model No.: FZBOX1200AC

Model Difference: N/A

FCC ID: 2ADGL-FZ1200AC


Date of test: 2014/10/28 ~ 2014/11/14

Date of EUT Received: 2014/10/28

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:	 _____ Dino Chen / Engineer	Date:	2014/11/17 _____
Prepared By:	 _____ Gigi Yeh / Specialist	Date:	2014/11/17 _____
Approved By:	 _____ Vincent Su / Technical Manager	Date:	2014/11/17 _____

Version

Version No.	Date	Description
00	2014/11/17	Initial creation of document

Table of Contents

1	GENERAL INFORMATION	6
1.1	Related Submittal(s) / Grant (s)	8
1.2	Test Methodology	8
1.3	Test Facility	8
1.4	Special Accessories	8
1.5	Equipment Modifications	8
2	SYSTEM TEST CONFIGURATION	9
2.1	EUT Configuration	9
2.2	EUT Exercise	9
2.3	Test Procedure	9
2.4	Configuration of Tested System	10
3	SUMMARY OF TEST RESULTS	11
4	DESCRIPTION OF TEST MODES	11
5	CONDUCTED EMISSION TEST	12
5.1	Standard Applicable:	12
5.2	Measurement Equipment Used:	12
5.3	EUT Setup:	12
5.4	Measurement Procedure:	13
5.5	Measurement Result:	13
6	PEAK /AVERAGE OUTPUT POWER MEASUREMENT	16
6.1	Standard Applicable:	16
6.2	Measurement Equipment Used:	17
6.3	Test Set-up:	17
6.4	Measurement Procedure:	17
6.5	Measurement Result:	18
7	6dB Bandwidth & 99% Bandwidth	20
7.1	Standard Applicable:	20
7.2	Measurement Equipment Used:	20
7.3	Test Set-up:	20
7.4	Measurement Procedure:	20
7.5	Measurement Result:	21
8	100KHz BANDWIDTH OF BAND EDGES MEASUREMENT	28
8.1	Standard Applicable:	28
8.2	Measurement Equipment Used:	28
8.3	Test SET-UP:	29
8.4	Measurement Procedure:	30
8.5	Field Strength Calculation:	30
8.6	Measurement Result:	30
9	SPURIOUS RADIATED EMISSION TEST	41
9.1	Standard Applicable	41
9.2	Measurement Equipment Used:	41
9.3	Test SET-UP:	41
9.4	Measurement Procedure:	41
9.5	Field Strength Calculation	42
9.6	Measurement Result:	42

10	Peak Power Spectral Density	55
10.1	Standard Applicable:	55
10.2	Measurement Equipment Used:	55
10.3	Test Set-up:	55
10.4	Measurement Procedure:	55
10.5	Measurement Result:	56
11	ANTENNA REQUIREMENT	66
11.1	Standard Applicable	66
11.2	Antenna Connected Construction	66

1 GENERAL INFORMATION

General:

Product Name	Dual Band Gigabit 802.11ac Wi-Fi Router	
Brand Name	B Communications Ltd (BCOM) 	
Model Name	FZBOX1200AC	
Model Difference	N/A	
Hardware Version	N/A	
Software Version	N/A	
Adhoc Mode	No	
DFS Mode	N/A	
TPC	No	
Operation Environment	Indoor used	
USB port	one provided for Data link	
WAN port	one provided	
Gigabit LAN	four provided	
Power Supply	12Vdc from AC/DC adapter	
	Adapter:	Model: WA-18Q12FN
Antenna Designation	PCB DIPOLE ANTENNA P/N: PCA-2214-25GC1-A9 WiFi 2.4G Antenna : 2.78 dBi (Max) WiFi 5G Antenna : 2.53 dBi (Max) According to KDB662911 D01 SM-MIMO signals could be considered uncorrelated for purposes of directional gain computation. Directional gain = G_{ANT}	

2.4GHz WLAN: 2TX/2RX SM-MIMO / 5GHz WLAN: 2TX/2RX

Wi-Fi	Frequency Range (MHz)	Channels	Peak / Average Rated Power	Modulation Technology
802.11b	2412 – 2462(DTS)	11	22.14dBm (PK)	DSSS
802.11g	2412 – 2462(DTS)	11	24.85dBm (PK)	OFDM
802.11n (2.4G)	HT20 2412 – 2462(DTS)	11	27.65dBm (PK)	
	HT40 2422 – 2452(DTS)	7	27.29dBm (PK)	
802.11a	5180 – 5240(NII)	4	19.83dBm (AV)	
	5745 – 5825(NII)	5	17.29dBm (AV)	
802.11n(5G)	HT20 5180 – 5240(NII)	4	20.25dBm (AV)	
	HT20 5745 – 5825(NII)	5	19.83 dBm (AV)	
	HT40 5190 – 5230(NII)	3	19.90dBm (AV)	
	HT40 5755 – 5815(NII)	4	17.58dBm (AV)	
802.11ac	HT80 5210(NII)	1	19.86dBm (AV)	
	HT80 5775(NII)	1	16.84dBm (AV)	
Modulation type		CCK, DQPSK, DBPSK for DSSS 256QAM.64QAM. 16QAM, QPSK, BPSK for OFDM		

The EUT is compliance with IEEE 802.11 a/b/g/n/ac Standard.

This report applies for 802.11 b/g/n Wifi 2.4GHz modes.

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2ADGL-FZ1200AC** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2009 and RSS-Gen: 2010. Radiated testing was performed at an antenna to EUT distance 3 meters.

KDB Document: 558074 D01 DTS Meas Guidance v03r02

1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory** <Lung-Tan LAB> No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd., Lung-Tan Hsiang, Tao Yuan County 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2009. FCC Registration Number is: TW1036, Canada Registration Number: 4067B-3.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4: 2009, conducted emissions from the EUT are measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) were rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4: 2009.

2.4 Configuration of Tested System

Fig. 1 AC Power line and Radiated/Conducted Emission Configuration




Table 1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	Notebook	Lenovo	X220i	N/A	Shield	Non-shield

3 SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a) RSS-Gen §7.2.4	AC Power Line Conducted Emission	Compliant
§15.247(b) (3),(4) RSS-210 §A8.4(4)	Peak Output Power	Compliant
§15.247(a)(2) RSS-Gen §4.6.1	6dB Bandwidth & 99% Power Bandwidth	Compliant
§15.247(d) RSS-210 §A8.5	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d) RSS-210 §A8.5	Spurious Emission	Compliant
§15.247(e) RSS-210 §A8.2(b) & §A8.3(2)	Peak Power Density	Compliant
§15.203 §RSS-210 issue 8, §A8.4	Antenna Requirement	Compliant

4 DESCRIPTION OF TEST MODES

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

2.4GHz:

802.11 b mode: Channel low (2412MHz)、mid (2437MHz) and high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz)、mid (2437MHz) and high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n _20MHz: Channel low (2412MHz)、mid (2437MHz) and high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

802.11 n _40MHz: Channel low (2422MHz)、mid (2437MHz) and high (2452MHz) with 13.5Mbps lowest data rate are chosen for full testing.

The worst case 802.11n _20MHz mode was reported for Radiated Emission.

5 CONDUCTED EMISSION TEST

5.1 Standard Applicable:

According to §15.207 & RSS-Gen §7.2.4, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

5.2 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Conduction 04-1 Cable	WOKEN	CFD 300-NL	Conduction 04 -1	09/24/2014	09/23/2015
EMI Receiver 16	Rohde & Schwarz	ESCI	101221	05/08/2014	05/07/2015
LISN 18	ROHDE & SCHWARZ	ENV216	101424	03/13/2014	03/12/2015
LISN 19	ROHDE & SCHWARZ	ENV216	101425	03/13/2014	03/12/2015

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4: 2009.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.


5.5 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Operation Mode	Test Date:	2014/10/31
Test By:	Dino		



No.	Frequency (MHz)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)	Note
1	0.154	9.64	51.24	65.78	-14.54	35.79	55.78	-19.99	
2	0.186	9.61	48.24	64.21	-15.97	35.15	54.21	-19.06	
3	0.226	9.60	43.12	62.60	-19.48	28.30	52.60	-24.30	
4	0.234	9.60	42.34	62.31	-19.97	22.09	52.31	-30.22	
5	0.371	9.61	38.47	58.47	-20.00	29.67	48.47	-18.80	
6	0.454	9.61	42.93	56.80	-13.87	30.85	46.80	-15.95	
7	0.470	9.61	46.47	56.51	-10.04	39.95	46.51	-6.56	
8	0.494	9.61	39.79	56.10	-16.31	29.88	46.10	-16.22	



Address: No.120, Lane 180, San Ho Tsuen, Hsin Ho Road, Lung-Tan Hsiang,
Tao Yuan County, Taiwan R.O.C.
Tel: 03-4071718


Conducted Emission Measurement

Date: 2014/10/31

operator: Anson J Huang

Temperature: 26 °C

Humidity: 54 %



Site: Conduction 04

Phase: *N*

Limit: CISPR22 Class B Conduction(QP)

No.	Frequency (MHz)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)	Note
1	0.166	9.62	50.95	65.16	-14.21	28.34	55.16	-26.82	
2	0.186	9.62	49.84	64.21	-14.37	32.74	54.21	-21.47	
3	0.206	9.62	46.67	63.37	-16.70	22.33	53.37	-31.04	
4	0.214	9.62	46.11	63.05	-16.94	28.10	53.05	-24.95	
5	0.446	9.62	39.56	56.95	-17.39	25.62	46.95	-21.33	
6	0.470	9.62	45.86	56.51	-10.65	35.00	46.51	-11.51	
7	0.490	9.62	39.12	56.17	-17.05	26.10	46.17	-20.07	
8	22.190	10.12	37.74	60.00	-22.26	30.47	50.00	-19.53	

6 PEAK /AVERAGE OUTPUT POWER MEASUREMENT

6.1 Standard Applicable:

According to §15.247(b)(3),(4)(b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple 802.11n_40Ms of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:


(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

6.2 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power Meter 05	Anritsu	ML2495A	1116010	05/08/2014	05/07/2015
Power Sensor 05	Anritsu	MA2411B	34NKF50	05/08/2014	05/07/2015
Power Sensor 06	DARE	RPR3006W	13I00030SNO33	10/18/2014	10/17/2015
Power Sensor 07	DARE	RPR3006W	13I00030SNO34	10/18/2014	10/17/2015
Temperature Chamber	KSON	THS-B4H100	2287	03/17/2014	03/16/2015
DC Power supply	ABM	51850	N/A	07/16/2014	07/15/2015
AC Power supply	EXTECH	CFC105W	NA	12/19/2013	12/18/2014
Attenuator	Woken	Watt-65m3502	11051601	NA	NA
Splitter	MCLI	PS4-199	12465	12/27/2013	12/26/2014
Spectrum analyzer	Agilent	N9030A	MY51360021	05/02/2014	05/01/2015

6.3 Test Set-up:



6.4 Measurement Procedure:

Refer to section 9.1.3 and 9.2.3 Peak and Average Conducted Output Power Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r02

6.5 Measurement Result:

WiFi 1TX

802.11b

Cable loss = 0		Output Power		Limit (dBm)
CH	Frequency (MHz)	Detector		
		PK (dBm)	AV (dBm)	
1	2412	22.14	19.91	30
6	2437	21.94	19.74	
11	2462	20.65	18.48	

802.11g

Cable loss = 0		Output Power		Limit (dBm)
CH	Frequency (MHz)	Detector		
		PK (dBm)	AV (dBm)	
1	2412	24.85	17.11	30
6	2437	24.78	17.09	
11	2462	24.71	16.69	

PEAK FOR 2.4G

2*2

Channel		Frequency (MHz)	Output Chain (dBm)		Combine Output Power (dBm)	Limit(dBm)	Result
			Chain A	chain B			
AN HT20	1	2412	24.52	24.75	27.65	30	Pass
	6	2437	24.42	24.63	27.54	30	Pass
	11	2462	24.41	24.61	27.52	30	Pass
AN HT40	3	2422	24.51	24.03	27.29	30	Pass
	7	2437	24.48	23.91	27.21	30	Pass
	9	2452	24.12	23.59	26.87	30	Pass

AV FOR 2.4G

2*2

Channel		Frequency (MHz)	Output Chain (dBm)		Combine Output Power (dBm)	Limit(dBm)	Result
			Chain A	chain B			
AN HT20	1	2412	16.21	16.72	19.48	30	Pass
	6	2437	16.13	16.64	19.40	30	Pass
	11	2462	15.99	16.15	19.08	30	Pass
AN HT40	3	2422	16.13	16.06	19.11	30	Pass
	6	2437	16.12	16.02	19.08	30	Pass
	9	2452	16.11	15.84	18.99	30	Pass

7 6dB Bandwidth & 99% Bandwidth

7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

7.3 Test Set-up:

Refer to section 6.3 for details.

7.4 Measurement Procedure:

Refer to section 8.1 DTS bandwidth Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r02

1. Set resolution bandwidth (RBW) = 100KHz.
2. Set the video bandwidth (VBW) = 300KHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement.

7.5 Measurement Result:

802.11b

Frequency (MHz)	Bandwidth (MHz)	Bandwidth (KHz)	Result
2412	10.08	> 500	PASS
2437	10.02	> 500	PASS
2462	10.14	> 500	PASS

802.11g

Frequency (MHz)	Bandwidth (MHz)	Bandwidth (KHz)	Result
2412	16.44	> 500	PASS
2437	16.44	> 500	PASS
2462	16.38	> 500	PASS

802.11n HT20

Frequency (MHz)	Bandwidth (MHz)	Bandwidth (KHz)	Result
2412	17.58	> 500	PASS
2437	17.64	> 500	PASS
2462	17.70	> 500	PASS


802.11n HT40

Frequency (MHz)	Bandwidth (MHz)	Bandwidth (KHz)	Result
2422	35.52	> 500	PASS
2437	35.52	> 500	PASS
2452	36.12	> 500	PASS

Note: Refer to next page for plots.


802.11b

6dB Band Width Test Data CH-Low




Date: 3.NOV.2014 10:20:06

6dB Band Width Test Data CH-Mid



Date: 3.NOV.2014 10:21:31


6dB Band Width Test Data CH-High



Date: 3.NOV.2014 10:22:57


802.11g

6dB Band Width Test Data CH-Low




Date: 3.NOV.2014 10:25:27

6dB Band Width Test Data CH-Mid



Date: 3.NOV.2014 10:26:56


6dB Band Width Test Data CH-High



Date: 3.NOV.2014 10:28:47


802.11n_20M

6dB Band Width Test Data CH-Low




Date: 3.NOV.2014 10:32:10

6dB Band Width Test Data CH-Mid



Date: 3.NOV.2014 10:35:22


6dB Band Width Test Data CH-High



Date: 3.NOV.2014 10:39:41


802.11n_40M

6dB Band Width Test Data CH-Low




Date: 3.NOV.2014 10:43:03

6dB Band Width Test Data CH-Mid



Date: 3.NOV.2014 10:45:07

6dB Band Width Test Data CH-High



Date: 3.NOV.2014 10:46:43

8 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

8.1 Standard Applicable:

According to §15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Measurement Equipment Used:

8.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2 Radiated emission:

Chamber 14(966)					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer 21(26.5GHz)	Agilent	N9010A	MY49060537	07/29/2014	07/28/2015
Spectrum Analyzer 20(6.5GHz)	Agilent	E4443A	MY48250315	05/26/2014	05/25/2015
Spectrum Analyzer 22(43GHz)	R&S	FSU43	100143	05/07/2014	05/06/2015
Loop Antenna9K-30M	A.H.SYSTEM	SAS-564	294	03/07/2013	03/06/2015
Bilog Antenna30-1G	Schaffner	CBL 6112B	2756	01/08/2014	01/07/2015
Horn antenna1-18G(06)	EMCO	3117	0006665	11/04/2014	11/03/2015
Horn antenna26-40G(05)	Com-power	AH-640	100A	01/09/2013	01/08/2015
Horn antenna18-26G(04)	Com-power	AH-826	081001	05/15/2013	05/14/2015
Preamplifier9-1000M	HP	8447D	NA	02/20/2014	02/19/2015
Preamplifier1-18G	MITEQ	AFS44-001018 00-25-10P-44	1329256	07/30/2014	07/29/2015
Preamplifier1-26G	EM	EM01M26G	NA	02/20/2014	02/19/2015
Preamplifier26-40G	MITEQ	JS-26004000-2 7-5A	818471	05/08/2013	05/07/2015
Cable1-18G	HUBER SUHNER	Sucoflex 106	NA	02/17/2014	02/16/2015
Cable UP to 1G	HUBER SUHNER	RG 214/U	NA	10/17/2014	10/16/2015
SUCOFLEX 1GHz~40GHz cable	HUBER SUHNER	Sucoflex 102	27963/2&3742 1/2	10/03/2013	10/02/2015
2.4G Filter	Micro-Tronics	Brm50702	76	12/27/2013	12/26/2014
5G Filter	Micro-Tronics	Brm50716	005	12/27/2013	12/26/2014


8.3 Test SET-UP:

8.3.1 Conducted Emission at antenna port:


Refer to section 6.3 for details.

8.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



8.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW=100kHz, VBW=3* RBW, Span=25MHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

Refer to section 11 and 12 emissions in restricted and non-restricted frequency bands Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r02

The measurement of unwanted emissions at the edge of the authorized frequency bands can be complicated by the leakage of RF energy from the fundamental emission into the RBW pass band. Thus, for measurements at the band edges, a narrower resolution bandwidth (no less than 10 kHz) can be used within the first 1 MHz beyond the fundamental emission, provided that that measured energy is subsequently integrated over the appropriate reference bandwidth (i.e., 100 kHz or 1 MHz). This integration can be performed using the band power function of the spectrum analyzer or by summing the spectral levels (in linear power units) over the appropriate reference bandwidth.

8.5 Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$


Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.


802.11b

Band Edges Test Data CH-Low



Date: 3.NOV.2014 10:52:36

Band Edges Test Data CH-High



Date: 3.NOV.2014 10:54:28

Radiated Emission: 802.11 b mode

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2388.85	18.74	31.39	50.13	54.00	-3.87	Average	VERTICAL
2	2388.85	40.58	31.39	71.97	74.00	-2.03	Peak	VERTICAL
3	2390.00	18.18	31.40	49.58	54.00	-4.42	Average	VERTICAL
4	2390.00	38.29	31.40	69.69	74.00	-4.31	Peak	VERTICAL
1	2389.07	16.33	31.39	47.72	54.00	-6.28	Average	HORIZONTAL
2	2389.07	40.72	31.39	72.11	74.00	-1.89	Peak	HORIZONTAL
3	2390.00	18.03	31.40	49.43	54.00	-4.57	Average	HORIZONTAL
4	2390.00	38.69	31.40	70.09	74.00	-3.91	Peak	HORIZONTAL

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %


No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2483.50	17.12	31.56	48.68	54.00	-5.32	Average	VERTICAL
2	2483.50	38.53	31.56	70.09	74.00	-3.91	Peak	VERTICAL
3	2486.46	17.23	31.56	48.79	54.00	-5.21	Average	VERTICAL
4	2486.46	40.40	31.56	71.96	74.00	-2.04	Peak	VERTICAL
1	2483.50	16.28	31.56	47.84	54.00	-6.16	Average	HORIZONTAL
2	2483.50	38.92	31.56	70.48	74.00	-3.52	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.


802.11g

Band Edges Test Data CH-Low



Date: 3.NOV.2014 10:56:20

Band Edges Test Data CH-High



Date: 3.NOV.2014 10:58:05

Radiated Emission: 802.11 g mode

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2390.00	19.71	31.40	51.11	54.00	-2.89	Average	VERTICAL
2	2390.00	34.49	31.40	65.89	74.00	-8.11	Peak	VERTICAL
1	2390.00	18.57	31.40	49.97	54.00	-4.03	Average	HORIZONTAL
2	2390.00	32.48	31.40	63.88	74.00	-10.12	Peak	HORIZONTAL

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25


Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2483.50	18.66	31.56	50.22	54.00	-3.78	Average	VERTICAL
2	2483.50	35.87	31.56	67.43	74.00	-6.57	Peak	VERTICAL
3	2483.87	18.82	31.56	50.38	54.00	-3.62	Average	VERTICAL
4	2483.87	38.78	31.56	70.34	74.00	-3.66	Peak	VERTICAL
1	2483.50	17.60	31.56	49.16	54.00	-4.84	Average	HORIZONTAL
2	2483.50	33.03	31.56	64.59	74.00	-9.41	Peak	HORIZONTAL

Remark:


- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

802.11n_20M chain A Band Edges Test Data CH-Low



Date: 3.NOV.2014 11:02:17


Band Edges Test Data CH-High



Date: 3.NOV.2014 11:13:25


802.11n_20M chain B

Band Edges Test Data CH-Low



Date: 3.NOV.2014 11:23:48

Band Edges Test Data CH-High



Date: 3.NOV.2014 11:25:40

Radiated Emission: 802.11 n_20M mode

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2383.70	19.50	31.39	50.89	54.00	-3.11	Average	VERTICAL
2	2383.70	37.31	31.39	68.70	74.00	-5.30	Peak	VERTICAL
3	2390.00	20.13	31.40	51.53	54.00	-2.47	Average	VERTICAL
4	2390.00	35.47	31.40	66.87	74.00	-7.13	Peak	VERTICAL
1	2383.92	18.76	31.39	50.15	54.00	-3.85	Average	HORIZONTAL
2	2383.92	35.61	31.39	67.00	74.00	-7.00	Peak	HORIZONTAL
3	2390.00	18.94	31.40	50.34	54.00	-3.66	Average	HORIZONTAL
4	2390.00	35.00	31.40	66.40	74.00	-7.60	Peak	HORIZONTAL

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25


Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2483.50	19.67	31.56	51.23	54.00	-2.77	Average	VERTICAL
2	2483.50	36.46	31.56	68.02	74.00	-5.98	Peak	VERTICAL
3	2484.06	18.63	31.56	50.19	54.00	-3.81	Average	VERTICAL
4	2484.06	38.36	31.56	69.92	74.00	-4.08	Peak	VERTICAL
1	2483.50	17.71	31.56	49.27	54.00	-4.73	Average	HORIZONTAL
2	2483.50	31.92	31.56	63.48	74.00	-10.52	Peak	HORIZONTAL
3	2488.38	17.63	31.56	49.19	54.00	-4.81	Average	HORIZONTAL
4	2488.38	36.10	31.56	67.66	74.00	-6.34	Peak	HORIZONTAL

Remark:


- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

802.11n_40M chain A Band Edges Test Data CH-Low



Date: 3.NOV.2014 11:15:10


Band Edges Test Data CH-High



Date: 3.NOV.2014 11:17:05


802.11n_40M chain B

Band Edges Test Data CH-Low



Date: 3.NOV.2014 11:21:16

Band Edges Test Data CH-High



Date: 3.NOV.2014 11:19:21

Radiated Emission: 802.11n_40M mode

Operation Mode TX CH Low
Fundamental Frequency 2422 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2380.88	18.73	31.38	50.11	54.00	-3.89	Average	VERTICAL
2	2380.88	39.98	31.38	71.36	74.00	-2.64	Peak	VERTICAL
3	2390.00	18.51	31.40	49.91	54.00	-4.09	Average	VERTICAL
4	2390.00	37.74	31.40	69.14	74.00	-4.86	Peak	VERTICAL
1	2386.43	16.52	31.39	47.91	54.00	-6.09	Average	HORIZONTAL
2	2386.43	37.30	31.39	68.69	74.00	-5.31	Peak	HORIZONTAL
3	2390.00	18.67	31.40	50.07	54.00	-3.93	Average	HORIZONTAL
4	2390.00	34.91	31.40	66.31	74.00	-7.69	Peak	HORIZONTAL

Operation Mode TX CH High
Fundamental Frequency 2452 MHz
Temperature 25

Test Date 2014/11/05
Test By Dino
Humidity 60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2483.50	17.17	31.56	48.73	54.00	-5.27	Average	VERTICAL
2	2483.50	37.22	31.56	68.78	74.00	-5.22	Peak	VERTICAL
3	2483.61	17.33	31.56	48.89	54.00	-5.11	Average	VERTICAL
4	2483.61	40.00	31.56	71.56	74.00	-2.44	Peak	VERTICAL
1	2483.50	16.65	31.56	48.21	54.00	-5.79	Average	HORIZONTAL
2	2483.50	32.35	31.56	63.91	74.00	-10.09	Peak	HORIZONTAL
3	2485.04	16.85	31.56	48.41	54.00	-5.59	Average	HORIZONTAL
4	2485.04	37.49	31.56	69.05	74.00	-4.95	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

9 SPURIOUS RADIATED EMISSION TEST

9.1 Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

9.2 Measurement Equipment Used:

9.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

9.2.2 Radiated emission:

Refer to section 7.2 for details.

9.3 Test SET-UP:

9.3.1 Conducted Emission at antenna port:

Refer to section 6.3 for details.

9.3.2 Radiated emission:

Refer to section 7.3 for details.

9.4 Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

Refer to section 11 and 12 emissions in restricted and non-restricted frequency bands Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r02

9.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	


9.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Conducted Spurious Emission Measurement Result (802.11n 20M chain A)


(worst case)

Ch Low 30MHz – 3GHz



Date: 3.NOV.2014 13:10:55

Ch Low 3GHz – 26.5GHz



Date: 3.NOV.2014 13:11:31




翔智科技股份有限公司
International Standards Laboratory

-44 of 66-


FCC ID: 2ADGL-FZ1200AC

Ch Mid 30MHz – 3GHz



Date: 3.NOV.2014 13:12:44

Ch Mid 3GHz – 26.5GHz



Date: 3.NOV.2014 13:13:37




翔智科技股份有限公司
International Standards Laboratory

-45 of 66-


FCC ID: 2ADGL-FZ1200AC

Ch High 30MHz – 3GHz



Date: 3.NOV.2014 13:14:43

Ch High 3GHz – 26.5GHz




Date: 3.NOV.2014 13:15:23

Conducted Spurious Emission Measurement Result (802.11n 20M chain B)


(worst case)

Ch Low 30MHz – 3GHz



Date: 3.NOV.2014 12:42:59

Ch Low 3GHz – 26.5GHz



Date: 3.NOV.2014 12:43:52




翔智科技股份有限公司
International Standards Laboratory

-47 of 66-


FCC ID: 2ADGL-FZ1200AC

Ch Mid 30MHz – 3GHz



Date: 3.NOV.2014 12:45:18

Ch Mid 3GHz – 26.5GHz



Date: 3.NOV.2014 12:48:25




翔智科技股份有限公司
International Standards Laboratory

-48 of 66-


FCC ID: 2ADGL-FZ1200AC

Ch High 30MHz – 3GHz



Date: 3.NOV.2014 12:39:56

Ch High 3GHz – 26.5GHz



Date: 3.NOV.2014 12:41:13

Radiated Spurious Emission Measurement Result (below 1GHz) (worst case)

Operation Mode	802.11n_20M TX CH Low	Test Date	2014/11/05
Fundamental Frequency	2412MHz	Test By	Dino
Temperature	25	Humidity	60 %

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	125.06	51.99	-14.50	37.49	43.50	-6.01	Peak	VERTICAL
2	174.53	52.01	-13.02	38.99	43.50	-4.51	Peak	VERTICAL
3	199.75	53.39	-15.22	38.17	43.50	-5.33	Peak	VERTICAL
4	399.57	41.05	-9.19	31.86	46.00	-14.14	Peak	VERTICAL
5	480.08	34.91	-7.59	27.32	46.00	-18.68	Peak	VERTICAL
6	740.04	30.50	-3.12	27.38	46.00	-18.62	Peak	VERTICAL
1	104.69	50.53	-16.72	33.81	43.50	-9.69	Peak	HORIZONTAL
2	155.13	47.77	-12.10	35.67	43.50	-7.83	Peak	HORIZONTAL
3	199.75	53.79	-15.22	38.57	43.50	-4.93	Peak	HORIZONTAL
4	255.04	52.31	-12.76	39.55	46.00	-6.45	Peak	HORIZONTAL
5	364.65	41.16	-9.84	31.32	46.00	-14.68	Peak	HORIZONTAL
6	813.76	32.38	-1.99	30.39	46.00	-15.61	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n_20M TX CH Mid	Test Date	2014/11/05
Fundamental Frequency	2437MHz	Test By	Dino
Temperature	25	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	125.06	52.43	-14.50	37.93	43.50	-5.57	Peak	VERTICAL
2	174.53	51.19	-13.02	38.17	43.50	-5.33	Peak	VERTICAL
3	199.75	53.30	-15.22	38.08	43.50	-5.42	Peak	VERTICAL
4	333.61	41.03	-10.43	30.60	46.00	-15.40	Peak	VERTICAL
5	399.57	40.39	-9.19	31.20	46.00	-14.80	Peak	VERTICAL
6	854.50	29.30	-1.36	27.94	46.00	-18.06	Peak	VERTICAL
1	104.69	49.45	-16.72	32.73	43.50	-10.77	Peak	HORIZONTAL
2	199.75	54.19	-15.22	38.97	43.50	-4.53	Peak	HORIZONTAL
3	255.04	52.48	-12.76	39.72	46.00	-6.28	Peak	HORIZONTAL
4	399.57	42.85	-9.19	33.66	46.00	-12.34	Peak	HORIZONTAL
5	480.08	38.39	-7.59	30.80	46.00	-15.20	Peak	HORIZONTAL
6	813.76	32.19	-1.99	30.20	46.00	-15.80	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n_20M TX CH High	Test Date	2014/11/05
Fundamental Frequency	2462MHz	Test By	Dino
Temperature	25	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	125.06	51.85	-14.50	37.35	43.50	-6.15	Peak	VERTICAL
2	174.53	51.87	-13.02	38.85	43.50	-4.65	Peak	VERTICAL
3	199.75	53.20	-15.22	37.98	43.50	-5.52	Peak	VERTICAL
4	250.19	46.24	-12.89	33.35	46.00	-12.65	Peak	VERTICAL
5	399.57	40.17	-9.19	30.98	46.00	-15.02	Peak	VERTICAL
6	854.50	29.12	-1.36	27.76	46.00	-18.24	Peak	VERTICAL
1	104.69	49.51	-16.72	32.79	43.50	-10.71	Peak	HORIZONTAL
2	155.13	47.55	-12.10	35.45	43.50	-8.05	Peak	HORIZONTAL
3	199.75	53.99	-15.22	38.77	43.50	-4.73	Peak	HORIZONTAL
4	250.19	51.74	-12.89	38.85	46.00	-7.15	Peak	HORIZONTAL
5	399.57	41.78	-9.19	32.59	46.00	-13.41	Peak	HORIZONTAL
6	816.67	31.64	-1.94	29.70	46.00	-16.30	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz) (worst case)

Operation Mode	802.11n_20M TX CH Low	Test Date	2014/11/05
Fundamental Frequency	2412MHz	Test By	Dino
Temperature	25	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2162.00	62.10	-11.64	50.46	74.00	-23.54	Peak	VERTICAL
2	4824.00	45.15	-1.83	43.32	74.00	-30.68	Peak	VERTICAL
1	2162.00	60.60	-11.64	48.96	74.00	-25.04	Peak	HORIZONTAL
2	4824.00	46.13	-1.83	44.30	74.00	-29.70	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n_20M TX CH Mid	Test Date	2014/11/05
Fundamental Frequency	2437MHz	Test By	Dino
Temperature	25	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2162.00	63.01	-11.64	51.37	74.00	-22.63	Peak	VERTICAL
2	4874.00	44.73	-1.63	43.10	74.00	-30.90	Peak	VERTICAL
1	2162.00	61.20	-11.64	49.56	74.00	-24.44	Peak	HORIZONTAL
2	4874.00	45.01	-1.63	43.38	74.00	-30.62	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n_20M TX CH High	Test Date	2014/11/05
Fundamental Frequency	2462MHz	Test By	Dino
Temperature	25	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2162.00	63.33	-11.64	51.69	74.00	-22.31	Peak	VERTICAL
2	4924.00	45.90	-1.44	44.46	74.00	-29.54	Peak	VERTICAL
1	2162.00	61.22	-11.64	49.58	74.00	-24.42	Peak	HORIZONTAL
2	4924.00	43.87	-1.44	42.43	74.00	-31.57	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

10 Peak Power Spectral Density

10.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

10.2 Measurement Equipment Used:

Refer to section 6.2 for details.

10.3 Test Set-up:

Refer to section 6.3 for details.

10.4 Measurement Procedure:

Refer to section 10.2 Peak Power Density(PKPPSD) Measurement Procedure of KDB Document: 558074 D01 DTS Meas Guidance v03r02

1. Set analyzer center frequency to DTS channel frequency
2. Set the span to 1.5 times the DTS bandwidth.
3. Set resolution bandwidth $3\text{KHz} \leq \text{RBW} \leq 100\text{KHz}$.
4. Set the video bandwidth $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

10.5 Measurement Result:

WiFi 1TX

802.11b Mode

Frequency MHz	Power Density Level (dBm)	Maximum Limit (dBm)
2412	4.04	8
2437	-1.5	8
2462	3.36	8

802.11g Mode


Frequency MHz	Power Density Level (dBm)	Maximum Limit (dBm)
2412	-11.75	8
2437	-11.79	8
2462	-12.64	8

WiFi 2TX * 2TX

	Frequency (MHz)	Output Chain dbm		Combine Power Density (dBm/3KHz)	Limit(dBm)	Result
		Chain A	chain B			
AN HT20	2412	-12.18	-9.4	-7.56	8	Pass
	2437	-12.22	-9.37	-7.55	8	Pass
	2462	-12.35	-10.44	-8.28	8	Pass
AN HT40	2422	-17.56	-15.22	-13.22	8	Pass
	2437	-17.04	-16	-13.48	8	Pass
	2452	-18.08	-15.69	-13.71	8	Pass


802.11b

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 13:37:18

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 13:38:10


Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 13:43:11


802.11g

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 13:45:34

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 13:46:25


Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 13:47:04


802.11n_20M chain A

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 13:50:05

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 13:49:13


Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 13:48:30


802.11n_20M chain B

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 14:00:38

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 14:02:58


Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 14:03:42


802.11n_40M chain A

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 13:32:50

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 13:33:49


Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 13:31:50


802.11n_40M chain B

Power Spectral Density Test Plot (CH-Low)




Date: 3.NOV.2014 13:57:32

Power Spectral Density Test Plot (CH-Mid)



Date: 3.NOV.2014 13:58:15

Power Spectral Density Test Plot (CH-High)



Date: 3.NOV.2014 13:56:31

11 ANTENNA REQUIREMENT

11.1 Standard Applicable

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

11.2 Antenna Connected Construction

The directional gains of antenna used for transmitting is 2.78dBi for 2.4GHz, 2.53dBi for 5GHz, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.

According to KDB662911 D01 SM-MIMO signals could be considered uncorrelated for purposes of directional gain computation.

Directional gain = G_{ANT}