


RF Exposure Evaluation Report

APPLICANT : E-filliate Incorporated
EQUIPMENT : DEWALT TRUE WIRELESS EARBUDS & CHARGING CASE
BRAND NAME : DEWALT
MODEL NAME : 190 2092 DW2, 190 2092,190 2092 DW3,190 2092 DWE,190 2092 XXX,DXMA1902092,DXMA1902092E; 190 2095 DW2, 190 2095,190 2095 DW3,190 2095 DWE,190 2095 XXX,DXMA1902095,DXMA1902095E
FCC ID : 2ADH6-190209L
STANDARD : 47 CFR PART 2.1093
FCC KDB 447498 D01 v06

We, Sporton International (Kunshan) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Reviewed by: Nick Hu / Supervisor



Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE EVALUATION	7



1. Administration Data

1.1. Testing Laboratory

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory		
Test Firm	Sporton International (Kunshan) Inc.	
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1257	314309

Applicant	
Company Name	E-filliate Incorporated
Address	11321 White Rock Rd. Rancho Cordova, CA 95742, USA.

Manufacturer	
Company Name	CHANGSHU OBO SEAHORN ACOUSTICS ELECTRONIC CO., LTD
Address	No.15 Dianchang Road, Bixi District, CHANGSHU CITY, SUZHOU CITY, China.



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	DEWALT TRUE WIRELESS EARBUDS & CHARGING CASE
Model Name	DEWALT
Model Name	190 2092 DW2, 190 2092,190 2092 DW3,190 2092 DWE,190 2092 XXX,DXMA1902092,DXMA1902092E; 190 2095 DW2, 190 2095,190 2095 DW3,190 2095 DWE,190 2095 XXX,DXMA1902095,DXMA1902095E
FCC ID	2ADH6-190209L
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth BR/EDR/LE
Antenna Type	Bluetooth : PIFA Antenna
Antenna Gain	Bluetooth: gain 0.0 dBi
HW Version	V4
SW Version	V20210416
EUT Stage	Identical Prototype
Remark:	
<ol style="list-style-type: none"> The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. EUT has different model names, the products are exactly the same, only different model names correspond to different markets. 	

Comments and Explanations:
<ol style="list-style-type: none"> The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up power among production units

<Bluetooth>

Mode	Maximum Average Power (dBm)
Bluetooth BR/EDR	4.0
Bluetooth LE	3.5



4. RF Exposure Evaluation

Mode	Average power(dBm)
Bluetooth	4.0

Note:

- Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f(GHz)}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
4.0	< 5	2.48	0.8

Conclusion:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.8 which is ≤ 3.0 for 1-g SAR, 1g SAR testing is not required and complied with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for 1g SAR) specified in FCC 47 CFR part 2 (2.1093).

-----THE END-----