

Prüfbericht-Nr.: <i>Test report no.:</i>	CN24LZTX 001	Auftrags-Nr.: <i>Order no.:</i>	48223857	Seite 1 von 26 Page 1 of 26
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2023-09-13	
Auftraggeber: <i>Client:</i>	Microchip Technology Inc. 2355 West Chandler Blvd. Chandler, Arizona 85224-6199, United States			
Prüfgegenstand: <i>Test item:</i>	IEEE 802.11 b/g/n Link Controller Module			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	ATWILC1000-MR110UB			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (WiFi 2.4GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2023-12-06			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003618205-010 A003537723-005 A003648659-009, 011			
Prüfzeitraum: <i>Testing period:</i>	2024-02-22 - 2024-06-11			
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
Prüflaboratorium: <i>Testing laboratory:</i>	Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
überprüft von: <i>compiled by:</i>		genehmigt von: <i>authorized by:</i>		
Datum: <i>Date:</i>	2024-06-24	Ausstellungsdatum: <i>Issue date:</i>	2024-06-24	
Stellung / Position:	Senior Project Manager	Stellung / Position:	Senior Project Manager	
Sonstiges / Other:	This report is to add new source of crystal (Taisaw: TZ1039PAAF32 and Taitien: A0183-X-001-3). Only the output power at normal temperature and radiated spurious emissions tests were evaluated. For other test results, please refer to original report no.: 50116065 001.			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN24LZTX 001

Seite 2 von 26
Page 2 of 26

Anmerkungen
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
-	15.247(a)(2)	6 dB Bandwidth	Note 1
-	2.1049	99% Occupied Bandwidth	Note 1
-	15.247(e)	Power Spectral Density	Note 1
-	15.247(d)	Conducted Spurious Emissions and Band Edges	Note 1
5.1.3	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
-	15.207	Mains Conducted Emission	N/A

Note:

1. Please refer to original report.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS.....	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY.....	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION.....	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS.....	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	12
3.4 SUBMITTED DOCUMENTS.....	12
4. TEST SET-UP AND OPERATION MODES	13
4.1 PRINCIPLE OF CONFIGURATION SELECTION	13
4.2 CARRIER FREQUENCY AND CHANNEL.....	13
4.3 TEST OPERATION AND TEST SOFTWARE.....	14
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	16
4.5 TEST SETUP DIAGRAM	17
5. TEST RESULTS	18
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	18
5.1.1 <i>Antenna Requirement</i>	<i>18</i>
5.1.2 <i>Peak Output Power</i>	<i>19</i>
5.1.3 <i>Radiated Spurious Emissions and Band Edges</i>	<i>22</i>

Prüfbericht - Nr.: **CN24LZTX 001**
Test Report No.

Seite 5 von 26
Page 5 of 26

APPENDIX A - TEST RESULT OF RADIATED EMISSIONS

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN24LZTX 001**
Test Report No.

Seite 6 von 26
Page 6 of 26

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2024-06-24

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Radiated Emissions

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a IEEE 802.11 b/g/n Link Controller Module. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.
 For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	IEEE 802.11 b/g/n Link Controller Module
Type Identification	ATWILC1000-MR110UB
FCC ID	2ADHKATWILC1000U

Technical Specification of EUT

Item	EUT information
Operating Frequency	2412 MHz ~ 2462 MHz
Channel Spacing	5 MHz
Channel Number	802.11b/g/n HT20: 11
Data Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
Operation Voltage	3.0 Vdc ~ 4.2 Vdc (Typical = 3.3 Vdc)
Modulation	DSSS (DBPSK, DQPSK, CCK) OFDM (BPSK, QPSK, 16QAM, 64QAM)
Maximum Output Power (mW)	802.11b: 77.09 802.11g: 206.54 802.11n HT20: 205.12
Antenna Information	Refer to Note for antenna list
Accessory Device	Refer to 4.4

Note:

Antenna List

S/no.	P/N	Vendor	Antenna Gain @ 2.4GHz Band	Antenna type
1	W3525B039	Pulse Electronics Corporation	2 dBi	PCB
3	RFDPA870920IMLB301	WALSIN	1.84 dBi	Dipole
10	RFA-02-P33	Aristotle	2 dBi	PCB
12	RN-SMA-S	Microchip	0.56 dBi	Dipole
15	RFA-02-D3	Aristotle	2dBi	Dipole
16	RFA-02-G03	Aristotle	2dBi	PIFA (Metal Stamp)
17	RFA-02-L2H1	Aristotle	2 dBi	Dipole
18	RFA-02-P05	Aristotle	2 dBi	PCB
19	RFA-02-C2M2	Aristotle	2 dBi	Dipole
20	86254	Delock	2 dBi	PCB

* S/no. 16, 17, 18 was selected for e.i.r.p. test.

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

Mode	802.11b			802.11g			802.11n HT20		
Channel	1	6	11	1	6	11	1	6	11
Frequency (MHz)	2412	2437	2462	2412	2437	2462	2412	2437	2462
Power Setting	-11.5	-11	-11	-11.5	-5.5	-12.5	-12.5	-5.5	-13

4.2 Carrier Frequency and Channel

802.11b, 802.11g and 802.11n HT20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	MCHPRT2 ver1.7.6.1
---------------	--------------------

The samples were used as follows:

A003618205-010

A003537723-005

A003648659-009, 011

Full test was applied on all test modes, but only worst case was shown.

The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitter and receiver.

Modulation Mode	Tx Function
802.11b	1TX (SISO)
802.11g	1TX (SISO)
802.11n HT20	1TX (SISO)

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	-	-

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Y-plane**.
2. "-" means no effect.

Antenna Port Conducted Measurement

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	1.0
-	802.11g	1 to 11	1, 6, 11	6.0
-	802.11n HT20	1 to 11	1, 6, 11	MCS0

Radiated Spurious Emissions (Above 1 GHz)

Pre-Scan full test was applied on all test modes, but only worst case was shown.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	1.0
-	802.11g	1 to 11	1, 6, 11	6.0
-	802.11n HT20	1 to 11	1, 6, 11	MCS0

Prüfbericht - Nr.: CN24LZTX 001
Test Report No.

 Seite 15 von 26
 Page 15 of 26

Radiated Spurious Emissions (Below 1 GHz)

- Pre-Scan full test was applied on all test modes, but only worst case was shown.
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11g	1 to 11	6	6.0

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	22.5-25.8 °C	54-62 %	Nick Guan / Andy Chen
Radiated Spurious Emissions above 1 GHz	23.7-24.6 °C	52-55 %	Roger Liao
Radiated Spurious Emissions below 1 GHz	23.7-24.6 °C	52-55 %	Roger Liao

Prüfbericht - Nr.: CN24LZTX 001
Test Report No.

 Seite 16 von 26
 Page 16 of 26

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT

None.


Support Unit

Support Unit								
No.	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
Radiated Test								
Dipole Antenna								
A	Antenna	Microchip	RFA-02-L2H1	-	NO	N/A	23	A003537723-005
1	DC Power Supply	Gwinstek	GPS-3030	-	-	-	-	-
PCB Antenna								
A	Antenna	Microchip	RFA-02-P05	-	NO	N/A	20	A003648659-009
1	DC Power Supply	Gwinstek	GPS-3030	-	-	-	-	-
PIFA Antenna								
A	Antenna	Microchip	RFA-02-G03	-	NO	N/A	18	A003648659-011
1	DC Power Supply	Gwinstek	GPS-3030	-	-	-	-	-
Conducted Test								
-	Notebook	HP	TPN-C139	CND93662WT	-	-	-	-
-	Power Supply	GWINSTEK	GPS-3303	GEU915620	-	-	-	-

4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>

DIPOLE ANTENNA, PCB ANTENNA, PIFA ANTENNA



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the antenna information is as listed below.
 The antenna is with no possibility of replacement with a non-approved antenna by the end-user.
 Therefore, the EUT is considered to comply with this provision.

S/no.	P/N	Vendor	Antenna Gain @ 2.4GHz Band	Antenna type
1	W3525B039	Pulse Electronics Corporation	2 dBi	PCB
3	RFDPA870920IMLB301	WALSIN	1.84 dBi	Dipole
10	RFA-02-P33	Aristotle	2 dBi	PCB
12	RN-SMA-S	Microchip	0.56 dBi	Dipole
15	RFA-02-D3	Aristotle	2dBi	Dipole
16	RFA-02-G03	Aristotle	2dBi	PIFA (Metal Stamp)
17	RFA-02-L2H1	Aristotle	2 dBi	Dipole
18	RFA-02-P05	Aristotle	2 dBi	PCB
19	RFA-02-C2M2	Aristotle	2 dBi	Dipole
20	86254	Delock	2 dBi	PCB


Prüfbericht - Nr.: CN24LZTX 001
Test Report No.

 Seite 19 von 26
 Page 19 of 26

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup

Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2024/03/12	2025/03/12	2024/6/11	2024/6/11
Power Sensor	Anritsu	MA2411B	1725269	2024/03/12	2025/03/12	2024/6/11	2024/6/11

Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Test Result
Peak Output Power
<802.11b>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	18.51	70.96	30
6	2437	18.78	75.51	30
11	2462	18.87	77.09	30

<802.11g>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	20.70	117.49	30
6	2437	23.15	206.54	30
11	2462	18.92	77.98	30

<802.11n HT20>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	20.31	107.40	30
6	2437	23.12	205.12	30
11	2462	21.29	134.59	30

Average Power
<802.11b>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	15.60	36.31
6	2437	15.91	38.99
11	2462	16.02	39.99

<802.11g>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	12.64	18.37
6	2437	17.29	53.58
11	2462	11.09	12.85

<802.11n HT20>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	12.18	16.52
6	2437	17.28	53.46
11	2462	13.52	22.49

5.1.3 Radiated Spurious Emissions and Band Edges

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN24LZTX 001
Test Report No.
Test Instruments

Test date: 2024-02-22 ~ 2024-06-06

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1GHz					
Signal Analyzer	R&S	FSV40	101509	2023/4/26	2024/4/24
Signal Analyzer	R&S	FSV40	101509	2024/4/30	2025/4/29
Horn Antenna	ETS-Lindgren	3117	00218929	2023/11/17	2024/11/15
HF-AMP + AC source	EMCI	EM01G18GA	980657	2024/1/24	2025/1/22
HF-AMP + AC source	EMCI	EMC184045SE	980656	2024/1/18	2025/1/16
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2023/5/4	2024/5/2
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2024/4/30	2025/4/29
30MHz ~ 1GHz					
Receiver	R&S	ESR7	102109	2024/1/24	2025/1/22
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2023/3/31	2024/3/29
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2024/3/21	2025/3/20
LF-AMP	Agilent	8447D	2727A05146	2024/1/24	2025/1/22
Below 30MHz					
Receiver	R&S	ESR7	102109	2024/1/24	2025/1/22
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/1/4	2025/1/2

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN24LZTX 001**
Test Report No.

Seite 26 von 26
Page 26 of 26

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix A.

Appendix A: Test Results of Radiated Spurious Emissions

Dipole Antenna

Band Edges, 2.31GHz ~ 2.9GHz

802.11b

Low Channel (Horizontal) Peak


Low Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Read Level	Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2386.95	55.00	16.96	38.04	74.00	-19.00	282	266	Peak	Horizontal	
2	2412.00	99.98	61.75	38.15	74.00	25.98	282	266	Peak	Horizontal	
3	2493.16	55.96	17.65	38.31	74.00	-18.04	282	266	Peak	Horizontal	



1	2	3	Read Level	Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2386.44	59.85	21.81	38.04	74.00	-14.15	238	65	Peak	Vertical	
2	2412.00	109.80	71.65	38.15	74.00	35.80	238	65	Peak	Vertical	
3	2487.21	56.53	18.21	38.32	74.00	-17.47	238	65	Peak	Vertical	


802.11b

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
Hz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2387.01	44.42	6.38	38.04	54.00	-9.58	282	266	Average	Horizontal	
2	2412.00	96.75	58.60	38.15	54.00	42.75	282	266	Average	Horizontal	
3	2491.26	42.16	3.84	38.32	54.00	-11.84	282	266	Average	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
Hz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
1	2386.19	51.84	13.80	38.04	54.00	-2.16	238	65	Average	Vertical	
2	2412.00	106.70	68.55	38.15	54.00	52.70	238	65	Average	Vertical	
3	2489.87	44.84	6.52	38.32	54.00	-9.16	238	65	Average	Vertical	


802.11b

Middle Channel (Horizontal) Peak

Middle Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2389.74	54.96	16.90	38.06	74.00	-19.04	282	325 Peak	Horizontal	
2	2437.00	102.54	64.26	38.28	74.00	28.54	282	325 Peak	Horizontal	
3	2485.18	55.84	17.52	38.32	74.00	-18.16	282	325 Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2313.10	57.12	19.38	37.74	74.00	-16.88	217	48 Peak	Vertical	
2	2437.00	112.49	74.21	38.28	74.00	38.49	217	48 Peak	Vertical	
3	2485.37	55.47	17.15	38.32	74.00	-18.53	217	48 Peak	Vertical	


802.11b

Middle Channel (Horizontal) Average

Middle Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2389.55	41.18	3.12	38.06	54.00	-12.82	282	325	Average	Horizontal		
2437.00	99.26	60.98	38.28	54.00	45.26	282	325	Average	Horizontal		
2494.68	41.91	3.60	38.31	54.00	-12.09	282	325	Average	Horizontal		



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2312.79	47.12	9.38	37.74	54.00	-6.88	217	48	Average	Vertical		
2437.00	109.37	71.09	38.28	54.00	55.37	217	48	Average	Vertical		
2484.23	43.34	5.02	38.32	54.00	-10.66	217	48	Average	Vertical		


802.11b

High Channel (Horizontal) Peak

High Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2315.00	54.73	16.98	37.75	74.00	-19.27	100	59	Peak	Horizontal	
2 *	2462.00	97.80	59.46	38.34	74.00	23.80	100	59	Peak	Horizontal	
3	2499.24	55.94	17.63	38.31	74.00	-18.06	100	59	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2314.81	58.55	20.80	37.75	74.00	-15.45	167	193	Peak	Vertical	
2 *	2462.00	111.38	73.04	38.34	74.00	37.38	167	193	Peak	Vertical	
3	2484.42	60.18	21.86	38.32	74.00	-13.82	167	193	Peak	Vertical	


802.11b

High Channel (Horizontal) Average

High Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2315.45	41.68	3.93	37.75	54.00	-12.32	100	59 Average	Horizontal
2	2462.00	94.31	55.97	38.34	54.00	40.31	100	59 Average	Horizontal
3	2487.78	42.69	4.37	38.32	54.00	-11.31	100	59 Average	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2315.57	50.86	13.11	37.75	54.00	-3.14	167	193 Average	Vertical
2	2462.00	108.03	69.69	38.34	54.00	54.03	167	193 Average	Vertical
3	2484.80	50.19	11.87	38.32	54.00	-3.81	167	193 Average	Vertical

802.11g

Low Channel (Horizontal) Peak



Low Channel (Vertical) Peak



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2389.74	55.78	17.72	38.06	74.00	-18.22	148	262	Peak	Horizontal	
2 *	2412.00	96.97	58.82	38.15	74.00	22.97	148	262	Peak	Horizontal	
3	2484.10	55.28	16.96	38.32	74.00	-18.72	148	262	Peak	Horizontal	

Peak	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1 !	2389.93	72.43	34.37	38.06	74.00	-1.57	100	202	Peak	Vertical	
2 *	2412.00	108.53	70.38	38.15	74.00	34.53	100	202	Peak	Vertical	
3	2489.42	56.11	17.79	38.32	74.00	-17.89	100	202	Peak	Vertical	


802.11g

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Read Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
Hz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2389.99	42.10	4.04	38.06	54.00	-11.90	148	262	Average	Horizontal		
2412.00	86.05	47.90	38.15	54.00	32.05	148	262	Average	Horizontal		
2496.96	42.26	3.94	38.32	54.00	-11.74	148	262	Average	Horizontal		



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Read Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
Hz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2389.99	52.04	13.98	38.06	54.00	-1.96	100	202	Average	Vertical		
2412.00	98.56	60.41	38.15	54.00	44.56	100	202	Average	Vertical		
2486.07	43.28	4.96	38.32	54.00	-10.72	100	202	Average	Vertical		


802.11g

Middle Channel (Horizontal) Peak

Middle Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2373.08	54.97	16.96	38.01	74.00	-19.03	100	254	Peak	Horizontal	
2	2437.00	100.22	61.94	38.28	74.00	26.22	100	254	Peak	Horizontal	
3	2492.02	55.17	16.85	38.32	74.00	-18.83	100	254	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	2389.80	66.12	28.06	38.06	74.00	-7.88	107	202	Peak	Vertical	
2	2437.00	115.41	77.13	38.28	74.00	41.41	107	202	Peak	Vertical	
3	2483.60	63.26	24.94	38.32	74.00	-10.74	107	202	Peak	Vertical	


802.11g

Middle Channel (Horizontal) Average

Middle Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Read Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2337.11	41.32	3.46	37.86	54.00	-12.68	100	254	Average	Horizontal		
2437.00	89.69	51.41	38.28	54.00	35.69	100	254	Average	Horizontal		
2485.18	42.25	3.93	38.32	54.00	-11.75	100	254	Average	Horizontal		



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Read Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2389.99	45.00	6.94	38.06	54.00	-9.00	107	202	Average	Vertical		
2437.00	104.38	66.10	38.28	54.00	50.38	107	202	Average	Vertical		
2483.60	44.79	6.47	38.32	54.00	-9.21	107	202	Average	Vertical		


802.11g

High Channel (Horizontal) Peak

High Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2382.98	55.76	17.72	38.04	74.00	-18.24	100	255	Peak	Horizontal	
2 *	2462.00	96.82	58.48	38.34	74.00	22.82	100	255	Peak	Horizontal	
3	2483.98	59.33	21.01	38.32	74.00	-14.67	100	255	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2323.87	57.01	19.21	37.80	74.00	-16.99	100	204	Peak	Vertical	
2 *	2462.00	108.73	70.39	38.34	74.00	34.73	100	204	Peak	Vertical	
3 !	2483.79	71.76	33.44	38.32	74.00	-2.24	100	204	Peak	Vertical	

802.11g

High Channel (Horizontal) Average


High Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3
2339.83	2462.00	2483.91
41.39	86.05	43.09
3.51	47.71	4.77
37.88	38.34	38.32
54.00	54.00	54.00
-12.61	32.05	-10.91
100	100	100
255	255	255
Average	Average	Average
Horizontal	Horizontal	Horizontal



1	2	3
2318.89	2462.00	2483.53
44.34	98.87	51.69
6.62	60.53	13.37
37.72	38.34	38.32
54.00	54.00	54.00
-9.66	44.87	-2.31
100	100	100
204	204	204
Average	Average	Average
Vertical	Vertical	Vertical


802.11n HT20

Low Channel (Horizontal) Peak

Low Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2388.28	55.92	17.86	38.06	74.00	-18.08	106	251	Peak	Horizontal	
2 *	2412.00	95.18	57.03	38.15	74.00	21.18	106	251	Peak	Horizontal	
3	2498.48	55.34	17.03	38.31	74.00	-18.66	106	251	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1 !	2389.86	72.17	34.11	38.06	74.00	-1.83	111	202	Peak	Vertical	
2 *	2412.00	108.68	70.53	38.15	74.00	34.68	111	202	Peak	Vertical	
3	2497.59	55.96	17.65	38.31	74.00	-18.04	111	202	Peak	Vertical	


802.11n HT20

Low Channel (Horizontal) Average

Low Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3
2389.61	2412.00	2485.69
42.33	84.56	42.19
4.27	46.41	3.87
38.06	38.15	38.32
54.00	54.00	54.00
-11.67	30.56	-11.81
106	106	106
251	251	251
Average	Average	Average
Horizontal	Horizontal	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3
2389.86	2412.00	2486.19
52.78	97.88	42.97
14.72	59.73	4.65
38.06	38.15	38.32
54.00	54.00	54.00
-1.22	43.88	-11.03
111	111	111
202	202	202
Average	Average	Average
Vertical	Vertical	Vertical

802.11n HT20

Middle Channel (Horizontal) Peak


Middle Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2385.11	54.00	16.76	38.04	74.00	-19.20	137	263	Peak	Horizontal		
2437.00	102.31	64.03	38.28	74.00	28.31	137	263	Peak	Horizontal		
2493.10	55.66	17.35	38.31	74.00	-18.34	137	263	Peak	Horizontal		



1	2	3	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg				
2389.74	67.14	29.08	38.06	74.00	-6.86	178	184	Peak	Vertical		
2437.00	114.53	76.25	38.28	74.00	40.53	178	184	Peak	Vertical		
2484.67	65.61	27.29	38.32	74.00	-8.39	178	184	Peak	Vertical		


802.11n HT20

Middle Channel (Horizontal) Average

Middle Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3
2384.04	2437.00	2485.94
41.42	91.32	42.23
3.38	53.04	3.91
38.04	38.28	38.32
54.00	54.00	54.00
-12.58	37.32	-11.77
137	137	137
263	263	263
Average	Average	Average
Horizontal	Horizontal	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3
2389.86	2437.00	2484.17
45.44	103.92	44.77
7.38	65.64	6.45
38.06	38.28	38.32
54.00	54.00	54.00
-8.56	49.92	-9.23
178	178	178
184	184	184
Average	Average	Average
Vertical	Vertical	Vertical


802.11n HT20

High Channel (Horizontal) Peak

High Channel (Vertical) Peak




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2315.89	55.38	17.63	37.75	74.00	-18.62	100	302	Peak	Horizontal	
2 *	2462.00	99.73	61.39	38.34	74.00	25.73	100	302	Peak	Horizontal	
3	2484.04	62.57	24.25	38.32	74.00	-11.43	100	302	Peak	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	2312.22	57.57	19.84	37.73	74.00	-16.43	100	290	Peak	Vertical	
2 *	2462.00	109.79	71.45	38.34	74.00	35.79	100	290	Peak	Vertical	
3 !	2484.23	72.79	34.47	38.32	74.00	-1.21	100	290	Peak	Vertical	


802.11n HT20

High Channel (Horizontal) Average

High Channel (Vertical) Average




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2369.91	41.47	3.48	37.99	54.00	-12.53	100	302 Average	Horizontal
2 *	2462.00	88.98	50.64	38.34	54.00	34.98	100	302 Average	Horizontal
3	2483.53	44.46	6.14	38.32	54.00	-9.54	100	302 Average	Horizontal



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2312.34	44.86	7.13	37.73	54.00	-9.14	100	290 Average	Vertical
2 *	2462.00	99.03	60.69	38.34	54.00	45.03	100	290 Average	Vertical
3 !	2483.72	52.42	14.10	38.32	54.00	-1.58	100	290 Average	Vertical

Spurious Emissions, Tx Mode, 9kHz ~ 30MHz


802.11g

Middle Channel(Open) 9kHz~150kHz

Middle Channel(Open) 150kHz~30MHz




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	0.01	59.41	41.10	18.31	127.60	-68.19	100	0	Peak	Open	
2	0.03	64.84	45.03	19.81	119.13	-54.29	100	122	Peak	Open	
3	0.05	43.88	24.58	19.30	113.11	-69.23	100	103	Peak	Open	
4	0.08	35.31	15.71	19.60	110.00	-74.69	100	30	Peak	Open	
5	0.11	32.89	14.29	18.60	106.49	-73.60	100	288	Peak	Open	
6	0.13	26.35	7.64	18.71	105.20	-78.85	100	250	Peak	Open	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel:+886-2172-1000 Fax:+886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	0.93	40.45	21.31	19.14	68.27	-27.82	100	280	Peak	Open	
2	3.14	33.21	14.02	19.19	69.50	-36.29	100	0	Peak	Open	
3	9.55	34.66	13.61	21.05	69.50	-34.84	100	221	Peak	Open	
4	16.93	34.88	12.64	22.24	69.50	-34.62	100	339	Peak	Open	
5	21.49	35.59	13.38	22.21	69.50	-33.91	100	359	Peak	Open	
6	26.36	35.47	12.65	22.82	69.50	-34.03	100	0	Peak	Open	

Spurious Emissions, Tx Mode, 30MHz ~ 1GHz

802.11g

Middle Channel (Horizontal)



Middle Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	141.55	30.52	37.12	-6.60	43.50	-12.98	200	248	Peak	Horizontal	
2	304.51	34.32	38.90	-4.58	46.00	-11.68	100	282	Peak	Horizontal	
3	568.35	32.35	32.85	-0.50	46.00	-13.65	200	309	Peak	Horizontal	
4	690.57	34.12	32.35	1.76	46.00	-11.88	100	243	Peak	Horizontal	
5	812.79	34.80	31.41	3.39	46.00	-11.20	100	87	Peak	Horizontal	
6	935.01	40.89	35.47	5.42	46.00	-5.11	100	30	Peak	Horizontal	

Peak	Freq (MHz)	Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit Line (dBuV/m)	Over Limit (dB)	APos (cm)	TPos (deg)	Remark	Pol/Phase	Note
1	141.55	28.40	35.00	-6.60	43.50	-15.10	100	304	Peak	Vertical	
2	296.75	31.15	36.04	-4.89	46.00	-14.85	100	80	Peak	Vertical	
3	447.10	27.85	29.77	-1.92	46.00	-18.15	100	239	Peak	Vertical	
4	579.02	32.18	32.47	-0.29	46.00	-13.82	146	0	Peak	Vertical	
5	741.01	32.11	29.30	2.81	46.00	-13.89	100	43	Peak	Vertical	
6	914.64	35.65	30.61	5.04	46.00	-10.35	100	154	Peak	Vertical	

Spurious Emissions, Tx Mode, 1GHz ~ 26.5GHz


802.11b

Low Channel (Horizontal)

Low Channel (Vertical)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4824.00	51.38	59.33	-7.95	74.00	-22.62	100	338 Peak	Horizontal	
2	4824.00	47.72	55.67	-7.95	54.00	-6.28	100	338 Average	Horizontal	



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4824.00	49.77	57.72	-7.95	74.00	-24.23	300	39 Peak	Vertical	
2	4824.00	45.27	53.22	-7.95	54.00	-8.73	300	39 Average	Vertical	

802.11b

Middle Channel (Horizontal)



Middle Channel (Vertical)



TUV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TUV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4874.00	52.05	59.96	-7.91	74.00	-21.95	100	330 Peak	Horizontal	
2	4874.00	48.96	56.87	-7.91	54.00	-5.04	100	330 Average	Horizontal	
3	7311.00	47.49	52.85	-5.36	74.00	-26.51	100	170 Peak	Horizontal	
4	7311.00	39.95	45.31	-5.36	54.00	-14.05	100	170 Average	Horizontal	
5	12185.00	54.34	52.01	2.33	74.00	-19.66	100	162 Peak	Horizontal	
6	12185.00	50.27	47.94	2.33	54.00	-3.73	100	162 Average	Horizontal	

Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4874.00	52.84	60.75	-7.91	74.00	-21.16	100	10 Peak	Vertical	
2	4874.00	48.92	56.83	-7.91	54.00	-5.08	100	10 Average	Vertical	
3	7311.00	47.21	52.57	-5.36	74.00	-26.79	200	177 Peak	Vertical	
4	7311.00	41.80	47.16	-5.36	54.00	-12.20	200	177 Average	Vertical	
5	12185.00	55.39	53.06	2.33	74.00	-18.61	100	107 Peak	Vertical	
6	12185.00	52.95	50.62	2.33	54.00	-1.05	100	107 Average	Vertical	

802.11b

High Channel (Horizontal)



High Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4924.00	46.87	54.75	-7.88	74.00	-27.13	300	252 Peak	Horizontal	
2	4924.00	45.53	53.41	-7.88	54.00	-8.47	300	252 Average	Horizontal	

Freq	Level	Read Level	Factor	Limit	Over	APos	TPos	Remark	Pol/Phase	Note
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4924.00	47.46	55.34	-7.88	74.00	-26.54	100	300 Peak	Vertical	
2	4924.00	45.55	53.43	-7.88	54.00	-8.45	100	300 Average	Vertical	



802.11g

Middle Channel (Horizontal)



Middle Channel (Vertical)



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4								
Level	Level	Level	Level								
Factor	Factor	Factor	Factor								
Line	Line	Line	Line								
Limit	Limit	Limit	Limit								
Over	Over	Over	Over								
Limit	Limit	Limit	Limit								
APos	APos	APos	APos								
TPos	TPos	TPos	TPos								
Remark	Remark	Remark	Remark								
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase								
Note	Note	Note	Note								
1	4874.00	46.22	54.13	-7.91	74.00	-27.78	100	16	Peak	Horizontal	
2	4874.00	35.63	43.54	-7.91	54.00	-18.37	100	16	Average	Horizontal	
3	12185.00	51.99	49.65	2.33	74.00	-22.02	100	360	Peak	Horizontal	
4	12185.00	41.67	39.34	2.33	54.00	-12.33	100	360	Average	Horizontal	

1	2	3	4								
Level	Level	Level	Level								
Factor	Factor	Factor	Factor								
Line	Line	Line	Line								
Limit	Limit	Limit	Limit								
Over	Over	Over	Over								
Limit	Limit	Limit	Limit								
APos	APos	APos	APos								
TPos	TPos	TPos	TPos								
Remark	Remark	Remark	Remark								
Pol/Phase	Pol/Phase	Pol/Phase	Pol/Phase								
Note	Note	Note	Note								
1	4874.00	43.09	51.00	-7.91	74.00	-30.91	100	17	Peak	Vertical	
2	4874.00	35.32	43.23	-7.91	54.00	-18.68	100	17	Average	Vertical	
3	12185.00	54.34	52.01	2.33	74.00	-19.66	219	360	Peak	Vertical	
4	12185.00	44.61	42.28	2.33	54.00	-9.39	219	360	Average	Vertical	

802.11n HT20

Low Channel (Horizontal)


Low Channel (Vertical)




TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TÜV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note	
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4824.00	38.44	46.39	-7.95	74.00	-35.56	100	360	Peak	Horizontal
2	4824.00	30.94	38.89	-7.95	54.00	-23.06	100	360	Average	Horizontal



Freq	Level	Read Level Factor	Limit Line	Over Limit	APos	TPos	Remark	Pol/Phase	Note	
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg			
1	4824.00	40.43	48.38	-7.95	74.00	-33.57	100	360	Peak	Vertical
2	4824.00	30.90	38.85	-7.95	54.00	-23.10	100	360	Average	Vertical

802.11n HT20

Middle Channel (Horizontal)


Middle Channel (Vertical)




TUV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



TUV Rheinland Taiwan Ltd.
No. 458-18, Sec 2, Fenliao, Linkou Dist., New Taipei City 244, Taiwan(R.O.C.)
Tel: +886-2172-1000 Fax: +886-2172-1322



1	2	3	4
4874.00	4874.00	12185.00	12185.00
42.60	34.10	54.01	43.81
50.51	42.01	51.68	41.48
-7.91	-7.91	2.33	2.33
74.00	54.00	74.00	54.00
-31.40	-19.90	-19.99	-10.19
100	100	113	113
155	155	360	360
Peak	Average	Peak	Average
Horizontal	Horizontal	Horizontal	Horizontal



1	2	3	4
4874.00	4874.00	12185.00	12185.00
43.03	34.91	54.05	43.32
50.94	42.82	51.72	40.99
-7.91	-7.91	2.33	2.33
74.00	54.00	74.00	54.00
-30.97	-19.09	-19.95	-10.68
100	100	200	200
16	16	33	33
Peak	Average	Peak	Average
Vertical	Vertical	Vertical	Vertical

