



# Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## Test Report

Prepared for: Emotiv Inc.

Model: Insight

Description: Wireless Neurological Headset

Serial Number: N/A

FCC ID: 2ADIH-INSIGHT01

IC: 12769A-INSIGHT01

To

FCC Part 15.247 DTS

Date of Issue: April 30, 2015

On the behalf of the applicant:

Emotiv Inc.  
490 Post Street  
Suite 824  
San Francisco, CA 94102

Attention of:

Geoffrey Mackellar, CTO  
Ph: (415) 828-9895  
E-Mail: [geoff@emotiv.co](mailto:geoff@emotiv.co)

Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1530017

Alex Macon  
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing.  
All results contained herein relate only to the sample tested.



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	April 9, 2015	Alex Macon	Original Document

## Table of Contents

<u>Description</u>	<u>Page</u>
Standard Test Conditions Engineering Practices	6
Peak Output Power	9
Radiated Spurious Emissions	10
Emissions at Band Edges	12
Occupied Bandwidth	16
Transmitter Power Spectral Density (PSD)	19
A/C Powerline Conducted Emission	22
Test Equipment Utilized	24

**ILAC / A2LA**

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

**The applicant has been cautioned as to the following**

15.21 - Information to User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) - Special Accessories

Equipment marked to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

## Standard Test Conditions Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.10-2009 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F) unless the particular equipment requirements specified testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Measurement results, unless otherwise noted, are worst-case measurements.

Environmental Conditions		
Temperature (°C)	Humidity (%)	Pressure (mbar)
24.2 – 25.3	28.7 – 32.4	964.5 – 967.7

### EUT Description

**Model:** Insight

**Description:** Wireless Neurological Headset

**Serial Number:** N/A

**Software:** Nordic Semiconductor Master Control Panel

**Additional Information:**

The device is a Wireless Neurological Headset transceiver, which communicates to a USB transceiver connected to a personal computer. The link between the headset transceiver and USB transceiver transmits data continuously and is required for proper operation of the product. The device incorporates an integral antenna; all measurements are done by radiated means.

### EUT Operation during Tests

The Client has provided several dongles to place the EUT in High Mid and Low channels and also a dongle for normal operation

**Accessories:**

Qty	Description	Manufacturer	Model	S/N
1	Bluetooth Dongle	Nordic Semiconductor	PCA10000	N/A

**Cables:** None

**Modifications:** None

**15.203: Antenna Requirement:**

- The antenna is permanently attached to the EUT
- The antenna uses a unique coupling
- The EUT must be professionally installed
- The antenna requirement does not apply

## Test Reports Summary

Specification	Test Name	Pass, Fail, N/A	Comments
15.247(b)(3)	Peak Output Power	Pass	
15.247(b)	Conducted Spurious Emissions	N/A	All measurements are taken by radiated means
15.247(d), 15.209(a), 15.205	Radiated Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Emissions At Band Edges	Pass	
15.247(a)(2)	Occupied Bandwidth	Pass	
15.247(e)	Transmitter Power Spectral Density	Pass	
15.207	A/C Powerline Conducted Emissions	Pass	
RSS-Gen 6(b)	Receiver Spurious Emission Limits	Pass	



**Peak Output Power**
**Name of Test:**

Peak Output Power

**Engineer:** Alex Macon


**Test Equipment Utilized:**

i00271,i00331, i00428

**Test Date:** 4/6/15

**Test Procedure**

The EUT was tested in a semi anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements. The peak readings were taken and the result was then compared to the limit.

**Test Setup**

**Transmitter Peak Output Power**

Tuned Frequency (MHz)	Measured Value (dBm)	Specification Limit	Result
2402	-16.21	1 W (30 dBm)	Pass
2442	-17.7	1 W (30 dBm)	Pass
2480	-19.52	1 W (30 dBm)	Pass

**Radiated Spurious Emissions**
**Name of Test:**

Radiated Spurious Emissions

**Engineer:** Alex Macon

**Test Equipment Utilized:**

i00271, i00273, i00331, i00349, i00428

**Test Date:** 4/7/15

**Test Procedure**
**Radiated Spurious Emissions: 30 – 1000 MHz**

The EUT was tested in a semi anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360° with the antennas in both the vertical and horizontal orientation and was raised from 1 to 4 meters to ensure the TX signal levels were maximized. All emissions from 30 MHz to 1 GHz were examined.

Measured Level includes antenna and receiver cable correction factors.

Correction factors were input into the spectrum analyzer before recording “Measured Level”.

RBW = 100 KHz


VBW = 300 KHz

Detector – Quasi Peak

Limit = -20dBc

Lowest fundamental power = 87.47 dBuV

Limit = 67.7 dBuV


**Test Setup**

**Radiated Spurious Emissions Test Data: 30 MHz – 1000 MHz**

Frequency (MHz)	Measured Value (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarity (H or V)
186.98	25.08	67.7	-41.92	V
290.030	22.99	67.7	-44.01	H
253.410	22.13	67.7	-44.87	H
187.800	19.82	67.7	-47.18	H
257.270	18.38	67.7	-48.62	V
30.870	20.22	67.7	-46.78	H

### Test Procedure for Radiated Spurious Emissions above 1 GHz

The EUT was tested in a semi anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Spurious Emissions. The antenna, band reject filter, amplifier and cable correction factors were input into the spectrum analyzer before recording the Measured Level to ensure accurate readings. The spectrum for each tuned frequency was examined to the 10th harmonic.

#### Test Setup



Detector Settings	RBW	VBW	Span
Peak	1 MHz	3 MHz	As Necessary
Average	1 MHz	3 MHz	As Necessary

#### Radiated Spurious Emissions

Tuned Frequency (MHz)	Emission Frequency (MHz)	Peak Measured Value (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
2402	4804	52.94	74.0	54.0	Pass
2441	4884.2	50.29	74.0	54.0	Pass
2480	4960.2	44.27	74.0	54.0	Pass

All peak readings were below the average limits  
 No other emissions were detectable. All emissions were more than -20 dBc.

**Emissions at Band Edges**
**Name of Test:**

Emissions at Band Edges

**Engineer:** Alex Macon


**Test Equipment Utilized:**

i00271, i00331, i00349, i00428


**Test Date:** 4/6/15

**Test Procedure**

The EUT was tested in a semi-anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for band edge and restricted band for both peak and average measurements. The cable and antenna correction factors were input into the analyzer as a reference level offset to ensure accurate readings. For the restricted band the amplifier and band reject filter correction factors were also input to the spectrum analyzer.


**Band Edge Test Setup**

**Band Edge Emissions Summary**

Tuned Frequency (MHz)	Emission Frequency (MHz)	Measured Value (dBc)	Detector	Limit (dBc)	Result
2402	2397.8	-39.61	Peak	-20 dBc	Pass
2480	2488.7	-41.4	Peak	-20dBc	Pass


**Restricted Band Test Setup**

**Restricted Band Emissions Summary**

Restricted Band (MHz)	Tuned Frequency (MHz)	Emission Frequency (MHz)	Measured Value (dBuV/m)	Detector	Limit (dBuV/m)	Result
2300 – 2390	2402	2368.4	51.61	Peak	74	Pass
2300 – 2390	2402	2362.8	46.59	Average	54	Pass
2483.5 - 2500	2480	2483.5	59.53	Peak	74	Pass
2483.5 - 2500	2480	2483.5	51.57	Average	54	Pass

**Band Edge 2400 MHz**  
**Tuned Frequency= 2402 MHz**



**Band Edge 2483.5 MHz**  
**Tuned Frequency= 2480 MHz**







### Restricted Band 2300 – 2390 MHz – Peak Tuned Frequency= 2402MHz




### Restricted Band 2300 – 2390 MHz – Avg Tuned Frequency= 2402 MHz



Restricted Band 2483.5 – 2500 MHz – Peak  
Tuned Frequency= 2480 MHz



Restricted Band 2483.5 – 2500 MHz – Avg  
Tuned Frequency= 2480 MHz



### Occupied Bandwidth


**Name of Test:** Occupied Bandwidth  
**Test Equipment Utilized:** i00271, i00331, i00428

**Engineer:** Alex Macon  
**Test Date:** 4/6/15

### Test Procedure

The EUT was tested in a semi-anechoic chamber set 3m from the receiving antenna. The Span was set wide enough to capture the entire transmit spectrum and the resolution bandwidth was set to at least 1% of the span. The analyzer was set to max hold and when the entire spectrum was captured the 6dB and 99% bandwidths were measured to verify the bandwidth met the specification.

### Test Setup



### 6 dB Occupied Bandwidth Summary

Frequency (MHz)	Measured Bandwidth (MHz)	Specification Limit (kHz)	Result
2402	720.1	≥ 500	Pass
2442	717.8	≥ 500	Pass
2480	722.2	≥ 500	Pass

### 99% Bandwidth Summary


Frequency (MHz)	Measured Bandwidth (MHz)	Result
2402	1.143	Pass
2442	1.221	Pass
2480	1.304	Pass





### Occupied Bandwidth 2402 MHz

Agilent 10:58:20 Apr 6, 2015 R T



Center 2.402 GHz Span 5 MHz  
#Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)


**Occupied Bandwidth**  
1.1435 MHz

Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error -13.734 kHz  
x dB Bandwidth 720.106 kHz

### Occupied Bandwidth 2442 MHz

Agilent 11:41:29 Apr 6, 2015 R T



Center 2.442 GHz Span 5 MHz  
#Res BW 100 kHz #VBW 300 kHz Sweep 6 ms (601 pts)

**Occupied Bandwidth**  
1.2214 MHz


Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error 5.171 kHz  
x dB Bandwidth 717.812 kHz



### Occupied Bandwidth 2480 MHz

Agilent 12:06:41 Apr 6, 2015 R T



Center 2.48 GHz Span 5 MHz  
#Res BW 100 kHz #VBW 300 kHz Sweep 6 ms (601 pts)

**Occupied Bandwidth**  
**1.3045 MHz**

Occ BW % Pwr 99.00 %  
x dB -6.00 dB


Transmit Freq Error -3.033 kHz  
x dB Bandwidth 722.238 kHz

**Transmitter Power Spectral Density (PSD)**

**Name of Test:** Transmitter Power Spectral Density (PSD)      **Engineer:** Alex Macon  
**Test Equipment Utilized:** i00271, i00331, i00428      **Test Date:** 4/6/15


**Test Procedure**

The EUT was connected directly to a spectrum analyzer. The test was performed per section 6.11.2.3 of C63.10 - 2009 "Procedure for determining PSD for DTS devices".


**Test Setup**

**PSD Summary**

Frequency (MHz)	Measured Data (dBm)	Specification Limit (dBm)	Result
2402	-30.32	8	Pass
2442	-31.66	8	Pass
2480	-33.07	8	Pass

### PSD 2402 MHz




### PSD 2442 MHz





### PSD 2480 MHz



**A/C Powerline Conducted Emission**

**Name of Test:**

A/C Powerline Conducted Emissions

**Engineer:** Alex Macon

**Test Equipment Utilized:**


i00033, i00123, i00446 ,i00447

**Test Date:** 4/7/15

**Test Procedure**


The EUT power cable was connected to a LISN and the monitored output of the LISN was connected to a transient limiter, which then connected directly to a spectrum analyzer. The conducted emissions from 150 kHz to 30 MHz were measured and compared to the specification limits.

**Test Setup**




**Conducted Emission Test Results**

**Line 1 Peak Plot**



**Line 2 Peak Plot**



**Line 1 Neutral AVG Detector**

Frequency	Measured Value (dBuV)	LISN Correction Factor (dB)	Cable Loss (dB)	Transient Limiter (dB)	Final Data (dBuV)	Limit (dBuV)	Avg Margin (dB)
519.96 KHz	18.78	0.1	0.03	10.1	29.013	46	-16.987
514.14 KHz	20.46	0.1	0.03	10.1	30.693	46	-15.307
506.85 KHz	22.8	0.1	0.03	10.1	33.033	46	-12.967
490.5 KHz	29.28	0.1	0.03	10.1	39.507	46.271	-6.765
488.2 KHz	29.82	0.1	0.03	10.1	40.05	46.337	-6.287
483.2 KHz	28.84	0.1	0.03	10.1	39.073	46.48	-7.407

**Line 2 Phase AVG Detector**

Frequency	Measured Value (dBuV)	LISN Correction Factor (dB)	Cable Loss (dB)	Transient Limiter (dB)	Final Data (dBuV)	Limit (dBuV)	Avg Margin (dB)
511.78 KHz	15.82	0.1	0.03	10.1	26.053	46	-19.947
508.78 KHz	16.27	0.1	0.03	10.1	26.497	46	-19.503
502.67 KHz	18.49	0.1	0.03	10.1	28.72	46	-17.28
495.91 KHz	20.42	0.1	0.03	10.1	30.65	46.117	-15.467
492.3 KHz	22.23	0.1	0.03	10.1	32.46	46.22	-13.76
491.37 KHz	22.49	0.1	0.03	10.1	32.717	46.247	-13.53

**Line 1 Neutral QP Detector**

Frequency	Measured Value (dBuV)	LISN Correction Factor (dB)	Cable Loss (dB)	Transient Limiter (dB)	Final Data (dBuV)	Limit (dBuV)	QP Margin (dB)
519.96 KHz	26.88	0.1	0.03	10.1	37.11	56	-18.89
514.14 KHz	27.21	0.1	0.03	10.1	37.44	56	-18.56
506.85 KHz	27.57	0.1	0.03	10.1	37.8	56	-18.2
490.5 KHz	32.69	0.1	0.03	10.1	42.92	56.271	-13.351
488.2 KHz	33.18	0.1	0.03	10.1	43.41	56.337	-12.927
483.2 KHz	32.91	0.1	0.03	10.1	43.14	56.48	-13.34

**Line 2 Phase QP Detector**

Frequency	Measured Value (dBuV)	LISN Correction Factor (dB)	Cable Loss (dB)	Transient Limiter (dB)	Final Data (dBuV)	Limit (dBuV)	QP Margin (dB)
511.78 KHz	30.46	0.1	0.03	10.1	40.69	56	-15.31
508.78 KHz	30.48	0.1	0.03	10.1	40.71	56	-15.29
502.67 KHz	31.59	0.1	0.03	10.1	41.82	56	-14.18
495.91 KHz	32.09	0.1	0.03	10.1	42.32	56.117	-13.797
492.3 KHz	32.66	0.1	0.03	10.1	42.89	56.22	-13.33
491.37 KHz	32.68	0.1	0.03	10.1	42.91	56.247	-13.337



### Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
EMI Receiver	HP	8546A	i00033	2/26/15	2/26/16
Transient Limiter	Com-Power	LIT-153	i00123	Verified on:4/7/15	
Horn Antenna, Amplified	ARA	DRG-118/A	i00271	5/8/14	5/8/16
Horn Antenna, Amplified	ARA	MWH-1826/B	i00273	4/9/12	4/9/2015
Humidity / Temp Meter	Newport	IBTHX-W-5	i00282	4/1/15	4/1/16
Voltmeter	Fluke	75III	i00320	3/24/15	3/24/16
Spectrum Analyzer	Agilent	E4407B	i00331	6/13/14	6/13/15
Bi-Log Antenna	Schaffner	CBL 6111D	i00349	10/8/13	10/8/15
EMI Analyzer	Agilent	E7405A	i00379	2/5/15	2/5/16
3 Meter Semi-Anechoic Chamber	Panashield	3 Meter Semi-Anechoic Chamber	i00428	11/26/13	11/26/15
LISN	COM-Power	LI-125A	i00446	7/25/14	7/25/15
LISN	COM-Power	LI-125A	i00447	7/25/14	7/25/15

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT