

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

LTE Smart Phone

**FCC ID: 2ADINS6006L
Model Name: S6006L, NUU X7, X7**

**Report Number: 4791221995-1-RF-4
Issue Date: July 24, 2024**

Prepared for

**Sun Cupid Technology (HK) Ltd.
16/F, CEO Tower, 77 Wing Hong Street, Cheung Sha Wan, Kowloon, Hong Kong**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|---------------|---------------|------------|
| V0 | July 24, 2024 | Initial Issue | |

Summary of Test Results

| Test Item | Clause | Limit/Requirement | Result |
|-------------------------------------------|-----------------------------------------------|-----------------------------------------------|--------|
| Antenna Requirement | N/A | FCC Part 15.203/15.247 (c) | Pass |
| AC Power Line Conducted Emission | ANSI C63.10-2013, Clause 6.2 | FCC Part 15.207 | Pass |
| Conducted Output Power | ANSI C63.10-2013, Clause 11.9.1.3 | FCC Part 15.247 (b)(3) | Pass |
| 6dB Bandwidth and 99% Occupied Bandwidth | ANSI C63.10-2013, Clause 11.8.1 | FCC Part 15.247 (a)(2) | Pass |
| Power Spectral Density | ANSI C63.10-2013, Clause 11.10.2 | FCC Part 15.247 (e) | Pass |
| Conducted Band edge and spurious emission | ANSI C63.10-2013, Clause 11.11 | FCC Part 15.247(d) | Pass |
| Radiated Band edge and Spurious Emission | ANSI C63.10-2013, Clause 11.12 & Clause 11.13 | FCC Part 15.247 (d) FCC Part 15.205/15.209 | Pass |
| Duty Cycle | ANSI C63.10-2013, Clause 11.6 | None; for reporting purposes only. | Pass |

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Simple Acceptance> decision rule is applied.

CONTENTS

| | |
|------------------------------------------------------------|-----------|
| 1. ATTESTATION OF TEST RESULTS..... | 6 |
| 2. TEST METHODOLOGY..... | 7 |
| 3. FACILITIES AND ACCREDITATION..... | 7 |
| 4. CALIBRATION AND UNCERTAINTY | 8 |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> | <i>8</i> |
| 4.2. <i>MEASUREMENT UNCERTAINTY</i> | <i>8</i> |
| 5. EQUIPMENT UNDER TEST | 9 |
| 5.1. <i>DESCRIPTION OF EUT</i> | <i>9</i> |
| 5.2. <i>CHANNEL LIST</i> | <i>10</i> |
| 5.3. <i>MAXIMUM POWER</i> | <i>10</i> |
| 5.4. <i>TEST CHANNEL CONFIGURATION.....</i> | <i>10</i> |
| 5.5. <i>THE WORST-CASE CONFIGURATIONS.....</i> | <i>11</i> |
| 5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> | <i>11</i> |
| 5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i> | <i>11</i> |
| 5.8. <i>SETUP DIAGRAM</i> | <i>12</i> |
| 6. MEASURING EQUIPMENT AND SOFTWARE USED..... | 13 |
| 7. ANTENNA PORT TEST RESULTS | 16 |
| 7.1. <i>CONDUCTED OUTPUT POWER</i> | <i>16</i> |
| 7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i> | <i>17</i> |
| 7.3. <i>POWER SPECTRAL DENSITY</i> | <i>19</i> |
| 7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i> | <i>21</i> |
| 7.5. <i>DUTY CYCLE</i> | <i>23</i> |
| 8. RADIATED TEST RESULTS..... | 24 |
| 8.1. <i>RESTRICTED BANDEDGE</i> | <i>32</i> |
| 8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i> | <i>36</i> |
| 8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i> | <i>42</i> |
| 8.4. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i> | <i>54</i> |
| 8.5. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i> | <i>56</i> |
| 8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i> | <i>59</i> |
| 9. ANTENNA REQUIREMENT | 61 |
| 10. AC POWER LINE CONDUCTED EMISSION | 62 |

| | | |
|----------------------------------------------------------|-------------------------------------------------|-----------|
| 11. | TEST DATA..... | 66 |
| 11.1. | APPENDIX A: DTS BANDWIDTH..... | 66 |
| 11.1.1. | Test Result..... | 66 |
| 11.1.2. | Test Graphs | 67 |
| 11.2. | APPENDIX B: OCCUPIED CHANNEL BANDWIDTH..... | 69 |
| 11.2.1. | Test Result..... | 69 |
| 11.2.2. | Test Graphs | 70 |
| 11.3. | APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER..... | 72 |
| 11.3.1. | Test Result..... | 72 |
| 11.3.2. | Test Graphs | 73 |
| 11.4. | APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY..... | 75 |
| 11.4.1. | Test Result..... | 75 |
| 11.4.2. | Test Graphs | 76 |
| 11.5. | APPENDIX E: BAND EDGE MEASUREMENTS..... | 78 |
| 11.5.1. | Test Result..... | 78 |
| 11.5.2. | Test Graphs | 79 |
| 11.6. | APPENDIX F: CONDUCTED SPURIOUS EMISSION | 81 |
| 11.6.1. | Test Result..... | 81 |
| 11.6.2. | Test Graphs | 82 |
| 11.7. | APPENDIX G: DUTY CYCLE..... | 88 |
| 11.7.1. | Test Result..... | 88 |
| 11.7.2. | Test Graphs | 89 |
| APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION | | 90 |
| APPENDIX: PHOTOGRAPHS OF THE EUT | | 90 |

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Sun Cupid Technology (HK) Ltd.
Address: 16/F, CEO Tower, 77 Wing Hong St, Cheung Sha Wan, Kowloon
Hong Kong

Manufacturer Information


Company Name: Sun Cupid Technology (HK) Ltd.
Address: 16/F, CEO Tower, 77 Wing Hong St, Cheung Sha Wan, Kowloon
Hong Kong

EUT Information

EUT Name: LTE Smart Phone
Model: S6006L
Series Model: NUU X7, X7
Model Difference: NUU X7, X7 have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with S6006L. The difference lies only the model number. all these changes do not degrade the unwanted emissions of the certified product.
Sample Received Date: March 26, 2024
Sample Status: Normal
Sample ID: 7066315
Date of Tested: May 5, 2024 to July 24, 2024


| APPLICABLE STANDARDS | |
|------------------------------|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C | Pass |

Prepared By:



James Qin
Project Engineer

Checked By:



Denny Huang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

| | |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accreditation Certificate | <p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p> |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item | Uncertainty |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Conduction emission | 3.62 dB |
| Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz) | 2.2 dB |
| Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz) | 4.00 dB |
| Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz) | 5.78 dB (1 GHz ~ 18 GHz) |
| | 5.23 dB (18 GHz ~ 26 GHz) |
| Duty Cycle | ±0.028% |
| DTS and 99% Occupied Bandwidth | ±0.0196% |
| Maximum Conducted Output Power | ±0.686 dB |
| Maximum Power Spectral Density Level | ±0.743 dB |
| Conducted Band-edge Compliance | ±1.328 dB |
| Conducted Unwanted Emissions In Non-restricted Frequency Bands | ±0.746 dB (9 kHz ~ 1 GHz) |
| | ±1.328dB (1 GHz ~ 26 GHz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. | |

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

| | |
|----------|-----------------|
| EUT Name | LTE Smart Phone |
| Model | S6006L |

| | |
|----------------------|------------------------------|
| Frequency Band: | 2400 MHz to 2483.5 MHz |
| Frequency Range: | 2402 MHz to 2480 MHz |
| Support Standards: | CFR 47 FCC PART 15 SUBPART C |
| Type of Modulation: | GFSK |
| Number of Channels: | 40 |
| Antenna Type: | PIFA Antenna |
| Antenna Gain: | 2.97 dBi |
| Normal Test Voltage: | 3.8 Vdc |
| EUT Test software: | MTK |

EUT configurations:

| Material type | First resources material information | | Second resources material information | |
|----------------------|--------------------------------------|----------|---------------------------------------|----------|
| | Part number | Supplier | Part number | Supplier |
| MODU(Baseband chips) | MT6761V/WBA | MTK | MT8766V/WBA | MTK |

5.2. CHANNEL LIST

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0 | 2402 | 11 | 2424 | 22 | 2446 | 33 | 2468 |
| 1 | 2404 | 12 | 2426 | 23 | 2448 | 34 | 2470 |
| 2 | 2406 | 13 | 2428 | 24 | 2450 | 35 | 2472 |
| 3 | 2408 | 14 | 2430 | 25 | 2452 | 36 | 2474 |
| 4 | 2410 | 15 | 2432 | 26 | 2454 | 37 | 2476 |
| 5 | 2412 | 16 | 2434 | 27 | 2456 | 38 | 2478 |
| 6 | 2414 | 17 | 2436 | 28 | 2458 | 39 | 2480 |
| 7 | 2416 | 18 | 2438 | 29 | 2460 | / | / |
| 8 | 2418 | 19 | 2440 | 30 | 2462 | / | / |
| 9 | 2420 | 20 | 2442 | 31 | 2464 | / | / |
| 10 | 2422 | 21 | 2444 | 32 | 2466 | / | / |

5.3. MAXIMUM POWER

| Test Mode | Frequency (MHz) | Channel Number | Maximum Output Power (dBm) |
|-----------|-----------------|----------------|----------------------------|
| LE 1M | 2402 ~ 2480 | 0-39[40] | 2.71 |
| LE 2M | 2402 ~ 2480 | 0-39[40] | 4.47 |

5.4. TEST CHANNEL CONFIGURATION

| Test Mode | Test Channel | Frequency |
|-----------|---------------------------------------------------------------|------------------------------|
| LE 1M | CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel) | 2402 MHz, 2440 MHz, 2480 MHz |
| LE 2M | CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel) | 2402 MHz, 2440 MHz, 2480 MHz |

5.5. THE WORST-CASE CONFIGURATIONS

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band | | | | |
|--------------------------------------------------------------------|-------------------------|-----------------------------|---------|---------|
| Test Software Version | | MTK | | |
| Modulation Type | Transmit Antenna Number | Test Software setting value | | |
| | | CH 0 | CH 19 | CH 39 |
| GFSK(1Mbps) | 1 | default | default | default |
| GFSK(2Mbps) | 1 | default | default | default |

Note:

1. Based on preliminary testing, there were no significant differences between the two models and therefore model [MT6761 version] was fully tested.

5.6. DESCRIPTION OF AVAILABLE ANTENNAS


| Antenna | Frequency (MHz) | Antenna Type | MAX Antenna Gain (dBi) |
|---------|-----------------|--------------|------------------------|
| 1 | 2402-2480 | FPC | 2.97 |

| Test Mode | Transmit and Receive Mode | Description |
|--------------------------------------------------------------------------------------------------|----------------------------------------------|----------------------------------------------------------|
| LE 1M | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 3 can be used as transmitting/receiving antenna. |
| LE 2M | <input checked="" type="checkbox"/> 1TX, 1RX | Antenna 3 can be used as transmitting/receiving antenna. |
| Note: 1.BT&WLAN 2.4G, WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client) | | |

5.7. SUPPORT UNITS FOR SYSTEM TEST

The EUT has been tested as an independent unit

5.8. SETUP DIAGRAM



6. MEASURING EQUIPMENT AND SOFTWARE USED

| R&S TS 8997 Test System | | | | | |
|-------------------------------------|-----------------|-------------------------|------------------|--------------|--------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| Power sensor, Power Meter | R&S | OSP120 | 100921 | Mar.25,2024 | Mar.24,2025 |
| Vector Signal Generator | R&S | SMBV100A | 261637 | Oct.12, 2023 | Oct.11, 2024 |
| Signal Generator | R&S | SMB100A | 178553 | Oct.12, 2023 | Oct.11, 2024 |
| Signal Analyzer | R&S | FSV40 | 101118 | Oct.12, 2023 | Oct.11, 2024 |
| Software | | | | | |
| Description | Manufacturer | | Name | Version | |
| For R&S TS 8997 Test System | Rohde & Schwarz | | EMC 32 | 10.60.10 | |
| Tonsend RF Test System | | | | | |
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due. Date |
| Wideband Radio Communication Tester | R&S | CMW500 | 155523 | Oct.12, 2023 | Oct.11, 2024 |
| Wireless Connectivity Tester | R&S | CMW270 | 1201.0002N75-102 | Sep.25, 2023 | Sep.24, 2024 |
| PXA Signal Analyzer | Keysight | N9030A | MY55410512 | Oct.12, 2023 | Oct.11, 2024 |
| MXG Vector Signal Generator | Keysight | N5182B | MY56200284 | Oct.12, 2023 | Oct.11, 2024 |
| MXG Vector Signal Generator | Keysight | N5172B | MY56200301 | Oct.12, 2023 | Oct.11, 2024 |
| DC power supply | Keysight | E3642A | MY55159130 | Oct.12, 2023 | Oct.11, 2024 |
| Temperature & Humidity Chamber | SANMOOD | SG-80-CC-2 | 2088 | Oct.12, 2023 | Oct.11, 2024 |
| Attenuator | Aglient | 8495B | 2814a12853 | Oct.12, 2023 | Oct.11, 2024 |
| RF Control Unit | Tonscend | JS0806-2 | 23B80620666 | Mar.25,2024 | Mar.24,2025 |
| Software | | | | | |
| Description | Manufacturer | Name | | Version | |
| Tonsend SRD Test System | Tonsend | JS1120-3 RF Test System | | V3.2.22 | |

| Conducted Emissions | | | | | |
|---------------------------------------|--------------|-----------|--------------|--------------|--------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| EMI Test Receiver | R&S | ESR3 | 101961 | Oct.13, 2023 | Oct.12, 2024 |
| Two-Line V-Network | R&S | ENV216 | 101983 | Oct.13, 2023 | Oct.12, 2024 |
| Artificial Mains Networks | Schwarzbeck | NSLK 8126 | 8126465 | Oct.13, 2023 | Oct.12, 2024 |
| Software | | | | | |
| Description | | | Manufacturer | Name | Version |
| Test Software for Conducted Emissions | | | Farad | EZ-EMC | Ver. UL-3A1 |

| Radiated Emissions | | | | | |
|-----------------------------|--------------|----------------------------------|---------------|---------------|---------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| MXE EMI Receiver | KESIGHT | N9038A | MY56400036 | Oct.12, 2023 | Oct.11, 2024 |
| Hybrid Log Periodic Antenna | TDK | HLP-3003C | 130959 | Aug.02, 2021 | Aug.01, 2024 |
| Preamplifier | HP | 8447D | 2944A09099 | Oct.12, 2023 | Oct.11, 2024 |
| EMI Measurement Receiver | R&S | ESR26 | 101377 | Oct.12, 2023 | Oct.11, 2024 |
| Horn Antenna | TDK | HRN-0118 | 130940 | July 20, 2021 | July 19, 2024 |
| Preamplifier | TDK | PA-02-0118 | TRS-305-00067 | Oct.12, 2023 | Oct.11, 2024 |
| Horn Antenna | Schwarzbeck | BBHA9170 | 697 | July 20, 2021 | July 19, 2024 |
| Preamplifier | TDK | PA-02-2 | TRS-307-00003 | Oct.12, 2023 | Oct.11, 2024 |
| Preamplifier | TDK | PA-02-3 | TRS-308-00002 | Oct.12, 2023 | Oct.11, 2024 |
| Loop antenna | Schwarzbeck | 1519B | 00008 | Dec.14, 2021 | Dec.13, 2024 |
| Preamplifier | TDK | PA-02-001-3000 | TRS-302-00050 | Oct.12, 2023 | Oct.11, 2024 |
| High Pass Filter | Wi | WHKX10-2700-3000-18000-40SS | 23 | Oct.12, 2023 | Oct.11, 2024 |
| Highpass Filter | Wainwright | WHKX10-5850-6500-1800-40SS | 4 | Oct.12, 2023 | Oct.11, 2024 |
| Band Reject Filter | Wainwright | WRCJV12-5695-5725-5850-5880-40SS | 4 | Oct.12, 2023 | Oct.11, 2024 |
| Band Reject Filter | Wainwright | WRCJV20-5120-5150- | 2 | Oct.12, 2023 | Oct.11, 2024 |

| | | | | | |
|--------------------------------------|------------|--------------------------------------|--------------|--------------|--------------|
| | | 5350-5380-60SS | | | |
| Band Reject Filter | Wainwright | WRCJV20-5440-5470-5725-5755-60SS | 1 | Oct.12, 2023 | Oct.11, 2024 |
| Band Reject Filter | Wainwright | WRCJV8-2350-2400-2483.5-2533.5-40SS | 4 | Oct.12, 2023 | Oct.11, 2024 |
| Band Reject Filter | Wainwright | WRCD5-1879-1879.85-1880.15-1881-40SS | 1 | Oct.12, 2023 | Oct.11, 2024 |
| Notch Filter | Wainwright | WHJ10-882-980-7000-40SS | 1 | Oct.12, 2023 | Oct.11, 2024 |
| Highpass Filter | Xingbo | XBLBQ-GTA68 | 211115-2-1 | Oct.12, 2023 | Oct.11, 2024 |
| Notch Filter (5905-6445 MHz) | Xingbo | XBLBQ-DZA175 | 210922-2-1 | Oct.12, 2023 | Oct.11, 2024 |
| Notch Filter (6425-6525 MHz) | Xingbo | XBLBQ-DZA176 | 210922-2-2 | Oct.12, 2023 | Oct.11, 2024 |
| Notch Filter (6825-7125 MHz) | Xingbo | XBLBQ-DZA177 | 210922-2-3 | Oct.12, 2023 | Oct.11, 2024 |
| Notch Filter (6525-6875 MHz) | Xingbo | XBLBQ-DZA178 | 210922-2-4 | Oct.12, 2023 | Oct.11, 2024 |
| Software | | | | | |
| Description | | | Manufacturer | Name | Version |
| Test Software for Radiated Emissions | | | Farad | EZ-EMC | Ver. UL-3A1 |

| Other Instrument | | | | | |
|----------------------------|--------------|-----------|------------|--------------|--------------|
| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Due Date |
| Temperature humidity probe | OMEGA | ITHX-SD-5 | 18470007 | Oct.21, 2023 | Oct.20, 2024 |
| Barometer | Yiyi | Baro | N/A | Oct.19, 2023 | Oct.18, 2024 |
| Attenuator | Agilent | 8495B | 2814a12853 | Oct.12, 2023 | Oct.11, 2024 |

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER


LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C | | | |
|--------------------------------------|---------------------------|------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3) | Peak Conduct Output Power | 1 watt or 30 dBm | 2400-2483.5 |

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).
Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.3°C | Relative Humidity | 60% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.8V |

TEST DATE / ENGINEER

| | | | |
|-----------|-------------|---------|-------------|
| Test Date | May 6, 2024 | Test By | Walker Yuan |
|-----------|-------------|---------|-------------|

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C | | | |
|--------------------------------------|----------------|----------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2) | 6 dB Bandwidth | ≥ 500 kHz | 2400-2483.5 |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

| | |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Frequency Span | For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW |
| Detector | Peak |
| RBW | For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth |
| VBW | For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW |
| Trace | Max hold |
| Sweep | Auto couple |

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.3°C | Relative Humidity | 60% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.8V |

TEST DATE / ENGINEER

| | | | |
|-----------|-------------|---------|-------------|
| Test Date | May 6, 2024 | Test By | Walker Yuan |
|-----------|-------------|---------|-------------|

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C | | | |
|--------------------------------------|------------------------|-------------------------|-----------------------|
| Section | Test Item | Limit | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e) | Power Spectral Density | 8 dBm in any 3 kHz band | 2400-2483.5 |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.2.


Connect the EUT to the spectrum analyzer and use the following settings:

| | |
|------------------|------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | $1.5 \times \text{DTS bandwidth}$ |
| Trace | Max hold |
| Sweep time | Auto couple |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.3°C | Relative Humidity | 60% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.8V |

TEST DATE / ENGINEER

| | | | |
|-----------|-------------|---------|-------------|
| Test Date | May 6, 2024 | Test By | Walker Yuan |
|-----------|-------------|---------|-------------|

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C | | |
|--------------------------------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Section | Test Item | Limit |
| CFR 47 FCC §15.247 (d) | Conducted Bandedge and Spurious Emissions | at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power |

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


| | |
|------------------|------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| Span | 1.5 x DTS bandwidth |
| Trace | Max hold |
| Sweep time | Auto couple. |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

| | |
|--------------------|-------------------------------------------------------------------------------|
| Span | Set the center frequency and span to encompass frequency range to be measured |
| Detector | Peak |
| RBW | 100 kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| measurement points | $\geq \text{span}/\text{RBW}$ |
| Trace | Max hold |
| Sweep time | Auto couple. |

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.3℃ | Relative Humidity | 60% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.8V |

TEST DATE / ENGINEER

| | | | |
|-----------|-------------|---------|-------------|
| Test Date | May 6, 2024 | Test By | Walker Yuan |
|-----------|-------------|---------|-------------|

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.3°C | Relative Humidity | 60% |
| Atmosphere Pressure | 101kPa | Test Voltage | DC 3.8V |

TEST DATE / ENGINEER

| | | | |
|-----------|-------------|---------|-------------|
| Test Date | May 6, 2024 | Test By | Walker Yuan |
|-----------|-------------|---------|-------------|

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

| Emissions radiated outside of the specified frequency bands above 30 MHz | | | |
|--------------------------------------------------------------------------|---------------------------------------|-----------------------------------------|---------|
| Frequency Range (MHz) | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m | |
| | | Quasi-Peak | |
| 30 - 88 | 100 | 40 | |
| 88 - 216 | 150 | 43.5 | |
| 216 - 960 | 200 | 46 | |
| Above 960 | 500 | 54 | |
| Above 1000 | 500 | Peak | Average |
| | | 74 | 54 |

| FCC Emissions radiated outside of the specified frequency bands below 30 MHz | | |
|------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |

FCC Restricted bands of operation refer to FCC §15.205 (a):

| MHz | MHz | MHz | GHz |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| ¹ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (²) |
| 13.36-13.41 | | | |

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

| | |
|-------|------------------------------------------------------------------|
| RBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| VBW | 200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz) |
| Sweep | Auto |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

| | |
|----------|----------|
| RBW | 120 kHz |
| VBW | 300 kHz |
| Sweep | Auto |
| Detector | Peak/QP |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

| | |
|----------|--------------------------------|
| RBW | 1 MHz |
| VBW | PEAK: 3 MHz AVG: see note 6 |
| Sweep | Auto |
| Detector | Peak |
| Trace | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



TEST ENVIRONMENT

| | | | |
|---------------------|--------|-------------------|-----|
| Temperature | 23°C | Relative Humidity | 55% |
| Atmosphere Pressure | 101kPa | Test Voltage | |


TEST DATE / ENGINEER

| | | | |
|-----------|--------------|---------|-----------|
| Test Date | May 23, 2024 | Test By | James Qin |
|-----------|--------------|---------|-----------|

TEST RESULTS


8.1. RESTRICTED BANDEDGE

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M PK | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2330.000 | 18.04 | 32.60 | 50.64 | 74.00 | -23.36 | peak |
| 2 | 2390.000 | 15.68 | 32.92 | 48.60 | 74.00 | -25.40 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M PK | Frequency(MHz): | 2480 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2483.500 | 14.45 | 32.94 | 47.39 | 74.00 | -26.61 | peak |
| 2 | 2487.250 | 16.05 | 32.94 | 48.99 | 74.00 | -25.01 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 2M PK | Frequency(MHz): | 2404 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2329.200 | 18.91 | 32.59 | 51.50 | 74.00 | -22.50 | peak |
| 2 | 2390.000 | 14.79 | 32.92 | 47.71 | 74.00 | -26.29 | peak |

Note:

- based on preliminary testing, there were no significant differences between the two models and therefore model [MT6761 version] was fully tested.


| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 2M PK | Frequency(MHz): | 2478 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 2483.500 | 14.27 | 32.94 | 47.21 | 74.00 | -26.79 | peak |
| 2 | 2489.011 | 15.96 | 32.93 | 48.89 | 74.00 | -25.11 | peak |


8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1634.000 | 46.23 | -11.01 | 35.22 | 74.00 | -38.78 | peak |
| 2 | 1726.000 | 46.57 | -10.59 | 35.98 | 74.00 | -38.02 | peak |
| 3 | 1958.000 | 45.51 | -10.14 | 35.37 | 74.00 | -38.63 | peak |
| 4 | 2338.000 | 55.17 | -7.85 | 47.32 | 74.00 | -26.68 | peak |
| 5 | 2522.000 | 45.55 | -7.53 | 38.02 | 74.00 | -35.98 | peak |
| 6 | 2586.000 | 45.29 | -7.66 | 37.63 | 74.00 | -36.37 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1620.000 | 46.71 | -11.07 | 35.64 | 74.00 | -38.36 | peak |
| 2 | 1956.000 | 45.94 | -10.14 | 35.80 | 74.00 | -38.20 | peak |
| 3 | 2334.000 | 55.04 | -7.89 | 47.15 | 74.00 | -26.85 | peak |
| 4 | 2524.000 | 45.21 | -7.54 | 37.67 | 74.00 | -36.33 | peak |
| 5 | 2760.000 | 44.97 | -6.98 | 37.99 | 74.00 | -36.01 | peak |
| 6 | 2838.000 | 44.05 | -6.62 | 37.43 | 74.00 | -36.57 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2440 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1588.000 | 46.33 | -11.24 | 35.09 | 74.00 | -38.91 | peak |
| 2 | 1782.000 | 45.68 | -10.32 | 35.36 | 74.00 | -38.64 | peak |
| 3 | 1892.000 | 45.49 | -10.18 | 35.31 | 74.00 | -38.69 | peak |
| 4 | 2330.000 | 54.33 | -7.92 | 46.41 | 74.00 | -27.59 | peak |
| 5 | 2440.000 | 46.03 | -7.44 | 38.59 | 74.00 | -35.41 | peak |
| 6 | 2526.000 | 45.84 | -7.54 | 38.30 | 74.00 | -35.70 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2440 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1548.000 | 46.05 | -11.46 | 34.59 | 74.00 | -39.41 | peak |
| 2 | 1838.000 | 45.67 | -10.22 | 35.45 | 74.00 | -38.55 | peak |
| 3 | 2068.000 | 45.79 | -9.69 | 36.10 | 74.00 | -37.90 | peak |
| 4 | 2328.000 | 52.83 | -7.94 | 44.89 | 74.00 | -29.11 | peak |
| 5 | 2522.000 | 45.47 | -7.53 | 37.94 | 74.00 | -36.06 | peak |
| 6 | 2768.000 | 45.19 | -6.94 | 38.25 | 74.00 | -35.75 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2480 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1778.000 | 45.61 | -10.34 | 35.27 | 74.00 | -38.73 | peak |
| 2 | 2070.000 | 45.45 | -9.68 | 35.77 | 74.00 | -38.23 | peak |
| 3 | 2330.000 | 49.55 | -7.92 | 41.63 | 74.00 | -32.37 | peak |
| 4 | 2470.000 | 44.45 | -7.47 | 36.98 | 74.00 | -37.02 | peak |
| 5 | 2584.000 | 44.76 | -7.65 | 37.11 | 74.00 | -36.89 | peak |
| 6 | 2810.000 | 45.20 | -6.75 | 38.45 | 74.00 | -35.55 | peak |


| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2480 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 1612.000 | 46.67 | -11.11 | 35.56 | 74.00 | -38.44 | peak |
| 2 | 2016.000 | 45.89 | -10.01 | 35.88 | 74.00 | -38.12 | peak |
| 3 | 2228.000 | 46.02 | -8.68 | 37.34 | 74.00 | -36.66 | peak |
| 4 | 2336.000 | 52.59 | -7.87 | 44.72 | 74.00 | -29.28 | peak |
| 5 | 2382.000 | 44.82 | -7.53 | 37.29 | 74.00 | -36.71 | peak |
| 6 | 2838.000 | 44.56 | -6.62 | 37.94 | 74.00 | -36.06 | peak |


8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 4440.000 | 43.73 | -0.89 | 42.84 | 74.00 | -31.16 | peak |
| 2 | 8985.000 | 36.40 | 10.97 | 47.37 | 74.00 | -26.63 | peak |
| 3 | 10455.000 | 35.80 | 13.59 | 49.39 | 74.00 | -24.61 | peak |
| 4 | 11910.000 | 31.71 | 18.11 | 49.82 | 74.00 | -24.18 | peak |
| 5 | 13860.000 | 27.52 | 22.68 | 50.20 | 74.00 | -23.80 | peak |
| 6 | 17940.000 | 24.03 | 26.61 | 50.64 | 74.00 | -23.36 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7905.000 | 37.91 | 7.25 | 45.16 | 74.00 | -28.84 | peak |
| 2 | 9060.000 | 37.81 | 10.82 | 48.63 | 74.00 | -25.37 | peak |
| 3 | 10215.000 | 36.82 | 12.56 | 49.38 | 74.00 | -24.62 | peak |
| 4 | 11355.000 | 34.20 | 16.27 | 50.47 | 74.00 | -23.53 | peak |
| 5 | 12675.000 | 31.81 | 18.54 | 50.35 | 74.00 | -23.65 | peak |
| 6 | 18000.000 | 24.02 | 26.83 | 50.85 | 74.00 | -23.15 | peak |

Note:


- based on preliminary testing, there were no significant differences between the two models and therefore model [MT6761 version] was fully tested.

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2440 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 5700.000 | 40.09 | 2.54 | 42.63 | 74.00 | -31.37 | peak |
| 2 | 9060.000 | 36.72 | 10.82 | 47.54 | 74.00 | -26.46 | peak |
| 3 | 11070.000 | 35.41 | 15.08 | 50.49 | 74.00 | -23.51 | peak |
| 4 | 12045.000 | 32.40 | 18.46 | 50.86 | 74.00 | -23.14 | peak |
| 5 | 13515.000 | 29.11 | 21.69 | 50.80 | 74.00 | -23.20 | peak |
| 6 | 17940.000 | 24.08 | 26.61 | 50.69 | 74.00 | -23.31 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2440 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7500.000 | 36.95 | 7.18 | 44.13 | 74.00 | -29.87 | peak |
| 2 | 8265.000 | 37.27 | 8.53 | 45.80 | 74.00 | -28.20 | peak |
| 3 | 10440.000 | 35.71 | 13.56 | 49.27 | 74.00 | -24.73 | peak |
| 4 | 11925.000 | 31.82 | 18.17 | 49.99 | 74.00 | -24.01 | peak |
| 5 | 13890.000 | 27.88 | 22.69 | 50.57 | 74.00 | -23.43 | peak |
| 6 | 17850.000 | 24.17 | 26.28 | 50.45 | 74.00 | -23.55 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2480 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7305.000 | 36.44 | 6.89 | 43.33 | 74.00 | -30.67 | peak |
| 2 | 9060.000 | 37.73 | 10.82 | 48.55 | 74.00 | -25.45 | peak |
| 3 | 9960.000 | 37.08 | 12.28 | 49.36 | 74.00 | -24.64 | peak |
| 4 | 11805.000 | 31.72 | 17.65 | 49.37 | 74.00 | -24.63 | peak |
| 5 | 12555.000 | 31.71 | 18.39 | 50.10 | 74.00 | -23.90 | peak |
| 6 | 17745.000 | 23.01 | 25.58 | 48.59 | 74.00 | -25.41 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2480 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 8985.000 | 36.64 | 10.97 | 47.61 | 74.00 | -26.39 | peak |
| 2 | 10605.000 | 35.78 | 13.94 | 49.72 | 74.00 | -24.28 | peak |
| 3 | 11055.000 | 34.94 | 15.04 | 49.98 | 74.00 | -24.02 | peak |
| 4 | 12240.000 | 31.33 | 18.46 | 49.79 | 74.00 | -24.21 | peak |
| 5 | 13620.000 | 28.26 | 21.76 | 50.02 | 74.00 | -23.98 | peak |
| 6 | 18000.000 | 23.89 | 26.83 | 50.72 | 74.00 | -23.28 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2404 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7050.000 | 37.29 | 7.19 | 44.48 | 74.00 | -29.52 | peak |
| 2 | 8940.000 | 37.01 | 10.35 | 47.36 | 74.00 | -26.64 | peak |
| 3 | 11070.000 | 34.48 | 15.08 | 49.56 | 74.00 | -24.44 | peak |
| 4 | 12300.000 | 31.25 | 18.65 | 49.90 | 74.00 | -24.10 | peak |
| 5 | 13530.000 | 28.81 | 21.68 | 50.49 | 74.00 | -23.51 | peak |
| 6 | 17925.000 | 23.61 | 26.55 | 50.16 | 74.00 | -23.84 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2404 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 5700.000 | 40.00 | 2.54 | 42.54 | 74.00 | -31.46 | peak |
| 2 | 9060.000 | 37.12 | 10.82 | 47.94 | 74.00 | -26.06 | peak |
| 3 | 10380.000 | 35.29 | 13.36 | 48.65 | 74.00 | -25.35 | peak |
| 4 | 12300.000 | 31.21 | 18.65 | 49.86 | 74.00 | -24.14 | peak |
| 5 | 13920.000 | 27.10 | 22.71 | 49.81 | 74.00 | -24.19 | peak |
| 6 | 17985.000 | 23.33 | 26.77 | 50.10 | 74.00 | -23.90 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2440 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7830.000 | 38.25 | 7.46 | 45.71 | 74.00 | -28.29 | peak |
| 2 | 9375.000 | 36.62 | 10.40 | 47.02 | 74.00 | -26.98 | peak |
| 3 | 10920.000 | 34.70 | 14.54 | 49.24 | 74.00 | -24.76 | peak |
| 4 | 12345.000 | 30.94 | 18.81 | 49.75 | 74.00 | -24.25 | peak |
| 5 | 14010.000 | 27.64 | 22.73 | 50.37 | 74.00 | -23.63 | peak |
| 6 | 17955.000 | 24.00 | 26.66 | 50.66 | 74.00 | -23.34 | peak |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2440 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7305.000 | 36.97 | 6.89 | 43.86 | 74.00 | -30.14 | peak |
| 2 | 9075.000 | 36.35 | 10.74 | 47.09 | 74.00 | -26.91 | peak |
| 3 | 11055.000 | 34.41 | 15.04 | 49.45 | 74.00 | -24.55 | peak |
| 4 | 12645.000 | 32.29 | 18.44 | 50.73 | 74.00 | -23.27 | peak |
| 5 | 13530.000 | 28.47 | 21.68 | 50.15 | 74.00 | -23.85 | peak |
| 6 | 17970.000 | 23.17 | 26.72 | 49.89 | 74.00 | -24.11 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2478 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 8970.000 | 36.80 | 10.75 | 47.55 | 74.00 | -26.45 | peak |
| 2 | 10350.000 | 35.51 | 13.21 | 48.72 | 74.00 | -25.28 | peak |
| 3 | 11685.000 | 32.51 | 17.28 | 49.79 | 74.00 | -24.21 | peak |
| 4 | 12675.000 | 31.65 | 18.54 | 50.19 | 74.00 | -23.81 | peak |
| 5 | 13965.000 | 27.31 | 22.74 | 50.05 | 74.00 | -23.95 | peak |
| 6 | 17970.000 | 23.49 | 26.72 | 50.21 | 74.00 | -23.79 | peak |


| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 2M | Frequency(MHz): | 2478 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 7890.000 | 38.29 | 7.29 | 45.58 | 74.00 | -28.42 | peak |
| 2 | 8985.000 | 36.91 | 10.97 | 47.88 | 74.00 | -26.12 | peak |
| 3 | 10335.000 | 35.48 | 13.14 | 48.62 | 74.00 | -25.38 | peak |
| 4 | 12645.000 | 31.63 | 18.44 | 50.07 | 74.00 | -23.93 | peak |
| 5 | 13380.000 | 28.85 | 21.33 | 50.18 | 74.00 | -23.82 | peak |
| 6 | 17985.000 | 23.78 | 26.77 | 50.55 | 74.00 | -23.45 | peak |


8.4. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18680.000 | 50.45 | -5.38 | 45.07 | 74.00 | -28.93 | peak |
| 2 | 20256.000 | 49.53 | -5.61 | 43.92 | 74.00 | -30.08 | peak |
| 3 | 21248.000 | 49.29 | -4.77 | 44.52 | 74.00 | -29.48 | peak |
| 4 | 22024.000 | 49.04 | -4.46 | 44.58 | 74.00 | -29.42 | peak |
| 5 | 23536.000 | 47.56 | -3.15 | 44.41 | 74.00 | -29.59 | peak |
| 6 | 25000.000 | 46.86 | -2.10 | 44.76 | 74.00 | -29.24 | peak |


| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 18768.000 | 49.31 | -5.41 | 43.90 | 74.00 | -30.10 | peak |
| 2 | 19984.000 | 49.71 | -5.44 | 44.27 | 74.00 | -29.73 | peak |
| 3 | 21584.000 | 48.10 | -4.56 | 43.54 | 74.00 | -30.46 | peak |
| 4 | 23216.000 | 46.51 | -3.38 | 43.13 | 74.00 | -30.87 | peak |
| 5 | 24968.000 | 46.76 | -2.14 | 44.62 | 74.00 | -29.38 | peak |
| 6 | 25688.000 | 45.31 | -0.90 | 44.41 | 74.00 | -29.59 | peak |


8.5. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 0.0100 | 76.72 | -101.40 | -24.68 | 47.60 | -72.28 | peak |
| 2 | 0.0131 | 72.97 | -101.38 | -28.41 | 45.25 | -73.66 | peak |
| 3 | 0.0212 | 70.04 | -101.35 | -31.31 | 41.07 | -72.38 | peak |
| 4 | 0.0279 | 68.17 | -101.38 | -33.21 | 38.69 | -71.90 | peak |
| 5 | 0.0534 | 62.04 | -101.49 | -39.45 | 33.05 | -72.50 | peak |
| 6 | 0.1014 | 58.06 | -101.79 | -43.73 | 27.48 | -71.21 | peak |

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 0.1554 | 76.27 | -101.65 | -25.38 | 23.77 | -49.15 | peak |
| 2 | 0.1822 | 73.39 | -101.68 | -28.29 | 22.39 | -50.68 | peak |
| 3 | 0.2149 | 69.20 | -101.75 | -32.55 | 20.96 | -53.51 | peak |
| 4 | 0.2540 | 67.10 | -101.80 | -34.70 | 19.50 | -54.20 | peak |
| 5 | 0.3431 | 61.67 | -101.90 | -40.23 | 16.89 | -57.12 | peak |
| 6 | 0.4364 | 57.36 | -101.99 | -44.63 | 14.80 | -59.43 | peak |


| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 0.5039 | 63.43 | -62.07 | 1.36 | 33.56 | -32.20 | peak |
| 2 | 1.1868 | 59.20 | -62.18 | -2.98 | 26.12 | -29.10 | peak |
| 3 | 1.7036 | 57.44 | -61.96 | -4.52 | 22.98 | -27.50 | peak |
| 4 | 3.7100 | 55.20 | -61.41 | -6.21 | 29.54 | -35.75 | peak |
| 5 | 11.0838 | 54.28 | -60.84 | -6.56 | 29.54 | -36.10 | peak |
| 6 | 17.5167 | 54.40 | -60.92 | -6.52 | 29.54 | -36.06 | peak |


8.6. SPURIOUS EMISSIONS(30 MHz~1 GHZ)

| | | | |
|------------|------------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Horizontal | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 34.8500 | 33.87 | -14.75 | 19.12 | 40.00 | -20.88 | QP |
| 2 | 94.0199 | 29.31 | -16.65 | 12.66 | 43.50 | -30.84 | QP |
| 3 | 184.2300 | 28.62 | -12.10 | 16.52 | 43.50 | -26.98 | QP |
| 4 | 226.9100 | 32.42 | -13.32 | 19.10 | 46.00 | -26.90 | QP |
| 5 | 839.9500 | 31.38 | -2.67 | 28.71 | 46.00 | -17.29 | QP |
| 6 | 888.4500 | 28.95 | -1.63 | 27.32 | 46.00 | -18.68 | QP |

| | | | |
|------------|----------|-----------------|--------------|
| Test Mode: | BLE 1M | Frequency(MHz): | 2402 |
| Polarity: | Vertical | Test Voltage: | AC 120V_60Hz |



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|----------------|-----------------|----------------|-------------|--------|
| 1 | 34.8500 | 36.16 | -14.75 | 21.41 | 40.00 | -18.59 | QP |
| 2 | 48.4300 | 35.35 | -15.44 | 19.91 | 40.00 | -20.09 | QP |
| 3 | 93.0500 | 38.58 | -16.71 | 21.87 | 43.50 | -21.63 | QP |
| 4 | 207.5100 | 31.69 | -12.51 | 19.18 | 43.50 | -24.32 | QP |
| 5 | 226.9100 | 35.52 | -13.32 | 22.20 | 46.00 | -23.80 | QP |
| 6 | 839.9500 | 28.84 | -2.67 | 26.17 | 46.00 | -19.83 | QP |

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a)


| FREQUENCY (MHz) | Quasi-peak | Average |
|-----------------|------------|-----------|
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


| | | | |
|---------------------|--------|-------------------|---------|
| Temperature | 23.6°C | Relative Humidity | 56% |
| Atmosphere Pressure | 101kPa | Test Voltage | AC 120V |

TEST DATE / ENGINEER

| | | | |
|-----------|--------------|---------|-----------|
| Test Date | May 15, 2024 | Test By | James Qin |
|-----------|--------------|---------|-----------|

TEST RESULTS

| | | | |
|------------|-----|-------|------|
| Test Mode: | BLE | Line: | Line |
|------------|-----|-------|------|



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1 | 0.1604 | 31.38 | 10.32 | 41.70 | 65.44 | -23.74 | QP |
| 2 | 0.1604 | 18.13 | 10.32 | 28.45 | 55.44 | -26.99 | AVG |
| 3 | 0.4851 | 30.20 | 10.24 | 40.44 | 56.25 | -15.81 | QP |
| 4 | 0.4851 | 19.97 | 10.24 | 30.21 | 46.25 | -16.04 | AVG |
| 5 | 0.9677 | 26.15 | 10.05 | 36.20 | 56.00 | -19.80 | QP |
| 6 | 0.9677 | 15.01 | 10.05 | 25.06 | 46.00 | -20.94 | AVG |
| 7 | 1.8501 | 21.06 | 9.95 | 31.01 | 56.00 | -24.99 | QP |
| 8 | 1.8501 | 13.16 | 9.95 | 23.11 | 46.00 | -22.89 | AVG |
| 9 | 2.8041 | 19.85 | 10.05 | 29.90 | 56.00 | -26.10 | QP |
| 10 | 2.8041 | 12.65 | 10.05 | 22.70 | 46.00 | -23.30 | AVG |
| 11 | 15.6533 | 23.71 | 10.58 | 34.29 | 60.00 | -25.71 | QP |
| 12 | 15.6533 | 12.09 | 10.58 | 22.67 | 50.00 | -27.33 | AVG |


Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

| | | | |
|------------|-----|-------|---------|
| Test Mode: | BLE | Line: | Neutral |
|------------|-----|-------|---------|



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1 | 0.1607 | 31.12 | 10.22 | 41.34 | 65.43 | -24.09 | QP |
| 2 | 0.1607 | 18.71 | 10.22 | 28.93 | 55.43 | -26.50 | AVG |
| 3 | 0.4860 | 36.48 | 10.04 | 46.52 | 56.24 | -9.72 | QP |
| 4 | 0.4860 | 24.28 | 10.04 | 34.32 | 46.24 | -11.92 | AVG |
| 5 | 0.9661 | 34.24 | 9.85 | 44.09 | 56.00 | -11.91 | QP |
| 6 | 0.9661 | 20.17 | 9.85 | 30.02 | 46.00 | -15.98 | AVG |
| 7 | 1.8449 | 28.71 | 10.01 | 38.72 | 56.00 | -17.28 | QP |
| 8 | 1.8449 | 18.07 | 10.01 | 28.08 | 46.00 | -17.92 | AVG |
| 9 | 2.8028 | 27.04 | 10.15 | 37.19 | 56.00 | -18.81 | QP |
| 10 | 2.8028 | 17.55 | 10.15 | 27.70 | 46.00 | -18.30 | AVG |
| 11 | 15.4911 | 27.61 | 10.67 | 38.28 | 60.00 | -21.72 | QP |
| 12 | 15.4911 | 16.87 | 10.67 | 27.54 | 50.00 | -22.46 | AVG |

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH

11.1.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | DTS BW [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|--------------|---------|---------|------------|---------|
| BLE_1M | Ant1 | 2402 | 0.70 | 2401.64 | 2402.34 | 0.5 | PASS |
| | | 2440 | 0.70 | 2439.65 | 2440.34 | 0.5 | PASS |
| | | 2480 | 0.70 | 2479.64 | 2480.34 | 0.5 | PASS |
| BLE_2M | Ant1 | 2404 | 1.15 | 2403.43 | 2404.58 | 0.5 | PASS |
| | | 2440 | 1.15 | 2439.42 | 2440.58 | 0.5 | PASS |
| | | 2478 | 1.15 | 2477.42 | 2478.57 | 0.5 | PASS |

11.1.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | OCB [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|-----------|-----------|-----------|------------|---------|
| BLE_1M | Ant1 | 2402 | 1.047 | 2401.4805 | 2402.5275 | --- | --- |
| | | 2440 | 1.043 | 2439.4805 | 2440.5235 | --- | --- |
| | | 2480 | 1.043 | 2479.4805 | 2480.5235 | --- | --- |
| BLE_2M | Ant1 | 2404 | 2.074 | 2402.9770 | 2405.0509 | --- | --- |
| | | 2440 | 2.074 | 2438.9730 | 2441.0470 | --- | --- |
| | | 2478 | 2.07 | 2476.9730 | 2479.0430 | --- | --- |

11.2.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

11.3.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|----------------|-------------|------------|---------|
| BLE_1M | Ant1 | 2402 | 1.55 | ≤30 | PASS |
| | | 2440 | 2.71 | ≤30 | PASS |
| | | 2480 | 1.53 | ≤30 | PASS |
| BLE_2M | Ant1 | 2404 | 2.55 | ≤30 | PASS |
| | | 2440 | 4.47 | ≤30 | PASS |
| | | 2478 | 3.72 | ≤30 | PASS |

11.3.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

11.4.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|----------------|------------------|-----------------|---------|
| BLE_1M | Ant1 | 2402 | -13.79 | ≤8.00 | PASS |
| | | 2440 | -12.60 | ≤8.00 | PASS |
| | | 2480 | -13.86 | ≤8.00 | PASS |
| BLE_2M | Ant1 | 2404 | -15.45 | ≤8.00 | PASS |
| | | 2440 | -13.32 | ≤8.00 | PASS |
| | | 2478 | -14.14 | ≤8.00 | PASS |

11.4.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.5. APPENDIX E: BAND EDGE MEASUREMENTS

11.5.1. Test Result

| Test Mode | Antenna | ChName | Frequency [MHz] | RefLevel [dBm] | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|--------|-----------------|----------------|-------------|---------------|---------|
| BLE_1M | Ant1 | Low | 2402 | 0.66 | -46.42 | ≤ -19.34 | PASS |
| | | High | 2480 | 0.58 | -46.04 | ≤ -19.42 | PASS |
| BLE_2M | Ant1 | Low | 2404 | 1.63 | -47.52 | ≤ -18.37 | PASS |
| | | High | 2478 | 4.19 | -41.65 | ≤ -15.81 | PASS |

11.5.2. Test Graphs







11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION

11.6.1. Test Result


| Test Mode | Antenna | Frequency[MHz] | FreqRange [MHz] | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|----------------|-----------------|-------------|---------------|---------|
| BLE_1M | Ant1 | 2402 | Reference | 0.65 | --- | PASS |
| | | | 30~1000 | -49.98 | ≤ -19.35 | PASS |
| | | | 1000~26500 | -50.28 | ≤ -19.35 | PASS |
| | | 2440 | Reference | 1.83 | --- | PASS |
| | | | 30~1000 | -50.23 | ≤ -18.17 | PASS |
| | | | 1000~26500 | -49.83 | ≤ -18.17 | PASS |
| | | 2480 | Reference | 0.60 | --- | PASS |
| | | | 30~1000 | -49.34 | ≤ -19.4 | PASS |
| | | | 1000~26500 | -49.83 | ≤ -19.4 | PASS |
| BLE_2M | Ant1 | 2404 | Reference | 1.57 | --- | PASS |
| | | | 30~1000 | -50.4 | ≤ -18.43 | PASS |
| | | | 1000~26500 | -49.97 | ≤ -18.43 | PASS |
| | | 2440 | Reference | 3.69 | --- | PASS |
| | | | 30~1000 | -50.31 | ≤ -16.31 | PASS |
| | | | 1000~26500 | -50.42 | ≤ -16.31 | PASS |
| | | 2478 | Reference | 2.89 | --- | PASS |
| | | | 30~1000 | -50.11 | ≤ -17.11 | PASS |
| | | | 1000~26500 | -50.28 | ≤ -17.11 | PASS |

11.6.2. Test Graphs







BLE_1M_Ant1_2440_0~Reference




BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference




BLE_1M_Ant1_2480_30~1000




BLE_1M_Ant1_2480_1000~26500




BLE_2M_Ant1_2404_0~Reference




BLE_2M_Ant1_2404_30~1000




BLE_2M_Ant1_2404_1000~26500




BLE_2M_Ant1_2440_0~Reference




BLE_2M_Ant1_2440_30~1000




BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant1_2478_0~Reference



BLE_2M_Ant1_2478_30~1000



BLE_2M_Ant1_2478_1000~26500

11.7. APPENDIX G: DUTY CYCLE

11.7.1. Test Result

| TestMode | Antenna | Frequency[MHz] | ON Time [ms] | Period [ms] | X | DC [%] | xFactor | Limit | Verdict |
|----------|---------|----------------|-----------------|----------------|--------|-----------|---------|-------|---------|
| BLE_1M | Ant1 | 2402 | 0.38 | 0.62 | 0.6129 | 61.29 | 2.13 | --- | --- |
| BLE_2M | Ant1 | 2404 | 0.20 | 0.62 | 0.3226 | 32.26 | 4.91 | --- | --- |

11.7.2. Test Graphs



APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION

Referred to 4791221995-1_Appendix_EUTPhoto_External

APPENDIX: PHOTOGRAPHS OF THE EUT

Referred to 4791221995-1_Appendix_EUTPhoto_External

END OF REPORT