

RF Exposure Evaluation Report

Product	: Sleep Dot Mini Sleep Tracker
Trade mark	: N/A
Model/Type reference	: B502T
Serial Number	: N/A
Report Number	: EED32P80442202
FCC ID	: 2ADIOB502T
Date of Issue	: Apr. 20, 2023
Test Standards	: 47 CFR Part 1.1307
	: 47 CFR Part 2.1093
Test result	KDB447498D01 General RF
	Exposure Guidance v06
	: PASS

Prepared for:

Shenzhen Medica Technology Development Co., Ltd
Floor 12,Block A,Building 7, Vanke Yun city,XingKe
one street, NanShan District,Shenzhen City

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

mark.chen.

Mark Chen

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Apr. 20, 2023

Check No.: 8438211222



1 Version

Version No.	Date	Description
00	Apr. 20, 2023	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
3.4 TEST LOCATION	4
3.5 DEVIATION FROM STANDARDS	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
4 SAR EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Standard Requirement</i>	6
4.1.2 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	Shenzhen Medica Technology Development Co., Ltd
Address of Applicant:	Floor 12,Block A,Building 7, Vanke Yun city,XingKe one street,NanShan District,Shenzhen City
Manufacturer:	Shenzhen Medica Technology Development Co., Ltd
Address of Manufacturer:	Floor 12,Block A,Building 7, Vanke Yun city,XingKe one street,NanShan District,Shenzhen City
Factory:	Shenzhen Medica Technology Development Co., Ltd
Address of Factory:	Floor 12,Block A,Building 7, Vanke Yun city,XingKe one street,NanShan District,Shenzhen City

3.2 General Description of EUT

Product Name:	Sleep Dot Mini Sleep Tracker
Model No.(EUT):	B502T
Trade mark:	N/A
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Power Supply:	Battery DC 3.0V
Test Voltage:	DC 3.0V
Sample Received Date:	Mar. 31, 2023
Sample tested Date:	Mar. 31, 2023 to Apr. 10, 2023
Remark:	Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	<input checked="" type="checkbox"/> 1Mbps
Number of Channel:	40
Antenna Type:	Ceramic Antenna
Antenna Gain:	2.5 dBi

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.2 EUT RF Exposure

1) For BLE

Measurement Data:

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.79	-1±1	0	1
Middle(2440MHz)	-1.41	-1±1	0	1
Highest(2480MHz)	-0.95	-1±1	0	1

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-1.79	-1±1	0	1	0.315	3.0
Middle (2440MHz)	-1.41	-1±1	0	1	0.315	
Highest (2480MHz)	-0.95	-1±1	0	1	0.315	

Conclusion: the calculated value ≤ 3.0 , SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32P80442201.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***