

**FCC ID:2ADK3-OT427**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:1M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3.292	0.47	-3±1	-2.00	0.63	<5	0.19558	3.00	YES
	2.44	-3.922	0.41	-3±1	-2.00	0.63	<5	0.19712	3.00	YES
	2.480	-4.997	0.32	-4±1	-3.00	0.50	<5	0.15785	3.00	YES

2M

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3.3	0.47	-3±1	-2.00	0.63	<5	0.19558	3.00	YES
	2.44	-3.884	0.41	-3±1	-2.00	0.63	<5	0.19712	3.00	YES
	2.480	-5.039	0.31	-5±1	-4.00	0.40	<5	0.12539	3.00	YES

**Conclusion:**

For the max result :  $0.19712 \leq \text{FCC Limit } 3.0$  for 1g SAR.