

FCC ID: 2ADK3XY-AU048

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculatio n | SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|---------------------|-------------------------|--------------------|
| GFSK | 2.402 | -1.582 | 0.69 | -1±1 | 0.00 | 1.00 | <5 | 0.30997 | 3.00 | YES |
| | 2.441 | -1.632 | 0.69 | -1±1 | 0.00 | 1.00 | <5 | 0.31247 | 3.00 | YES |
| | 2.480 | -1.351 | 0.73 | -1±1 | 0.00 | 1.00 | <5 | 0.31496 | 3.00 | YES |
| π /4DQPSK | 2.402 | -1.437 | 0.72 | -1±1 | 0.00 | 1.00 | <5 | 0.30997 | 3.00 | YES |
| | 2.441 | -1.415 | 0.72 | -1±1 | 0.00 | 1.00 | <5 | 0.31247 | 3.00 | YES |
| | 2.480 | -1.139 | 0.77 | -1±1 | 0.00 | 1.00 | <5 | 0.31496 | 3.00 | YES |

Conclusion:

For the max result : $0.31496 \leq$ FCC Limit 3.0 for 1g SAR.