

WARNER BROS. HOME ENTERTAINMENT INC.

Application
For
Certification

FCC ID: 2ADL5-3000061480

ZEUS XBOX 360 PORTAL

Model: 3000061480

Class B Personal Computer Peripherals

Report No.: SZHH00944908-002

Prepared and Checked by:

Approved by:

Sign on file

Jimmy Wen
Senior Engineer

Andy Yan
Senior Project Engineer
Date: April 24, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_PC_b

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labeling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT / TECHNICAL REPORT

WARNER BROS. HOME ENTERTAINMENT INC.

MODEL: 3000061480

FCC ID: 2ADL5-3000061480

This report concerns (check one:) Original Grant Class II Change

Equipment Type: JBP-Part 15 Class B Computing Device/Peripherals

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart B for unintentional radiator – the new 47 CFR [10-01-13 Edition] provision.

Report prepared by:

Jimmy Wen
Intertek Test Services Shenzhen Ltd.
Kejiyuan Branch
6F, D Block, Huahan Building, Langshan Road
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0713
Fax: (86 755) 8614 6751

TRF No.: FCC 15C_PC_b
FCC ID: 2ADL5-3000061480
Report No.: SZHH00944908-002

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	2
1.1	Product Description.....	2
1.2	Related Submittal(s) Grants.....	2
1.3	Test Methodology.....	2
1.4	Test Facility.....	2
2.0	<u>System Test Configuration</u>	4
2.1	Justification.....	4
2.2	EUT Exercising Software.....	4
2.3	Special Accessories.....	4
2.4	Equipment Modification.....	4
2.5	Measurement Uncertainty.....	5
2.6	Support Equipment List and Description.....	5
3.0	<u>Emission Results</u>	7
3.1	Field Strength Calculation.....	8
3.2	Radiated Emission Configuration Photograph.....	9
3.3	Radiated Emission Data.....	9
3.4	Conducted Emission Configuration Photograph.....	11
3.5	Conducted Emission Data.....	11
4.0	<u>Equipment Photographs</u>	15
5.0	<u>Product Labelling</u>	17
6.0	<u>Technical Specifications</u>	19
7.0	<u>Instruction Manual</u>	21
8.0	<u>Miscellaneous Information</u>	23
8.1	Emissions Test Procedures.....	23
9.0	<u>Confidentiality Request</u>	26
10.0	<u>Test Equipment List</u>	28

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a transceiver for a ZEUS XBOX 360 PORTAL model: 3000061480 operating at 13.56 MHz. The EUT is powered by DC 5.0V with power by USB host Unit. Data can be transferred through USB port between the personal computers and the EUT. For more detailed features description, please refer to the user's manual.

1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripherals.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Test Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

INTERTEK TESTING SERVICES

EXHIBIT 2

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for Test in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by DC 5.0V USB Port through the notebook (the notebook was powered through AC 120V/60Hz) during test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for Test in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the Senior Engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 1GHz (EUT highest frequency is less than 1GHz, so according to 15.33, the test range is update to 1GHz) was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted Test was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified Test.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to Test by WARNER BROS. HOME ENTERTAINMENT INC. Will be incorporated in each production model sold / leased in the United States.

INTERTEK TESTING SERVICES

No modifications were installed by Intertek Test Services Shenzhen Ltd. Kejiyuan Branch.

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	Lenovo	T420
Hard Disk	Smart.drive	HD-003
1394 Cable	Smart.drive	Unshielded, Length 180cm
USB Cable	Smart.drive	Unshielded, Length 120cm

INTERTEK TESTING SERVICES

EXHIBIT 3

EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0dB μ V is obtained. The antenna factor of 7.4dB and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0\text{dB}\mu\text{V}$$

$$AF = 7.4\text{dB}$$

$$CF = 1.6\text{dB}$$

$$AG = 29.0\text{dB}$$

$$PD = 0\text{dB}$$

$$AV = -10\text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32\text{dB}\mu\text{V/m})/20] = 39.8\mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
At
40.67MHz (Data transfer Mode)

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 5.8dB margin (Data transfer Mode)

TEST PERSONNEL:

Sign on file

Jimmy Wen Senior Engineer
Typed/Printed Name

April 11, 2015
Date

INTERTEK TESTING SERVICES

Applicant: WARNER BROS. HOME ENTERTAINMENT INC.

Model: 3000061480

Worst case operating Mode: Data transfer and transmitting

Radiated Emissions (30MHz~1GHz)

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	54.240	30.8	20.0	16.8	27.6	40.0	-12.4
Horizontal	121.665	29.0	20.0	20.8	29.8	43.5	-13.7
Horizontal	242.430	34.9	20.0	22.7	37.6	46.0	-8.4
Vertical	40.670	37.4	20.0	16.8	34.2	40.0	-5.8
Vertical	94.990	25.5	20.0	20.8	26.3	43.5	-17.2
Vertical	110.025	24.8	20.0	22.7	27.5	43.5	-16.0

NOTES:

1. Quasi-Peak detector is used for frequency up to 1GHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

3.4 Conducted Emission Configuration Photograph

Worst Case Conducted Configuration
at
13.562 MHz (Data transfer Mode)

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.5 Conducted Emission Data

Judgement: Passed by 7.1 dB margin (Data transfer Mode)

TEST PERSONNEL:

Sign on file


Jimmy Wen Senior Engineer
Typed/Printed Name

April 11, 2015
Date

INTERTEK TESTING SERVICES

Applicant: WARNER BROS. HOME ENTERTAINMENT INC.
 Model: 3000061480
 Worst case operating Mode: Data transfer and transmitting
 Line: Live

Conducted Emission Test – FCC Pursuant to 15.107 Emissions Requirement



Result Table QP

Frequency (MHz)	QuasiPeak (dB µV)	Line	Margin (dB)	Limit (dB µV)
0.166000	38.1	L1	27.1	65.2
0.222000	39.2	L1	23.5	62.7
0.382000	40.1	L1	18.1	58.2
0.650000	42.1	L1	13.9	56.0
0.782000	35.9	L1	20.1	56.0
13.562000	43.6	L1	16.4	60.0

Result Table AV


Frequency (MHz)	Average (dB µV)	Line	Margin (dB)	Limit (dB µV)
0.166000	32.0	L1	23.2	55.2
0.222000	32.4	L1	20.3	52.7
0.382000	34.4	L1	13.8	48.2
0.650000	28.8	L1	17.2	46.0
0.782000	24.3	L1	21.7	46.0
13.562000	42.1	L1	7.9	50.0

TRF No.: FCC 15C_PC_b
 FCC ID: 2ADL5-3000061480
 Report No.: SZHH00944908-002

INTERTEK TESTING SERVICES

Applicant: WARNER BROS. HOME ENTERTAINMENT INC.
 Model: 3000061480
 Worst case operating Mode: Data transfer and transmitting
 Line: Neutral

Conducted Emission Test – FCC Pursuant to 15.107 Emissions Requirement



Result Table QP

Frequency (MHz)	QuasiPeak (dB µ V)	Line	Margin (dB)	Limit (dB µ V)
0.154000	39.8	N	26.0	65.8
0.270000	40.0	N	21.1	61.1
0.382000	40.7	N	17.5	58.2
0.650000	43.9	N	12.1	56.0
0.778000	38.8	N	17.2	56.0
13.562000	44.4	N	15.6	60.0

Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Margin (dB)	Limit (dB µ V)
0.154000	33.6	N	22.2	55.8
0.270000	33.1	N	18.0	51.1
0.382000	35.1	N	13.1	48.2
0.650000	30.4	N	15.6	46.0
0.778000	27.9	N	18.1	46.0
13.562000	42.9	N	7.1	50.0

TRF No.: FCC 15C_PC_b
 FCC ID: 2ADL5-3000061480
 Report No.: SZHH00944908-002

INTERTEK TESTING SERVICES

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 7
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 Miscellaneous Information

This miscellaneous information includes emission measuring procedure.

8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Test Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The computer equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the Test to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

INTERTEK TESTING SERVICES

8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 - 2009.

INTERTEK TESTING SERVICES

EXHIBIT 9

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 10
TEST EQUIPMENT LIST

INTERTEK TESTING SERVICES

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-2014	28-Jun-2015
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-May-2014	10-May-2015
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	19-Apr-2014	19-Apr-2015
SZ062-02	RF Cable	RADIALL	RG 213U	--	03-Jan-2015	03-Jan-2016
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	29-Oct-2014	29-Apr-2015
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	29-Oct-2014	29-Apr-2015
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	01-Nov-2014	01-Nov-2015
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	01-Nov-2014	01-Nov-2015
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	16-Jun-2014	16-Jun-2015
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-2014	23-Aug-2015