



RF Test Report

For



Applicant Name: Xwireless LLC
Address: 11565 Old Georgetown Road, Rockville, MD, USA
EUT Name: Mobile Phone
Brand Name: Vortex
Model Number: HD55

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park,
Tantou Community, Songgang Street, Bao'an District, Shenzhen,
China

Report Number: BTF240105R00404
Test Standards: 47 CFR Part 15E

Test Conclusion: Pass
FCC ID: 2ADLJ-HD55
Test Date: 2024-01-06 to 2024-01-24
Date of Issue: 2024-01-26

Prepared By: 
Chris Liu / Project Engineer
Date: 2024-01-26
Approved By: 
Ryan.CJ / EMC Manager
Date: 2024-01-26



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.



Revision History		
Version	Issue Date	Revisions Content
R_V0	2024-01-26	Original
<i>Note: Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1	INTRODUCTION	5
1.1	Identification of Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Announcement	5
2	PRODUCT INFORMATION.....	6
2.1	Application Information	6
2.2	Manufacturer Information.....	6
2.3	Factory Information	6
2.4	General Description of Equipment under Test (EUT)	6
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards.....	7
3.2	Uncertainty of Test	7
3.3	Summary of Test Result	7
4	TEST CONFIGURATION	8
4.1	Test Equipment List	8
4.2	Test Auxiliary Equipment	14
4.3	Test Modes	14
5	EVALUATION RESULTS (EVALUATION).....	15
5.1	Antenna requirement	15
6	RADIO SPECTRUM MATTER TEST RESULTS (RF).....	15
6.1	Conducted Emission at AC power line	15
6.1.1	E.U.T. Operation:	15
6.1.2	Test Setup Diagram:	15
6.1.3	Test Data:	16
6.2	Duty Cycle.....	18
6.2.1	E.U.T. Operation:	18
6.2.2	Test Data:	18
6.3	Maximum conducted output power.....	19
6.3.1	E.U.T. Operation:	20
6.3.2	Test Data:	20
6.4	Power spectral density	21
6.4.1	E.U.T. Operation:	22
6.4.2	Test Data:	22
6.5	Emission bandwidth and occupied bandwidth.....	23
6.5.1	E.U.T. Operation:	24
6.5.2	Test Data:	24
6.6	Band edge emissions (Radiated)	25
6.6.1	E.U.T. Operation:	26
6.6.2	Test Setup Diagram:	27
6.6.3	Test Data:	28
6.7	Undesirable emission limits (below 1GHz).....	32
6.7.1	E.U.T. Operation:	33
6.7.2	Test Setup Diagram:	34
6.7.3	Test Data:	35
6.8	Undesirable emission limits (above 1GHz)	37
6.8.1	E.U.T. Operation:	38



6.8.2 Test Data:39

7 TEST SETUP PHOTOS43

8 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)45

APPENDIX46

1 Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130
FCC Registration Number:	518915
Designation Number:	CN1330

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 Product Information

2.1 Application Information

Company Name:	Xwireless LLC
Address:	11565 Old Georgetown Road, Rockville, MD, USA

2.2 Manufacturer Information

Company Name:	Xwireless LLC
Address:	11565 Old Georgetown Road, Rockville, MD, USA

2.3 Factory Information

Company Name:	ZTECH COMMUNICATION(SZ) CO LTD
Address:	FL 7 BLOCK D BAO'AN ZHIGU INNOVATION PARK YIN'TIAN ROAD NO.4 XI'XIANG STR' BAO'AN DISTRICT SZ CHINA

2.4 General Description of Equipment under Test (EUT)

EUT Name:	Mobile Phone
Test Model Number:	HD55
Hardware Version:	N/A
Software Version:	N/A

2.5 Technical Information

Power Supply:	DC 3.8V form battery
Power Adaptor:	Input:100-240V 50/60Hz 0.15A Output:5.0V=1.0A
Operation Frequency Range	U-NII Band 1: 5.18~5.24 GHz U-NII Band 3: 5.745~5.825 GHz
Frequency Block	U-NII Band 1: 5.15~5.25 GHz U-NII Band 3: 5.725~5.85 GHz
Channel Bandwidth	802.11a: 20 MHz 802.11n: 20 MHz, 40 MHz 802.11ac: 20 MHz, 40 MHz, 80 MHz
Antenna Type:	FPC Antenna
Antenna Gain:	1.36dBi

Note:

#: The antenna gain provided by the applicant, and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

3.2 Uncertainty of Test

Item	Measurement Uncertainty
Conducted Emission (150 kHz-30 MHz)	±2.64dB
Occupied Bandwidth	±69kHz
Transmitter Power, Conducted	±0.87dB
Power Spectral Density	±0.69dB
Conducted Spurious Emissions	±0.95dB
Radiated Spurious Emissions (above 1GHz)	1-6GHz: ±3.94dB 6-18GHz: ±4.16dB
Radiated Spurious Emissions (30M - 1GHz)	±4.12dB
The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15E	Part 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15E	47 CFR Part 15.207(a)	Pass
Maximum conducted output power	47 CFR Part 15E	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(2) 47 CFR Part 15.407(a)(3)(i)	Pass
Power spectral density	47 CFR Part 15E	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(2) 47 CFR Part 15.407(a)(3)(i)	Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. 47 CFR Part 15.407(e)	Pass
Channel Availability Check Time	47 CFR Part 15E	47 CFR Part 15.407(h)(2)(ii)	Pass
U-NII Detection Bandwidth	47 CFR Part 15E	47 CFR Part 15.407(h)(2)	Pass
Statistical Performance Check	47 CFR Part 15E	KDB 935210 D02, Clause 5.1 Table 2	Pass
Channel Move Time, Channel Closing Transmission Time	47 CFR Part 15E	47 CFR Part 15.407(h)(2)(iii)	Pass
Non-Occupancy Period Test	47 CFR Part 15E	47 CFR Part 15.407(h)(2)(iv)	Pass
DFS Detection Thresholds	47 CFR Part 15E	KDB 905462 D02, Clause 5.2 Table 3	Pass
Band edge emissions (Radiated)	47 CFR Part 15E	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(2) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass

Undesirable emission limits (below 1GHz)	47 CFR Part 15E	47 CFR Part 15.407(b)(9)	Pass
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(2) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass

4 Test Configuration

4.1 Test Equipment List

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	00953	2023-11-16	2024-11-15
Coaxial Switcher	SCHWARZBECK	CX210	CX210	2023-11-16	2024-11-15
V-LISN	SCHWARZBECK	NSLK 8127	01073	2023-11-16	2024-11-15
LISN	AFJ	LS16/110VAC	16010020076	2023-02-23	2024-02-22
EMI Receiver	ROHDE&SCHWARZ	ESCI3	101422	2023-11-16	2024-11-15

Duty Cycle					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Maximum conducted output power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15

TESTER					
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Power spectral density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Emission bandwidth and occupied bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Channel Availability Check Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct	Dongguan	etm-6050c	20211026123	2023-11-16	2024-11-15

Current Regulated Power Supply	Tongmen Electronic Technology Co., LTD				
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

U-NII Detection Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Statistical Performance Check					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Channel Move Time, Channel Closing Transmission Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15

and humidity box					
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Non-Occupancy Period Test

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

DFS Detection Thresholds

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2023-11-16	2024-11-15
RF Sensor Unit	Techy	TR1029-2	/	2023-11-16	2024-11-15
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2023-11-16	2024-11-15
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2023-11-16	2024-11-15
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2023-11-16	2024-11-15
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2023-11-16	2024-11-15

Band edge emissions (Radiated)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2023-11-16	2023-11-23

RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	2024-11-15
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2023-11-16	2024-11-15
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2023-11-16	2024-11-15
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamp	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2023-11-16	2024-11-15

Undesirable emission limits (below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamp	SCHWARZBECK	BBV9744	00246	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2023-11-16	2024-11-15
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2023-11-16	2024-11-15
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamp	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/

Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2024-11-15
----------------------	-------------	-----------	-------	------------	------------

Undesirable emission limits (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2023-11-16	2024-11-15
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2023-11-16	2024-11-15
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2023-11-16	2024-11-15
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2023-11-16	2024-11-15
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2023-11-16	2024-11-15

4.2 Test Auxiliary Equipment

The EUT was tested as an independent device.

4.3 Test Modes

No.	Test Modes	Description
TM1	802.11a mode	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11a modulation type. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report.
TM2	802.11n mode	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11n modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.
TM3	802.11ac mode	Keep the EUT connect to AC power line and works in continuously transmitting mode with 802.11ac modulation type. Only the data of worst case is recorded in the report.
TM4	Normal Operating	Keep the EUT works in normal operating mode and connect to companion device

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	47 CFR Part 15.207(a)		
Test Method:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		

6.1.1 E.U.T. Operation:


Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.1.2 Test Setup Diagram:



6.1.3 Test Data:


TM1 / Line: Line / Band 1/Mode:802.11a/CH:M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1725	38.83	10.50	49.33	64.84	-15.51	QP	P	
2	0.1725	17.20	10.50	27.70	54.84	-27.14	AVG	P	
3	0.4065	33.68	10.57	44.25	57.72	-13.47	QP	P	
4	0.4065	15.93	10.57	26.50	47.72	-21.22	AVG	P	
5	1.5000	17.80	10.66	28.46	46.00	-17.54	AVG	P	
6 *	1.5225	36.93	10.66	47.59	56.00	-8.41	QP	P	
7	3.7095	34.85	10.65	45.50	56.00	-10.50	QP	P	
8	3.7095	18.94	10.65	29.59	46.00	-16.41	AVG	P	
9	6.4410	29.96	10.78	40.74	60.00	-19.26	QP	P	
10	6.4545	11.44	10.78	22.22	50.00	-27.78	AVG	P	
11	27.8070	28.97	11.22	40.19	60.00	-19.81	QP	P	
12	27.8070	12.51	11.22	23.73	50.00	-26.27	AVG	P	

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

TM1 / Line: Neutral / Band 1/Mode:802.11a/CH:M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	38.32	10.48	48.80	65.28	-16.48	QP	P	
2	0.1680	21.14	10.49	31.63	55.06	-23.43	AVG	P	
3	0.5055	35.01	10.58	45.59	56.00	-10.41	QP	P	
4	0.5055	16.59	10.58	27.17	46.00	-18.83	AVG	P	
5	1.8600	21.15	10.67	31.82	46.00	-14.18	AVG	P	
6	1.8690	34.33	10.67	45.00	56.00	-11.00	QP	P	
7	3.4395	18.53	10.64	29.17	46.00	-16.83	AVG	P	
8 *	3.5565	38.39	10.64	49.03	56.00	-6.97	QP	P	
9	6.3239	12.24	10.78	23.02	50.00	-26.98	AVG	P	
10	6.3735	34.33	10.78	45.11	60.00	-14.89	QP	P	
11	12.7545	26.32	10.83	37.15	60.00	-22.85	QP	P	
12	12.7905	6.16	10.83	16.99	50.00	-33.01	AVG	P	

N Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

6.2 Duty Cycle

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.
Test Method:	ANSI C63.10-2013 section 12.2 (b)
Test Limit:	No limits, only for report use.
Procedure:	<ul style="list-style-type: none"> i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW \geq EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW \geq RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

6.2.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.2.2 Test Data:

Please Refer to Appendix for Details.

6.3 Maximum conducted output power

<p>Test Requirement:</p>	<p>47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(2) 47 CFR Part 15.407(a)(3)(i)</p>
<p>Test Method:</p>	<p>ANSI C63.10-2013, section 12.3</p>
<p>Test Limit:</p>	<p>For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).</p> <p>For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.</p> <p>For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>

	<p>For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.</p>
<p>Procedure:</p>	<p>Method SA-1 a) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal. b) Set RBW = 1 MHz. c) Set VBW >= 3 MHz. d) Number of points in sweep >= [2 × span / RBW]. (This gives bin-to-bin spacing <= RBW / 2, so that narrowband signals are not lost between frequency bins.) e) Sweep time = auto. f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. g) If transmit duty cycle < 98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle >= 98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.” h) Trace average at least 100 traces in power averaging (rms) mode. i) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.</p>

6.3.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.3.2 Test Data:

Please Refer to Appendix for Details.

6.4 Power spectral density

<p>Test Requirement:</p>	<p>47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(1)(ii) 47 CFR Part 15.407(a)(1)(iii) 47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(2) 47 CFR Part 15.407(a)(3)(i)</p>
<p>Test Method:</p>	<p>ANSI C63.10-2013, section 12.5</p>
<p>Test Limit:</p>	<p>For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.</p> <p>For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter</p>

	<p>conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.</p>
<p>Procedure:</p>	<p>a) Create an average power spectrum for the EUT operating mode being tested by following the instructions in 12.3.2 for measuring maximum conducted output power using a spectrum analyzer or EMI receiver; that is, select the appropriate test method (SA-1, SA-2, SA-3, or their respective alternatives) and apply it up to, but not including, the step labeled, "Compute power...." (This procedure is required even if the maximum conducted output power measurement was performed using the power meter method PM.) b) Use the peak search function on the instrument to find the peak of the spectrum. c) Make the following adjustments to the peak value of the spectrum, if applicable: 1) If method SA-2 or SA-2A was used, then add $[10 \log (1 / D)]$, where D is the duty cycle, to the peak of the spectrum. 2) If method SA-3A was used and the linear mode was used in step h) of 12.3.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. d) The result is the PPSD. e) The procedure in item a) through item c) requires the use of 1 MHz resolution bandwidth to satisfy the 1 MHz measurement bandwidth specified by some regulatory authorities. This requirement also permits use of resolution bandwidths less than 1 MHz "provided that the measured power is integrated to show the total power over the measurement bandwidth" (i.e., 1 MHz). If measurements are performed using a reduced resolution bandwidth and integrated over 1 MHz bandwidth, the following adjustments to the procedures apply: 1) Set $RBW \geq 1 / T$, where T is defined in 12.2 a). 2) Set $VBW \geq [3 \times RBW]$. 3) Care shall be taken such that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.</p>

6.4.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.4.2 Test Data:

Please Refer to Appendix for Details.

6.5 Emission bandwidth and occupied bandwidth

Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: 47 CFR Part 15.407(e)
Test Method:	ANSI C63.10-2013, section 6.9.3 & 12.4 KDB 789033 D02, Clause C.2
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Procedure:	<p>Emission bandwidth:</p> <ul style="list-style-type: none"> a) Set RBW = approximately 1% of the emission bandwidth. b) Set the VBW > RBW. c) Detector = peak. d) Trace mode = max hold. e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. <p>Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.</p> <p>Occupied bandwidth:</p> <ul style="list-style-type: none"> a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99%

	<p>power bandwidth is the difference between these two frequencies.</p> <p>h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p> <p>6 dB emission bandwidth:</p> <p>a) Set RBW = 100 kHz.</p> <p>b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.</p> <p>c) Detector = Peak.</p> <p>d) Trace mode = max hold.</p> <p>e) Sweep = auto couple.</p> <p>f) Allow the trace to stabilize.</p> <p>g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</p>
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.5.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.5.2 Test Data:

Please Refer to Appendix for Details.

6.6 Band edge emissions (Radiated)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(2) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																				
Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6																																																																																				
Test Limit:	<p>For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.</p> <table border="1" data-bbox="470 913 1348 1556"> <thead> <tr> <th>MHz</th> <th>MHz</th> <th>MHz</th> <th>GHz</th> </tr> </thead> <tbody> <tr> <td>0.090-0.110</td> <td>16.42-16.423</td> <td>399.9-410</td> <td>4.5-5.15</td> </tr> <tr> <td>¹0.495-0.505</td> <td>16.69475-16.69525</td> <td>608-614</td> <td>5.35-5.46</td> </tr> <tr> <td>2.1735-2.1905</td> <td>16.80425-16.80475</td> <td>960-1240</td> <td>7.25-7.75</td> </tr> <tr> <td>4.125-4.128</td> <td>25.5-25.67</td> <td>1300-1427</td> <td>8.025-8.5</td> </tr> <tr> <td>4.17725-4.17775</td> <td>37.5-38.25</td> <td>1435-1626.5</td> <td>9.0-9.2</td> </tr> <tr> <td>4.20725-4.20775</td> <td>73-74.6</td> <td>1645.5-1646.</td> <td>9.3-9.5</td> </tr> <tr> <td></td> <td></td> <td>5</td> <td></td> </tr> <tr> <td>6.215-6.218</td> <td>74.8-75.2</td> <td>1660-1710</td> <td>10.6-12.7</td> </tr> <tr> <td>6.26775-6.26825</td> <td>108-121.94</td> <td>1718.8-1722.</td> <td>13.25-13.4</td> </tr> <tr> <td></td> <td></td> <td>2</td> <td></td> </tr> <tr> <td>6.31175-6.31225</td> <td>123-138</td> <td>2200-2300</td> <td>14.47-14.5</td> </tr> <tr> <td>8.291-8.294</td> <td>149.9-150.05</td> <td>2310-2390</td> <td>15.35-16.2</td> </tr> <tr> <td>8.362-8.366</td> <td>156.52475-156.525</td> <td>2483.5-2500</td> <td>17.7-21.4</td> </tr> <tr> <td></td> <td>25</td> <td></td> <td></td> </tr> <tr> <td>8.37625-8.38675</td> <td>156.7-156.9</td> <td>2690-2900</td> <td>22.01-23.12</td> </tr> <tr> <td>8.41425-8.41475</td> <td>162.0125-167.17</td> <td>3260-3267</td> <td>23.6-24.0</td> </tr> <tr> <td>12.29-12.293</td> <td>167.72-173.2</td> <td>3332-3339</td> <td>31.2-31.8</td> </tr> <tr> <td>12.51975-12.52025</td> <td>240-285</td> <td>3345.8-3358</td> <td>36.43-36.5</td> </tr> <tr> <td>12.57675-12.57725</td> <td>322-335.4</td> <td>3600-4400</td> <td>(²)</td> </tr> <tr> <td>13.36-13.41</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.</p> <p>²Above 38.6</p> <p>The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.</p> <p>Except as provided elsewhere in this subpart, the emissions from an intentional</p>	MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.	9.3-9.5			5		6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.	13.25-13.4			2		6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.525	2483.5-2500	17.7-21.4		25			8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41			
MHz	MHz	MHz	GHz																																																																																		
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																		
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																		
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																		
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																		
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																		
4.20725-4.20775	73-74.6	1645.5-1646.	9.3-9.5																																																																																		
		5																																																																																			
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																		
6.26775-6.26825	108-121.94	1718.8-1722.	13.25-13.4																																																																																		
		2																																																																																			
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																		
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																		
8.362-8.366	156.52475-156.525	2483.5-2500	17.7-21.4																																																																																		
	25																																																																																				
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																		
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																		
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																		
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																		
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																		
13.36-13.41																																																																																					


	<p>radiator shall not exceed the field strength levels specified in the following table:</p> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Field strength (microvolts/meter)</th> <th>Measurement distance (meters)</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(kHz)</td> <td>300</td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(kHz)</td> <td>30</td> </tr> <tr> <td>1.705-30.0</td> <td>30</td> <td>30</td> </tr> <tr> <td>30-88</td> <td>100 **</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150 **</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200 **</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> </tr> </tbody> </table>	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
<p>Procedure:</p>	<p>Above 1GHz:</p> <ol style="list-style-type: none"> For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. Test the EUT in the lowest channel, the middle channel, the Highest channel. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. Repeat above procedures until all frequencies measured was complete. <p>Remark:</p> <ol style="list-style-type: none"> Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. 																								

6.6.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %

Atmospheric Pressure:	1010 mbar
-----------------------	-----------

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

UNII-1 802.11a_5180MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5096.675	42.32	5.28	47.60	68.2	-20.6	peak	P
2	5150.000	43.26	5.33	48.59	68.2	-19.61	peak	P

UNII-1 802.11a_5180MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5085.155	40.95	5.28	46.23	68.2	-21.97	peak	P
2	5150.000	43.62	5.33	48.95	68.2	-19.25	peak	P

UNII-1 802.11a_5240MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.000	42.29	5.45	47.74	68.2	-20.46	peak	P
2	5460.000	43.65	5.52	49.17	68.2	-19.03	peak	P

UNII-1 802.11a_5240MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.000	42.29	5.45	47.74	68.2	-20.46	peak	P
2	5460.000	44.32	5.52	49.84	68.2	-18.36	peak	P

UNII-3 802.11a_5745MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	47.01	5.63	52.64	68.2	-15.56	peak	P
2	5700	47.79	5.7	50.23	105.2	-54.97	peak	P
3	5720	48.99	5.66	50.06	110.8	-60.74	peak	P

UNII-3 802.11a_5745MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	47.46	5.63	53.09	68.2	-15.11	peak	P
2	5700	48.24	5.7	50.23	105.2	-54.97	peak	P
3	5720	49.44	5.66	50.06	110.8	-60.74	peak	P

UNII-3 802.11a_5825MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5855	54.45	5.73	51.37	110.8	-59.43	peak	P
2	5875	51.34	5.74	57.08	105.2	-48.12	peak	P
3	5925	47.34	5.79	53.13	68.2	-15.07	peak	P

UNII-3 802.11a_5825MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5855	53.79	5.73	51.37	110.8	-59.43	peak	P
2	5875	50.68	5.74	56.42	105.2	-48.78	peak	P
3	5925	46.68	5.79	52.47	68.2	-15.73	peak	P

UNII-1 802.11n(40)_5190MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5060.880	44.51	5.28	49.79	68.2	-18.41	peak	P
2	5150.000	45.45	5.33	50.78	68.2	-17.42	peak	P

UNII-1 802.11n(40)_5190MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5049.360	43.93	5.28	49.21	68.2	-18.99	peak	P
2	5150.000	46.60	5.33	51.93	68.2	-16.27	peak	P

UNII-1 802.11n(40)_5230MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.000	45.48	5.51	50.99	68.2	-17.21	peak	P
2	5460.000	46.84	5.58	52.42	68.2	-15.78	peak	P

UNII-1 802.11n(40)_5230MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.000	45.16	5.51	50.67	68.2	-17.53	peak	P
2	5460.000	47.19	5.58	52.77	68.2	-15.43	peak	P

UNII-3 802.11n(40)_5750MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	45.91	5.63	51.54	68.2	-16.66	peak	P
2	5700	47.54	5.7	50.23	105.2	-54.97	peak	P
3	5720	48.54	5.66	50.06	110.8	-60.74	peak	P

UNII-3 802.11n(40) _5750MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	46.34	5.63	51.97	68.2	-16.23	peak	P
2	5700	47.12	5.7	50.23	105.2	-54.97	peak	P
3	5720	48.32	5.66	50.06	110.8	-60.74	peak	P

UNII-3802.11n(40) _5795MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5855	51.78	5.73	51.37	110.8	-59.43	peak	P
2	5875	49.23	5.74	54.97	105.2	-50.23	peak	P
3	5925	44.56	5.79	50.35	68.2	-17.85	peak	P

UNII-3 802.11n(40) _5795MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5855	53.34	5.73	51.37	110.8	-59.43	peak	P
2	5875	50.23	5.74	55.97	105.2	-49.23	peak	P
3	5925	46.23	5.79	52.02	68.2	-16.18	peak	P

UNII-1 802.11ac(80) _5210MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5071.013	45.75	5.28	51.03	68.2	-17.17	peak	P
2	5150.000	46.69	5.33	52.02	68.2	-16.18	peak	P
3	5350.000	46.27	5.51	51.78	68.2	-16.42	peak	P
4	5460.000	47.63	5.58	53.21	68.2	-14.99	peak	P

UNII-3 802.11ac(80) _5210MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5037.325	44.72	5.28	50.00	68.2	-18.2	peak	P
2	5150.000	47.39	5.33	52.72	68.2	-15.48	peak	P
3	5350.000	45.50	5.51	51.01	68.2	-17.19	peak	P
4	5460.000	47.53	5.58	53.11	68.2	-15.09	peak	P

UNII-3802.11ac(80)_5775MHz_Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	44.07	5.63	49.7	68.2	-24.3	peak	P
2	5700	47.12	5.7	50.23	105.2	-23.77	peak	P
3	5720	49.89	5.66	50.06	110.8	-23.94	peak	P
4	5855	50,21	5.73	51.37	110.8	-22.63	peak	P
5	5875	49.21	5.74	54.95	105.2	-50.25	peak	P
6	5925	46.17	5.79	51.96	68.2	-16.24	peak	P

UNII-3 802.11ac(80)_5820MHz_Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	44.98	5.63	50.61	68.2	-17.59	peak	P
2	5700	48.23	5.7	50.23	105.2	-54.97	peak	P
3	5720	48.02	5.66	50.06	110.8	-60.74	peak	P
4	5855	51,21	5.73	51.37	110.8	-59.43	peak	P
5	5875	49.76	5.74	55.5	105.2	-49.7	peak	P
6	5925	45.24	5.79	51.03	68.2	-17.17	peak	P

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

6.7 Undesirable emission limits (below 1GHz)


Test Requirement:	47 CFR Part 15.407(b)(9)																								
Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6																								
Test Limit:	<p>Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.</p> <p>Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:</p> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Field strength (microvolts/meter)</th> <th>Measurement distance (meters)</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(kHz)</td> <td>300</td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(kHz)</td> <td>30</td> </tr> <tr> <td>1.705-30.0</td> <td>30</td> <td>30</td> </tr> <tr> <td>30-88</td> <td>100 **</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150 **</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200 **</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> </tr> </tbody> </table>	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Procedure:	<p>Below 1GHz:</p> <p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <ol style="list-style-type: none"> Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. <p>Above 1GHz:</p>																								

	<p>a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <ol style="list-style-type: none"> 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.7.1 E.U.T. Operation:


Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.7.2 Test Setup Diagram:



6.7.3 Test Data:


TM1 / Polarization: Horizontal / Band 1/Mode:802.11a/CH:M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	30.5306	35.01	-18.67	16.34	40.00	-23.66	QP	P
2	36.9600	33.58	-18.44	15.14	40.00	-24.86	QP	P
3	141.0822	46.23	-27.86	18.37	43.50	-25.13	QP	P
4	289.5092	44.81	-25.51	19.30	46.00	-26.70	QP	P
5	392.0951	50.27	-24.70	25.57	46.00	-20.43	QP	P
6 *	524.5541	48.45	-21.40	27.05	46.00	-18.95	QP	P

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

TM1 / Polarization: Vertical / Band 1/Mode:802.11a/CH:M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	30.6379	51.37	-19.63	31.74	40.00	-8.26	QP	P
2	35.1278	48.02	-20.63	27.39	40.00	-12.61	QP	P
3	61.2389	44.37	-20.14	24.23	40.00	-15.77	QP	P
4	87.2645	39.30	-16.69	22.61	40.00	-17.39	QP	P
5	166.0680	43.60	-14.28	29.32	43.50	-14.18	QP	P
6	208.9463	44.56	-15.69	28.87	43.50	-14.63	QP	P

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

6.8 Undesirable emission limits (above 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(2) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																							
Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6																																																																																							
Test Limit:	<p>For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.</p> <table border="1"> <thead> <tr> <th>MHz</th> <th>MHz</th> <th>MHz</th> <th>GHz</th> </tr> </thead> <tbody> <tr> <td>0.090-0.110</td> <td>16.42-16.423</td> <td>399.9-410</td> <td>4.5-5.15</td> </tr> <tr> <td>¹0.495-0.505</td> <td>16.69475-16.69525</td> <td>608-614</td> <td>5.35-5.46</td> </tr> <tr> <td>2.1735-2.1905</td> <td>16.80425-16.80475</td> <td>960-1240</td> <td>7.25-7.75</td> </tr> <tr> <td>4.125-4.128</td> <td>25.5-25.67</td> <td>1300-1427</td> <td>8.025-8.5</td> </tr> <tr> <td>4.17725-4.17775</td> <td>37.5-38.25</td> <td>1435-1626.5</td> <td>9.0-9.2</td> </tr> <tr> <td>4.20725-4.20775</td> <td>73-74.6</td> <td>1645.5-1646.</td> <td>9.3-9.5</td> </tr> <tr> <td></td> <td></td> <td>5</td> <td></td> </tr> <tr> <td>6.215-6.218</td> <td>74.8-75.2</td> <td>1660-1710</td> <td>10.6-12.7</td> </tr> <tr> <td>6.26775-6.26825</td> <td>108-121.94</td> <td>1718.8-1722.</td> <td>13.25-13.4</td> </tr> <tr> <td></td> <td></td> <td>2</td> <td></td> </tr> <tr> <td>6.31175-6.31225</td> <td>123-138</td> <td>2200-2300</td> <td>14.47-14.5</td> </tr> <tr> <td>8.291-8.294</td> <td>149.9-150.05</td> <td>2310-2390</td> <td>15.35-16.2</td> </tr> <tr> <td>8.362-8.366</td> <td>156.52475-156.525</td> <td>2483.5-2500</td> <td>17.7-21.4</td> </tr> <tr> <td></td> <td>25</td> <td></td> <td></td> </tr> <tr> <td>8.37625-8.38675</td> <td>156.7-156.9</td> <td>2690-2900</td> <td>22.01-23.12</td> </tr> <tr> <td>8.41425-8.41475</td> <td>162.0125-167.17</td> <td>3260-3267</td> <td>23.6-24.0</td> </tr> <tr> <td>12.29-12.293</td> <td>167.72-173.2</td> <td>3332-3339</td> <td>31.2-31.8</td> </tr> <tr> <td>12.51975-12.52025</td> <td>240-285</td> <td>3345.8-3358</td> <td>36.43-36.5</td> </tr> <tr> <td>12.57675-12.57725</td> <td>322-335.4</td> <td>3600-4400</td> <td>(²)</td> </tr> <tr> <td>13.36-13.41</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ²Above 38.6</p> <p>The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.</p> <p>Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:</p> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Field strength</th> <th>Measurement</th> </tr> </thead> </table>	MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.	9.3-9.5			5		6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.	13.25-13.4			2		6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.525	2483.5-2500	17.7-21.4		25			8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength	Measurement
MHz	MHz	MHz	GHz																																																																																					
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																					
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																					
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																					
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																					
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																					
4.20725-4.20775	73-74.6	1645.5-1646.	9.3-9.5																																																																																					
		5																																																																																						
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																					
6.26775-6.26825	108-121.94	1718.8-1722.	13.25-13.4																																																																																					
		2																																																																																						
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																					
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																					
8.362-8.366	156.52475-156.525	2483.5-2500	17.7-21.4																																																																																					
	25																																																																																							
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																					
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																					
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																					
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																					
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																					
13.36-13.41																																																																																								
Frequency (MHz)	Field strength	Measurement																																																																																						

	(microvolts/meter)	distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

Procedure:	<p>Above 1GHz:</p> <p>a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <p>1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor</p> <p>2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.</p> <p>3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.</p> <p>4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.</p>
------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.8.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.5 °C
Humidity:	50.6 %
Atmospheric Pressure:	1010 mbar

6.8.2 Test Data:

UNII-1_802.11a_5180MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10360.000	80.68	-24.45	56.23	74.00	-17.77	peak	P
2	15540.000	81.89	-21.50	60.39	74.00	-13.61	peak	P

UNII-1_802.11a_5180MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10360.000	81.78	-21.50	60.28	74.00	-13.72	peak	P
2	15540.000	80.77	-24.45	56.32	74.00	-17.68	peak	P

UNII-1_802.11a_5200MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10400.000	80.12	-24.47	55.65	74.00	-18.35	peak	P
2	15600.000	81.33	-21.51	59.82	74.00	-14.18	peak	P

UNII-1_802.11a_5200MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10400.000	80.87	-24.47	56.40	74.00	-17.60	peak	P
2	15600.000	81.10	-21.51	59.59	74.00	-14.41	peak	P

UNII-1_802.11a_5240MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10480.000	79.47	-24.51	54.96	74.00	-19.04	peak	P
2	15720.000	80.68	-21.53	59.15	74.00	-14.85	peak	P

UNII-1_802.11a_5240MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10480.000	80.41	-24.51	55.90	74.00	-18.10	peak	P
2	15720.000	80.64	-21.53	59.11	74.00	-14.89	peak	P

UNII-3_802.11a_5745MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11490.000	81.21	-23.07	58.14	74.00	-15.86	peak	P
2	17235.000	83.23	-17.36	65.87	74.00	-8.13	peak	P

UNII-3_802.11a_5745MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11490.000	80.84	-23.07	57.77	74.00	-16.23	peak	P
2	17235.000	82.69	-17.36	65.33	74.00	-8.67	peak	P

UNII-3_802.11a_5785MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11570.000	80.58	-22.95	57.63	74.00	-16.37	peak	P
2	17355.000	82.60	-16.89	65.71	74.00	-8.29	peak	P

UNII-3_802.11a_5785MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11570.000	79.99	-22.95	57.04	74.00	-16.96	peak	P
2	17355.000	81.84	-16.89	64.95	74.00	-9.05	peak	P

UNII-3_802.11a_5825MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11650.000	81.60	-22.80	58.80	74.00	-15.20	peak	P
2	17475.000	83.62	-16.41	67.21	74.00	-6.79	peak	P

UNII-3_802.11a_5825MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11650.000	81.52	-22.80	58.72	74.00	-15.28	peak	P
2	17475.000	83.37	-16.41	66.96	74.00	-7.04	peak	P

UNII-1_802.11n(40)_5190MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10380.000	81.66	-24.45	57.21	74.00	-16.79	peak	P
2	15570.000	82.87	-21.50	61.37	74.00	-12.63	peak	P

UNII-1_802.11n(40)_5190MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10380.000	81.78	-21.50	60.28	74.00	-13.72	peak	P
2	15570.000	80.77	-24.45	56.32	74.00	-17.68	peak	P

UNII-1_802.11n(40)_5230MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10460.000	80.87	-24.51	56.36	74.00	-17.64	peak	P
2	15690.000	82.08	-21.53	60.55	74.00	-13.45	peak	P

UNII-1_802.11n(40)_5230MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10460.000	80.41	-24.51	55.90	74.00	-18.10	peak	P
2	15690.000	80.64	-21.53	59.11	74.00	-14.89	peak	P

UNII-3_802.11n(40)_5755MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11510.000	80.65	-23.07	57.58	74.00	-16.42	peak	P
2	17265.000	82.67	-17.36	65.31	74.00	-8.69	peak	P

UNII-3_802.11n(40)_5755MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11590.000	79.63	-23.07	56.56	74.00	-17.44	peak	P
2	17385.000	81.48	-17.36	64.12	74.00	-9.88	peak	P

UNII-3_802.11n(40)_5795MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11590.000	80.00	-22.80	57.20	74.00	-16.80	peak	P
2	17385.000	82.02	-16.41	65.61	74.00	-8.39	peak	P

UNII-3_802.11n(40)_5795MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11650.000	81.05	-22.80	58.25	74.00	-15.75	peak	P
2	17475.000	82.90	-16.41	66.49	74.00	-7.51	peak	P

UNII-1_802.11ac(80)_5210MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10420.000	80.49	-24.56	55.93	74.00	-18.07	peak	P
2	15630.000	81.70	-21.61	60.09	74.00	-13.91	peak	P

UNII-1_802.11ac(80)_5210MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10420.000	81.78	-21.50	60.28	74.00	-13.72	peak	P
2	15630.000	80.77	-24.45	56.32	74.00	-17.68	peak	P

UNII-3_802.11ac(80)_5775MHz_Horizontal								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11550.000	80.12	-24.63	55.49	74.00	-18.51	peak	P
2	17325.000	81.33	-21.67	59.66	74.00	-14.34	peak	P

UNII-3_802.11ac(80)_5775MHz_Vertical								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11550.000	81.61	-24.63	56.98	74.00	-17.02	peak	P
2	17325.000	81.84	-21.67	60.17	74.00	-13.83	peak	P

Note: Reading=Receiver reading
 Factor=Antenna factor+Cable loss
 Level=Reading+Factor
 Limit=Limit stated in standard
 Margin=Measurement-Limits

7 Test Setup Photos


Conducted Emission at AC power line



Band edge emissions (Radiated)
Emissions in frequency bands (above 1GHz)



Emissions in frequency bands (below 1GHz)



8 EUT Constructional Details (EUT Photos)

Please refer to the test report No. BTF240105R00401

Appendix


1. Duty Cycle



1.1 Ant1



1.1.1 Test Result

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	1.393	1.563	89.12	0.50	1.58
		5200	1.393	1.563	89.12	0.50	1.58
		5240	1.393	1.563	89.12	0.50	1.58
		5745	1.392	1.564	89.00	0.51	1.67
		5785	1.393	1.545	90.16	0.45	0.53
		5825	1.394	1.788	77.96	1.08	12.75
802.11n (HT20)	SISO	5180	1.174	1.345	87.29	0.59	1.78
		5200	1.174	1.344	87.35	0.59	1.79
		5240	1.174	1.345	87.29	0.59	1.81
		5745	1.174	1.345	87.29	0.59	1.76
		5785	1.174	1.345	87.29	0.59	1.82
		5825	1.174	1.345	87.29	0.59	1.81
802.11n (HT40)	SISO	5190	0.587	0.739	79.43	1.00	1.02
		5230	0.587	0.739	79.43	1.00	0.99
		5755	0.587	0.739	79.43	1.00	1.00
		5795	0.588	0.739	79.57	0.99	0.99
802.11ac (VHT20)	SISO	5180	1.186	1.356	87.46	0.58	1.78
		5200	1.186	1.356	87.46	0.58	1.82
		5240	1.186	1.356	87.46	0.58	1.82
		5745	1.186	1.356	87.46	0.58	1.75
		5785	1.186	1.356	87.46	0.58	1.78
		5825	1.185	1.356	87.39	0.59	1.82
802.11ac (VHT40)	SISO	5190	0.591	0.761	77.66	1.10	2.90
		5230	0.592	0.761	77.79	1.09	2.86
		5755	0.592	0.743	79.68	0.99	0.99
		5795	0.591	0.761	77.66	1.10	2.86
802.11ac (VHT80)	SISO	5210	0.296	0.466	63.52	1.97	3.92
		5775	0.302	0.466	64.81	1.88	4.04


1.1.2 Test Graph









802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5745MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5210MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5775MHz_Ant1_NTNV




2. Bandwidth



2.1 OBW



2.1.1 Test Result



Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11a	SISO	5180	1	19.451	/	Pass
		5200	1	19.139	/	Pass
		5240	1	19.064	/	Pass
		5745	1	23.739	/	Pass
		5785	1	22.383	/	Pass
		5825	1	20.823	/	Pass
802.11n (HT20)	SISO	5180	1	19.199	/	Pass
		5200	1	19.447	/	Pass
		5240	1	19.365	/	Pass
		5745	1	23.367	/	Pass
		5785	1	22.107	/	Pass
		5825	1	21.213	/	Pass
802.11n (HT40)	SISO	5190	1	37.414	/	Pass
		5230	1	37.595	/	Pass
		5755	1	42.830	/	Pass
		5795	1	40.127	/	Pass
802.11ac (VHT20)	SISO	5180	1	19.079	/	Pass
		5200	1	18.916	/	Pass
		5240	1	18.892	/	Pass
		5745	1	22.978	/	Pass
		5785	1	22.321	/	Pass
		5825	1	21.064	/	Pass
802.11ac (VHT40)	SISO	5190	1	38.229	/	Pass
		5230	1	38.490	/	Pass
		5755	1	41.977	/	Pass
		5795	1	42.396	/	Pass
802.11ac (VHT80)	SISO	5210	1	77.707	/	Pass
		5775	1	80.451	/	Pass

2.1.2 Test Graph












802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5745MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5210MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5775MHz_Ant1_NTNV






2.2 6dB BW

2.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11a	SISO	5745	1	16.397	>=0.5	Pass
		5785	1	16.379	>=0.5	Pass
		5825	1	16.380	>=0.5	Pass
802.11n (HT20)	SISO	5745	1	17.206	>=0.5	Pass
		5785	1	17.248	>=0.5	Pass
		5825	1	17.311	>=0.5	Pass
802.11n (HT40)	SISO	5755	1	35.742	>=0.5	Pass
		5795	1	35.651	>=0.5	Pass
802.11ac (VHT20)	SISO	5745	1	17.235	>=0.5	Pass
		5785	1	17.248	>=0.5	Pass
		5825	1	17.255	>=0.5	Pass
802.11ac (VHT40)	SISO	5755	1	35.654	>=0.5	Pass
		5795	1	35.550	>=0.5	Pass
802.11ac (VHT80)	SISO	5775	1	75.555	>=0.5	Pass

2.2.2 Test Graph







802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5745MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV



802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5775MHz_Ant1_NTNV






2.3 26dB BW

2.3.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	26dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11a	SISO	5180	1	32.262	/	Pass
		5200	1	31.901	/	Pass
		5240	1	30.967	/	Pass
802.11n (HT20)	SISO	5180	1	33.863	/	Pass
		5200	1	34.278	/	Pass
		5240	1	33.282	/	Pass
802.11n (HT40)	SISO	5190	1	77.077	/	Pass
		5230	1	71.925	/	Pass
802.11ac (VHT20)	SISO	5180	1	35.198	/	Pass
		5200	1	33.674	/	Pass
		5240	1	32.738	/	Pass
802.11ac (VHT40)	SISO	5190	1	76.999	/	Pass
		5230	1	77.609	/	Pass
802.11ac (VHT80)	SISO	5210	1	139.744	/	Pass

2.3.2 Test Graph







802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV



802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5210MHz_Ant1_NTNV



3. Maximum Conducted Output Power


3.1 Power


3.1.1 Test Result



Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11a	SISO	5180	9.22	<=23.98	Pass
		5200	8.47	<=23.98	Pass
		5240	7.03	<=23.98	Pass
		5745	12.08	<=30	Pass
		5785	10.74	<=30	Pass
		5825	10.66	<=30	Pass
802.11n (HT20)	SISO	5180	9.03	<=23.98	Pass
		5200	8.28	<=23.98	Pass
		5240	6.92	<=23.98	Pass
		5745	11.75	<=30	Pass
		5785	10.94	<=30	Pass
		5825	10.19	<=30	Pass
802.11n (HT40)	SISO	5190	9.20	<=23.98	Pass
		5230	7.83	<=23.98	Pass
		5755	12.12	<=30	Pass
		5795	11.11	<=30	Pass
802.11ac (VHT20)	SISO	5180	8.98	<=23.98	Pass
		5200	8.30	<=23.98	Pass
		5240	6.74	<=23.98	Pass
		5745	12.23	<=30	Pass
		5785	10.84	<=30	Pass
		5825	9.96	<=30	Pass
802.11ac (VHT40)	SISO	5190	9.46	<=23.98	Pass
		5230	9.09	<=23.98	Pass
		5755	12.16	<=30	Pass
		5795	11.49	<=30	Pass
802.11ac (VHT80)	SISO	5210	9.97	<=23.98	Pass
		5775	11.88	<=30	Pass



Note1: Antenna Gain: Ant1: 1.05dBi;



3.1.2 Test Graph














802.11n(HT20)_MCH_5785MHz_Ant1_NTV




802.11n(HT20)_HCH_5825MHz_Ant1_NTV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5745MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV





802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV



802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV





4. Maximum Power Spectral Density


4.1 PSD



4.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/MHz)		Verdict
			ANT1	Limit	
802.11a	SISO	5180	-1.86	<=11	Pass
		5200	-2.72	<=11	Pass
		5240	-4.22	<=11	Pass
802.11n (HT20)	SISO	5180	-2.48	<=11	Pass
		5200	-3.01	<=11	Pass
		5240	-4.58	<=11	Pass
802.11n (HT40)	SISO	5190	-4.97	<=11	Pass
		5230	-6.54	<=11	Pass
802.11ac (VHT20)	SISO	5180	-2.30	<=11	Pass
		5200	-3.16	<=11	Pass
		5240	-4.69	<=11	Pass
802.11ac (VHT40)	SISO	5190	-5.11	<=11	Pass
		5230	-5.46	<=11	Pass
802.11ac (VHT80)	SISO	5210	-7.08	<=11	Pass


Note1: Antenna Gain: Ant1: 1.05dBi;

4.1.2 Test Graph







802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT40)_LCH_5190MHz_Ant1_NTNV




802.11n(HT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV



802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5210MHz_Ant1_NTNV




4.2 PSD-Band3



4.2.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/500kHz)		Verdict
			ANT1	Limit	
802.11a	SISO	5745	-11.38	<=30	Pass
		5785	-11.96	<=30	Pass
		5825	-11.34	<=30	Pass
802.11n (HT20)	SISO	5745	-11.96	<=30	Pass
		5785	-12.12	<=30	Pass
		5825	-12.29	<=30	Pass
802.11n (HT40)	SISO	5755	-13.91	<=30	Pass
		5795	-14.35	<=30	Pass
802.11ac (VHT20)	SISO	5745	-11.00	<=30	Pass
		5785	-11.44	<=30	Pass
		5825	-11.29	<=30	Pass
802.11ac (VHT40)	SISO	5755	-13.41	<=30	Pass
		5795	-13.24	<=30	Pass
802.11ac (VHT80)	SISO	5775	-16.19	<=30	Pass


Note1: Antenna Gain: Ant1: 1.05dBi;

4.2.2 Test Graph







802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5745MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV



802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV



802.11ac(VHT80)_MCH_5775MHz_Ant1_NTNV



5. Frequency Stability

5.1 Ant1

5.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Temperature (°C)	Ant1			Verdict		
				Voltage (VAC)	Measured Frequency (MHz)	Limit (MHz)			
802.11a	SISO	5180	20	102	5180.000	5150 to 5250	Pass		
				120	5180.020	5150 to 5250	Pass		
				138	5180.000	5150 to 5250	Pass		
			5200	-30	120	5180.020	5150 to 5250	Pass	
					-20	120	5179.980	5150 to 5250	Pass
						-10	120	5180.000	5150 to 5250
				0			120	5180.000	5150 to 5250
					10		120	5179.980	5150 to 5250
						30	120	5180.000	5150 to 5250
		40		120			5179.960	5150 to 5250	Pass
				50	120		5180.020	5150 to 5250	Pass
					5240	20	102	5199.980	5150 to 5250
		120	5199.960				5150 to 5250	Pass	
		138	5199.980	5150 to 5250			Pass		
		5745	-30	120		5200.000	5150 to 5250	Pass	
				-20		120	5200.040	5150 to 5250	Pass
						-10	120	5199.980	5150 to 5250
			0				120	5200.000	5150 to 5250
				10			120	5200.000	5150 to 5250
						30	120	5199.940	5150 to 5250
			40		120		5200.020	5150 to 5250	Pass
				50	120		5200.020	5150 to 5250	Pass
					5240	20	102	5240.000	5150 to 5250
		120	5239.940				5150 to 5250	Pass	
		138	5240.020	5150 to 5250			Pass		
		5745	-30	120		5239.960	5150 to 5250	Pass	
				-20		120	5240.020	5150 to 5250	Pass
						-10	120	5239.980	5150 to 5250
			0				120	5240.020	5150 to 5250
				10			120	5240.040	5150 to 5250
						30	120	5240.020	5150 to 5250
			40		120		5239.980	5150 to 5250	Pass
				50	120		5240.000	5150 to 5250	Pass
					5745	20	102	5745.080	5725 to 5850
		120	5745.000				5725 to 5850	Pass	
		138	5745.040	5725 to 5850			Pass		
		5745	-30	120		5745.040	5725 to 5850	Pass	
				-20		120	5745.000	5725 to 5850	Pass
						-10	120	5745.000	5725 to 5850
			0				120	5744.980	5725 to 5850
				10			120	5745.020	5725 to 5850

			30	120	5745.000	5725 to 5850	Pass		
			40	120	5745.040	5725 to 5850	Pass		
			50	120	5744.960	5725 to 5850	Pass		
		5785	20	102	5784.980	5725 to 5850	Pass		
				120	5784.960	5725 to 5850	Pass		
				138	5785.000	5725 to 5850	Pass		
			-30	120	5785.020	5725 to 5850	Pass		
			-20	120	5784.960	5725 to 5850	Pass		
			-10	120	5785.020	5725 to 5850	Pass		
			0	120	5785.020	5725 to 5850	Pass		
			10	120	5785.060	5725 to 5850	Pass		
			30	120	5785.020	5725 to 5850	Pass		
			40	120	5785.040	5725 to 5850	Pass		
			50	120	5785.020	5725 to 5850	Pass		
		5825	20	102	5825.080	5725 to 5850	Pass		
				120	5825.020	5725 to 5850	Pass		
				138	5825.020	5725 to 5850	Pass		
			-30	120	5825.040	5725 to 5850	Pass		
			-20	120	5825.020	5725 to 5850	Pass		
			-10	120	5824.980	5725 to 5850	Pass		
			0	120	5825.020	5725 to 5850	Pass		
			10	120	5825.000	5725 to 5850	Pass		
			30	120	5824.920	5725 to 5850	Pass		
			40	120	5825.020	5725 to 5850	Pass		
			50	120	5825.020	5725 to 5850	Pass		
		802.11n (HT20)	SISO	5180	20	102	5179.960	5150 to 5250	Pass
						120	5180.000	5150 to 5250	Pass
138	5179.960					5150 to 5250	Pass		
-30	120				5179.960	5150 to 5250	Pass		
-20	120				5179.940	5150 to 5250	Pass		
-10	120				5179.980	5150 to 5250	Pass		
0	120				5180.020	5150 to 5250	Pass		
10	120				5180.040	5150 to 5250	Pass		
30	120				5180.040	5150 to 5250	Pass		
40	120				5179.960	5150 to 5250	Pass		
50	120				5180.000	5150 to 5250	Pass		
5200	20			102	5199.980	5150 to 5250	Pass		
				120	5199.940	5150 to 5250	Pass		
				138	5199.960	5150 to 5250	Pass		
	-30			120	5199.940	5150 to 5250	Pass		
	-20			120	5199.920	5150 to 5250	Pass		
	-10			120	5199.960	5150 to 5250	Pass		
	0			120	5199.980	5150 to 5250	Pass		
	10			120	5199.960	5150 to 5250	Pass		
	30			120	5199.940	5150 to 5250	Pass		
	40			120	5200.000	5150 to 5250	Pass		
	50			120	5199.980	5150 to 5250	Pass		
5240	20			102	5240.000	5150 to 5250	Pass		
				120	5239.940	5150 to 5250	Pass		
				138	5239.980	5150 to 5250	Pass		
	-30			120	5239.940	5150 to 5250	Pass		
	-20			120	5239.980	5150 to 5250	Pass		
-10	120	5240.020	5150 to 5250	Pass					

			0	120	5240.020	5150 to 5250	Pass			
			10	120	5239.920	5150 to 5250	Pass			
			30	120	5240.000	5150 to 5250	Pass			
			40	120	5239.980	5150 to 5250	Pass			
			50	120	5239.980	5150 to 5250	Pass			
		5745	20	102	5744.940	5725 to 5850	Pass			
				120	5744.960	5725 to 5850	Pass			
				138	5745.000	5725 to 5850	Pass			
			-30	120	5745.020	5725 to 5850	Pass			
			-20	120	5745.020	5725 to 5850	Pass			
			-10	120	5745.020	5725 to 5850	Pass			
			0	120	5744.960	5725 to 5850	Pass			
			10	120	5745.020	5725 to 5850	Pass			
			30	120	5745.000	5725 to 5850	Pass			
			40	120	5745.000	5725 to 5850	Pass			
			50	120	5745.020	5725 to 5850	Pass			
			5785	20	102	5784.980	5725 to 5850	Pass		
					120	5785.000	5725 to 5850	Pass		
		138			5785.040	5725 to 5850	Pass			
		-30		120	5785.000	5725 to 5850	Pass			
		-20		120	5785.020	5725 to 5850	Pass			
		-10		120	5785.040	5725 to 5850	Pass			
		0		120	5785.000	5725 to 5850	Pass			
		10		120	5785.000	5725 to 5850	Pass			
		30		120	5785.020	5725 to 5850	Pass			
		40		120	5785.020	5725 to 5850	Pass			
		50		120	5785.000	5725 to 5850	Pass			
		5825		20	102	5825.000	5725 to 5850	Pass		
					120	5825.020	5725 to 5850	Pass		
			138		5824.980	5725 to 5850	Pass			
			-30	120	5824.980	5725 to 5850	Pass			
			-20	120	5825.000	5725 to 5850	Pass			
			-10	120	5825.020	5725 to 5850	Pass			
			0	120	5824.980	5725 to 5850	Pass			
			10	120	5824.980	5725 to 5850	Pass			
			30	120	5825.040	5725 to 5850	Pass			
			40	120	5825.020	5725 to 5850	Pass			
			50	120	5824.920	5725 to 5850	Pass			
			802.11n (HT40)	SISO	5190	20	102	5190.000	5150 to 5250	Pass
							120	5190.000	5150 to 5250	Pass
		138					5190.040	5150 to 5250	Pass	
		-30				120	5190.000	5150 to 5250	Pass	
-20	120	5189.960				5150 to 5250	Pass			
-10	120	5190.000				5150 to 5250	Pass			
0	120	5189.960				5150 to 5250	Pass			
10	120	5190.040				5150 to 5250	Pass			
30	120	5189.960				5150 to 5250	Pass			
40	120	5190.000				5150 to 5250	Pass			
50	120	5190.000				5150 to 5250	Pass			
5230	20	102				5229.960	5150 to 5250	Pass		
		120				5229.960	5150 to 5250	Pass		
		138			5230.000	5150 to 5250	Pass			
	-30	120			5230.000	5150 to 5250	Pass			

			-20	120	5230.000	5150 to 5250	Pass			
			-10	120	5230.000	5150 to 5250	Pass			
			0	120	5230.000	5150 to 5250	Pass			
			10	120	5230.000	5150 to 5250	Pass			
			30	120	5230.000	5150 to 5250	Pass			
			40	120	5229.960	5150 to 5250	Pass			
			50	120	5229.960	5150 to 5250	Pass			
		5755	20	102	5755.040	5725 to 5850	Pass			
				120	5755.000	5725 to 5850	Pass			
				138	5755.040	5725 to 5850	Pass			
			-30	120	5755.000	5725 to 5850	Pass			
			-20	120	5754.960	5725 to 5850	Pass			
			-10	120	5755.040	5725 to 5850	Pass			
			0	120	5755.040	5725 to 5850	Pass			
			10	120	5755.000	5725 to 5850	Pass			
			30	120	5755.120	5725 to 5850	Pass			
			40	120	5755.000	5725 to 5850	Pass			
			50	120	5754.960	5725 to 5850	Pass			
			5795	20	102	5795.080	5725 to 5850	Pass		
					120	5795.000	5725 to 5850	Pass		
		138			5795.000	5725 to 5850	Pass			
		-30		120	5795.040	5725 to 5850	Pass			
		-20		120	5795.040	5725 to 5850	Pass			
		-10		120	5795.000	5725 to 5850	Pass			
		0		120	5795.000	5725 to 5850	Pass			
		10		120	5794.960	5725 to 5850	Pass			
		30		120	5794.960	5725 to 5850	Pass			
		40		120	5795.000	5725 to 5850	Pass			
		50		120	5795.000	5725 to 5850	Pass			
		802.11ac (VHT20)		SISO	5180	20	102	5180.040	5150 to 5250	Pass
							120	5180.020	5150 to 5250	Pass
			138				5179.980	5150 to 5250	Pass	
			-30			120	5179.980	5150 to 5250	Pass	
			-20			120	5180.020	5150 to 5250	Pass	
			-10			120	5179.940	5150 to 5250	Pass	
			0			120	5179.980	5150 to 5250	Pass	
10	120		5180.000			5150 to 5250	Pass			
30	120		5180.000			5150 to 5250	Pass			
40	120		5179.960			5150 to 5250	Pass			
50	120		5179.960			5150 to 5250	Pass			
5200	20		102			5200.000	5150 to 5250	Pass		
			120			5199.980	5150 to 5250	Pass		
			138		5199.940	5150 to 5250	Pass			
	-30		120		5200.000	5150 to 5250	Pass			
	-20		120		5200.020	5150 to 5250	Pass			
	-10		120		5199.960	5150 to 5250	Pass			
	0		120		5199.940	5150 to 5250	Pass			
10	120		5200.000		5150 to 5250	Pass				
30	120		5199.980		5150 to 5250	Pass				
40	120	5200.020	5150 to 5250	Pass						
50	120	5199.980	5150 to 5250	Pass						
5240	20	102	5239.980	5150 to 5250	Pass					
		120	5239.960	5150 to 5250	Pass					

				138	5239.920	5150 to 5250	Pass
			-30	120	5239.960	5150 to 5250	Pass
			-20	120	5240.000	5150 to 5250	Pass
			-10	120	5239.960	5150 to 5250	Pass
			0	120	5240.000	5150 to 5250	Pass
			10	120	5240.000	5150 to 5250	Pass
			30	120	5239.980	5150 to 5250	Pass
			40	120	5239.980	5150 to 5250	Pass
		50	120	5240.000	5150 to 5250	Pass	
		5745	20	102	5745.000	5725 to 5850	Pass
				120	5745.020	5725 to 5850	Pass
				138	5745.000	5725 to 5850	Pass
			-30	120	5744.940	5725 to 5850	Pass
			-20	120	5745.020	5725 to 5850	Pass
			-10	120	5744.980	5725 to 5850	Pass
			0	120	5744.980	5725 to 5850	Pass
			10	120	5744.960	5725 to 5850	Pass
			30	120	5745.020	5725 to 5850	Pass
			40	120	5744.940	5725 to 5850	Pass
			50	120	5745.000	5725 to 5850	Pass
			5785	20	102	5785.020	5725 to 5850
		120			5785.000	5725 to 5850	Pass
		138			5784.980	5725 to 5850	Pass
		-30		120	5785.060	5725 to 5850	Pass
		-20		120	5784.940	5725 to 5850	Pass
		-10		120	5784.980	5725 to 5850	Pass
		0		120	5785.000	5725 to 5850	Pass
		10		120	5784.940	5725 to 5850	Pass
		30		120	5785.000	5725 to 5850	Pass
		40		120	5785.020	5725 to 5850	Pass
		50		120	5784.960	5725 to 5850	Pass
		5825		20	102	5824.960	5725 to 5850
			120		5825.000	5725 to 5850	Pass
			138		5825.020	5725 to 5850	Pass
			-30	120	5825.000	5725 to 5850	Pass
			-20	120	5824.940	5725 to 5850	Pass
			-10	120	5825.020	5725 to 5850	Pass
			0	120	5825.000	5725 to 5850	Pass
			10	120	5825.040	5725 to 5850	Pass
			30	120	5825.020	5725 to 5850	Pass
			40	120	5824.940	5725 to 5850	Pass
			50	120	5824.980	5725 to 5850	Pass
802.11ac (VHT40)	SISO		5190	20	102	5189.960	5150 to 5250
		120			5190.000	5150 to 5250	Pass
		138			5190.040	5150 to 5250	Pass
		-30		120	5189.960	5150 to 5250	Pass
		-20		120	5190.000	5150 to 5250	Pass
		-10		120	5190.000	5150 to 5250	Pass
		0		120	5190.000	5150 to 5250	Pass
		10		120	5190.000	5150 to 5250	Pass
		30		120	5189.960	5150 to 5250	Pass
		40		120	5190.000	5150 to 5250	Pass
50	120	5189.960	5150 to 5250	Pass			

		5230	20	102	5230.000	5150 to 5250	Pass		
				120	5230.000	5150 to 5250	Pass		
				138	5230.000	5150 to 5250	Pass		
			-30	120	5230.040	5150 to 5250	Pass		
			-20	120	5229.960	5150 to 5250	Pass		
			-10	120	5230.000	5150 to 5250	Pass		
			0	120	5230.040	5150 to 5250	Pass		
			10	120	5230.040	5150 to 5250	Pass		
			30	120	5230.000	5150 to 5250	Pass		
		40	120	5230.000	5150 to 5250	Pass			
		50	120	5229.960	5150 to 5250	Pass			
		5755	20	102	5755.000	5725 to 5850	Pass		
				120	5755.040	5725 to 5850	Pass		
				138	5755.080	5725 to 5850	Pass		
			-30	120	5755.000	5725 to 5850	Pass		
			-20	120	5755.000	5725 to 5850	Pass		
			-10	120	5755.000	5725 to 5850	Pass		
			0	120	5755.040	5725 to 5850	Pass		
			10	120	5754.960	5725 to 5850	Pass		
			30	120	5754.960	5725 to 5850	Pass		
		40	120	5755.080	5725 to 5850	Pass			
		50	120	5755.080	5725 to 5850	Pass			
		5795	20	102	5795.040	5725 to 5850	Pass		
				120	5795.080	5725 to 5850	Pass		
				138	5795.040	5725 to 5850	Pass		
			-30	120	5795.040	5725 to 5850	Pass		
			-20	120	5795.040	5725 to 5850	Pass		
			-10	120	5795.000	5725 to 5850	Pass		
			0	120	5795.000	5725 to 5850	Pass		
			10	120	5795.000	5725 to 5850	Pass		
			30	120	5795.040	5725 to 5850	Pass		
		40	120	5795.040	5725 to 5850	Pass			
		50	120	5795.040	5725 to 5850	Pass			
		802.11ac (VHT80)	SISO	5210	20	102	5210.000	5150 to 5250	Pass
						120	5209.925	5150 to 5250	Pass
						138	5209.850	5150 to 5250	Pass
-30	120				5209.850	5150 to 5250	Pass		
-20	120				5209.925	5150 to 5250	Pass		
-10	120				5210.000	5150 to 5250	Pass		
0	120				5209.925	5150 to 5250	Pass		
10	120				5210.000	5150 to 5250	Pass		
30	120				5210.000	5150 to 5250	Pass		
40	120			5209.925	5150 to 5250	Pass			
50	120			5210.000	5150 to 5250	Pass			
5775	20			102	5775.075	5725 to 5850	Pass		
				120	5775.000	5725 to 5850	Pass		
				138	5775.000	5725 to 5850	Pass		
	-30			120	5775.075	5725 to 5850	Pass		
	-20			120	5775.000	5725 to 5850	Pass		
	-10			120	5775.075	5725 to 5850	Pass		
	0			120	5775.075	5725 to 5850	Pass		
	10	120	5775.075	5725 to 5850	Pass				
	30	120	5775.000	5725 to 5850	Pass				

			40	120	5775.000	5725 to 5850	Pass
			50	120	5775.000	5725 to 5850	Pass

6. Form731

6.1 Form731

6.1.1 Test Result

Lower Freq (MHz)	High Freq (MHz)	MAX Power (W)	MAX Power (dBm)
5180	5240	0.0084	9.22
5745	5825	0.0167	12.23
5190	5230	0.0088	9.46
5755	5795	0.0164	12.16
5210	5210	0.0099	9.97



Test Report Number: BTF230913R00704



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT --