

1. Effective (Isotropic) Radiated Power Output Data

1.1 GSM850_ERP

1.1.1 Test Result

Band: GSM850								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	824.2	32.73	0.66	31.24	<=38.45	Pass
			836.6	32.69	0.66	31.20	<=38.45	Pass
			848.8	32.69	0.66	31.20	<=38.45	Pass
	GPRS	1 TX Slot	824.2	32.75	0.66	31.26	<=38.45	Pass
			824.2	31.99	0.66	30.50	<=38.45	Pass
			824.2	30.21	0.66	28.72	<=38.45	Pass
			824.2	29.06	0.66	27.57	<=38.45	Pass
			836.6	32.55	0.66	31.06	<=38.45	Pass
			836.6	31.89	0.66	30.40	<=38.45	Pass
			836.6	30.11	0.66	28.62	<=38.45	Pass
			836.6	28.95	0.66	27.46	<=38.45	Pass
			848.8	32.51	0.66	31.02	<=38.45	Pass
			848.8	31.86	0.66	30.37	<=38.45	Pass
			848.8	30.08	0.66	28.59	<=38.45	Pass
			848.8	28.91	0.66	27.42	<=38.45	Pass
	EGPRS	1 TX Slot	824.2	26.18	0.66	24.69	<=38.45	Pass
			824.2	25.26	0.66	23.77	<=38.45	Pass
			824.2	23.19	0.66	21.70	<=38.45	Pass
			824.2	22.21	0.66	20.72	<=38.45	Pass
			836.6	25.89	0.66	24.40	<=38.45	Pass
			836.6	25.05	0.66	23.56	<=38.45	Pass
			836.6	22.95	0.66	21.46	<=38.45	Pass
			836.6	24.51	0.66	23.02	<=38.45	Pass
			848.8	25.62	0.66	24.13	<=38.45	Pass
848.8			24.86	0.66	23.37	<=38.45	Pass	
848.8			22.96	0.66	21.47	<=38.45	Pass	
848.8			21.74	0.66	20.25	<=38.45	Pass	

Note1: ERP=Conducted Power+Antenna Gain-2.15

2. Frequency Stability

2.1 GSM850

2.1.1 Test Result

Band: GSM850							
Network	Frequency (MHz)	Temp. (°C)	Voltage (VDC)	Freq. Error (Hz)	Freq. vs. Rated (ppm)		Verdict
					Result	Limit	
GSM	824.2	20	3.27	3.067	0.0037	-2.5 to 2.5	Pass
			3.85	-1.743	-0.0021	-2.5 to 2.5	Pass
			4.43	-1.614	-0.0020	-2.5 to 2.5	Pass

	836.6	-30	3.85	-2.034	-0.0025	-2.5 to 2.5	Pass
		-20	3.85	2.841	0.0034	-2.5 to 2.5	Pass
		-10	3.85	4.455	0.0054	-2.5 to 2.5	Pass
		0	3.85	5.198	0.0063	-2.5 to 2.5	Pass
		10	3.85	2.454	0.0030	-2.5 to 2.5	Pass
		30	3.85	4.488	0.0054	-2.5 to 2.5	Pass
		40	3.85	5.230	0.0063	-2.5 to 2.5	Pass
	50	3.85	4.423	0.0054	-2.5 to 2.5	Pass	
	836.6	20	3.27	3.551	0.0042	-2.5 to 2.5	Pass
			3.85	6.167	0.0074	-2.5 to 2.5	Pass
			4.43	3.067	0.0037	-2.5 to 2.5	Pass
		-30	3.85	3.907	0.0047	-2.5 to 2.5	Pass
		-20	3.85	6.102	0.0073	-2.5 to 2.5	Pass
		-10	3.85	2.938	0.0035	-2.5 to 2.5	Pass
		0	3.85	5.489	0.0066	-2.5 to 2.5	Pass
		10	3.85	4.003	0.0048	-2.5 to 2.5	Pass
		30	3.85	6.393	0.0076	-2.5 to 2.5	Pass
		40	3.85	0.484	0.0006	-2.5 to 2.5	Pass
	50	3.85	2.615	0.0031	-2.5 to 2.5	Pass	
	848.8	20	3.27	3.745	0.0044	-2.5 to 2.5	Pass
			3.85	2.518	0.0030	-2.5 to 2.5	Pass
			4.43	2.228	0.0026	-2.5 to 2.5	Pass
		-30	3.85	1.001	0.0012	-2.5 to 2.5	Pass
		-20	3.85	0.581	0.0007	-2.5 to 2.5	Pass
		-10	3.85	5.037	0.0059	-2.5 to 2.5	Pass
		0	3.85	2.486	0.0029	-2.5 to 2.5	Pass
		10	3.85	-1.001	-0.0012	-2.5 to 2.5	Pass
		30	3.85	1.162	0.0014	-2.5 to 2.5	Pass
		40	3.85	2.809	0.0033	-2.5 to 2.5	Pass
	50	3.85	2.841	0.0033	-2.5 to 2.5	Pass	
GPRS	824.2	20	3.27	0.258	0.0003	-2.5 to 2.5	Pass
			3.85	2.002	0.0024	-2.5 to 2.5	Pass
			4.43	0.226	0.0003	-2.5 to 2.5	Pass
		-30	3.85	-1.195	-0.0014	-2.5 to 2.5	Pass
		-20	3.85	1.905	0.0023	-2.5 to 2.5	Pass
		-10	3.85	1.324	0.0016	-2.5 to 2.5	Pass
		0	3.85	2.389	0.0029	-2.5 to 2.5	Pass
		10	3.85	-0.032	0.0000	-2.5 to 2.5	Pass
		30	3.85	-0.291	-0.0004	-2.5 to 2.5	Pass
		40	3.85	1.679	0.0020	-2.5 to 2.5	Pass
	50	3.85	0.549	0.0007	-2.5 to 2.5	Pass	
	836.6	20	3.27	1.614	0.0019	-2.5 to 2.5	Pass
			3.85	4.326	0.0052	-2.5 to 2.5	Pass
			4.43	-0.065	-0.0001	-2.5 to 2.5	Pass
		-30	3.85	0.775	0.0009	-2.5 to 2.5	Pass
		-20	3.85	0.807	0.0010	-2.5 to 2.5	Pass
		-10	3.85	-0.291	-0.0003	-2.5 to 2.5	Pass
		0	3.85	1.711	0.0020	-2.5 to 2.5	Pass
		10	3.85	0.420	0.0005	-2.5 to 2.5	Pass
		30	3.85	-0.129	-0.0002	-2.5 to 2.5	Pass
		40	3.85	4.165	0.0050	-2.5 to 2.5	Pass
	50	3.85	3.874	0.0046	-2.5 to 2.5	Pass	
	848.8	20	3.27	-0.065	-0.0001	-2.5 to 2.5	Pass
			3.85	0.743	0.0009	-2.5 to 2.5	Pass
			4.43	0.032	0.0000	-2.5 to 2.5	Pass

		-30	3.85	0.613	0.0007	-2.5 to 2.5	Pass	
		-20	3.85	2.163	0.0025	-2.5 to 2.5	Pass	
		-10	3.85	2.325	0.0027	-2.5 to 2.5	Pass	
		0	3.85	1.227	0.0014	-2.5 to 2.5	Pass	
		10	3.85	0.936	0.0011	-2.5 to 2.5	Pass	
		30	3.85	1.485	0.0017	-2.5 to 2.5	Pass	
		40	3.85	1.873	0.0022	-2.5 to 2.5	Pass	
EGPRS	824.2	50	3.85	-1.582	-0.0019	-2.5 to 2.5	Pass	
		20	3.27	-793.231	-0.9624	-2.5 to 2.5	Pass	
			3.85	-39.582	-0.0480	-2.5 to 2.5	Pass	
			4.43	62.861	0.0763	-2.5 to 2.5	Pass	
		-30	3.85	-205.144	-0.2489	-2.5 to 2.5	Pass	
		-20	3.85	-200.075	-0.2428	-2.5 to 2.5	Pass	
		-10	3.85	24.957	0.0303	-2.5 to 2.5	Pass	
		0	3.85	-130.435	-0.1583	-2.5 to 2.5	Pass	
		10	3.85	-129.854	-0.1576	-2.5 to 2.5	Pass	
		30	3.85	-402.153	-0.4879	-2.5 to 2.5	Pass	
		40	3.85	-197.945	-0.2402	-2.5 to 2.5	Pass	
		50	3.85	-956.371	-1.1604	-2.5 to 2.5	Pass	
		836.6	20	3.27	116.100	0.1388	-2.5 to 2.5	Pass
				3.85	542.854	0.6489	-2.5 to 2.5	Pass
	4.43			-55.822	-0.0667	-2.5 to 2.5	Pass	
	-30		3.85	105.446	0.1260	-2.5 to 2.5	Pass	
	-20		3.85	-180.575	-0.2158	-2.5 to 2.5	Pass	
	-10		3.85	-587.764	-0.7026	-2.5 to 2.5	Pass	
	0		3.85	507.049	0.6061	-2.5 to 2.5	Pass	
	10		3.85	-278.336	-0.3327	-2.5 to 2.5	Pass	
	30		3.85	-934.030	-1.1165	-2.5 to 2.5	Pass	
	40		3.85	-271.298	-0.3243	-2.5 to 2.5	Pass	
	50		3.85	-60.827	-0.0727	-2.5 to 2.5	Pass	
	848.8		20	3.27	-7.619	-0.0090	-2.5 to 2.5	Pass
				3.85	-8.685	-0.0102	-2.5 to 2.5	Pass
				4.43	-10.525	-0.0124	-2.5 to 2.5	Pass
		-30	3.85	-7.749	-0.0091	-2.5 to 2.5	Pass	
		-20	3.85	-7.845	-0.0092	-2.5 to 2.5	Pass	
-10		3.85	-7.942	-0.0094	-2.5 to 2.5	Pass		
0		3.85	-3.551	-0.0042	-2.5 to 2.5	Pass		
10		3.85	-6.070	-0.0072	-2.5 to 2.5	Pass		
30		3.85	-3.971	-0.0047	-2.5 to 2.5	Pass		
40		3.85	-5.037	-0.0059	-2.5 to 2.5	Pass		
50		3.85	-5.359	-0.0063	-2.5 to 2.5	Pass		

3. Modulation Characteristics


3.1 GSM850

3.1.1 Test Result

Band: GSM850						
ENV	Mode		Frequency (MHz)	Modulation Characteristics		Verdict
	Network	Subset		Result	Limit	
NTNV	GSM	GSM	836.6	Refer To Test Graph		Pass

	GPRS	1 TX Slot	836.6	Refer To Test Graph	Pass
	EGPRS	1 TX Slot	836.6	Refer To Test Graph	Pass

3.1.2 Test Graph



GSM850_EGPRS_MCH_836.6MHz_1 TX Slot_NTNV

GSM Measurement - V3.7.30 - Base V 3.7.160 - TX Measurement

Band/Ch: GSM850 / 190 Freq.: 836.60000 MHz Ref. Level: 42.23 dBm Meas Slots: [●●●●●●●●] Tim. Advance.: 0

IQ

Statistic Count: 10 / 10

Bursts out of Tolerance: 0.00 %

Mod.View Throughput: 100.0 %

Burst Type: 8PSK

CS: Synchronized PS: TBF Established DL: MCS-5 UL: MCS-5

Go To Local Show Remote Screen

GSM

Multi Evaluation RDY

RF Settings

Trigger

Display

Signaling Parameter

GSM Signaling ON



4. 99% & 26dB Bandwidth

4.1 GSM850_OBW


4.1.1 Test Result

Band: GSM850					
ENV	Mode		Frequency (MHz)	99% Occupied Bandwidth (MHz)	Verdict
	Network	Subset		Result	
NTNV	GSM	GSM	824.2	0.242	Pass
			836.6	0.248	Pass
			848.8	0.243	Pass
	GPRS	1 TX Slot	824.2	0.245	Pass
			836.6	0.246	Pass
			848.8	0.245	Pass
	EGPRS	1 TX Slot	824.2	0.231	Pass
			836.6	0.238	Pass
			848.8	0.253	Pass


4.1.2 Test Graph




GSM850_GSM_HCH_848.8MHz_GSM_NTNV




GSM850_GPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_GPRS_MCH_836.6MHz_1 TX Slot_NTNV




GSM850_GPRS_HCH_848.8MHz_1 TX Slot_NTNV




GSM850_EGPRS_LCH_824.2MHz_1 TX Slot_NTNV



GSM850_EGPRS_MCH_836.6MHz_1 TX Slot_NTNV



GSM850_EGPRS_HCH_848.8MHz_1 TX Slot_NTNV





4.2 GSM850_XDB


4.2.1 Test Result

Band: GSM850					
ENV	Mode		Frequency (MHz)	26dB Bandwidth (MHz)	Verdict
	Network	Subset		Result	
NTNV	GSM	GSM	824.2	0.313	Pass
			836.6	0.313	Pass
			848.8	0.315	Pass
	GPRS	1 TX Slot	824.2	0.318	Pass
			836.6	0.314	Pass
			848.8	0.311	Pass
	EGPRS	1 TX Slot	824.2	0.307	Pass
			836.6	0.294	Pass
			848.8	0.308	Pass


4.2.2 Test Graph




GSM850_GSM_HCH_848.8MHz_GSM_NTNV




GSM850_GPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_GPRS_MCH_836.6MHz_1 TX Slot_NTNV




GSM850_GPRS_HCH_848.8MHz_1 TX Slot_NTNV




GSM850_EGPRS_LCH_824.2MHz_1 TX Slot_NTNV



GSM850_EGPRS_MCH_836.6MHz_1 TX Slot_NTNV



GSM850_EGPRS_HCH_848.8MHz_1 TX Slot_NTNV




5. Peak-Average Ratio

5.1 GSM850


5.1.1 Test Result

Band: GSM850						
ENV	Mode		Frequency (MHz)	Peak-Average Ratio (dB)		Verdict
	Network	Subset		Result	Limit	
NTNV	GSM	GSM	824.2	9.65	<=13	Pass
			836.6	9.48	<=13	Pass
			848.8	9.23	<=13	Pass
	GPRS	4 TX Slots	824.2	9.75	<=13	Pass
			836.6	3.57	<=13	Pass
			848.8	3.61	<=13	Pass
	EGPRS	4 TX Slots	824.2	6.71	<=13	Pass
			836.6	6.75	<=13	Pass
			848.8	10.95	<=13	Pass


5.1.2 Test Graph




GSM850_GSM_HCH_848.8MHz_GSM_NTNV




GSM850_GPRS_LCH_824.2MHz_4 TX Slots_NTNV




GSM850_GPRS_MCH_836.6MHz_4 TX Slots_NTNV




GSM850_GPRS_HCH_848.8MHz_4 TX Slots_NTNV




GSM850_EGPRS_LCH_824.2MHz_4 TX Slots_NTNV



GSM850_EGPRS_MCH_836.6MHz_4 TX Slots_NTNV



GSM850_EGPRS_HCH_848.8MHz_4 TX Slots_NTNV





6. Spurious Emission

6.1 GSM850


6.1.1 Test Result

Band: GSM850						
ENV	Mode		Frequency (MHz)	Spurious Emission		Verdict
	Network	Subset		Result	Limit	
NTNV	GSM	GSM	824.2	Refer To Test Graph		Pass
			836.6	Refer To Test Graph		Pass
			848.8	Refer To Test Graph		Pass
	GPRS	1 TX Slot	824.2	Refer To Test Graph		Pass
			836.6	Refer To Test Graph		Pass
			848.8	Refer To Test Graph		Pass
	EGPRS	1 TX Slot	824.2	Refer To Test Graph		Pass
			836.6	Refer To Test Graph		Pass
			848.8	Refer To Test Graph		Pass


6.1.2 Test Graph




GSM850_GSM_MCH_836.6MHz_GSM_NTNV




GSM850_GSM_HCH_848.8MHz_GSM_NTNV




GSM850_GSM_HCH_848.8MHz_GSM_NTNV




GSM850_GPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_GPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_GPRS_MCH_836.6MHz_1 TX Slot_NTNV




GSM850_GPRS_HCH_848.8MHz_1 TX Slot_NTNV




GSM850_GPRS_HCH_848.8MHz_1 TX Slot_NTNV




GSM850_EGPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_EGPRS_LCH_824.2MHz_1 TX Slot_NTNV




GSM850_EGPRS_MCH_836.6MHz_1 TX Slot_NTNV



GSM850_EGPRS_HCH_848.8MHz_1 TX Slot_NTNV



GSM850_EGPRS_HCH_848.8MHz_1 TX Slot_NTNV



7. Form731

7.1 Form731_Power

7.1.1 Test Result

Band	BW	Lower Freq	High Freq	MAX Power (W)	Value	Hz/ppm	Emission Designator	Rule Parts	MAX Power (dBm)
GSM850	0.2	824.2	848.8	1.8836	0.0076	ppm	248KGXW	22H	32.75
GSM850	0.2	824.2	848.8	0.4150	1.1604	ppm	253KG7W	22H	26.18

7.2 Form731_ERP

7.2.1 Test Result

Band	BW	Lower Freq	High Freq	MAX Power (W)	Value	Hz/ppm	Emission Designator	Rule Parts	MAX Power (dBm)
GSM850	0.2	824.2	848.8	1.3366	0.0076	ppm	248KGXW	22H	31.26
GSM850	0.2	824.2	848.8	0.2944	1.1604	ppm	253KG7W	22H	24.69