

TEST REPORT

Reference No...... : WTS16S0243645E
FCC ID : 2ADLJPROFILE3G
Applicant..... : Xwireless LLC
Address..... : 11426 Rockville pike,Rockville, MD 20852United States
Manufacturer : Xwireless LLC
Address..... : 11426 Rockville pike,Rockville, MD 20852United States
Product Name..... : Mobile Phone
Model No..... : Profile 3G, UW2405S
Brand..... : VORTEX
Standards : FCC PART15 SUBPART B: 2015
Date of Receipt sample : Feb, 29, 2016
Date of Test : Mar. 01, 2016 –Mar. 11, 2016
Date of Issue..... : Mar. 18, 2016
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.


Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

1 Test Summary

Test Item	Test Requirement	Class	Test Method	Test Result
Power Line Conducted Emission (150kHz to 30MHz)	FCC PART 15, SUBPART B: 2015	Class B	ANSI C63.4: 2009	Pass
Radiated Emission 30MHz to 1GHz)	FCC PART 15, SUBPART B: 2015	Class B	ANSI C63.4: 2009	Pass
Radiated Emission (Above 1GHz)	FCC PART 15, SUBPART B: 2015	Class B	ANSI C63.4: 2009	Pass

Remark:

Pass Test item meets the requirement

Fail Test item does not meet the requirement

N/A Test case does not apply to the test object

2 Contents

	Page
COVER PAGE	1
1 TEST SUMMARY	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 GENERAL DESCRIPTION OF E.U.T.....	4
3.2 DETAILS OF E.U.T.....	4
3.3 STANDARDS APPLICABLE FOR TESTING	4
3.4 TEST FACILITY	5
3.5 SUBCONTRACTED	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4 EQUIPMENT USED DURING TEST	6
4.1 EQUIPMENT LIST.....	6
4.2 DESCRIPTION OF SUPPORT UNITS	7
4.3 MEASUREMENT UNCERTAINTY	7
5 EMISSION TEST RESULTS	8
5.1 POWER LINE CONDUCTED EMISSION, 150KHZ TO 30MHZ	8
5.2 RADIATION EMISSION, 30MHZ TO 1000MHZ.....	11
5.3 RADIATION EMISSION, ABOVE 1000MHZ	14
6 PHOTOGRAPHS – TEST SETUP	17
6.1 PHOTOGRAPH –POWER LINE CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#.....	17
6.2 PHOTOGRAPH – RADIATED EMISSION TEST SETUP FOR 30~1000MHZ AT TEST SITE 2#.....	17
6.3 PHOTOGRAPH – RADIATED EMISSION TEST SETUP FOR ABOVE 1GHZ AT TEST SITE 1#.....	18

3 General Information

3.1 General Description of E.U.T.

Product Name	: Mobile Phone
Model No.	: Profile 3G, UW2405S
Model Description	: Only model name is different.
GSM Band(s)	: GSM 850/900/1800/1900MHz
GPRS Class	: 12
WCDMA Band(s)	: FDD Band II/V
LTE Bnad(s)	: N/A
Wi-Fi Specification	: N/A
Bluetooth Version	: Bluetooth v2.1+EDR
GPS	: N/A
NFC	: N/A
Hardware Version	: SC7701_SP7701_HTXPA1
Software Version	: P1911_W1_ST_CARON_SC7701_V0.1
Highest Operate Frequency	: 460MHz

3.2 Details of E.U.T.

Technical Data:	: Battery DC 3.7V 1000mAh DC 5V, 0.5A, charging from adapter (Adapter Input: 100-240V~50/60Hz, 0.15A)
Adapter:	: Manufacture: Shenzhen HengChangShengDing Electronics Co ., ltd . Model No.: MK5P

3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC PART 15, SUBPART B: Electronic Code of Federal Regulations- Unintentional Radiators 2015

3.4 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services (Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration 7760A-1, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

3.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

3.6 Abnormalities from Standard Conditions

None.

4 Equipment Used during Test

4.1 Equipment List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.15,2015	Sep.14,2016
2.	LISN	R&S	ENV216	101215	Sep.15,2015	Sep.14,2016
3.	Cable	Top	TYPE16(3.5M)	-	Sep.15,2015	Sep.14,2016
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.15,2015	Sep.14,2016
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.15,2015	Sep.14,2016
3.	Limitter	York	MTS-IMP-136	261115-001-0024	Sep.15,2015	Sep.14,2016
4.	Cable	LARGE	RF300	-	Sep.15,2015	Sep.14,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.15,2015	Sep.14,2016
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2015	Apr.18,2016
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.15,2015	Sep.14,2016
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2015	Apr.18,2016
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.19,2015	Apr.18,2016
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2015	Mar.16,2016
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.10,2015	Apr.09,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Sep.15,2015	Sep.14,2016
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Sep.15,2015	Sep.14,2016
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Sep.15,2015	Sep.14,2016

4	Cable	HUBER+SUHNER	CBL2	525178	Sep.15,2015	Sep.14,2016
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.15,2015	Sep.14,2016
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.15,2015	Sep.14,2016

4.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
MacBook Air	APPLE	A1465	C17KTQDNF5N7

4.3 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	±3.64dB	(1)
Radiation Emission	30MHz~1000MHz	±5.03dB	(1)
	1GHz~18GHz	±5.47dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5 Emission Test Results

5.1 Power Line Conducted Emission, 150kHz to 30MHz

Test Requirement : FCC PART 15, SUBPART B
 Test Method : ANSI C63.4 2009
 Test Result : Pass
 Frequency Range : 150kHz to 30MHz
 Class : Class B
 Limit :

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

5.1.1 E.U.T. Operation

Operating Environment:


Temperature : 23°C
 Humidity : 53.6%RH
 Atmospheric Pressure..... : 101kPa

EUT Operation:

Input Voltage..... : DC 5V by Adapter Input AC 120V/60Hz
 Operating Mode : Data transmitting +earphone+adapter mode
 Remark : The worse case(Data transmitting+earphone+adapter mode) is under the condition of AC 120V/60Hz adapter input and the data is shown as follow.

5.1.2 Block Diagram of Test Setup

The Mains Terminals Disturbance Voltage tests were performed in accordance with the ANSI C63.4 2009.




5.1.3 Measurement Data

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line. According to the data in section 5.1.4, the EUT complied with the FCC PART 15, SUBPART B standards.


5.1.4 Power Line Conducted Emission Test Data

Live Line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1539	41.57	10.13	51.70	65.78	-14.08	QP	
2	0.1539	13.77	10.13	23.90	55.78	-31.88	AVG	
3	0.1980	47.17	10.15	57.32	63.69	-6.37	QP	
4	0.1980	29.45	10.15	39.60	53.69	-14.09	AVG	
5	0.2060	46.29	10.15	56.44	63.36	-6.92	QP	
6	0.2060	29.17	10.15	39.32	53.36	-14.04	AVG	
7	0.2620	40.41	10.16	50.57	61.36	-10.79	QP	
8	0.2620	21.98	10.16	32.14	51.36	-19.22	AVG	
9	0.3260	33.98	10.17	44.15	59.55	-15.40	QP	
10	0.3260	15.09	10.17	25.26	49.55	-24.29	AVG	
11	3.7820	28.31	10.30	38.61	56.00	-17.39	QP	
12	3.7820	15.64	10.30	25.94	46.00	-20.06	AVG	

Neutral Line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	42.12	10.13	52.25	65.99	-13.74	QP	
2	0.1500	19.90	10.13	30.03	55.99	-25.96	AVG	
3	0.1940	46.16	10.15	56.31	63.86	-7.55	QP	
4	0.1940	26.65	10.15	36.80	53.86	-17.06	AVG	
5	0.2029	45.29	10.15	55.44	63.49	-8.05	QP	
6	0.2029	29.01	10.15	39.16	53.49	-14.33	AVG	
7	0.2620	39.46	10.16	49.62	61.36	-11.74	QP	
8	0.2620	20.99	10.16	31.15	51.36	-20.21	AVG	
9	0.3379	32.06	10.17	42.23	59.25	-17.02	QP	
10	0.3379	14.66	10.17	24.83	49.25	-24.42	AVG	
11	3.6260	32.21	10.29	42.50	56.00	-13.50	QP	
12	3.6260	21.11	10.29	31.40	46.00	-14.60	AVG	

5.2 Radiation Emission, 30MHz to 1000MHz

Test Requirement : FCC PART 15, SUBPART B
 Test Method : ANSI C63.4 2009
 Test Result : Pass
 Frequency Range : 30MHz to 1000MHz
 Class. : Class B
 Limit..... :

Frequency (MHz)	Distance (Meter)	Limit (dB μ V/m
		Quasi-peak
30 to 88	3	40
88 to 211	3	43.5
216 to 960	3	46
960 to 1000	3	54

5.2.1 E.U.T. Operation

Operating Environment:


Temperature : 22.5°C
 Humidity : 52.6%RH
 Atmospheric Pressure..... : 101.2kPa

EUT Operation:

Input Voltage..... : DC 5V by Adapter Input AC 120V/60Hz
 Operating Mode : Data transmitting +earphone+adapter
 Remark : The worse case(Data transmitting +earphone+adapter) is under the condition of AC 120V/60Hz adapter input and the data is shown as follow.

5.2.2 Block Diagram of Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4.




5.2.3 Measurement Data

The maximised peak emissions from the EUT was scanned and measured for both the Antenna Vertical Polarization and Antenna Horizontal Polarization. Quasi-peak measurements were performed if peak emissions were within 6dB of the Quasi-peak limit line.


5.2.4 Radiated Emission Test Data, 30MHz to 1000MHz

Antenna Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	160.3456	38.52	-18.92	19.60	43.50	-23.90	QP	
2	218.3085	36.60	-17.13	19.47	46.00	-26.53	QP	
3	241.6763	37.34	-16.12	21.22	46.00	-24.78	QP	
4	383.9318	42.04	-13.00	29.04	46.00	-16.96	QP	
5	541.3725	37.12	-10.64	26.48	46.00	-19.52	QP	
6	595.1329	35.77	-9.93	25.84	46.00	-20.16	QP	

Antenna Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	93.4402	31.20	-17.91	13.29	43.50	-30.21	QP	
2	146.8877	33.14	-19.79	13.35	43.50	-30.15	QP	
3	160.9089	33.44	-18.89	14.55	43.50	-28.95	QP	
4	177.5092	37.43	-18.42	19.01	43.50	-24.49	QP	
5	216.0240	38.72	-17.05	21.67	46.00	-24.33	QP	
6	299.3158	38.46	-15.16	23.30	46.00	-22.70	QP	

5.3 Radiation Emission, Above 1000MHz

Test Requirement : FCC PART 15, SUBPART B
 Test Method : ANSI C63.4 2009
 Test Result..... : Pass
 Frequency Range : 1GHz~18GHz
 Class. : Class B
 Limit. :

Frequency Range (MHz)	Distance (Meter)	Average Limit dB(uV/m)	Peak Limit (dBuV/m)
Above 1GHz	3	54	74

5.3.1 E.U.T. Operation

Operating Environment:


Temperature..... : 22.4°C
 Humidity : 52.3%RH
 Atmospheric Pressure..... : 101.3kPa

EUT Operation:

Input Voltage : DC 5V by Adapter Input AC 120V/60Hz
 Operating Mode : Data transmitting+adapter+earphone mode
 Remark..... : The worse case(Data transmitting+adapter+earphone mode) is under the condition of AC 120V/60Hz adapter input and the data is shown as follow.

5.3.2 Block Diagram of Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4.




5.3.3 Measurement Data

The maximised peak emissions from the EUT was scanned and measured for both the Antenna Vertical Polarization and Antenna Horizontal Polarization. Average measurements were performed if peak emissions were within 6dB of the average limit line


5.3.4 Radiated Emission Test Data, Above 1000MHz

Antenna Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Rem ark
1	4995.000	48.33	-0.26	48.07	74.00	-25.93	peak	
2	4995.000	42.29	-0.26	42.03	54.00	-11.97	AVG	
3	6916.000	49.06	0.24	49.30	74.00	-24.70	peak	
4	6916.000	43.14	0.24	43.38	54.00	-10.62	AVG	
5	10367.000	45.33	5.90	51.23	74.00	-22.77	peak	
6	10367.000	40.06	5.90	45.96	54.00	-8.04	AVG	
7	11489.000	41.42	9.23	50.65	74.00	-23.35	peak	
8	11489.000	35.20	9.23	44.43	54.00	-9.57	AVG	
9	13291.000	44.50	6.64	51.14	74.00	-22.86	peak	
10	13291.000	38.73	6.64	45.37	54.00	-8.63	AVG	
11	16232.000	43.76	7.80	51.56	74.00	-22.44	peak	
12	16232.000	38.28	7.80	46.08	54.00	-7.92	AVG	

Antenna Polarization: Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Rem ark
1	4995.000	49.03	-0.26	48.77	74.00	-25.23	peak	
2	4995.000	42.95	-0.26	42.69	54.00	-11.31	AVG	
3	7426.000	47.30	3.21	50.51	74.00	-23.49	peak	
4	7426.000	41.19	3.21	44.40	54.00	-9.60	AVG	
5	9925.000	44.80	6.31	51.11	74.00	-22.89	peak	
6	9925.000	39.06	6.31	45.37	54.00	-8.63	AVG	
7	11506.000	41.93	9.25	51.18	74.00	-22.82	peak	
8	11506.000	35.92	9.25	45.17	54.00	-8.83	AVG	
9	14481.000	42.14	9.47	51.61	74.00	-22.39	peak	
10	14481.000	36.16	9.47	45.63	54.00	-8.37	AVG	
11	17235.000	38.70	12.55	51.25	74.00	-22.75	peak	
12	17235.000	33.29	12.55	45.84	54.00	-8.16	AVG	

6 Photographs – Test Setup

6.1 Photograph –Power Line Conducted Emission Test Setup at Test Site 1#



6.2 Photograph – Radiated Emission Test Setup for 30~1000MHz at Test Site 2#



6.3 Photograph – Radiated Emission Test Setup for Above 1GHz at Test Site 1#



====End of Report====