



FCC PART 15.247

TEST REPORT

For

Xwireless LLC

11565 Old Georgetown Road, Rockville, MD 20852

FCC ID: 2ADLJV50LTE

| | |
|---|--|
| Report Type: Original Report | Product Type: 4G Smart Phone |
| Report Number: RSZ171208001-00C | |
| Report Date: 2018-01-29 | |
| Reviewed By: RF Engineer | Candy Li <i>Candy Li</i> |
| Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn | |

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP* or any agency of the Federal Government. * This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 4 |
| OBJECTIVE | 4 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| MEASUREMENT UNCERTAINTY..... | 5 |
| SYSTEM TEST CONFIGURATION | 6 |
| DESCRIPTION OF TEST CONFIGURATION | 6 |
| EQUIPMENT MODIFICATIONS | 7 |
| EUT EXERCISE SOFTWARE | 7 |
| DUTY CYCLE | 7 |
| EXTERNAL I/O CABLE..... | 11 |
| BLOCK DIAGRAM OF TEST SETUP | 11 |
| SUMMARY OF TEST RESULTS | 12 |
| TEST EQUIPMENT LIST | 13 |
| FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE | 15 |
| APPLICABLE STANDARD | 15 |
| FCC §15.203 - ANTENNA REQUIREMENT | 16 |
| APPLICABLE STANDARD | 16 |
| ANTENNA CONNECTOR CONSTRUCTION | 16 |
| FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS | 17 |
| APPLICABLE STANDARD | 17 |
| EUT SETUP | 17 |
| EMI TEST RECEIVER SETUP..... | 17 |
| TEST PROCEDURE | 17 |
| CORRECTED FACTOR & MARGIN CALCULATION | 18 |
| TEST RESULTS SUMMARY | 18 |
| TEST DATA | 18 |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS | 23 |
| APPLICABLE STANDARD | 23 |
| EUT SETUP | 23 |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 24 |
| TEST PROCEDURE | 24 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 24 |
| TEST RESULTS SUMMARY | 24 |
| TEST DATA | 25 |
| FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH | 37 |
| APPLICABLE STANDARD | 37 |
| TEST PROCEDURE | 37 |
| TEST DATA | 37 |

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....48
 APPLICABLE STANDARD48
 TEST PROCEDURE48
 TEST DATA48

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....50
 APPLICABLE STANDARD50
 TEST PROCEDURE50
 TEST DATA50

FCC §15.247(e) - POWER SPECTRAL DENSITY58
 APPLICABLE STANDARD58
 TEST PROCEDURE58
 TEST DATA58

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Xwireless LLC*'s product, model number: V50LTE (*FCC ID: 2ADLJV50LTE*) or the "EUT" in this report was a *4G Smart Phone*, which was measured approximately: 14.4 cm (L) × 7.2 cm (W) × 1.6 cm(H), rated with input voltage: DC 3.8 V battery or DC 5V from adapter. The highest operating frequency is 2.155 GHz.

Adapter Information:

Model: V50LTE

Input: AC 100-240V, 50/60Hz, 0.15 A

Output: DC 5V, 1 A

**All measurement and test data in this report was gathered from production sample serial number: 1702679 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-12-08.*

Objective

This report is prepared on behalf of *Xwireless LLC* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS and Part 22H /24E/27 PCE submissions with FCC ID: 2ADLJV50LTE.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Parameter | | Uncertainty |
|------------------------------------|------------|-------------|
| Occupied Channel Bandwidth | | ±5% |
| RF Output Power with Power meter | | ±0.5dB |
| RF conducted test with spectrum | | ±1.5dB |
| AC Power Lines Conducted Emissions | | ±1.95dB |
| Emissions, Radiated | Below 1GHz | ±4.75dB |
| | Above 1GHz | ±4.88dB |
| Temperature | | ±3°C |
| Humidity | | ±6% |
| Supply voltages | | ±0.4% |

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 382179, the FCC Designation No. : CN5001.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1 | 2412 | 8 | 2447 |
| 2 | 2417 | 9 | 2452 |
| 3 | 2422 | 10 | 2457 |
| 4 | 2427 | 11 | 2462 |
| 5 | 2432 | 12 | 2467 |
| 6 | 2437 | 13 | 2472 |
| 7 | 2442 | / | / |

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13, add Channel 12 for 802.11g, 802.11n-HT20 mode.

For 802.11n-HT40 mode, EUT was tested with Channel 3, 7 and 11, add Channel 10.

For BLE mode, 40 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0 | 2402 | 20 | 2442 |
| 1 | 2404 | 21 | 2444 |
| 2 | 2406 | 22 | 2446 |
| 3 | 2408 | 23 | 2448 |
| 4 | 2410 | 24 | 2450 |
| 5 | 2412 | 25 | 2452 |
| 6 | 2414 | 26 | 2454 |
| 7 | 2416 | 27 | 2456 |
| 8 | 2418 | 28 | 2458 |
| 9 | 2420 | 29 | 2460 |
| 10 | 2422 | 30 | 2462 |
| 11 | 2424 | 31 | 2464 |
| 12 | 2426 | 32 | 2466 |
| 13 | 2428 | 33 | 2468 |
| 14 | 2430 | 34 | 2470 |
| 15 | 2432 | 35 | 2472 |
| 16 | 2434 | 36 | 2474 |
| 17 | 2436 | 37 | 2476 |
| 18 | 2438 | 38 | 2478 |
| 19 | 2440 | 39 | 2480 |

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & Wi-Fi test in the engineer mode.

The device was tested with worst case performed as below:


| Mode | Data rate | Power Level | | | |
|--------------|-----------|-------------|----------------|--------------|-------------|
| | | Low channel | Middle channel | High channel | Add Channel |
| 802.11b | 1 Mbps | 16 | 16 | 16 | / |
| 802.11g | 6 Mbps | 15 | 15 | 11 | 14 |
| 802.11n-HT20 | MCS0 | 15 | 15 | 10 | 14 |
| 802.11n-HT40 | MCS0 | 15 | 15 | 12 | 14 |

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

BLE was tested at default power level.


Duty cycle

802.11b mode




Date: 19.DEC.2017 14:14:21

802.11g mode




Date: 19.DEC.2017 14:13:39

802.11n-HT20 Mode




Date: 19.DEC.2017 14:12:55

802.11n-HT40 Mode



Date: 19.DEC.2017 14:12:27

BLE Mode



Date: 12.DEC.2017 17:01:43


| Band | Duty Cycle (%) | T(us) | 1/T(kHz) | VBW Setting | 10log(1/ Duty Cycle) |
|--------------|----------------|--------|----------|-------------|----------------------|
| 802.11b | 100 | - | - | 10Hz | 0 |
| 802.11g | 100 | - | - | 10Hz | 0 |
| 802.11n-HT20 | 100 | - | - | 10Hz | 0 |
| 802.11n-HT40 | 100 | - | - | 10Hz | 0 |
| BLE | 64.01 | 400.64 | 2.5 | 3kHz | 1.94 |

External I/O Cable

| Cable Description | Length (m) | From Port | To |
|-----------------------------------|------------|-----------|---------|
| Un-shielding Detachable USB Cable | 1.0 | EUT | Adapter |

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|--|--|---------------|
| §15.247 (i), §1.1307 (b) (1)& §2.1093 | RF Exposure | Compliance |
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | AC Line Conducted Emissions | Compliance |
| §15.205, §15.209, §15.247(d) | Spurious Emissions | Compliance |
| §15.247 (a)(2) | 6 dB Emission Bandwidth | Compliance |
| §15.247(b)(3) | Maximum Conducted Output Power | Compliance |
| §15.247(d) | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e) | Power Spectral Density | Compliance |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|---------------------------------|--------------------------|-------------------------|------------------------|------------------|----------------------|
| Conducted Emissions Test | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 100176 | 2017-08-04 | 2018-08-04 |
| Rohde & Schwarz | LISN | ENV216 | 3560.6650.12-101613-Yb | 2017-12-07 | 2018-12-07 |
| Rohde & Schwarz | Transient Limiter | ESH3Z2 | DE25985 | 2017-11-19 | 2018-05-21 |
| Rohde & Schwarz | CE Test software | EMC 32 | V8.53.0 | NCR | NCR |
| N/A | Conducted Emission Cable | N/A | UF A210B-1-0720-504504 | 2017-11-12 | 2018-05-12 |
| Radiated Emission Test | | | | | |
| A.H.System | Horn Antenna | SAS-200/571 | 135 | 2015-08-18 | 2018-08-17 |
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 8386001028 | 2017-04-24 | 2018-04-24 |
| Mini | Pre-amplifier | ZVA-183-S+ | 5969001149 | 2017-05-21 | 2018-05-21 |
| HP | Amplifier | HP8447E | 1937A01046 | 2017-11-19 | 2018-05-21 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-2 | 2017-12-17 | 2020-12-16 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 101120 | 2017-12-07 | 2018-12-07 |
| Ducommun technologies | RF Cable | UFA210A-1-4724-30050U | MFR64369223410-001 | 2017-11-19 | 2018-05-21 |
| Ducommun technologies | RF Cable | 104PEA | 218124002 | 2017-11-19 | 2018-05-21 |
| Ducommun technologies | RF Cable | RG-214 | 1 | 2017-11-19 | 2018-05-21 |
| Ducommun technologies | RF Cable | RG-214 | 2 | 2017-11-19 | 2018-05-21 |
| Ducommun Technologies | Horn Antenna | ARH-4223-02 | 1007726-04 | 2014-12-29 | 2017-12-28 |
| Ducommun Technologies | Horn Antenna | ARH-4223-02 | 1007726-04 | 2017-12-29 | 2020-12-28 |
| Ducommun Technologies | Pre-amplifier | ALN-22093530-01 | 991373-01 | 2017-08-03 | 2018-08-03 |
| Sinoscite | Band Reject Filter | BSF2402-2480MN-0898-001 | N/A | 2017-05-21 | 2018-05-21 |

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------|-----------------------|--------|---------------|------------------|----------------------|
| RF Conducted Test | | | | | |
| Agilent | P-Series Power Meter | N1912A | MY5000448 | 2017-12-05 | 2018-12-05 |
| Agilent | Wideband Power Sensor | N1921A | MY54210016 | 2017-12-05 | 2018-12-05 |
| WEINSCHTEL | 3 dB Attenuator | N/A | N/A | 2017-11-19 | 2018-05-21 |
| Rohde & Schwarz | SPECTRUM ANALYZER | FSU26 | 200120 | 2017-12-05 | 2018-12-05 |
| Ducommun technologies | RF Cable | RG-214 | 3 | 2017-11-22 | 2018-05-22 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

| Mode | Frequency (MHz) | Max Tune-up Conducted Power (dBm) | Max Tune-up Conducted Power (mW) | Calculated Distance (mm) | Calculated value | Threshold (1-g SAR) | SAR Test Exclusion |
|-------------|------------------------|--|---|---------------------------------|-------------------------|----------------------------|---------------------------|
| BLE | 2480 | 0 | 1.00 | 5 | 0.3 | 3.0 | Yes |
| Wi-Fi | 2472 | 9.0 | 7.94 | 5 | 2.5 | 3.0 | Yes |

Result: No SAR test is required.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 0.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Hill He on 2017-12-26.

EUT operation mode: Transmitting


BLE Mode: (worst case at Low channel)

AC 120V/60 Hz, Line



| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.344810 | 44.1 | 20.2 | 59.1 | 15.0 | QP |
| 0.411850 | 51.5 | 20.2 | 57.6 | 6.1 | QP |
| 0.427490 | 50.4 | 20.2 | 57.3 | 6.9 | QP |
| 0.644430 | 41.2 | 20.1 | 56.0 | 14.8 | QP |
| 0.849310 | 42.2 | 20.0 | 56.0 | 13.8 | QP |
| 1.550450 | 40.6 | 20.1 | 56.0 | 15.4 | QP |
| 0.344810 | 37.0 | 20.2 | 49.1 | 12.1 | Ave. |
| 0.411850 | 43.6 | 20.2 | 47.6 | 4.0 | Ave. |
| 0.427490 | 42.5 | 20.2 | 47.3 | 4.8 | Ave. |
| 0.644430 | 33.1 | 20.1 | 46.0 | 12.9 | Ave. |
| 0.849310 | 35.6 | 20.0 | 46.0 | 10.4 | Ave. |
| 1.550450 | 33.1 | 20.1 | 46.0 | 12.9 | Ave. |


AC 120V/60 Hz, Neutral



| Frequency (MHz) | Corrected Amplitude (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.424270 | 44.5 | 20.2 | 57.4 | 12.9 | QP |
| 0.444570 | 41.5 | 20.2 | 57.0 | 15.5 | QP |
| 0.853130 | 37.9 | 20.1 | 56.0 | 18.1 | QP |
| 1.673130 | 36.3 | 20.1 | 56.0 | 19.7 | QP |
| 2.630670 | 36.3 | 20.1 | 56.0 | 19.7 | QP |
| 2.965390 | 36.4 | 20.1 | 56.0 | 19.6 | QP |
| 0.424270 | 34.9 | 20.2 | 47.4 | 12.5 | Ave. |
| 0.444570 | 32.3 | 20.2 | 47.0 | 14.7 | Ave. |
| 0.853130 | 28.0 | 20.1 | 46.0 | 18.0 | Ave. |
| 1.673130 | 23.0 | 20.1 | 46.0 | 23.0 | Ave. |
| 2.630670 | 24.5 | 20.1 | 46.0 | 21.5 | Ave. |
| 2.965390 | 25.0 | 20.1 | 46.0 | 21.0 | Ave. |


Wi-Fi Mode: (worst case for 802.11n HT20 mode, middle channel)

AC 120 V/60 Hz, Line:



| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.415730 | 51.5 | 20.2 | 57.5 | 6.0 | QP |
| 0.427490 | 50.5 | 20.2 | 57.3 | 6.8 | QP |
| 0.829550 | 41.7 | 20.0 | 56.0 | 14.3 | QP |
| 1.255310 | 41.7 | 20.1 | 56.0 | 14.3 | QP |
| 1.337930 | 40.1 | 20.1 | 56.0 | 15.9 | QP |
| 1.641190 | 39.6 | 20.1 | 56.0 | 16.4 | QP |
| 0.415730 | 43.5 | 20.2 | 47.5 | 4.0 | Ave. |
| 0.427490 | 42.6 | 20.2 | 47.3 | 4.7 | Ave. |
| 0.829550 | 35.4 | 20.0 | 46.0 | 10.6 | Ave. |
| 1.255310 | 34.2 | 20.1 | 46.0 | 11.8 | Ave. |
| 1.337930 | 32.7 | 20.1 | 46.0 | 13.3 | Ave. |
| 1.641190 | 32.8 | 20.1 | 46.0 | 13.2 | Ave. |

AC 120V/ 60 Hz, Neutral:



| Frequency (MHz) | Corrected Amplitude (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.412090 | 45.8 | 20.2 | 57.6 | 11.8 | QP |
| 0.451250 | 39.6 | 20.2 | 56.9 | 17.3 | QP |
| 0.833550 | 38.8 | 20.0 | 56.0 | 17.2 | QP |
| 2.295290 | 37.0 | 20.1 | 56.0 | 19.0 | QP |
| 2.460530 | 36.7 | 20.1 | 56.0 | 19.3 | QP |
| 2.961030 | 36.8 | 20.1 | 56.0 | 19.2 | QP |
| 0.412090 | 36.2 | 20.2 | 47.6 | 11.4 | Ave. |
| 0.451250 | 29.7 | 20.2 | 46.9 | 17.2 | Ave. |
| 0.833550 | 28.0 | 20.0 | 46.0 | 18.0 | Ave. |
| 2.295290 | 25.6 | 20.1 | 46.0 | 20.4 | Ave. |
| 2.460530 | 25.3 | 20.1 | 46.0 | 20.7 | Ave. |
| 2.961030 | 25.2 | 20.1 | 46.0 | 20.8 | Ave. |

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Measurement |
|-------------------|---------|-------------------------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK |
| | 1MHz | 10 Hz ^{Note 1} | / | Average |
| | 1MHz | > 1/T ^{Note 2} | / | Average |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

| | |
|---------------------------|-----------------|
| Temperature: | 23~25 °C |
| Relative Humidity: | 49~52 % |
| ATM Pressure: | 100.0~101.0 kPa |

The testing was performed by Hill He from 2017-12-26 to 2018-01-12.

EUT operation mode: Transmitting

30 MHz~1 GHz: (worst case at 802.11n HT20 Mode, middle channel)



| Frequency (MHz) | Corrected Amplitude (dBµV/m) | Antenna height (cm) | Antenna Polarity | Turntable position (degree) | Correction Factor (dB/m) | Limit (dBµV/m) | Margin (dB) |
|-----------------|------------------------------|---------------------|------------------|-----------------------------|--------------------------|----------------|-------------|
| 30.095597 | 23.20 | 156.0 | V | 177.0 | 0.2 | 40.00 | 16.80 |
| 493.829500 | 24.85 | 183.0 | V | 228.0 | 2.6 | 46.00 | 21.15 |
| 530.717375 | 26.75 | 297.0 | V | 357.0 | 4.1 | 46.00 | 19.25 |
| 698.027625 | 28.48 | 338.0 | H | 259.0 | 6.6 | 46.00 | 17.52 |
| 818.666750 | 31.24 | 400.0 | H | 276.0 | 9.0 | 46.00 | 14.76 |
| 893.886875 | 30.90 | 109.0 | H | 329.0 | 9.6 | 46.00 | 15.10 |

1 GHz-25 GHz:

802.11b Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|---------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 2412.00 | 68.39 | PK | 53 | 2.1 | H | 33.92 | 102.31 | / | / |
| 2412.00 | 63.50 | Ave. | 53 | 2.1 | H | 33.92 | 97.42 | / | / |
| 2412.00 | 64.76 | PK | 141 | 2.4 | V | 33.92 | 98.68 | / | / |
| 2412.00 | 60.07 | Ave. | 141 | 2.4 | V | 33.92 | 93.99 | / | / |
| 2372.68 | 27.63 | PK | 254 | 1.7 | H | 33.92 | 61.55 | 74 | 12.45 |
| 2372.68 | 14.06 | Ave. | 254 | 1.7 | H | 33.92 | 47.98 | 54 | 6.02 |
| 2484.09 | 27.08 | PK | 265 | 2.2 | H | 34.08 | 61.16 | 74 | 12.84 |
| 2484.09 | 13.51 | Ave. | 265 | 2.2 | H | 34.08 | 47.59 | 54 | 6.41 |
| 4824.00 | 48.29 | PK | 158 | 2.0 | H | 5.84 | 54.13 | 74 | 19.87 |
| 4824.00 | 42.90 | Ave. | 158 | 2.0 | H | 5.84 | 48.74 | 54 | 5.26 |
| Middle Channel (2442MHz) | | | | | | | | | |
| 2442.00 | 68.21 | PK | 313 | 2.4 | H | 33.92 | 102.13 | / | / |
| 2442.00 | 63.20 | Ave. | 313 | 2.4 | H | 33.92 | 97.12 | / | / |
| 2442.00 | 66.14 | PK | 161 | 2.0 | V | 33.92 | 100.06 | / | / |
| 2442.00 | 61.47 | Ave. | 161 | 2.0 | V | 33.92 | 95.39 | / | / |
| 4884.00 | 47.25 | PK | 292 | 2.2 | H | 6.21 | 53.46 | 74 | 20.54 |
| 4884.00 | 39.93 | Ave. | 292 | 2.2 | H | 6.21 | 46.14 | 54 | 7.86 |
| High Channel (2472 MHz) | | | | | | | | | |
| 2472.00 | 66.67 | PK | 10 | 2.3 | H | 34.08 | 100.75 | / | / |
| 2472.00 | 62.05 | Ave. | 10 | 2.3 | H | 34.08 | 96.13 | / | / |
| 2472.00 | 64.06 | PK | 340 | 1.8 | V | 34.08 | 98.14 | / | / |
| 2472.00 | 59.47 | Ave. | 340 | 1.8 | V | 34.08 | 93.55 | / | / |
| 2381.40 | 27.42 | PK | 190 | 1.5 | H | 33.92 | 61.34 | 74 | 12.66 |
| 2381.40 | 14.02 | Ave. | 190 | 1.5 | H | 33.92 | 47.94 | 54 | 6.06 |
| 2494.01 | 27.76 | PK | 195 | 1.2 | H | 34.08 | 61.84 | 74 | 12.16 |
| 2494.01 | 14.03 | Ave. | 195 | 1.2 | H | 34.08 | 48.11 | 54 | 5.89 |
| 4884.00 | 44.37 | PK | 207 | 1.5 | H | 6.21 | 50.58 | 74 | 23.42 |
| 4884.00 | 34.44 | Ave. | 207 | 1.5 | H | 6.21 | 40.65 | 54 | 13.35 |

802.11g Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|---------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 2412.00 | 68.11 | PK | 236 | 2.3 | H | 33.92 | 102.03 | / | / |
| 2412.00 | 56.59 | Ave. | 236 | 2.3 | H | 33.92 | 90.51 | / | / |
| 2412.00 | 67.43 | PK | 146 | 1.8 | V | 33.92 | 101.35 | / | / |
| 2412.00 | 56.17 | Ave. | 146 | 1.8 | V | 33.92 | 90.09 | / | / |
| 2380.50 | 27.86 | PK | 154 | 1.4 | H | 33.92 | 61.78 | 74 | 12.22 |
| 2380.50 | 14.36 | Ave. | 154 | 1.4 | H | 33.92 | 48.28 | 54 | 5.72 |
| 2498.64 | 27.91 | PK | 348 | 2.4 | H | 34.08 | 61.99 | 74 | 12.01 |
| 2498.64 | 13.71 | Ave. | 348 | 2.4 | H | 34.08 | 47.79 | 54 | 6.21 |
| 4824.00 | 50.03 | PK | 334 | 2.3 | H | 5.84 | 55.87 | 74 | 18.13 |
| 4824.00 | 31.02 | Ave. | 334 | 2.3 | H | 5.84 | 36.86 | 54 | 17.14 |
| Middle Channel (2442MHz) | | | | | | | | | |
| 2442.00 | 68.59 | PK | 234 | 1.4 | H | 33.92 | 102.51 | / | / |
| 2442.00 | 56.73 | Ave. | 234 | 1.4 | H | 33.92 | 90.65 | / | / |
| 2442.00 | 65.87 | PK | 262 | 2.1 | V | 33.92 | 99.79 | / | / |
| 2442.00 | 54.23 | Ave. | 262 | 2.1 | V | 33.92 | 88.15 | / | / |
| 4882.00 | 49.87 | PK | 112 | 2.1 | H | 6.21 | 56.08 | 74 | 17.92 |
| 4882.00 | 30.57 | Ave. | 112 | 2.1 | H | 6.21 | 36.78 | 54 | 17.22 |
| High Channel (2467 MHz) | | | | | | | | | |
| 2467.00 | 67.96 | PK | 155 | 1.5 | H | 34.08 | 102.04 | / | / |
| 2467.00 | 55.32 | Ave. | 155 | 1.5 | H | 34.08 | 89.40 | / | / |
| 2467.00 | 64.28 | PK | 241 | 1.5 | V | 34.08 | 98.36 | / | / |
| 2467.00 | 52.08 | Ave. | 241 | 1.5 | V | 34.08 | 86.16 | / | / |
| 2374.36 | 27.34 | PK | 360 | 1.2 | H | 33.92 | 61.26 | 74 | 12.74 |
| 2374.36 | 14.26 | Ave. | 360 | 1.2 | H | 33.92 | 48.18 | 54 | 5.82 |
| 2483.84 | 28.31 | PK | 238 | 1.2 | H | 34.08 | 62.39 | 74 | 11.61 |
| 2483.84 | 14.11 | Ave. | 238 | 1.2 | H | 34.08 | 48.19 | 54 | 5.81 |
| 4934.00 | 52.37 | PK | 343 | 1.0 | H | 6.21 | 58.58 | 74 | 15.42 |
| 4934.00 | 27.98 | Ave. | 343 | 1.0 | H | 6.21 | 34.19 | 54 | 19.81 |
| High Channel (2472 MHz) | | | | | | | | | |
| 2472.00 | 62.91 | PK | 340 | 1.6 | H | 34.08 | 96.99 | / | / |
| 2472.00 | 52.23 | Ave. | 340 | 1.6 | H | 34.08 | 86.31 | / | / |
| 2472.00 | 59.52 | PK | 68 | 1.7 | V | 34.08 | 93.60 | / | / |
| 2472.00 | 48.35 | Ave. | 68 | 1.7 | V | 34.08 | 82.43 | / | / |
| 2352.32 | 27.81 | PK | 72 | 1.1 | H | 33.92 | 61.73 | 74 | 12.27 |
| 2352.32 | 14.24 | Ave. | 72 | 1.1 | H | 33.92 | 48.16 | 54 | 5.84 |
| 2498.21 | 26.83 | PK | 1 | 1.5 | H | 34.08 | 60.91 | 74 | 13.09 |
| 2498.21 | 13.42 | Ave. | 1 | 1.5 | H | 34.08 | 47.50 | 54 | 6.50 |
| 4944.00 | 43.52 | PK | 72 | 1.0 | H | 6.21 | 49.73 | 74 | 24.27 |
| 4944.00 | 30.14 | Ave. | 72 | 1.0 | H | 6.21 | 36.35 | 54 | 17.65 |

802.11n-HT20 Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|---------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| Low Channel (2412 MHz) | | | | | | | | | |
| 2412.00 | 69.32 | PK | 284 | 1.2 | H | 33.92 | 103.24 | / | / |
| 2412.00 | 57.77 | Ave. | 284 | 1.2 | H | 33.92 | 91.69 | / | / |
| 2412.00 | 65.87 | PK | 125 | 1.4 | V | 33.92 | 99.79 | / | / |
| 2412.00 | 54.13 | Ave. | 125 | 1.4 | V | 33.92 | 88.05 | / | / |
| 2389.59 | 28.64 | PK | 281 | 2.2 | H | 33.92 | 62.56 | 74 | 11.44 |
| 2389.59 | 14.10 | Ave. | 281 | 2.2 | H | 33.92 | 48.02 | 54 | 5.98 |
| 2487.62 | 28.52 | PK | 60 | 1.1 | H | 34.08 | 62.60 | 74 | 11.40 |
| 2487.62 | 13.25 | Ave. | 60 | 1.1 | H | 34.08 | 47.33 | 54 | 6.67 |
| 4824.00 | 62.87 | PK | 261 | 1.6 | H | 5.84 | 68.71 | 74 | 5.29 |
| 4824.00 | 40.96 | Ave. | 94 | 1.7 | H | 5.84 | 46.80 | 54 | 7.20 |
| Middle Channel (2442MHz) | | | | | | | | | |
| 2442.00 | 68.23 | PK | 32 | 2.0 | H | 33.92 | 102.15 | / | / |
| 2442.00 | 56.85 | Ave. | 32 | 2.0 | H | 33.92 | 90.77 | / | / |
| 2442.00 | 65.80 | PK | 344 | 2.2 | V | 33.92 | 99.72 | / | / |
| 2442.00 | 54.17 | Ave. | 344 | 2.2 | V | 33.92 | 88.09 | / | / |
| 4884.00 | 54.69 | PK | 335 | 1.7 | H | 6.21 | 60.90 | 74 | 13.10 |
| 4884.00 | 39.87 | Ave. | 335 | 1.7 | H | 6.21 | 46.08 | 54 | 7.92 |
| High Channel (2467 MHz) | | | | | | | | | |
| 2467.00 | 68.31 | PK | 349 | 1.7 | H | 34.08 | 102.39 | / | / |
| 2467.00 | 56.93 | Ave. | 349 | 1.7 | H | 34.08 | 91.01 | / | / |
| 2467.00 | 65.20 | PK | 18 | 1.4 | V | 34.08 | 99.28 | / | / |
| 2467.00 | 52.87 | Ave. | 18 | 1.4 | V | 34.08 | 86.95 | / | / |
| 2374.36 | 28.02 | PK | 124 | 1.0 | H | 33.92 | 61.94 | 74 | 12.06 |
| 2374.36 | 14.12 | Ave. | 124 | 1.0 | H | 33.92 | 48.04 | 54 | 5.96 |
| 2483.84 | 32.77 | PK | 10 | 1.9 | H | 34.08 | 66.85 | 74 | 7.15 |
| 2483.84 | 16.21 | Ave. | 10 | 1.9 | H | 34.08 | 50.29 | 54 | 3.71 |
| 4934.00 | 51.39 | PK | 321 | 1.6 | H | 6.21 | 57.60 | 74 | 16.40 |
| 4934.00 | 37.23 | Ave. | 321 | 1.6 | H | 6.21 | 43.44 | 54 | 10.56 |
| High Channel (2472 MHz) | | | | | | | | | |
| 2472.00 | 61.67 | PK | 57 | 2.2 | H | 34.08 | 95.75 | / | / |
| 2472.00 | 50.34 | Ave. | 57 | 2.2 | H | 34.08 | 84.42 | / | / |
| 2472.00 | 57.61 | PK | 98 | 1.7 | V | 34.08 | 91.69 | / | / |
| 2472.00 | 45.89 | Ave. | 98 | 1.7 | V | 34.08 | 79.97 | / | / |
| 2384.26 | 28.14 | PK | 87 | 1.2 | H | 33.92 | 62.06 | 74 | 11.94 |
| 2384.26 | 13.98 | Ave. | 87 | 1.2 | H | 33.92 | 47.90 | 54 | 6.10 |
| 2483.50 | 28.31 | PK | 36 | 1.1 | H | 34.08 | 62.39 | 74 | 11.61 |
| 2483.50 | 14.80 | Ave. | 36 | 1.1 | H | 34.08 | 48.88 | 54 | 5.12 |
| 4944.00 | 46.21 | PK | 257 | 2.1 | H | 6.21 | 52.42 | 74 | 21.58 |
| 4944.00 | 30.24 | Ave. | 257 | 2.1 | H | 6.21 | 36.45 | 54 | 17.55 |

802.11n-HT40 Mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|---------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| Low Channel (2422 MHz) | | | | | | | | | |
| 2422.00 | 65.66 | PK | 157 | 1.1 | H | 33.92 | 99.58 | / | / |
| 2422.00 | 54.50 | Ave. | 157 | 1.1 | H | 33.92 | 88.42 | / | / |
| 2422.00 | 63.11 | PK | 302 | 1.6 | V | 33.92 | 97.03 | / | / |
| 2422.00 | 50.78 | Ave. | 302 | 1.6 | V | 33.92 | 84.70 | / | / |
| 2385.35 | 29.38 | PK | 178 | 2.3 | H | 33.92 | 63.30 | 74 | 10.70 |
| 2385.35 | 15.75 | Ave. | 178 | 2.3 | H | 33.92 | 49.67 | 54 | 4.33 |
| 2497.78 | 27.16 | PK | 292 | 2.2 | H | 34.08 | 61.24 | 74 | 12.76 |
| 2497.78 | 13.52 | Ave. | 292 | 2.2 | H | 34.08 | 47.60 | 54 | 6.40 |
| 4844.00 | 51.51 | PK | 316 | 1.2 | H | 5.84 | 57.35 | 74 | 16.65 |
| 4844.00 | 38.14 | Ave. | 316 | 1.2 | H | 5.84 | 43.98 | 54 | 10.02 |
| Middle Channel (2442MHz) | | | | | | | | | |
| 2442.00 | 65.64 | PK | 4 | 1.7 | H | 33.92 | 99.56 | / | / |
| 2442.00 | 54.32 | Ave. | 4 | 1.7 | H | 33.92 | 88.24 | / | / |
| 2442.00 | 62.38 | PK | 27 | 1.8 | V | 33.92 | 96.30 | / | / |
| 2442.00 | 50.19 | Ave. | 27 | 1.8 | V | 33.92 | 84.11 | / | / |
| 4884.00 | 51.03 | PK | 82 | 2.5 | H | 6.21 | 57.24 | 74 | 16.76 |
| 4884.00 | 36.88 | Ave. | 82 | 2.5 | H | 6.21 | 43.09 | 54 | 10.91 |
| High Channel (2457 MHz) | | | | | | | | | |
| 2457.00 | 65.21 | PK | 17 | 2.0 | H | 34.08 | 99.29 | / | / |
| 2457.00 | 53.01 | Ave. | 17 | 2.0 | H | 34.08 | 87.09 | / | / |
| 2457.00 | 61.74 | PK | 211 | 1.3 | V | 34.08 | 95.82 | / | / |
| 2457.00 | 49.58 | Ave. | 211 | 1.3 | V | 34.08 | 83.66 | / | / |
| 2376.31 | 27.84 | PK | 280 | 2.5 | H | 34.08 | 61.92 | 74 | 12.08 |
| 2376.31 | 13.98 | Ave. | 280 | 2.5 | H | 34.08 | 48.06 | 54 | 5.94 |
| 2483.84 | 30.28 | PK | 298 | 1.3 | H | 34.08 | 64.36 | 74 | 9.64 |
| 2483.84 | 14.85 | Ave. | 298 | 1.3 | H | 34.08 | 48.93 | 54 | 5.07 |
| 4914.00 | 50.21 | PK | 92 | 1.6 | H | 6.21 | 56.42 | 74 | 17.58 |
| 4914.00 | 38.63 | Ave. | 92 | 1.6 | H | 6.21 | 44.84 | 54 | 9.16 |

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|--------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| High Channel (2462 MHz) | | | | | | | | | |
| 2462.00 | 61.34 | PK | 302 | 1.5 | H | 34.08 | 95.42 | / | / |
| 2462.00 | 49.86 | Ave. | 302 | 1.5 | H | 34.08 | 83.94 | / | / |
| 2462.00 | 59.71 | PK | 89 | 2.4 | V | 34.08 | 93.79 | / | / |
| 2462.00 | 48.02 | Ave. | 89 | 2.4 | V | 34.08 | 82.10 | / | / |
| 2388.55 | 27.44 | PK | 75 | 1.5 | H | 33.92 | 61.36 | 74 | 12.64 |
| 2388.55 | 13.97 | Ave. | 75 | 1.5 | H | 33.92 | 47.89 | 54 | 6.11 |
| 2483.50 | 29.97 | PK | 249 | 1.4 | H | 34.08 | 64.05 | 74 | 9.95 |
| 2483.50 | 15.10 | Ave. | 249 | 1.4 | H | 34.08 | 49.18 | 54 | 4.82 |
| 4924.00 | 46.32 | PK | 229 | 1.7 | H | 6.21 | 52.53 | 74 | 21.47 |
| 4924.00 | 31.47 | Ave. | 229 | 1.7 | H | 6.21 | 37.68 | 54 | 16.32 |

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.


Pre-scan with 802.11n HT20 Mode, low channel Horizontal

Ref Lvl 97 dBμV Marker 1 [T1] 62.64 dBμV RBW 1 MHz RF Att 0 dB
97 dBμV 4.81563126 GHz VBW 3 MHz Unit dBμV
SWT 98 ms



Date: 12.JAN.2018 11:37:59


Ref Lvl 97 dBμV Marker 1 [T1] 56.28 dBμV RBW 1 MHz RF Att 0 dB
97 dBμV 24.90180361 GHz VBW 3 MHz Unit dBμV
SWT 40 ms



Date: 12.JAN.2018 12:20:10


Vertical

 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
Ref Lvl 60.86 dB μ V VBW 3 MHz
97 dB μ V 4.81563126 GHz SWT 98 ms Unit dB μ V



Date: 12.JAN.2018 11:35:27

 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
Ref Lvl 56.43 dB μ V VBW 3 MHz
97 dB μ V 24.95791583 GHz SWT 40 ms Unit dB μ V



Date: 12.JAN.2018 12:24:10

For BLE mode:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dBµV/m) | FCC Part 15.247/205/209 | |
|----------------------------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|-------------------------|-------------|
| | Reading (dBµV) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dBµV/m) | Margin (dB) |
| Low Channel (2402 MHz) | | | | | | | | | |
| 2402.00 | 64.47 | PK | 311 | 2.3 | H | 33.92 | 97.08 | / | / |
| 2402.00 | 59.38 | Ave. | 311 | 2.3 | H | 33.92 | 92.00 | / | / |
| 2402.00 | 63.16 | PK | 182 | 2.0 | V | 33.92 | 98.39 | / | / |
| 2402.00 | 58.08 | Ave. | 182 | 2.0 | V | 33.92 | 93.17 | / | / |
| 2388.59 | 28.91 | PK | 219 | 2.3 | H | 33.92 | 62.83 | 74 | 11.17 |
| 2388.59 | 14.10 | Ave. | 219 | 2.3 | H | 33.92 | 48.02 | 54 | 5.98 |
| 2488.85 | 27.01 | PK | 233 | 1.9 | H | 34.08 | 61.09 | 74 | 12.91 |
| 2488.85 | 13.45 | Ave. | 233 | 1.9 | H | 34.08 | 47.53 | 54 | 6.47 |
| 4804.00 | 50.57 | PK | 256 | 1.7 | H | 5.84 | 56.41 | 74 | 17.59 |
| 4804.00 | 42.02 | Ave. | 256 | 1.7 | H | 5.84 | 47.86 | 54 | 6.14 |
| Middle Channel (2440 MHz) | | | | | | | | | |
| 2440.00 | 62.90 | PK | 205 | 2.1 | H | 33.92 | 96.82 | / | / |
| 2440.00 | 57.49 | Ave. | 205 | 2.1 | H | 33.92 | 91.41 | / | / |
| 2440.00 | 61.18 | PK | 138 | 2.2 | V | 33.92 | 95.10 | / | / |
| 2440.00 | 56.03 | Ave. | 138 | 2.2 | V | 33.92 | 89.95 | / | / |
| 4880.00 | 50.44 | PK | 312 | 2.4 | H | 6.21 | 56.65 | 74 | 17.35 |
| 4880.00 | 41.86 | Ave. | 312 | 2.4 | H | 6.21 | 48.07 | 54 | 5.93 |
| High Channel (2480 MHz) | | | | | | | | | |
| 2480.00 | 62.69 | PK | 65 | 2.3 | H | 34.08 | 96.77 | / | / |
| 2480.00 | 57.24 | Ave. | 65 | 2.3 | H | 34.08 | 91.32 | / | / |
| 2480.00 | 59.54 | PK | 144 | 1.4 | V | 34.08 | 93.62 | / | / |
| 2480.00 | 54.36 | Ave. | 144 | 1.4 | V | 34.08 | 88.44 | / | / |
| 2357.93 | 27.56 | PK | 221 | 1.3 | H | 33.92 | 61.48 | 74 | 12.52 |
| 2357.93 | 13.98 | Ave. | 221 | 1.3 | H | 33.92 | 47.90 | 54 | 6.10 |
| 2483.50 | 29.32 | PK | 23 | 2.3 | H | 34.08 | 63.40 | 74 | 10.60 |
| 2483.50 | 15.22 | Ave. | 23 | 2.3 | H | 34.08 | 49.30 | 54 | 4.70 |
| 4960.00 | 49.87 | PK | 45 | 1.6 | H | 7.82 | 57.69 | 74 | 16.31 |
| 4960.00 | 39.82 | Ave. | 196 | 1.2 | H | 7.82 | 47.64 | 54 | 6.36 |

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.

**Pre-scan with BLE mode, High channel
Horizontal**



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

| | |
|---------------------------|---------------|
| Temperature: | 21~25 °C |
| Relative Humidity: | 51~52 % |
| ATM Pressure: | 100~101.0 kPa |

The testing was performed by Hill He from 2017-12-12 to 2017-12-25.

Test Result: Pass.


Please refer to the following table and plots.

EUT operation mode: Transmitting

| Channel | Frequency (MHz) | 6 dB Emission Bandwidth (MHz) | Limit (kHz) |
|-------------------|-----------------|-------------------------------|-------------|
| 802.11b mode | | | |
| Low | 2412 | 9.28 | ≥500 |
| Middle | 2442 | 9.18 | ≥500 |
| High | 2472 | 9.13 | ≥500 |
| 802.11g mode | | | |
| Low | 2412 | 16.44 | ≥500 |
| Middle | 2442 | 16.44 | ≥500 |
| High | 2472 | 16.54 | ≥500 |
| Channel 12 | 2467 | 16.59 | ≥500 |
| 802.11n-HT20 mode | | | |
| Low | 2412 | 17.64 | ≥500 |
| Middle | 2442 | 17.69 | ≥500 |
| High | 2472 | 17.84 | ≥500 |
| Channel 12 | 2467 | 17.84 | ≥500 |
| 802.11n-HT40 mode | | | |
| Low | 2422 | 36.06 | ≥500 |
| Middle | 2442 | 36.25 | ≥500 |
| High | 2462 | 36.49 | ≥500 |
| Channel 10 | 2457 | 36.11 | ≥500 |


| Channel | Frequency (MHz) | 6 dB Emission Bandwidth(MHz) | Limit (kHz) |
|---------|-----------------|------------------------------|-------------|
| Low | 2402 | 0.721 | ≥500 |
| Middle | 2440 | 0.721 | ≥500 |
| High | 2480 | 0.689 | ≥500 |

802.11b Low Channel




Date: 19.DEC.2017 14:16:05

802.11b Middle Channel




Date: 19.DEC.2017 14:18:00

802.11b High Channel




Date: 19.DEC.2017 14:19:14

802.11g Low Channel




Date: 19.DEC.2017 14:21:45

802.11g Middle Channel




Date: 19.DEC.2017 14:22:52

802.11g High Channel




Date: 25.DEC.2017 10:17:50

802.11g Channel 12




Date: 25.DEC.2017 09:59:02

802.11n-HT20 Low Channel




Date: 19.DEC.2017 14:25:24

802.11n-HT20 Middle Channel




Date: 19.DEC.2017 14:26:34

802.11n-HT20 High Channel




Date: 25.DEC.2017 10:19:18

802.11n-HT20 Channel 12




Date: 25.DEC.2017 09:57:03

802.11n-HT40 Low Channel




Date: 19.DEC.2017 14:28:44

802.11n-HT40 Middle Channel




Date: 19.DEC.2017 14:29:52

802.11n-HT40 High Channel




Date: 25.DEC.2017 10:20:33

802.11n-HT40 Channel 10




Date: 25.DEC.2017 10:00:46

BLE Low Channel




Date: 12.DEC.2017 16:56:40

BLE Middle Channel



Date: 12.DEC.2017 16:55:51

BLE High Channel



Date: 12.DEC.2017 16:54:13


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Hill He on 2017-12-12.

EUT operation mode: Transmitting

Wi-Fi mode

| Channel | Frequency (MHz) | Max Conducted Peak Output Power (dBm) | Max Conducted Average Output Power (dBm) | Limit (dBm) |
|--------------|-----------------|---------------------------------------|--|-------------|
| 802.11b | | | | |
| Low | 2412 | 10.80 | 8.27 | 30 |
| Middle | 2442 | 10.96 | 8.34 | 30 |
| High | 2472 | 10.90 | 8.26 | 30 |
| 802.11g | | | | |
| Low | 2412 | 14.48 | 8.51 | 30 |
| Middle | 2442 | 14.74 | 8.67 | 30 |
| High | 2472 | 10.73 | 4.94 | 30 |
| Channel 12 | 2467 | 14.09 | 8.32 | 30 |
| 802.11n HT20 | | | | |
| Low | 2412 | 14.87 | 8.59 | 30 |
| Middle | 2442 | 15.09 | 8.83 | 30 |
| High | 2472 | 10.52 | 4.61 | 30 |
| Channel 12 | 2467 | 14.42 | 8.23 | 30 |
| 802.11n HT40 | | | | |
| Low | 2412 | 14.67 | 8.59 | 30 |
| Middle | 2442 | 14.58 | 8.83 | 30 |
| High | 2472 | 12.06 | 4.61 | 30 |
| Channel 10 | 2457 | 14.88 | 8.23 | 30 |

BLE mode

| Channel | Frequency (MHz) | Max Peak Output Power (dBm) | Limit (dBm) | Result |
|---------|-----------------|-----------------------------|-------------|--------|
| Low | 2402 | -0.29 | 30 | Pass |
| Middle | 2440 | -0.77 | 30 | Pass |
| High | 2480 | -1.27 | 30 | Pass |


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

| | |
|---------------------------|-----------------|
| Temperature: | 21~25 °C |
| Relative Humidity: | 19~52 % |
| ATM Pressure: | 100.0~101.0 kPa |


The testing was performed by Hill He from 2017-12-12 to 2018-01-29.

EUT operation mode: Transmitting

Test Result: Compliance


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 19.DEC.2017 14:50:38

802.11b: Band Edge, Right Side




Date: 19.DEC.2017 14:51:36

802.11g: Band Edge, Left Side




Date: 19.DEC.2017 14:49:54

802.11g: Band Edge, Right Side




Date: 22.DEC.2017 09:44:42

802.11g: Band Edge, Right Side (Channel 12)




Date: 29.JAN.2018 16:14:50

802.11n-HT20: Band Edge, Left Side




Date: 19.DEC.2017 14:42:52

802.11n-HT20: Band Edge, Right Side




Date: 22.DEC.2017 09:56:03

802.11n-HT20: Band Edge, Right Side (Channel 12)




Date: 29.JAN.2018 16:10:45

802.11n-HT40: Band Edge, Left Side




Date: 19.DEC.2017 14:47:36

802.11n-HT40: Band Edge, Right Side




Date: 22.DEC.2017 09:41:13

802.11n-HT40: Band Edge, Right Side (Channel 10)




Date: 29.JAN.2018 14:57:13

BLE: Band Edge, Left Side



Date: 12.DEC.2017 16:57:51

BLE: Band Edge, Right Side



Date: 12.DEC.2017 16:58:47


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

| | |
|---------------------------|---------------|
| Temperature: | 21~25 °C |
| Relative Humidity: | 19~52 % |
| ATM Pressure: | 100~101.0 kPa |


The testing was performed by Hill He from 2017-12-12 to 2018-01-13.

EUT operation mode: Transmitting

Test Result: Pass


| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|-------------------|-----------------|----------------|------------------|
| 802.11b mode | | | |
| Low | 2412 | -21.10 | ≤8 |
| Middle | 2442 | -20.19 | ≤8 |
| High | 2472 | -20.28 | ≤8 |
| 802.11g mode | | | |
| Low | 2412 | -15.95 | ≤8 |
| Middle | 2442 | -17.70 | ≤8 |
| High | 2472 | -21.92 | ≤8 |
| Channel 12 | 2467 | -22.45 | ≤8 |
| 802.11n-HT20 mode | | | |
| Low | 2412 | -22.41 | ≤8 |
| Middle | 2437 | -20.19 | ≤8 |
| High | 2472 | -23.55 | ≤8 |
| Channel 12 | 2467 | -21.72 | ≤8 |
| 802.11n-HT40 mode | | | |
| Low | 2422 | -23.45 | ≤8 |
| Middle | 2437 | -22.30 | ≤8 |
| High | 2452 | -26.04 | ≤8 |
| Channel 10 | 2457 | -23.16 | ≤8 |
| BLE mode | | | |
| Low | 2402 | -16.18 | ≤8 |
| Middle | 2440 | -16.25 | ≤8 |
| High | 2480 | -16.82 | ≤8 |

Power Spectral Density, 802.11b Low Channel




Date: 25.DEC.2017 11:07:35

Power Spectral Density, 802.11b Middle Channel




Date: 25.DEC.2017 11:08:22

Power Spectral Density, 802.11b High Channel




Date: 25.DEC.2017 11:08:54

Power Spectral Density, 802.11g Low Channel




Date: 25.DEC.2017 11:09:44

Power Spectral Density, 802.11g Middle Channel




Date: 25.DEC.2017 11:10:28

Power Spectral Density, 802.11g High Channel




Date: 25.DEC.2017 11:11:05

Power Spectral Density, Channel 12




Date: 25.DEC.2017 11:11:53

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 25.DEC.2017 11:12:45

Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 25.DEC.2017 11:13:24

Power Spectral Density, 802.11n-HT20 High Channel




Date: 25.DEC.2017 11:14:12

Power Spectral Density, 802.11n-HT20 Channel 12




Date: 25.DEC.2017 11:14:50

Power Spectral Density, 802.11n-HT40 Low Channel




Date: 25.DEC.2017 11:15:49

Power Spectral Density, 802.11n-HT40 Middle Channel




Date: 25.DEC.2017 11:16:44

Power Spectral Density, 802.11n-HT40 High Channel




Date: 25.DEC.2017 11:17:29

Power Spectral Density, 802.11n-HT40 Channel 10




Date: 25.DEC.2017 11:18:41

Power Spectral Density, BLE Low Channel




Date: 13.JAN.2018 15:56:43

Power Spectral Density, BLE Middle Channel



Date: 12.DEC.2017 17:04:45

Power Spectral Density, BLE High Channel



Date: 12.DEC.2017 17:06:04

***** END OF REPORT *****