

Application Information	
Version	1.243.331
TotalTime	1m 17s 934ms
AdditionalInfor	NULL
Model	3216
Manufacturer: Shenzhen Bluetrum Technology Co., Ltd	
Address: Building A, Wisdom Plaza, c.4068 Qiaoxiang Road, Gaofa Community, Shahu Street, Nanshan District, Shenzhen, China	

Passive Test For BT2_4												
Freq (MHz)	Eff1 (%)	Eff1 (dB)	Gain (dBi)	Gain (dBd)	UBIS (%)	UBIS (dB)	Max (dB)	Min (dB)	Directivity (dB)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	39.04	-4.00	0.52	-1.63	0	0	0.52	-15.74	4.00	60	47.36	46.86
2440	38.11	-4.98	0.73	-1.41	0	0	0.73	-16.63	4.98	60	47.4	46.9
2470	35.53	-5.52	0.47	-1.88	0	0	0.47	-17.32	5.52	60	47.28	46.75
2430	39.98	-3.98	1.14	-1.01	0	0	1.14	-17.19	3.98	30	47.33	46.78
2440	37.5	-4.26	0.98	-1.17	0	0	0.98	-17.75	4.26	30	47.15	46.65
2450	44.14	-3.55	1.89	-0.46	0	0	1.89	-17.33	3.55	30	47.33	46.85
2460	39.63	-4.03	1.17	-0.98	0	0	1.17	-18.04	4.03	60	47.73	47.23
2470	38.25	-4.17	0.95	-1.2	0	0	0.95	-18.88	4.17	60	47.36	46.93
2480	49.71	-3.04	2.96	-0.19	0	0	2.96	-18.94	3.04	60	47.59	47.14
2490	41.14	-3.86	1.2	-0.95	0	0	1.2	-19.39	3.86	60	47.03	46.67
2500	43.15	-3.65	1.32	-0.83	0	0	1.32	-19.07	3.65	60	47.01	46.63

