




FCC PART 15.247 TEST REPORT

For

Zeeva International Limited

Suite 1007B, 10th Floor, Exchange Tower 33 Wang Chiu Road, Kowloon Bay,
HongKong, China

FCC ID:2ADM5-SP-0691

Report Type: Original Report	Product Type: BT LED LAYER SPEAKER
Report Number: <u>RSZ190704831-00</u>	
Report Date: <u>2019-08-05</u>	
Reviewed By: RF Engineer	Nancy Wang 
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS.....	6
SUPPORT EQUIPMENT LIST AND DETAILS.....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP.....	7
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST.....	9
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE.....	11
APPLICABLE STANDARD.....	11
FCC §15.203 – ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD.....	12
ANTENNA CONNECTOR CONSTRUCTION.....	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	13
APPLICABLE STANDARD.....	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE.....	13
CORRECTED FACTOR & MARGIN CALCULATION.....	14
TEST RESULTS SUMMARY.....	14
TEST DATA.....	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	17
APPLICABLE STANDARD.....	17
EUT SETUP.....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	18
TEST PROCEDURE.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
TEST RESULTS SUMMARY.....	18
TEST DATA.....	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST.....	26
APPLICABLE STANDARD.....	26
TEST PROCEDURE.....	26
TEST DATA.....	26

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....33
 APPLICABLE STANDARD33
 TEST PROCEDURE33
 TEST DATA33

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST39
 APPLICABLE STANDARD39
 TEST PROCEDURE39
 TEST DATA39

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....42
 APPLICABLE STANDARD42
 TEST PROCEDURE42
 TEST DATA42

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT58
 APPLICABLE STANDARD58
 TEST PROCEDURE58
 TEST DATA58

FCC §15.247(d) - BAND EDGES TESTING59
 APPLICABLE STANDARD59
 TEST PROCEDURE59
 TEST DATA59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	BT LED LAYER SPEAKER
Tested Model	SP-0691
UPC Number	192234031735
SKU Number	3190030
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Power	Bluetooth: 1.38dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification	0dBi
Voltage Range	DC 3.7 V from battery
Date of Test	2019-07-22 to 2019-08-02
Sample serial number	190704831
Received date	2019-07-04
Sample/EUT Status	Good condition

Objective

This test report is prepared on behalf of *Zeeva International Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1°C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

“BT_Tool V1.0.8.exe” software was made to the EUT tested and the power level is 7.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Adapter	RH-050100JP	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding detachable USB Cable	0.3	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2019-07-11	2020-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-01
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Unknown	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
Radiated Emission Test					
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019-07-22	2020-07-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun Technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Sinoscite	Band Reject Filter	BSF2402-2480MN-0898-001	99632	2018-11-12	2019-11-12
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	USB wideband power meter	U2021XA	MY54250003	2019-07-10	2020-07-09
WEINSCHL	3dB Attenuator	6231	666	Each Time	
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2019-03-02	2020-03-01
Ducommun Technologies	RF Cable	RG-214	3	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
2480	1.5	1.41	5	0.44	3.0	Yes

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-08-02.


EUT operation mode: Transmitting & charging (the worst case is GFSK Mode, middle channel)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.241500	30.9	19.8	62.0	31.1	QP
0.289500	33.0	19.7	60.5	27.5	QP
0.336870	36.1	19.8	59.3	23.2	QP
0.352630	34.8	19.9	58.9	24.1	QP
0.498470	31.5	19.8	56.0	24.6	QP
0.766510	20.1	19.8	56.0	35.9	QP
0.241500	26.4	19.8	52.0	25.6	Ave.
0.289500	26.5	19.7	50.5	24.0	Ave.
0.336870	29.6	19.8	49.3	19.7	Ave.
0.352630	28.5	19.9	48.9	20.4	Ave.
0.498470	22.5	19.8	46.0	23.5	Ave.
0.766510	14.5	19.8	46.0	31.5	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.242501	32.9	19.8	62.0	29.1	QP
0.302500	35.5	19.7	60.2	24.7	QP
0.343070	34.6	19.8	59.1	24.5	QP
0.352630	36.9	19.9	58.9	22.0	QP
0.518170	32.3	19.8	56.0	23.7	QP
0.987210	27.7	19.8	56.0	28.3	QP
0.242501	28.4	19.8	52.0	23.6	Ave.
0.302500	28.7	19.7	50.2	21.5	Ave.
0.343070	28.7	19.8	49.1	20.4	Ave.
0.352630	30.4	19.9	48.9	18.5	Ave.
0.518170	24.2	19.8	46.0	21.8	Ave.
0.987210	21.1	19.8	46.0	24.9	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, according to the DA 00-705 Released March 30, 2000, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BAEL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	24~25 °C
Relative Humidity:	52~56 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Steve Lan on 2019-08-01 and Curry Xiang on 2019-07-22.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK mode, the worst case is GFSK Mode)

30 MHz~1 GHz: (the worst case is GFSK Mode, middle channel)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
104.005875	31.96	262.0	H	295.0	-16.5	43.50	11.54
156.017250	28.28	231.0	H	331.0	-14.3	43.50	15.22
312.004125	34.72	108.0	H	15.0	-10.7	46.00	11.28
364.002500	38.72	139.0	V	44.0	-10.7	46.00	7.28
855.486000	27.85	192.0	H	179.0	6.7	46.00	18.15
927.769875	29.49	116.0	V	0.0	7.4	46.00	16.51

1 GHz - 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2354.86	27.89	PK	105	2.2	H	31.77	59.66	74	14.34
2354.86	13.66	Ave.	105	2.2	H	31.77	45.43	54	8.57
2494.85	28.08	PK	267	1.1	H	32.13	60.21	74	13.79
2494.85	13.72	Ave.	267	1.1	H	32.13	45.85	54	8.15
4804.00	57.37	PK	12	1.5	H	6.28	63.65	74	10.35
4804.00	43.69	Ave.	12	1.5	H	6.28	49.97	54	4.03
Middle Channel (2441 MHz)									
4882.00	56.34	PK	78	1.8	H	6.76	63.10	74	10.90
4882.00	44.07	Ave.	78	1.8	H	6.76	50.83	54	3.17
High Channel (2480 MHz)									
2364.12	28.40	PK	127	1.9	H	31.87	60.27	74	13.73
2364.12	14.65	Ave.	127	1.9	H	31.87	46.52	54	7.48
2495.56	28.06	PK	51	1.8	H	32.13	60.19	74	13.81
2495.56	13.76	Ave.	51	1.8	H	32.13	45.89	54	8.11
4960.00	55.50	PK	137	2.3	H	6.80	62.30	74	11.70
4960.00	43.21	Ave.	137	2.3	H	6.80	50.01	54	3.99

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.

**Pre-scan with Middle Channel Peak
Horizontal**




Date: 22.JUL.2019 16:35:19




Date: 22.JUL.2019 17:31:55

Vertical




Date: 22.JUL.2019 16:42:03




Date: 22.JUL.2019 17:41:25


Pre-scan for Average Horizontal



Date: 22.JUL.2019 16:38:09




Date: 22.JUL.2019 17:36:18




Date: 22.JUL.2019 16:54:23


Vertical



Date: 22.JUL.2019 16:44:37



Date: 22.JUL.2019 17:45:18



Date: 22.JUL.2019 16:48:51

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Leo Huang on 2019-07-25.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result
BDR(GFSK)					
Low	1.000	0.883	0.589	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	0.883	0.589	> two-thirds of the 20 dB bandwidth	Compliance
High	1.003	0.883	0.589	> two-thirds of the 20 dB bandwidth	Compliance
EDR($\pi/4$-DQPSK)					
Low	1.000	1.238	0.825	> two-thirds of the 20 dB bandwidth	Compliance
Middle	1.000	1.238	0.825	> two-thirds of the 20 dB bandwidth	Compliance
High	1.003	1.242	0.828	> two-thirds of the 20 dB bandwidth	Compliance
EDR(8DPSK)					
Low	1.006	1.242	0.828	> two-thirds of the 20 dB bandwidth	Compliance
Middle	0.997	1.245	0.830	> two-thirds of the 20 dB bandwidth	Compliance
High	1.000	1.245	0.830	> two-thirds of the 20 dB bandwidth	Compliance


Please refer to the following plots.

BDR (GFSK): Low Channel




Date: 25.JUL.2019 10:10:30

BDR (GFSK): Middle Channel




Date: 25.JUL.2019 10:12:17

BDR (GFSK): High Channel




Date: 25.JUL.2019 10:13:45

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 25.JUL.2019 10:24:47

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 25.JUL.2019 10:21:38

EDR ($\pi/4$ -DQPSK): High Channel




Date: 25.JUL.2019 10:18:00

EDR (8DPSK): Low Channel




Date: 25.JUL.2019 10:28:49

EDR (8DPSK): Middle Channel



Date: 25.JUL.2019 10:33:50

EDR (8DPSK): High Channel



Date: 25.JUL.2019 10:58:39

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Leo Huang on 2019-07-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.883
	Middle	2441	0.883
	High	2480	0.883
EDR ($\pi/4$-DQPSK)	Low	2402	1.238
	Middle	2441	1.238
	High	2480	1.242
EDR (8DPSK)	Low	2402	1.242
	Middle	2441	1.245
	High	2480	1.245

20 dB Emission Bandwidth, BDR (GFSK): Low Channel




Date: 25.JUL.2019 09:15:30

20 dB Emission Bandwidth, BDR (GFSK): Middle Channel




Date: 25.JUL.2019 09:16:54

20 dB Emission Bandwidth, BDR (GFSK): High Channel




Date: 25.JUL.2019 09:18:13

20 dB Emission Bandwidth, EDR ($\pi/4$ -DQPSK): Low Channel




Date: 25.JUL.2019 09:25:57

20 dB Emission Bandwidth, EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 25.JUL.2019 09:21:25

20 dB Emission Bandwidth, EDR ($\pi/4$ -DQPSK): High Channel




Date: 25.JUL.2019 09:19:47

20 dB Emission Bandwidth, EDR (8DPSK): Low Channel




Date: 25.JUL.2019 09:27:30

20 dB Emission Bandwidth, EDR (8DPSK): Middle Channel



Date: 25.JUL.2019 09:28:53

20 dB Emission Bandwidth, EDR (8DPSK): High Channel



Date: 25.JUL.2019 09:30:14

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Leo Huang on 2019-07-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels




Date: 25.JUL.2019 10:06:57

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 25.JUL.2019 10:04:17

EDR (8DPSK): Number of Hopping Channels



Date: 25.JUL.2019 10:00:53

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Leo Huang on 2019-07-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.411	0.132	0.4	Pass
		Middle	0.411	0.132	0.4	Pass
		High	0.411	0.132	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	DH 3	Low	1.682	0.269	0.4	Pass
		Middle	1.682	0.269	0.4	Pass
		High	1.682	0.269	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	DH 5	Low	2.938	0.313	0.4	Pass
		Middle	2.938	0.313	0.4	Pass
		High	2.938	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
	EDR (π/4-DQPSK)	2DH 1	Low	0.424	0.136	0.4
Middle			0.424	0.136	0.4	Pass
High			0.424	0.136	0.4	Pass
Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s						
2DH 3		Low	1.682	0.269	0.4	Pass
		Middle	1.682	0.269	0.4	Pass
		High	1.682	0.269	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
2DH 5		Low	2.938	0.313	0.4	Pass
		Middle	2.938	0.313	0.4	Pass
		High	2.938	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR (8DPSK)		3DH 1	Low	0.424	0.136	0.4
	Middle		0.424	0.136	0.4	Pass
	High		0.424	0.136	0.4	Pass
	Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s					
	3DH 3	Low	1.682	0.269	0.4	Pass
		Middle	1.682	0.269	0.4	Pass
		High	1.682	0.269	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	3DH 5	Low	2.938	0.313	0.4	Pass
		Middle	2.938	0.313	0.4	Pass
		High	2.938	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				

BDR (GFSK): Pulse time, Low Channel, DH1




Date: 25.JUL.2019 11:03:27

Pulse time, Middle Channel, DH1




Date: 25.JUL.2019 11:03:03

Pulse time, High Channel, DH1




Date: 25.JUL.2019 11:02:22

Pulse time, Low Channel, DH3




Date: 25.JUL.2019 11:09:25

Pulse time, Middle Channel, DH3




Date: 25.JUL.2019 11:09:53

Pulse time, High Channel, DH3




Date: 25.JUL.2019 11:10:14

Pulse time, Low Channel, DH5




Date: 25.JUL.2019 11:15:37

Pulse time, Middle Channel, DH5



Date: 25.JUL.2019 11:15:21


Pulse time, High Channel, DH5



Date: 25.JUL.2019 11:14:45


EDR ($\pi/4$ -DQPSK):

Pulse time, Low Channel, 2DH1




Date: 25.JUL.2019 11:04:06

Pulse time, Middle Channel, 2DH1




Date: 25.JUL.2019 11:04:43

Pulse time, High Channel, 2DH1




Date: 25.JUL.2019 11:05:21

Pulse time, Low Channel, 2DH3




Date: 25.JUL.2019 11:12:08

Pulse time, Middle Channel, 2DH3




Date: 25.JUL.2019 11:11:48

Pulse time, High Channel, 2DH3




Date: 25.JUL.2019 11:11:14

Pulse time, Low Channel, 2DH5




Date: 25.JUL.2019 11:16:05

Pulse time, Middle Channel, 2DH5




Date: 25.JUL.2019 11:16:42

Pulse time, High Channel, 2DH5




Date: 25.JUL.2019 11:17:29

EDR (8DPSK): Pulse time, Low Channel, 3DH1




Date: 25.JUL.2019 11:07:05

Pulse time, Middle Channel, 3DH1




Date: 25.JUL.2019 11:06:41

Pulse time, High Channel, 3DH1




Date: 25.JUL.2019 11:05:50

Pulse time, Low Channel, 3DH3




Date: 25.JUL.2019 11:12:39

Pulse time, Middle Channel, 3DH3




Date: 25.JUL.2019 11:13:07

Pulse time, High Channel, 3DH3




Date: 25.JUL.2019 11:13:34

Pulse time, Low Channel, 3DH5




Date: 25.JUL.2019 11:18:59

Pulse time, Middle Channel, 3DH5



Date: 25.JUL.2019 11:18:37

Pulse time, High Channel, 3DH5



Date: 25.JUL.2019 11:17:58

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Leo Huang on 2019-07-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	0.42	1.10	125
	Middle	2441	0.38	1.09	125
	High	2480	-1.28	0.74	125
EDR ($\pi/4$-DQPSK)	Low	2402	0.96	1.25	125
	Middle	2441	0.17	1.04	125
	High	2480	-0.73	0.85	125
EDR (8DPSK)	Low	2402	1.38	1.37	125
	Middle	2441	0.59	1.15	125
	High	2480	-0.33	0.93	125

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Leo Huang on 2019-07-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.


BDR (GFSK): Band Edge-Left Side

Hopping




Date: 25.JUL.2019 09:42:35

Single




Date: 25.JUL.2019 09:38:11

BDR (GFSK): Band Edge-Right Side Hopping




Date: 25.JUL.2019 09:46:35

Single




Date: 25.JUL.2019 09:36:56

EDR ($\pi/4$ -DQPSK): Band Edge-Left Side Hopping




Date: 25.JUL.2019 09:51:41

Single




Date: 25.JUL.2019 09:35:22

EDR ($\pi/4$ -DQPSK): Band Edge-Right Side Hopping




Date: 25.JUL.2019 09:49:30

Single




Date: 25.JUL.2019 09:36:19

EDR (8DPSK): Band Edge-Left Side Hopping



Date: 25.JUL.2019 09:54:52


Single



Date: 25.JUL.2019 09:34:33


EDR (8DPSK): Band Edge-Right Side

Hopping



Date: 25.JUL.2019 09:57:59

Single



Date: 25.JUL.2019 09:33:21

******* END OF REPORT *******