

FCC

RF

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Bluetooth LED Speaker

ISSUED TO
Zeeva International Limited

Suite 1007B, 10th Floor, Exchange Tower 33 Wang Chiu Road,
Kowloon Bay



Tested by:

Cao Shaocong
Cao Shaocong
(Engineer)

Date *May 27, 2016*

Approved by:

Wei Yanquan
Wei Yanquan
(Chief Engineer)

Date *May 27, 2016*

Report No.: BL-SZ1650004-601

EUT Type: Bluetooth LED Speaker

Model Name: SP-0259

Brand Name: N/A

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2ADM5-SP0259

Test conclusion: Pass

Test Date: May 17, 2016 ~ May 24, 2016

Date of Issue: May 27, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

Version	Issue Date	Revisions Content
Rev. 01	May 27, 2016	Initial Issue

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	6
1.1	Identification of the Testing Laboratory	6
1.2	Identification of the Responsible Testing Location	6
1.3	Laboratory Condition	6
1.4	Announce	6
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information.....	7
2.3	Factory Information.....	7
2.4	General Description for Equipment under Test (EUT).....	7
2.5	Ancillary Equipment.....	7
2.6	Technical Information	8
2.7	Additional Instructions	8
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Verdict.....	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments.....	10
4.2	Test Equipment List.....	10
4.3	Description of Test Setup	11
4.3.1	For Antenna Port Test	11
4.3.2	For AC Power Supply Port Test.....	11
4.3.3	For Radiated Test (Below 30 MHz).....	12
4.3.4	For Radiated Test (30 MHz-1 GHz)	12
4.3.5	For Radiated Test (Above 1 GHz)	13
4.4	Measurement Results Explanation Example.....	14

4.4.1	For conducted test items:	14
4.4.2	For radiated band edges and spurious emission test:	14
5	TEST ITEMS	15
5.1	Antenna Requirements	15
5.1.1	Standard Applicable	15
5.1.2	Antenna Anti-Replacement Construction	15
5.1.3	Antenna Gain	15
5.2	Number of Hopping Frequency	16
5.2.1	Limit.....	16
5.2.2	Test Setup	16
5.2.3	Test Procedure	16
5.2.4	Test Result	16
5.3	Peak Output Power	17
5.3.1	Test Limit.....	17
5.3.2	Test Setup	17
5.3.3	Test Procedure	17
5.3.4	Test Result	17
5.4	Occupied Bandwidth.....	18
5.4.1	Limit.....	18
5.4.2	Test Setup	18
5.4.3	Test Procedure	18
5.4.4	Test Result	18
5.5	Carrier Frequency Separation.....	19
5.5.1	Limit.....	19
5.5.2	Test Setup	19
5.5.3	Test Procedure	19
5.5.4	Test Result	19
5.6	Time of Occupancy (Dwell time)	20
5.6.1	Limit.....	20
5.6.2	Test Setup	20
5.6.3	Test Procedure	20
5.6.4	Test Result	20

5.7	Conducted Spurious Emission.....	21
5.7.1	Limit.....	21
5.7.2	Test Setup.....	21
5.7.3	Test Procedure.....	21
5.7.4	Test Result	21
5.8	Conducted Emission.....	22
5.8.1	Limit.....	22
5.8.2	Test Setup.....	22
5.8.3	Test Procedure.....	22
5.8.4	Test Result	22
5.9	Radiated Spurious Emission.....	23
5.9.1	Limit.....	23
5.9.2	Test Setup.....	23
5.9.3	Test Procedure.....	23
5.9.4	Test Result	24
5.10	Band Edge.....	25
5.10.1	Limit.....	25
5.10.2	Test Setup	25
5.10.3	Test Procedure	25
5.10.4	Test Result	25
ANNEX A	TEST RESULT	26
A.1	Number of Hopping Frequency.....	26
A.2	Peak Output Power	28
A.3	20 dB and 99% bandwidth	32
A.4	Hopping Frequency Separation	36
A.5	Average Time of Occupancy	37
A.6	Conducted Spurious Emissions	41
A.7	Conducted Emissions.....	47
A.8	Radiated Emission.....	49
A.9	Band Edge.....	57
ANNEX B	TEST SETUP PHOTOS	62
ANNEX C	EUT EXTERNAL PHOTOS	62



ANNEX D	EUT INTERNAL PHOTOS.....	62
---------	--------------------------	----

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v3.1.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Zeeva International Limited
Address	Suite 1007B, 10th Floor, Exchange Tower 33 Wang Chiu Road, Kowloon Bay

2.2 Manufacturer Information

Manufacturer	Zeeva International Limited
Address	Suite 1007B, 10th Floor, Exchange Tower 33 Wang Chiu Road, Kowloon Bay

2.3 Factory Information

Factory	Zeeva International Limited
Address	Suite 1007B, 10th Floor, Exchange Tower 33 Wang Chiu Road, Kowloon Bay

2.4 General Description for Equipment under Test (EUT)

EUT Type	Bluetooth LED Speaker
Model Name Under Test	SP-0259
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Bluetooth 3.0

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Pengcheng world
	Model No.	503040
	Serial No.	N/A
	Capacitance	300 mAh
	Rated Voltage	3.7 V
	Extreme Voltage	4.2 V

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK
Transfer Rate	1 Mbps, 2 Mbps
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz)
Antenna Type	PCB Antenna
Antenna Gain	-0.68 dBi (All involve the antenna gain test item, has been included in the final results)
About the Product	The equipment is Bluetooth LED Speaker, it contains Bluetooth 3.0 operating at 2.4 GHz ISM band. Only the Bluetooth 3.0 was tested in this report.



2.7 Additional Instructions

EUT Software Settings:

During testing. Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software		
Test Software Version	FCCAssist 1.5	
Mode	Channel	Soft Set
DH5	ALL	10
2DH5	ALL	10

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-14 Edition)	Miscellaneous Wireless Communications Services
2	FCC PUBLIC NOTICE DA 00-705 (Mar. 30, 2000)	Filling and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note 1}
2	Number of Hopping Frequency	15.247(a)	ANNEX A.1	Pass
3	Peak Output Power	15.247(b)	ANNEX A.2	Pass
4	Occupied Bandwidth	15.247(a)	ANNEX A.3	Pass
5	Carrier Frequency Separation	15.247(a)	ANNEX A.4	Pass
6	Time of Occupancy (Dwell time)	15.247(a)	ANNEX A.5	Pass
7	Conducted Spurious Emission	15.247(d)	ANNEX A.6	Pass
8	Conducted Emission	15.207	ANNEX A.7	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	ANNEX A.8	Pass
10	Band Edge	15.209 15.247(d)	ANNEX A.9	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	20°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.7V from battery/5V from PC via USB port

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2015.07.16	2016.07.15
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2015.07.16	2016.07.15
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2015.07.01	2016.06.30
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2015.07.16	2016.07.15
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.15	2016.10.14
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2015.07.14	2016.07.13
LISN	SCHWARZBECK	NSLK 8127	8127-687	2015.07.14	2016.07.13
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2015.07.16	2016.07.15
Power Splitter	KMW	DCPD-LDC	1305003215	2015.07.01	2016.06.30
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2015.07.21	2016.07.20
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	18141664	2015.07.17	2016.07.16
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2015.08.07	2016.08.06
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703	--	--


4.3 Description of Test Setup

4.3.1 For Antenna Port Test




(Diagram 1)

4.3.2 For AC Power Supply Port Test




(Diagram 2)

4.3.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.3.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.3.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.4 Measurement Results Explanation Example

4.4.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.4.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	The antenna is welded on the mainboard, can't be replaced by the consumer

Reference Documents	Item
Photo	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequency

5.2.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Peak Output Power

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems that operates in the 2400 MHz to 2483.5 MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1 Watt.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.6.4 Test Result

Please refer to ANNEX A.5

5.7 Conducted Spurious Emission

5.7.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.9.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Please refer to ANNEX A.8.

5.10 Band Edge

5.10.1 Limit

FCC §15.209&15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.10.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak /AV

Trace = max hold

Allow the trace to stabilize.

$E \text{ [dB}\mu\text{V/m]} = UR + AT + A\text{Factor [dB]}; AT = LCable \text{ loss [dB]} - G\text{preamp [dB]}$

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

5.10.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
Π/4-DQPSK	2400 - 2483.5	79	15	Pass

Test plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



Π/4-DQPSK 2.4 GHz ~ 2.4415 GHz



Π/4-DQPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power

Test Data

GFSK Mode:


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	-0.46	0.90	30	1000	Pass
Middle	-0.19	0.96			Pass
High	0.22	1.05			Pass

π/4-DQPSK Mode:


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	0.63	1.16	30	1000	Pass
Middle	0.81	1.21			Pass
High	0.97	1.25			Pass

Test plots


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




Q/4-DQPSK LOW CHANNEL



□/4-DQPSK MIDDLE CHANNEL



□/4-DQPSK HIGH CHANNEL



A.3 20 dB and 99% bandwidth

Test Data

GFSK Mode:


Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.9566530	0.8473497
Middle	0.9568040	0.8501884
High	0.9559770	0.8515231

□/4-DQPSK:


Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.3090000	1.1891000
Middle	1.3110000	1.1889000
High	1.3100000	1.1881000

Test plots


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




□/4-DQPSK LOW CHANNEL



□/4-DQPSK MIDDLE CHANNEL



□/4-DQPSK HIGH CHANNEL



A.4 Hopping Frequency Separation


Test Data

Note: The systems operate with an output power no greater than 125 mw, The data provided in the section A.2.


Mode	Frequency separation (MHz)	Max 20 dB Bandwidth (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Verdict
GFSK	0.970	0.957	0.638	Pass
$\pi/4$ -DQPSK	1.090	1.311	0.874	Pass

Test Plots

GFSK



$\pi/4$ -DQPSK



A.5 Average Time of Occupancy

Test Data

GFSK Mode:


DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.3633	116.2600	0.4	Pass
DH 3	1.6270	260.3280	0.4	Pass
DH 5	2.8600	305.0760	0.4	Pass

π/4-DQPSK:


DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.3767	120.5480	0.4	Pass
DH 3	1.6240	259.8480	0.4	Pass
DH 5	2.8640	305.5030	0.4	Pass

Test Plots


GFSK DH1




GFSK DH3




GFSK DH5




$\pi/4$ -DQPSK DH1



$\pi/4$ -DQPSK DH3



□/4-DQPSK DH5



A.6 Conducted Spurious Emissions

Test Data

GFSK Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-34.29	-0.43	-20.43	Pass
Middle	-35.22	-0.27	-20.27	Pass
High	-35.02	0.00	-20.00	Pass

π/4-DQPSK:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-34.12	-0.14	-20.14	Pass
Middle	-40.23	-0.01	-20.01	Pass
High	-39.39	-3.65	-23.65	Pass

Hopping Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-35.22	0.34	-19.66	Pass
π/4-DQPSK	-37.86	0.52	-19.48	Pass

Test Plots


GFSK LOW CHANNEL , BAND EDGE




GFSK LOW CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK High CHANNEL , BAND EDGE




GFSK High CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK High CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




$\pi/4$ -DQPSK LOW CHANNEL , BAND EDGE




$\Pi/4$ -DQPSK LOW CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




$\Pi/4$ -DQPSK LOW CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




$\Pi/4$ -DQPSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




$\Pi/4$ -DQPSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




$\Pi/4$ -DQPSK High CHANNEL , BAND EDGE




$\square$ /4-DQPSK High CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




$\square$ /4-DQPSK High CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK Hopping BAND EDGE (LOW)




GFSK Hopping BAND EDGE (HIGH)




GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz




□/4-DQPSK Hopping BAND EDGE (LOW)




□/4-DQPSK Hopping BAND EDGE (HIGH)



□/4-DQPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



□/4-DQPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz




A.7 Conducted Emissions

Note 1: The EUT is working in the Normal link mode.

Note 2: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.16	56.7	13.00	65.8	9.10	Peak	L Line	Pass
1**	0.16	37.7	13.00	55.8	18.10	AV	L Line	Pass
2	0.20	54.0	13.00	64.5	10.50	Peak	L Line	Pass
2**	0.20	35.7	13.00	54.5	18.80	AV	L Line	Pass
3	0.43	43.5	13.00	58.1	14.60	Peak	L Line	Pass
3**	0.43	38.8	13.00	48.1	9.30	AV	L Line	Pass
4	1.66	37.0	13.00	56.0	19.00	Peak	L Line	Pass
4**	1.66	32.2	13.00	46.0	13.80	AV	L Line	Pass
5	3.28	35.9	13.00	56.0	20.10	Peak	L Line	Pass
5**	3.28	28.0	13.00	46.0	18.00	AV	L Line	Pass
6	17.64	39.6	13.00	60.0	20.40	Peak	L Line	Pass
6**	17.64	26.1	13.00	50.0	23.90	AV	L Line	Pass

PHASE N




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.16	56.6	13.00	65.7	9.10	Peak	N Line	Pass
1**	0.16	39.0	13.00	55.7	16.70	AV	N Line	Pass
2	0.20	54.0	13.00	64.5	10.50	Peak	N Line	Pass
2**	0.20	37.8	13.00	54.5	16.70	AV	N Line	Pass
3	1.69	36.6	13.00	56.0	19.40	Peak	N Line	Pass
3**	1.69	29.5	13.00	46.0	16.50	AV	N Line	Pass
4	3.67	36.1	13.00	56.0	19.90	Peak	N Line	Pass
4**	3.67	23.0	13.00	46.0	23.00	AV	N Line	Pass
5	17.87	40.0	13.00	60.0	20.00	Peak	N Line	Pass
5**	17.87	28.4	13.00	50.0	21.60	AV	N Line	Pass
6	19.85	38.0	13.00	60.0	22.00	Peak	N Line	Pass
6**	19.85	27.4	13.00	50.0	22.60	AV	N Line	Pass


A.8 Radiated Emission

Duty cycle correction factor for average measurement.

DH5 on time/100 ms(One Pulses) Plot on Channel 39



DH5 on time/100 ms(Count Pulse) Plot on Channel 39



Note:

1. Duty cycle = on time/100 milliseconds = $2 \times 2.86 / 100 = 5.72\%$
2. Duty cycle correction factor = $20 \times \log(\text{Duty cycle}) = -24.85 \text{ dB}$
3. DH5 has the highest duty cycle and is reported.

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The EUT is working in the Normal link mode below 1 GHz.

Test Data and Plots


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	105.64	19.46	-20.24	43.5	24.04	Peak	359.90	100	Vertical	N/A
1**	105.64	18.95	-20.24	43.5	24.55	QP	359.90	100	Vertical	Pass
2	165.04	17.82	-23.02	43.5	25.68	Peak	280.40	100	Vertical	N/A
2**	165.04	19.56	-23.02	43.5	23.94	QP	280.40	100	Vertical	Pass
3	239.95	31.59	-19.10	46.0	14.41	Peak	147.00	100	Vertical	N/A
3**	239.95	26.78	-19.10	46.0	19.22	QP	147.00	100	Vertical	Pass
4	359.96	29.65	-16.15	46.0	16.35	Peak	143.60	100	Vertical	N/A
4**	359.96	25.48	-16.15	46.0	20.52	QP	143.60	100	Vertical	Pass
5	599.98	31.65	-10.76	46.0	14.35	Peak	300.30	100	Vertical	N/A
5**	599.98	24.38	-10.76	46.0	21.62	QP	300.30	100	Vertical	Pass
6	747.62	30.83	-8.72	46.0	15.17	Peak	273.60	100	Vertical	N/A
6**	747.62	23.98	-8.72	46.0	22.02	QP	273.60	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	126.73	31.76	-22.76	43.5	11.74	Peak	285.70	100	Horizontal	N/A
1**	126.73	23.98	-22.76	43.5	19.52	QP	285.70	100	Horizontal	Pass
2	166.01	19.51	-22.86	43.5	23.99	Peak	21.80	100	Horizontal	N/A
2**	166.01	21.99	-22.86	43.5	21.51	QP	21.80	100	Horizontal	Pass
3	239.95	35.68	-19.10	46.0	10.32	Peak	309.10	100	Horizontal	N/A
3**	239.95	23.00	-19.10	46.0	23.00	QP	309.10	100	Horizontal	Pass
4	359.96	32.10	-16.15	46.0	13.90	Peak	309.10	100	Horizontal	N/A
4**	359.96	23.14	-16.15	46.0	22.86	QP	309.10	100	Horizontal	Pass
5	479.97	32.91	-13.81	46.0	13.09	Peak	335.70	100	Horizontal	N/A
5**	479.97	25.01	-13.81	46.0	20.99	QP	335.70	100	Horizontal	Pass
6	701.07	29.73	-8.96	46.0	16.27	Peak	265.50	100	Horizontal	N/A
6**	701.07	25.78	-8.96	46.0	20.22	QP	265.50	100	Horizontal	Pass

Note: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Test Data and Plots (1 GHz ~ 10th Harmonic)

GFSK LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1993.00	52.95	-2.52	74	21.05	Peak	327.9	150	Vertical	Pass
2	2401.74	91.51	-0.27	74	-17.51	Peak	292	150	Vertical	N/A
3	5911.79	51.57	15.83	74	22.43	Peak	168.9	150	Vertical	Pass
4	9616.47	47.00	14.28	74	27.00	Peak	43	150	Vertical	Pass
5	14434.69	44.37	10.75	74	29.63	Peak	49.3	150	Vertical	Pass
6	22424.29	46.06	13.17	74	27.94	Peak	104.2	150	Vertical	Pass

GFSK LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2378.85	49.94	-0.42	74	24.07	Peak	129.9	150	Horizontal	Pass
2	2401.70	97.55	-0.27	74	-23.55	Peak	143.9	150	Horizontal	N/A
3	4803.50	55.46	13.75	74	18.54	Peak	196	150	Horizontal	N/A
3**	4803.50	37.54	13.54	54	16.46	Av	196	150	Horizontal	Pass
4	11671.80	50.78	16.93	74	23.22	Peak	197.5	150	Horizontal	Pass
5	17700.08	44.92	10.82	74	29.08	Peak	311.6	150	Horizontal	Pass
6	20008.32	44.90	8.97	74	29.10	Peak	93.9	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1997.26	53.79	-2.51	74	20.21	Peak	135.4	150	Vertical	N/A
1**	1997.26	36.87	-2.51	54	17.13	AV	135.4	150	Vertical	Pass
2	2440.53	92.05	-0.23	74	-18.05	Peak	349.8	150	Vertical	N/A
3	5911.50	53.02	15.83	74	20.98	Peak	340.9	150	Vertical	N/A
3**	5911.50	36.1	15.83	54	17.9	AV	340.9	150	Vertical	Pass
4	11301.17	47.50	14.82	74	26.50	Peak	329.4	150	Vertical	Pass
5	17876.87	42.78	20.82	74	31.22	Peak	311.9	150	Vertical	Pass
6	22084.86	46.18	12.33	74	27.82	Peak	265.6	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2380.71	49.47	-0.51	74	24.54	Peak	284.7	150	Horizontal	Pass
2	2440.24	97.75	-0.31	74	-23.75	Peak	258	150	Horizontal	N/A
3	4804.22	55.58	13.74	54	18.42	AV	269.8	150	Horizontal	N/A
3**	4804.22	38.66	13.74	74	15.34	Peak	269.8	150	Horizontal	Pass
4	8897.67	45.02	13.80	74	28.98	Peak	196.8	150	Horizontal	Pass
5	15287.44	45.64	9.64	74	28.36	Peak	65	150	Horizontal	Pass
6	18719.22	45.65	9.72	74	28.35	Peak	158.3	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1994.60	54.14	-2.50	74	19.86	Peak	237.1	150	Vertical	N/A
1**	1994.60	37.22	-2.50	54	16.78	AV	237.1	150	Vertical	Pass
2	2480.74	92.27	-0.21	74	-18.27	Peak	49.2	150	Vertical	N/A
3	5910.23	51.53	15.72	74	22.47	Peak	47.6	150	Vertical	Pass
4	7381.45	49.10	18.21	74	24.90	Peak	346.5	150	Vertical	Pass
5	13852.33	41.94	9.65	74	32.06	Peak	82	150	Vertical	Pass
6	23562.40	46.05	11.23	74	27.95	Peak	178.7	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2379.46	50.02	-0.48	74	23.99	Peak	175.1	150	Horizontal	Pass
2	2480.61	96.39	-0.26	74	-22.39	Peak	296.3	150	Horizontal	N/A
3	4801.65	55.40	13.74	74	18.60	Peak	243.3	150	Horizontal	N/A
3**	4801.65	38.48	13.74	54	15.52	AV	243.3	150	Horizontal	Pass
4	11795.34	46.84	15.06	74	27.16	Peak	354.3	150	Horizontal	Pass
5	15651.41	43.19	8.70	74	30.82	Peak	227.8	150	Horizontal	Pass
6	21815.31	47.23	11.67	74	26.78	Peak	258.5	150	Horizontal	Pass

□/4-DQPSK LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2386.00	48.56	-0.52	74	25.44	Peak	199.7	150	Vertical	Pass
2	2402.23	96.65	-0.27	74	-22.65	Peak	84.4	150	Vertical	N/A
3	4806.73	52.88	13.77	74	21.12	Peak	213.1	150	Vertical	Pass
4	9886.02	42.37	15.91	74	31.63	Peak	14.5	150	Vertical	Pass
5	12401.83	44.98	9.46	74	29.02	Peak	45.3	150	Vertical	Pass
6	24960.07	44.20	10.36	74	29.81	Peak	322.4	150	Vertical	Pass

□/4-DQPSK LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1996.04	48.36	-2.51	74	25.64	Peak	109.9	150	Horizontal	Pass
2	2402.22	91.72	-0.26	74	-17.72	Peak	343.9	150	Horizontal	N/A
3	4667.30	51.43	13.13	74	22.57	Peak	73.2	150	Horizontal	Pass
4	7583.61	46.38	14.31	74	27.62	Peak	285.1	150	Horizontal	Pass
5	12592.76	43.91	9.35	74	30.09	Peak	76.3	150	Horizontal	Pass
6	24460.90	48.63	13.22	74	25.37	Peak	141.9	150	Horizontal	Pass

□/4-DQPSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2388.05	49.46	-0.52	74	24.54	Peak	10.5	150	Vertical	Pass
2	2440.41	96.20	-0.23	74	-22.20	Peak	76.7	150	Vertical	N/A
3	4800.75	50.09	13.77	74	23.91	Peak	335.4	150	Vertical	Pass
4	9234.61	43.02	13.98	74	30.98	Peak	331.3	150	Vertical	Pass
5	13956.32	47.24	11.00	74	26.76	Peak	242.2	150	Vertical	Pass
6	22524.13	44.56	11.83	74	29.44	Peak	181.5	150	Vertical	Pass

□/4-DQPSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1997.28	48.65	-2.53	74	25.35	Peak	220.1	150	Horizontal	Pass
2	2440.68	92.75	-0.34	74	-18.75	Peak	229.6	150	Horizontal	N/A
3	4667.37	50.14	13.09	74	23.86	Peak	253.9	150	Horizontal	Pass
4	7695.92	45.59	17.10	74	28.41	Peak	14.6	150	Horizontal	Pass
5	12716.31	50.65	9.49	74	23.35	Peak	251	150	Horizontal	Pass
6	21745.42	46.27	9.80	74	27.73	Peak	341.3	150	Horizontal	Pass

□/4-DQPSK HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2387.67	48.95	-0.52	74	25.05	Peak	172	150	Vertical	Pass
2	2480.41	97.86	-0.34	74	-23.86	Peak	273.3	150	Vertical	N/A
3	4804.09	51.48	13.77	74	22.52	Peak	17.1	150	Vertical	Pass
4	9212.15	46.48	13.69	74	27.53	Peak	267.4	150	Vertical	Pass
5	13706.74	46.63	10.48	74	27.37	Peak	293.8	150	Vertical	Pass
6	20048.25	44.27	11.31	74	29.73	Peak	138.9	150	Vertical	Pass

□/4-DQPSK HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1995.56	48.36	-2.51	74	25.64	Peak	34.5	150	Horizontal	Pass
2	2480.70	92.68	-0.27	74	-18.68	Peak	329	150	Horizontal	N/A
3	4667.04	52.27	13.09	74	21.73	Peak	294.5	150	Horizontal	Pass
4	10402.66	41.79	14.51	74	32.21	Peak	204.6	150	Horizontal	Pass
5	12802.00	42.46	9.07	74	31.54	Peak	338.9	150	Horizontal	Pass
6	19748.75	42.32	11.31	74	31.68	Peak	192.7	150	Horizontal	Pass

Hopping Mode:

GFSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2087.40	50.45	-1.72	74	23.55	Peak	22	150	Vertical	Pass
2	2445.19	94.08	-0.37	74	-20.08	Peak	326.6	150	Vertical	N/A
3	5830.87	52.24	15.52	74	21.76	Peak	162.4	150	Vertical	N/A
4	7358.99	41.80	14.23	74	32.20	Peak	19.2	150	Vertical	Pass
5	15641.02	45.67	9.48	74	28.33	Peak	68.3	150	Vertical	Pass
6	23682.20	47.52	9.24	74	26.48	Peak	65.9	150	Vertical	Pass

GFSK MODE 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2379.11	48.34	-0.51	74	25.66	Peak	5.6	150	Horizontal	Pass
2	2472.14	99.39	-0.53	74	-25.39	Peak	315.8	150	Horizontal	N/A
3	4831.19	52.45	13.73	74	21.55	Peak	142.5	150	Horizontal	N/A
4	7415.14	47.02	16.31	74	26.98	Peak	7.7	150	Horizontal	Pass
5	16545.76	47.05	9.06	74	26.95	Peak	60.8	150	Horizontal	Pass
6	18781.61	47.22	10.30	74	26.78	Peak	184.6	150	Horizontal	Pass

Π/4-DQPSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1993.40	50.48	-2.54	74	23.52	Peak	111.4	150	Vertical	Pass
2	2431.15	94.11	-0.63	74	-20.11	Peak	263.5	150	Vertical	N/A
3	5669.79	51.21	15.40	74	22.79	Peak	42.4	150	Vertical	N/A
4	6741.27	43.27	18.20	74	30.73	Peak	169.5	150	Vertical	Pass
5	12671.38	47.82	8.91	74	26.19	Peak	355.7	150	Vertical	Pass
6	24261.23	45.57	11.74	74	28.43	Peak	276.7	150	Vertical	Pass

Π/4-DQPSK MODE 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2146.72	52.84	-1.13	74	21.16	Peak	212.5	150	Horizontal	Pass
2	2480.17	98.17	-0.61	74	-24.17	Peak	258.7	150	Horizontal	N/A
3	4861.19	52.47	13.55	74	21.53	Peak	14.6	150	Horizontal	N/A
4	9223.38	43.82	14.59	74	30.18	Peak	70.9	150	Horizontal	Pass
5	17044.93	48.70	9.51	74	25.30	Peak	299.7	150	Horizontal	Pass
6	18459.24	44.13	12.67	74	29.88	Peak	166	150	Horizontal	Pass

A.9 Band Edge

Test Data

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note 3: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.85 dB) derived from $20\log(\text{dwell time}/100 \text{ ms})$.

For example: Average level = 58.98 dBuV/m – 24.85 (dB) =34.13 dBuV/m.


Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390.00	58.98	74	15.02	PEAK	Pass
		2390.00	34.13	54	19.87	AVERAGE	Pass
GFSK	HIGH	2483.50	58.09	74	15.91	PEAK	Pass
		2483.50	33.24	54	20.76	AVERAGE	Pass
π/4-DQPSK	Low	2390.00	59.11	74	14.89	PEAK	Pass
		2390.00	34.26	54	19.74	AVERAGE	Pass
π/4-DQPSK	HIGH	2483.50	58.92	74	15.08	PEAK	Pass
		2483.50	34.07	54	19.93	AVERAGE	Pass
GFSK(Hopping)	Low	2390.00	44.23	74	29.77	PEAK	Pass
		2390.00	19.38	54	34.62	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.50	48.42	74	25.58	PEAK	Pass
		2483.50	23.57	54	30.43	AVERAGE	Pass
π/4-DQPSK (Hopping)	Low	2390.00	45.76	74	28.24	PEAK	Pass
		2390.00	20.91	54	33.09	AVERAGE	Pass
π/4-DQPSK (Hopping)	HIGH	2483.50	48.58	74	25.42	PEAK	Pass
		2483.50	44.23	74	29.77	AVERAGE	Pass

Test Plots


GFSK LOW CHANNEL , PEAK




GFSK HIGH CHANNEL , PEAK



$\pi/4$ -DQPSK LOW CHANNEL , PEAK




$\pi/4$ -DQPSK HIGH CHANNEL , PEAK




Hopping Mode:


GFSK LOW FREQUENCY BAND, PEAK




GFSK HIGH FREQUENCY BAND, PEAK



$\pi/4$ -DQPSK LOW FREQUENCY BAND, PEAK



$\pi/4$ -DQPSK HIGH FREQUENCY BAND, PEAK



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ1650004-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ1650004-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ1650004-AI.PDF”.

--END OF REPORT--