



TESTING LABORATORY
CERTIFICATE # 4821.01



FCC PART 15.249

TEST REPORT

For

Zeeva International Limited

Suite 1007B, 10th Floor, Exchange Tower, 33 Wang Chiu Road, Kowloon Bay, Hong Kong

FCC ID: 2ADM5-U1

| | |
|--|---|
| Report Type: Original Report | Product Type: WIRELESS MOUSE USB DONGLE |
| Report Number: | <u>RSZ181120830-00</u> |
| Report Date: | <u>2018-12-10</u> |
| Reviewed By: | Rocky Kang <i>Rocky Kang</i> |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn |

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk **

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| MEASUREMENT UNCERTAINTY | 3 |
| TEST FACILITY..... | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 5 |
| SUPPORT CABLE DESCRIPTIONS..... | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS..... | 7 |
| TEST EQUIPMENT LIST | 8 |
| FCC§15.203 - ANTENNA REQUIREMENT..... | 9 |
| APPLICABLE STANDARD | 9 |
| ANTENNA CONNECTOR CONSTRUCTION | 9 |
| FCC §15.207 – AC LINE CONDUCTED EMISSIONS..... | 10 |
| APPLICABLE STANDARD | 10 |
| EUT SETUP | 10 |
| EMI TEST RECEIVER SETUP..... | 10 |
| TEST PROCEDURE | 10 |
| CORRECTED FACTOR & MARGIN CALCULATION | 11 |
| TEST RESULTS SUMMARY | 11 |
| TEST DATA | 11 |
| FCC§15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS..... | 14 |
| APPLICABLE STANDARD | 14 |
| TEST EQUIPMENT SETUP | 14 |
| EUT SETUP | 15 |
| TEST PROCEDURE | 16 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 16 |
| TEST RESULTS SUMMARY | 16 |
| TEST DATA | 16 |
| FCC§15.215(C) - 20DB EMISSION BANDWIDTH | 25 |
| APPLICABLE STANDARD | 25 |
| TEST PROCEDURE | 25 |
| TEST DATA | 25 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Zeeva International Limited's product, model number: *MO-0026 (FCC ID: 2ADM5-U1, UPC Number: 192234013960 & 192234015322, SKU Number: 3077690 & 3117132)* in this report is a **WIRELESS MOUSE USB DONGLE**, which was measured approximately: *1.8 cm (L) * 1.4 cm (W) * 0.6 cm (H)*, rated with input voltage: DC 5.0 V.

Notes: This series products model: MO-0027 and MO-0026 are electrically identical. Model MO-0026 was selected for fully testing, the detailed information can be referred to the declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 181120830 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-11-20.*

Objective

This type approval report is prepared on behalf of Zeeva International Limited in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

Submitted with part of a system with FCC ID: 2ADM5-MO-0026.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

| Parameter | uncertainty |
|----------------------------------|-------------|
| Occupied Channel Bandwidth | ±5% |
| RF Output Power with Power meter | ±0.5dB |
| RF conducted test with spectrum | ±1.5dB |
| All emissions, radiated | ±4.88dB |
| Temperature | ±3 °C |
| Humidity | ±6% |
| Supply voltages | ±0.4% |

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing by manufacturer.

8 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1 | 2405 | 5 | 2457 |
| 2 | 2411 | 6 | 2463 |
| 3 | 2417 | 7 | 2469 |
| 4 | 2451 | 8 | 2475 |

Channel 1, Channel 4 and Channel 8 were selected for testing.

EUT Exercise Software

“HID_Tool_1203_v1.0.2.exe” software was used.

Equipment Modifications

No modifications were made to the unit tested.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| Lenovo | Laptop | Y430P | Unknown |

Support Cable Descriptions

| Cable Description | Length (m) | From/Port | To |
|---------------------------------|------------|-----------|--------|
| Un-shielded detachable DC cable | 1.0 | Adapter | Laptop |

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|-----------------------------|--|------------|
| §15.203 | Antenna Requirement | Compliance |
| §15.207(a) | Conduction Emissions | Compliance |
| 15.205, §15.209, §15.249(d) | Radiated Emissions& Outside of Band Emission | Compliance |
| §15.215 (c) | 20 dB Bandwidth | Compliance |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--|--------------------|-------------------------|------------------------|------------------|----------------------|
| AC Line Conducted Emission Test | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 100176 | 2018-08-04 | 2019-08-04 |
| Rohde & Schwarz | LISN | ENV216 | 3560.6650.12-101613-Yb | 2017-12-21 | 2018-12-21 |
| Rohde & Schwarz | Transient Limiter | ESH3Z2 | DE25985 | 2018-11-21 | 2019-05-12 |
| Rohde & Schwarz | CE Test software | EMC 32 | V8.53.0 | NCR | NCR |
| Radiated Emission Test | | | | | |
| A.H. System | Horn Antenna | SAS-200/571 | 135 | 2018-09-01 | 2021-08-31 |
| Rohde & Schwarz | Signal Analyzer | FSEM | 845987/005 | 2018-06-23 | 2019-06-23 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2017-12-22 | 2020-12-21 |
| COM-POWER | Pre-amplifier | PA-122 | 181919 | 2018-11-22 | 2019-05-22 |
| Sonoma instrument | Amplifier | 310N | 186238 | 2018-11-12 | 2019-11-12 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 101120 | 2018-01-11 | 2019-01-11 |
| Ducommun technologies | RF Cable | UFA147A-2362-100100 | MFR64639 231029-003 | 2018-08-01 | 2019-02-01 |
| Ducommun technologies | RF Cable | 104PEA | 218124002 | 2018-11-21 | 2019-05-21 |
| Ducommun technologies | RF Cable | RG-214 | 1 | 2018-11-19 | 2019-05-21 |
| Ducommun technologies | RF Cable | RG-214 | 2 | 2018-11-22 | 2019-05-22 |
| Ducommun Technologies | Horn Antenna | ARH-4223-02 | 1007726-04 | 2017-12-29 | 2020-12-28 |
| Heatsink Required | Amplifier | QLW-18405536-J0 | 15964001002 | 2018-08-01 | 2019-02-01 |
| Sinoscite | Band Reject Filter | BSF2402-2480MN-0898-001 | 99632 | 2018-11-21 | 2019-05-21 |

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one PCB antenna which was permanently attached and the antenna gain is 4 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Shawn Xiao on 2018-12-07.


EUT Operation Mode: Transmitting

AC 120V/60 Hz, Line



| Frequency (MHz) | Corrected Amplitude (dB μ V) | Corrected Factor (dB) | Limit (dB μ V) | Margin (dB) | Remark (PK/QP/Ave.) |
|-----------------|----------------------------------|-----------------------|--------------------|-------------|---------------------|
| 0.150000 | 42.9 | 19.8 | 66.0 | 23.1 | QP |
| 0.285500 | 39.3 | 19.8 | 60.7 | 21.4 | QP |
| 0.297470 | 40.6 | 19.8 | 60.3 | 19.7 | QP |
| 0.321230 | 38.2 | 19.8 | 59.7 | 21.5 | QP |
| 7.376470 | 33.9 | 20.1 | 60.0 | 26.1 | QP |
| 7.544390 | 32.5 | 20.1 | 60.0 | 27.5 | QP |
| 0.150000 | 23.1 | 19.8 | 56.0 | 32.9 | Ave. |
| 0.285500 | 33.7 | 19.8 | 50.7 | 17 | Ave. |
| 0.297470 | 34.6 | 19.8 | 50.3 | 15.7 | Ave. |
| 0.321230 | 33.6 | 19.8 | 49.7 | 16.1 | Ave. |
| 7.376470 | 25.5 | 20.1 | 50.0 | 24.5 | Ave. |
| 7.544390 | 21.1 | 20.1 | 50.0 | 28.9 | Ave. |

AC 120V/60 Hz, Neutral



| Frequency (MHz) | Corrected Amplitude (dB μ V) | Corrected Factor (dB) | Limit (dB μ V) | Margin (dB) | Remark (PK/QP/Ave.) |
|-----------------|----------------------------------|-----------------------|--------------------|-------------|---------------------|
| 0.157500 | 39.7 | 19.7 | 65.6 | 25.9 | QP |
| 0.286500 | 39.6 | 19.8 | 60.6 | 21 | QP |
| 0.297500 | 40.7 | 19.8 | 60.3 | 19.6 | QP |
| 0.313230 | 38.2 | 19.8 | 59.9 | 21.7 | QP |
| 7.334430 | 35.8 | 20.1 | 60.0 | 24.2 | QP |
| 7.587610 | 34.8 | 20.1 | 60.0 | 25.2 | QP |
| 0.157500 | 23.6 | 19.7 | 55.6 | 32 | Ave. |
| 0.286500 | 33.8 | 19.8 | 50.6 | 16.8 | Ave. |
| 0.297500 | 34.7 | 19.8 | 50.3 | 15.6 | Ave. |
| 0.313230 | 32.9 | 19.8 | 49.9 | 17 | Ave. |
| 7.334430 | 25.0 | 20.1 | 50.0 | 25 | Ave. |
| 7.587610 | 25.8 | 20.1 | 50.0 | 24.2 | Ave. |

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC§15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS**Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental (millivolts/meter) | Field strength of harmonics (microvolts/meter) |
|-----------------------|--|--|
| 902–928 MHz | 50 | 500 |
| 2400–2483.5 MHz | 50 | 500 |
| 5725–5875 MHz | 50 | 500 |
| 24.0–24.25 GHz | 250 | 2500 |

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000MHz:

RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto


Above 1000MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto


Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.205, 15.209 & §15.249

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cisp}}$$

In BACL, $U_{(Lm)}$ is less than U_{cisp} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Shawn Xiao on 2018-12-05.

Test Mode: Transmitting

30MHz – 1 GHz (worst case is high channel):

| Frequency (MHz) | Corrected Amplitude (dB μ V/m) | Antenna height (cm) | Antenna Polarity | Turntable position (degree) | Correction Factor (dB/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|------------------------------------|---------------------|------------------|-----------------------------|--------------------------|----------------------|-------------|
| 155.483250 | 17.83 | 205.0 | V | 354.0 | -14.3 | 43.50 | 25.67 |
| 471.133250 | 17.05 | 123.0 | V | 96.0 | -7.8 | 46.00 | 28.95 |
| 583.538625 | 20.54 | 100.0 | V | 240.0 | -2.8 | 46.00 | 25.46 |
| 636.731250 | 18.57 | 113.0 | V | 288.0 | -3.0 | 46.00 | 27.43 |
| 828.327500 | 26.98 | 147.0 | V | 110.0 | 4.7 | 46.00 | 19.02 |
| 892.790000 | 27.32 | 118.0 | H | 135.0 | 4.5 | 46.00 | 18.68 |

1 GHz - 25 GHz:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dB μ V/m) | FCC Part 15.249&15.209 | |
|----------------------------------|-------------------------|------------|---------------------|---------------|----------------|-------------------------------|--|---------------------------|----------------|
| | Reading (dB μ V) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| Low Channel (2405 MHz) | | | | | | | | | |
| 2405.00 | 49.02 | PK | 31 | 1.8 | H | 33.00 | 82.02 | 114 | 31.98 |
| 2405.00 | 46.03 | Ave. | 31 | 1.8 | H | 33.00 | 79.03 | 94 | 14.97 |
| 2405.00 | 39.02 | PK | 202 | 2.1 | V | 33.00 | 72.02 | 114 | 41.98 |
| 2405.00 | 35.95 | Ave. | 202 | 2.1 | V | 33.00 | 68.95 | 94 | 25.05 |
| 2376.43 | 27.61 | PK | 62 | 1.5 | H | 33.00 | 60.61 | 74 | 13.39 |
| 2376.43 | 13.54 | Ave. | 62 | 1.5 | H | 33.00 | 46.54 | 54 | 7.46 |
| 2484.66 | 26.86 | PK | 217 | 1.2 | H | 33.20 | 60.06 | 74 | 13.94 |
| 2484.66 | 13.44 | Ave. | 217 | 1.2 | H | 33.20 | 46.64 | 54 | 7.36 |
| 4810.00 | 52.95 | PK | 204 | 2.4 | H | 7.88 | 60.83 | 74 | 13.17 |
| 4810.00 | 42.39 | Ave. | 204 | 2.4 | H | 7.88 | 50.27 | 54 | 3.73 |
| 7215.00 | 47.86 | PK | 161 | 1.3 | H | 15.88 | 63.74 | 74 | 10.26 |
| 7215.00 | 36.88 | Ave. | 161 | 1.3 | H | 15.88 | 52.76 | 54 | 1.24 |
| 9620.00 | 44.96 | PK | 308 | 2.4 | H | 18.96 | 63.92 | 74 | 10.08 |
| 9620.00 | 31.68 | Ave. | 308 | 2.4 | H | 18.96 | 50.64 | 54 | 3.36 |
| Middle Channel (2451 MHz) | | | | | | | | | |
| 2451.00 | 50.10 | PK | 290 | 2.5 | H | 33.10 | 83.20 | 114 | 30.80 |
| 2451.00 | 46.80 | Ave. | 290 | 2.5 | H | 33.10 | 79.90 | 94 | 14.10 |
| 2451.00 | 36.00 | PK | 38 | 1.2 | V | 33.10 | 69.10 | 114 | 44.90 |
| 2451.00 | 33.30 | Ave. | 38 | 1.2 | V | 33.10 | 66.40 | 94 | 27.60 |
| 4902.00 | 51.16 | PK | 283 | 2.3 | H | 9.21 | 60.37 | 74 | 13.63 |
| 4902.00 | 40.32 | Ave. | 283 | 2.3 | H | 9.21 | 49.53 | 54 | 4.47 |
| 7353.00 | 48.50 | PK | 171 | 1.1 | H | 14.69 | 63.19 | 74 | 10.81 |
| 7353.00 | 37.22 | Ave. | 171 | 1.1 | H | 14.69 | 51.91 | 54 | 2.09 |
| 9804.00 | 44.60 | PK | 331 | 1.8 | H | 18.40 | 63.00 | 74 | 11.00 |
| 9804.00 | 31.64 | Ave. | 331 | 1.8 | H | 18.40 | 50.04 | 54 | 3.96 |

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dB μ V/m) | FCC Part 15.249&15.209 | |
|--------------------------------|-------------------------|------------|---------------------|---------------|----------------|-------------------------------|--|---------------------------|----------------|
| | Reading (dB μ V) | PK/QP/Ave. | | Height (m) | Polar (H/V) | | | Limit (dB μ V/m) | Margin (dB) |
| High Channel (2475 MHz) | | | | | | | | | |
| 2475.00 | 49.21 | PK | 74 | 1.0 | H | 33.20 | 82.41 | 114 | 31.59 |
| 2475.00 | 46.14 | Ave. | 74 | 1.0 | H | 33.20 | 79.34 | 94 | 14.66 |
| 2475.00 | 40.89 | PK | 83 | 1.2 | V | 33.20 | 74.09 | 114 | 39.91 |
| 2475.00 | 36.77 | Ave. | 83 | 1.2 | V | 33.20 | 69.97 | 94 | 24.03 |
| 2345.59 | 27.42 | PK | 189 | 2.0 | H | 32.97 | 60.39 | 74 | 13.61 |
| 2345.59 | 13.63 | Ave. | 189 | 2.0 | H | 32.97 | 46.60 | 54 | 7.40 |
| 2496.45 | 27.51 | PK | 227 | 1.8 | H | 33.20 | 60.71 | 74 | 13.29 |
| 2496.45 | 13.51 | Ave. | 227 | 1.8 | H | 33.20 | 46.71 | 54 | 7.29 |
| 4950.00 | 55.79 | PK | 232 | 1.5 | H | 9.07 | 64.86 | 74 | 9.14 |
| 4950.00 | 42.24 | Ave. | 232 | 1.5 | H | 9.07 | 51.31 | 54 | 2.69 |
| 7425.00 | 50.63 | PK | 43 | 2.3 | H | 14.79 | 65.42 | 74 | 8.58 |
| 7425.00 | 39.11 | Ave. | 43 | 2.3 | H | 14.79 | 53.90 | 54 | 0.10 |
| 9900.00 | 43.00 | PK | 127 | 1.1 | H | 19.32 | 62.32 | 74 | 11.68 |
| 9900.00 | 28.64 | Ave. | 127 | 1.1 | H | 19.32 | 47.96 | 54 | 6.04 |

Note:



Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor



Margin = Limit- Corr. Amplitude

The emission more than 20dB below the limit was not required to be recorded.



Pre-scan with high channel Peak
Horizontal




Vertical






**Average value for the peak point at pre-scan
Horizontal**





Vertical





FCC§15.215(c) - 20dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions



| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Shawn Xiao on 2018-12-05.

Test Mode: Transmitting

Please refer to the following table and plots.

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| Low | 2405 | 2.635 |
| Middle | 2451 | 2.685 |
| High | 2475 | 2.625 |

Low Channel**Middle Channel**

High Channel******* END OF REPORT *******