

# TEST REPORT

**Report Number. :** 14888706-E4V2

**Applicant :** ENERGOUS CORPORATION  
3590 NORTH FIRST STREET,  
SUITE 210,  
SAN JOSE, CA 95134, U.S.A.

**Model :** VN55, VN55-E

**Brand :** ENERGOUS

**FCC ID :** 2ADNG-VN55

**EUT Description :** WIRELESS CHARGER

**Test Standard(s) :** FCC 47 CFR PART 1 SUBPART I  
FCC 47 CFR PART 2 SUBPART J

**Date Of Issue:**  
2023-10-17

**Prepared by:**  
UL VERIFICATION SERVICES INC.  
47173 Benicia Street  
Fremont, CA 94538, U.S.A.  
TEL: (510) 319-4000  
FAX: (510) 661-0888



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2023-08-14	Initial Issue	---
V2	2023-10-17	Added additional model number	Tina Chu

---

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. REFERENCES .....</b>	<b>5</b>
<b>4. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>5. DECISION RULES AND MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
5.1. <i>METROLOGICAL TRACEABILITY</i> .....	6
5.2. <i>DECISION RULES</i> .....	6
5.3. <i>MEASUREMENT UNCERTAINTY</i> .....	6
<b>6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS) .....</b>	<b>7</b>
6.1. <i>EQUATIONS</i> .....	7
<b>7. RF EXPOSURE RESULTS.....</b>	<b>10</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** ENERGOUS CORPORATION  
3590 NORTH FIRST STREET,  
SUITE 210,  
SAN JOSE, CA 95134, U.S.A.

**EUT DESCRIPTION:** WIRELESS CHARGER

**MODEL:** VN55, VN55-E(TESTED MODEL NUMBER)

**BRAND:** ENERGOUS

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document.

Approved & Released For  
UL Verification Services Inc. By:



Dan Corona  
Operations Leader  
UL Verification Services Inc.

Prepared By:



Tina Chu  
Senior Project Engineer  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06, KDB 447498 D03 V01, IEEE Std C95.1-2005, IEEE Std C95.3-2002.

## 3. REFERENCES

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer.

WPT/BLE/Zigbee output power data are excerpted from the applicable original test reports:  
UL Verification Services Inc. Document 14262501-E1 for WPT operation in the 900 MHz band,  
UL Verification Services Inc. Document 14262501-E2 for BLE operation in the 2.4 GHz band,  
UL Verification Services Inc. Document 14262501-E3 for Zigbee operation in the 2.4 GHz band.

BLE duty cycle are excerpted from the applicable class II permissive change reports:  
UL Verification Services Inc. Document 14888706-E2 for BLE operation in the 2.4 GHz band,

WPT/Zigbee duty cycle and WPT/ BLE/ Zigbee antenna gain data are provided by the customer.

## 4. FACILITIES AND ACCREDITATION

UL Verification Services Inc. is accredited by A2LA, Certificate Number 0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building 1: 47173 Benicia Street Fremont, CA 94538, U.S.A	US0104	2324A	550739
<input type="checkbox"/>	Building 2: 47266 Benicia Street Fremont, CA 94538, U.S.A			
<input checked="" type="checkbox"/>	Building 4: 47658 Kato Rd Fremont, CA 94538, U.S.A			

## 5. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 5.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 5.2. DECISION RULES

For all tests where the applicable  $U_{LAB} \leq U_{MAX}$  the Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2, where  $U_{MAX} = 30\%$  (0.3) for RF Exposure evaluations. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

For all tests where the applicable  $U_{LAB} > U_{MAX}$  the Decision Rule is based on Guarded Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.3.2, with a guard band equal to  $(U_{LAB} - U_{MAX})$ , where  $U_{MAX} = 30\%$  (0.3) for RF Exposure evaluations. (Test results are adjusted by the value of the guard band to determine conformity with a specified requirement.)

### 5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	$U_{Lab}$	$U_{MAX}$
Test method used to measure the power of the fundamental transmitting signal.	ANSI C63.10 Subclause - 11.9.1.3	30%

Uncertainty figures are valid to a confidence level of 95%.

## 6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)

### 6.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**Notes:**

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

## 6.2. EQUATIONS

### POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in mW



---

**MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{EIRP1}) + (\text{EIRP2}) + \dots + (\text{EIRPn})$$

where

EIRPx = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

**MIMO AND COLOCATED TRANSMITTERS (NON-IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as (Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

## 7. RF EXPOSURE RESULTS

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer.

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

Multiple chain or colocated transmitters

<b>Band</b>	<b>(GHz)</b>	0.907	2.4
<b>Mode</b>		WPT	BLE
<b>Transmitter</b>		SISO	SISO
<b>Separation Distance</b>	<b>(cm)</b>	30.0	30.0
<b>Output Power</b>	<b>(dBm)</b>	30	21.49
<b>Antenna Gain</b>	<b>(dBi)</b>	5.0	6.0
<b>Duty Cycle</b>	<b>(%)</b>	90	13.26
<b>Source Based EIRP</b>	<b>(mW)</b>	2846.0	74.4
<b>FCC Power Density</b>	<b>(mW/cm<sup>2</sup>)</b>	0.25	0.01
<b>FCC Power Density Limit</b>	<b>(mW/cm<sup>2</sup>)</b>	0.60	1
<b>FCC Fraction of Limit</b>	<b>(%)</b>	41.6	0.7
<b>FCC Sum of Fractions (%)</b>	<b>42.3</b>		

Multiple chain or colocated transmitters

<b>Band</b>	<b>(GHz)</b>	0.907	2.4
<b>Mode</b>		WPT	Zigbee
<b>Transmitter</b>		SISO	SISO
<b>Separation Distance</b>	<b>(cm)</b>	30.0	30.0
<b>Output Power</b>	<b>(dBm)</b>	30	21.27
<b>Antenna Gain</b>	<b>(dBi)</b>	5.0	6.0
<b>Duty Cycle</b>	<b>(%)</b>	90	90
<b>Source Based EIRP</b>	<b>(mW)</b>	2846.0	480.0
<b>FCC Power Density</b>	<b>(mW/cm<sup>2</sup>)</b>	0.25	0.04
<b>FCC Power Density Limit</b>	<b>(mW/cm<sup>2</sup>)</b>	0.60	1
<b>FCC Fraction of Limit</b>	<b>(%)</b>	41.6	4.2
<b>FCC Sum of Fractions (%)</b>	<b>45.9</b>		

**Notes:**

- 1) The manufacturer configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.
- 2) The output power in the tables above is the maximum declared output power among various channels and various modes within the specific band.
- 3) The antenna gain in the tables above is the maximum antenna gain among various channels within the specified band.

**END OF REPORT**