

---

# TEST REPORT FOR BLE TESTING

---

Report No.: SRTC2020-9004(F)-20041302(E)

Product Name: Smartphone

Product Model: HLTE103E

Applicant: Hisense International Co., Ltd.

Manufacturer: Hisense Communications Co., Ltd.

Specification: FCC Part 15 Subpart C (2019)

FCC ID: 2ADOBHLTE103E

The State Radio\_monitoring\_center Testing Center (SRTC)  
15th Building, No.30 Shixing Street, Shijingshan District,  
Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

## CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>2</b>
1.1 NOTES OF THE TEST REPORT .....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY .....	2
1.3 APPLICANT'S DETAILS .....	2
1.4 MANUFACTURER'S DETAILS .....	2
1.5 TEST ENVIRONMENT .....	3
<b>2 DESCRIPTION OF THE DEVICE UNDER TEST .....</b>	<b>4</b>
2.1 FINAL EQUIPMENT BUILD STATUS .....	4
2.2 DESCRIPTION OF TEST MODES .....	6
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	6
2.3 DUTY CYCLE OF TEST SIGNAL .....	7
2.4 EUT OPERATING CONDITIONS .....	7
2.5 SUPPORT EQUIPMENT .....	8
<b>3 REFERENCE SPECIFICATION .....</b>	<b>9</b>
<b>4 KEY TO NOTES AND RESULT CODES .....</b>	<b>9</b>
<b>5 RESULT SUMMARY .....</b>	<b>10</b>
<b>6 TEST RESULT .....</b>	<b>11</b>
6.1 6dB BANDWIDTH .....	11
6.2 TRANSMITTER OUTPUT POWER .....	12
6.3 TRANSMITTER POWER SPECTRAL DENSITY .....	13
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	14
6.5 BAND-EDGE MEASUREMENT .....	15
6.6 SPURIOUS RADIATED EMISSIONS .....	16
6.7 AC POWER LINE CONDUCTED EMISSION .....	21
<b>7 MEASUREMENT UNCERTAINTIES .....</b>	<b>23</b>
<b>8 TEST EQUIPMENTS .....</b>	<b>24</b>
<b>APPENDIX A – TEST DATA OF CONDUCTED EMISSION .....</b>	<b>25</b>
<b>APPENDIX B – TEST DATA OF RADIATED EMISSION .....</b>	<b>31</b>

## 1. GENERAL INFORMATION

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### 1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiuf@srtc.org.cn

### 1.3 Applicant's details

Company:	Hisense International Co., Ltd.
Address:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City:	Qingdao
Country or Region:	China
Contacted person:	Geng Ruifeng
Tel:	+86-532-80877742
Fax:	---
Email:	gengruifeng@hisense.com

### 1.4 Manufacturer's details

Company:	Hisense Communications Co., Ltd.
Address:	218 Qianwangang Road, Qingdao Economic & Technological Development Zone, Qingdao, China
City:	Qingdao
Country or Region:	China
Contacted person:	Deng Tingting
Tel:	+86-532-55753708
Fax:	---
Email:	dengtingting@hisense.com

### 1.5 Test Environment

Date of Receipt of test sample at SRTC:	2020-04-13
Testing Start Date:	2020-04-13
Testing End Date:	2020-04-24

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30
Maximum Extreme	50	---
Minimum Extreme	-30	---

Normal Supply Voltage (V d.c.):	3.8
---------------------------------	-----

## 2 DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status

Frequency Range	2.402GHz~2.480GHz
Number of Channel	40
Modulation Type	GFSK
Equipment Class	DTS
Channel Spacing	2MHz
Data Rate	1Mbps
Power Supply	Battery/Charger
Hardware Version	FS273--MB-V2.1
Software Version	Hisense_HLTE103E_20_S01_01_02_MX05
IMEI	868468040003527
Antenna type	Refer to Note
Antenna connector	Refer to Note

#### **Note: Antenna requirement (FCC part 15.203)**

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The antenna(s) of the EUT are permanently attached.
- There are no provisions for connection to an external antenna.

Note: The antenna provide to the EUT, please refer to the following table:

Brand	Model	Antenna gain	Frequency range(GHz)	Antenna type	Connector Type
N/A	N/A	-0.59dBi	2.402GHz~2.480GHz	Fixed Internal Antenna	N/A

Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance. The EUT complies with the requirement of §15.203.

Note: The equipments have two supplies, are different on the supplier of Camera, LCD, Battery, Memory and color. These differences don't affect RF performance.

### Main Supply

Part Name	Model	Supplier(Brand)	Description
Camera	BC15314 V0	LUZHOU Chengxiangtong technology CO.,LTD	Front CAM
Camera	BM1A300 V0		
CTP	Y140071B2-R	Dongguan Yuye Communication Technology CO.,ted	
LCD	Y88448	Shenzhen Digital Technology Co.,Ltd	
Battery	LIW380245	SHENZHEN UTILITY POWER SOURCE CO.,LTD	
Memory	KMQE60013M-B318	SAMSUNG	

### Secondary Supply

Part Name	Model Name	Supplier(Brand)	Description
Camera	ST-CFKS103A-FF-V1.0	Shenzhen Union Image Co.,Ltd	Front CAM
Camera	ST-CFKS103A-13MBA-V1.0	Shenzhen Union Image Co.,Ltd	
CTP	YX57042TSBA00	Shenzhen AGS Optronics Tech(Shenzhen) , co.,	
LCD	FPC-K1398A-01	SHENZHEN KINGDOM SCIENCE & TECHNOLOGY CO.,LTD	
Battery	LIW380245	ShenzhenAerospaceElectronicCo.,Ltd.	
Memory	KMQE10013M-B318	SAMSUNG	

## 2.2 Description of Test Modes

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

### 2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE ≥ 1G	RE<1G	PLC	APCM	-
GFSK	√	√	√	√	-

Where

RE ≥ 1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

### Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

### Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

### Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1

## 2.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

Duty cycle = 84.1%

Correction factor =  $10 * \log (1/\text{duty cycle}) = 10 * \log (1/0.841) = 0.75 \text{ dB}$

## 2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



## 2.5 Support Equipment

The following support equipment was used to exercise the DUT during testing:

Equipment	Battery 1
Manufacturer	Shenzhen Utility Power Source Co.,Ltd.
Model Number	KS103

Equipment	Battery 2
Manufacturer	ShenzhenAerospaceElectronic Co.,Ltd.
Model Number	KS103

Equipment	Charger
Manufacturer	Shenzhen Tianyin Electronics Co.,Ltd.
Model Number	TPA-97050100UW01

Equipment	Headset
Manufacturer	Dongguan Keling Electronic Technology Co., Ltd.
Model Number	KS103

### **3 REFERENCE SPECIFICATION**




Specification	Version	Title
FCC part15 Subpart C	2019	Intentional radiators
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074D01 V05R02r02	April 2, 2019	Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

### **4 KEY TO NOTES AND RESULT CODES**

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.

## 5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	6dB Bandwidth	15.247(a)(2)	Pass
2	Transmitter Output Power	15.247(b)(3) )	Pass
3	Transmitter Power Spectral Density	15.247(e) )	Pass
4	Conducted Out of band emission measurement	15.247(d)	Pass
5	Band-edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.205/15.209/15.247(d)	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass(refer to section 2.1)

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Miss.Wu Han 	Issued date:  20200506

## **6 TEST RESULT**

### **6.1 6dB Bandwidth**

#### **6.1.1 Ambient condition**

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

#### **6.1.2 Test limit**

Part15.247 (a) (2)

The minimum permissible 6dB bandwidth is 500 kHz

#### **6.1.3 Test Procedure Used**

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

#### **6.1.4 Test Settings**

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

2. RBW = 100 kHz

3. VBW ≥ 3 x RBW

4. Detector = Peak


5. Trace mode = max hold

6. Sweep = auto couple

7. The trace was allowed to stabilize

#### **6.1.5 Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



#### **6.1.6 Test result**

The test results are shown in Appendix A.

## 6.2 Transmitter Output Power

### 6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

### 6.2.2 Test limit

Part15.247 (b) (3)

The maximum permissible conducted output power is 1 Watt.

### 6.2.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3

### 6.2.4 Test Settings

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### 6.2.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.2.6 Test result

The test results are shown in Appendix A.

### 6.3 Transmitter Power Spectral Density

#### 6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

#### 6.3.2 Test limit

Part15.247 (e)

The maximum permissible power spectral density is 8.0dBm in any 3 kHz band.

#### 6.3.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD


KDB 558074 D01 v05r02 – Section 8.4

#### 6.3.4 Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3 kHz
4. VBW = 10 kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

#### 6.3.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



#### 6.3.7 Test result

The test results are shown in Appendix A.

## 6.4 Conducted Out of band emission measurement

### 6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

### 6.4.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.4.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.5

### 6.4.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to  $\geq 1.5$  MHz
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

### 6.4.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

### 6.4.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.4.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.

## 6.5 Band-edge measurement

### 6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

### 6.5.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

### 6.5.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.7.2

### 6.5.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to  $\geq 1.5$  MHz
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

### 6.5.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

### 6.5.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 6.5.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.



## 6.6 Spurious Radiated Emissions

### 6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

### 6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

### 6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209. The spectrum shall be investigated from the lowest radio frequency signal generated in the device

Frequency [MHz]	Field strength [ $\mu\text{V/m}$ ]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### Radiated Limits

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

**Used conversion factor: Limit (dB $\mu\text{V/m}$ ) = 20 log (Limit ( $\mu\text{V/m}$ )/1 $\mu\text{V/m}$ )**

Frequency [MHz]	Detector	Unit (dB $\mu\text{V/m}$ )
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

#### Conversion Radiated limits

### 6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02r02 – Section 12.2.7

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and recorded the reading with Maximum Hold Mode.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer complied the following setting:

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz

#### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground in chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and recorded the reading with Maximum Hold Mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detector and recorded the reading with Maximum Hold Mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**For the radiated emission test above 1GHz:**

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

**6.6.5 Test Settings**

**Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)**

Frequency	Detector
<1000MHz	Quasi-peak
>1000MHz	Peak and average

**Peak Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 6.6.6 Test Setup


#### For Radiated emission below 30MHz



#### For Radiated emission 30MHz to 1GHz



**For Radiated emission above 1GHz**



**6.6.7 Test result**

The test results are shown in Appendix B.

## 6.7 AC Power line Conducted Emission

### 6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

### 6.7.2 Test limit

FCC Part15.207

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

### 6.7.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/60Hz.

### 6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.5 Test result

The test results are shown in Appendix B.

## **7 MEASUREMENT UNCERTAINTIES**

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB



## **8 TEST EQUIPMENTS**

No.	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2019.08.20	2020.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2020.03.01	2021.02.28
3.	Power Sensor E9327A	Agilent	MY52420006	2020.03.01	2021.02.28
4.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----	----
5.	Turn table Diameter:5m	FRANKONIA	----	----	----
6.	Antenna master SAC(MA4.0)	MATURO	----	----	----
7.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----	----
8.	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2019.08.20	2020.08.19
9.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2019.08.20	2020.08.19
10.	ESI 40 EMI test receiver	R&S	100015	2019.08.20	2020.08.19
11.	ESCS30 EMI test receiver	R&S	100029	2019.08.20	2020.08.19
12.	HL562 Receive antenna	R&S	100167	2019.08.20	2020.08.19
13.	ENV216 AMN	R&S	3560.6550.12	2019.08.20	2020.08.19


## APPENDIX A – TEST DATA OF CONDUCTED EMISSION

### 6dB Bandwidth

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB


Modulation type: GFSK (LE 1Mbps)

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2402	0	665.93
2440	19	665.73
2480	39	664.33




Date: 20.APR.2020 04:10:16

Carrier frequency (MHz): 2402  
Channel No.:0  
Modulation type: GFSK (LE 1Mbps)



Carrier frequency (MHz): 2440  
Channel No.:19  
Modulation type: GFSK (LE 1Mbps)



Carrier frequency (MHz): 2480  
Channel No.:39  
Modulation type: GFSK (LE 1Mbps)

**Peak Power Output**

Modulation type	Peak Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-2.84	-2.09	-3.08


Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-5.09	-3.92	-5.13

**Transmitter Power Spectral Density**

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB


Modulation type: GFSK (LE 1Mbps)

Carrier frequency (MHz)	Channel No	Power Density( dBm/3kHz)
2402	0	-20.59
2440	19	-19.54
2480	39	-20.81




Date: 20.APR.2020 04:16:15

Carrier frequency (MHz): 2402  
Channel No.:0  
Modulation type: GFSK (LE 1Mbps)



Carrier frequency (MHz): 2440  
 Channel No.:19  
 Modulation type: GFSK (LE 1Mbps)





Carrier frequency (MHz): 2480  
 Channel No.:39  
 Modulation type: GFSK (LE 1Mbps)

**Conducted Out of band emission measurement**



Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

Modulation type: GFSK (LE 1Mbps)



CH0



CH19



CH39









**Band edge measurement (RF Conducted measurement)**

Offset 1.2dB = Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

**CH0 GFSK (LE 1Mbps)**



**CH39 GFSK (LE 1Mbps)**



## **APPENDIX B – TEST DATA OF RADIATED EMISSION**

### **Radiated Emission Band Edge**

The worst case attitude: The mobile lay down.

The measurement results are obtained as described below:

Measure Level = Reading Level + cable loss + antenna factor

Sample calculation: (88.79 dBuV/m) = (54.79 dBμV) + (8.90 dB) + (25.10 dB), the corresponding frequency is 2402MHz.

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	88.79	54.79	N/A	N/A	8.90	25.10
2	2390	32.66	-1.34	-41.34	74.00	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	80.88	46.88	N/A	N/A	8.90	25.10
2	2390	30.79	-3.21	-43.21	74.00	8.90	25.10

Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	73.75	39.75	N/A	N/A	8.90	25.10
2	2390	22.98	-11.02	-31.02	54.00	8.90	25.10



Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2402	69.18	35.18	N/A	N/A	8.90	25.10
2	2390	21.21	-12.79	-32.79	54.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	88.65	54.65	N/A	N/A	8.90	25.10
2	2483.5	33.26	-0.74	-40.74	74.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	80.63	46.63	N/A	N/A	8.90	25.10
2	2483.5	28.19	-5.81	-45.81	74.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE)

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	73.18	39.18	N/A	N/A	8.90	25.10
2	2483.5	21.37	-12.63	-32.63	54.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE)

Polarity: Horizontal

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	69.08	35.08	N/A	N/A	8.90	25.10
2	2483.5	21.72	-12.28	-32.28	54.00	8.90	25.10

### Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the  $A_{Rpl}$  is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result=  $P_{mea} + A_{Rpl}$

Sample calculation:  $(29.99\text{dBuV/m}) = (50.69\text{dBuV}) + (-20.7\text{dB})$ , the corresponding frequency is 31.455000MHz.

The worst case attitude: The mobile lay down.

For GFSK (LE)

Channel No.:0

Frequency (MHz)	Result (dBuV/m)	$A_{Rpl}$ (dB)	$P_{mea}$ (dBuV/m)	Polarity	Limit (dBuV/m)
31.455000	29.99	-20.7	50.69	Vertical	40.00
43.240500	22.70	-17.8	40.50	Vertical	40.00
77.190500	20.63	-23.3	43.93	Vertical	40.00
87.569500	15.93	-21.4	37.33	Vertical	40.00
196.112500	21.65	-18.6	40.25	Vertical	43.50
958.290000	24.31	-0.8	25.11	Vertical	46.00


Channel No.:19

Frequency (MHz)	Result (dBuV/m)	$A_{Rpl}$ (dB)	$P_{mea}$ (dBuV/m)	Polarity	Limit (dBuV/m)
32.0855	30.16	-20.6	50.76	Vertical	40
43.2405	22.27	-17.8	40.07	Vertical	40
77.724	20.17	-23.4	43.57	Vertical	40
87.7635	14.54	-21.3	35.84	Vertical	40
195.676	23.65	-18.7	42.35	Vertical	43.5
944.419	23.29	-0.9	24.19	Vertical	46


Channel No.:39

Frequency (MHz)	Result (dBuV/m)	A <sub>Rpl</sub> (dB)	P <sub>mea</sub> (dBuV/m)	Polarity	Limit (dBuV/m)
32.037	28.72	-20.6	49.32	Vertical	40
43.3375	23.45	-17.7	41.15	Vertical	40
63.5135	20.84	-19.6	40.44	Vertical	40
87.9575	14.96	-21.2	36.16	Vertical	40
192.184	22.65	-19	41.65	Vertical	43.5
932.973	23.53	-1	24.53	Vertical	46


Channel No.:0



Frequency Range: 30MHz-1000 MHz  
Detector: QP mode  
Modulation type: GFSK (LE)




Frequency Range: 1GHz-6GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)



Frequency Range: 6GHz-18GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)

Full Spectrum




Preview Result 2-AVG    Preview Result 1-PK+    PK70-74    AV50-54


Comment

Frequency Range: 18GHz-25GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)


Channel No.:19



Frequency Range: 30MHz-1000 MHz  
Detector: QP mode  
Modulation type: GFSK (LE)




Frequency Range: 1GHz-6GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)



Frequency Range: 6GHz-18GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)

Full Spectrum




Preview Result 2-AVG    Preview Result 1-PK+    PK70-74    AV50-54


Comment

Frequency Range: 18GHz-25GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)

Channel No.:39




Frequency Range: 30MHz-1000 MHz  
Detector: QP mode  
Modulation type: GFSK (LE)




Frequency Range: 1GHz-6GHz  
Detector: Av mode and PK mode  
Modulation type: GFSK (LE)





Frequency Range: 6GHz-18GHz  
 Detector: Av mode and PK mode  
 Modulation type: GFSK (LE)

Full Spectrum



Preview Result 2-AVG    Preview Result 1-PK+    PK70-74    AV50-54

Comment

Frequency Range: 18GHz-25GHz  
 Detector: Av mode and PK mode  
 Modulation type: GFSK (LE)

**AC Power line Conducted Emission**


A "reference path loss" Corr.(dB) is established and the  $L_{cable}+ATT+VDF$  is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$P_{result}=P_{mea}+ Corr.(dB)$

Sample calculation:  $(53.98\text{ dB}\mu\text{V}) = (24.28\text{ dB}\mu\text{V}) + (29.7\text{ dB})$ , the corresponding frequency is 0.214000MHz.

Full Spectrum



L+N Line

**MEASUREMENT RESULT:**

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	P <sub>mea</sub> QuasiPeak (dBμV)	P <sub>mea</sub> Average (dBμV)
0.214000	53.98	---	63.05	9.07	N	29.7	24.28	---
0.286000	---	39.15	50.64	11.49	L1	29.7	---	9.45
0.786000	49.39	---	56.00	6.61	L1	29.7	19.69	---
0.786000	---	41.53	46.00	4.47	L1	29.7	---	11.83
1.146000	---	35.96	46.00	10.04	L1	29.7	---	6.26
1.646000	46.58	---	56.00	9.42	L1	29.7	16.88	---
4.582000	---	37.88	46.00	8.12	L1	29.8	---	8.08
4.666000	48.47	---	56.00	7.53	L1	29.8	18.67	---
5.162000	42.82	---	60.00	17.18	L1	29.8	13.02	---
5.162000	---	28.90	50.00	21.10	L1	29.8	---	-0.9
17.318000	---	22.66	50.00	27.34	L1	29.9	---	-7.24
29.938000	32.08	---	60.00	27.92	N	29.9	2.18	---

---End of Test Report---