



TEST REPORT

Report No.: SRTC2020-9003(F)-0010
Product Name: Smartphone
Model Name: HLTE103E
Applicant: Hisense International Co., Ltd.
Manufacturer: Hisense Communications Co., Ltd.
Specification: FCC Part15B (Certification)
(2020 edition)
ANSI C63.4-2014
FCC ID: 2ADOBHLTE103E

The State Radio_monitoring_center Testing Center (SRTC)
15th Building, No.30 Shixing Street, Shijingshan District,
Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory.....	3
1.3 Applicant's details	3
1.4 Manufacturer's details.....	3
1.5 Application details	4
1.6 Reference specification.....	4
1.7 Information of EUT.....	4
1.7.1 General information.....	4
1.7.2EUT details	5
1.7.3 Auxiliary equipment details.....	5
2. Test information	6
2.1 Summary of the test results	6
2.2 Test result.....	7
2.2.1Conducted Emissions-FCC Part15.107	7
2.2.2Radiated Emissions-FCC Part15.109.....	12
2.3. List of test equipments	24

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: 15th Building, No.30 Shixing Street, Shijingshan District
Testing location: No.80, Zhaojiachang, BeizangCun, Daxing District, Beijing, China.
City: Beijing
Country or Region: China
Contacted person: Liu Jia
Tel: +86 10 57996183
Fax: +86 10 57996388
Email: liujiaf@srtc.org.cn

1.3 Applicant's details

Company: Hisense International Co., Ltd.
Address: Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City: Qingdao
Country or Region: China
Contacted person: Geng Ruifeng
Tel: +86-532-80877742
Email: gengruifeng@hisense.com

1.4 Manufacturer's details

Company: Hisense Communications Co., Ltd.
Address: 218 Qianwangang Road, Qingdao Economic & Technological Development Zone, Qingdao, China
City: Qingdao
Country or Region: China
Contacted person: Deng Tingting
Tel: +86-532-55753708
Email: dengtingting@hisense.com

1.5 Application details

Date of reception of test sample: 13th Apr. 2020

Date of test: 15th Apr. 2020 to 23th Apr. 2020

1.6 Reference specification

FCC Part 15B, 2020 (Certification)

1.7 Information of EUT

1.7.1 General information

Product Name of EUT	Smartphone
Model of EUT	HLTE103E
Marketing Name of EUT	Hisense E20
FCC ID	2ADOBHLTE103E
Frequency Range	GSM850/PCS1900 WCDMA Band II / WCDMA Band IV / WCDMA Band V LTE band II/ LTE band IV / LTE band V / LTE band VII/ LTE band XII Bluetooth: 2.4~2.4835GHz WiFi: 2.4~2.4835GHz
Power Supply	Charger/Battery
Nominal Voltage	3.8V
Extreme Temperature	Lowest: -30°C Highest: +50°C
Extreme Voltage	Minimum: 3.5V Maximum: 4.35V
HW Version	FS273--MB-V2.1
SW Version	Hisense_HLTE103E_20_S01_01_02_MX05

1.7.2EUT details

No.	Product Name	Model Name	IMEI
EUT1	Smartphone	HLTE103E	868468040002321
EUT2	Smartphone	HLTE103E	868468040000861

Note1: Hisense Communications Co., Ltd. declares that this two Smartphone is different on the supplier of Camera, LCD, Battery and Memory.

Note2:In this report ,we have test the radiated emissions for both two Smartphone.

1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Charger

Manufacturer	Shenzhen Tianyin Electronics Co.,Ltd
Model Number	TPA-97050100UW01
Input Voltage	100V-240V AC
Output Voltage	5V DC

AE (Auxiliary Equipment) 2#: Battery

Manufacturer	Shenzhen Aerospace Electronic Co.,Ltd.
Model Number	KS103
Capacity	2450mAh
Nominal Voltage	3.8V

AE (Auxiliary Equipment) 3#: Battery

Manufacturer	Shenzhen Utility Power Source Co.,ltd.
Model Number	KS103
Capacity	2450mAh
Nominal Voltage	3.8V

AE (Auxiliary Equipment) 4#: Headset




Manufacturer	Dongguan Keling Electronic Technology Co., Ltd.
Model Number	KS103

Note: In this report, EUT1 exercised by the charger AE1 the Battery AE3 and the headset AE4 while EUT2 exercised by the charger AE1 the Battery AE2 and the headset AE4.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By: Liu Wei Director of the test department 	Checked By: Guo Yu Vice director of the test department 
Tested by: Mr. Lv Youyou Test engineer 	Issued date: 2020.04.24

2.2 Test result

2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
22.6°C	40.9%	100.8kPa

Test Setup with charger:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT is connected with LISN via the charger. The LISN is connected to the reference ground.

The test set-up and the test methods are performed according to ANSI C63.4:2014. Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

Test Setup with laptop:




Figure 2

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and was charged. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained.

The AC main power supply of the laptop is connected to LISN and LISN is connected to the reference ground. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

A “reference path loss” Corr.(dB) is established and the $L_{cable}+ATT+VDF$ is the attenuation of “reference path loss”, and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{result}=P_{mea}+Corr.(dB)$$

Sample calculation: $(39.85dB\mu V) = (10.1 dB\mu V) + (29.7 dB)$, the corresponding frequency is 0.286000MHz.


Limit:

Frequency of Emission(MHz)	Limits(dB μ V)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: * Decreases with the logarithm of the frequency


Test result:

Noise Level of the Measuring Instrument



Pic1.Conducted emission L and N Line


EUT1+ charger:



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)	P _{mea} QuasiPeak	P _{mea} Average
0.286000	---	39.85	50.64	10.79	L1	29.7	---	10.1
0.286000	53.83	---	60.64	6.81	L1	29.7	24.1	---
0.502000	49.74	---	56.00	6.26	L1	29.7	20.0	---
0.718000	---	43.31	46.00	2.69	L1	29.7	---	13.6
1.646000	---	39.33	46.00	6.67	L1	29.7	---	9.63
1.722000	47.30	---	56.00	8.70	L1	29.7	17.6	---
4.582000	52.53	---	56.00	3.47	L1	29.8	22.7	---
4.582000	---	39.16	46.00	6.84	L1	29.8	---	9.36
5.162000	47.08	---	60.00	12.92	L1	29.8	17.2	---
5.162000	---	37.36	50.00	12.64	L1	29.8	---	7.56
14.826000	---	19.45	50.00	30.55	L1	29.9	---	-10.4
18.198000	28.72	---	60.00	31.28	N	30.0	-1.28	---

EUT1+Laptop:



Pic3. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr (dB)	Pmea QuasiPeak	Pmea Average
0.150000	---	30.93	56.00	25.07	N	29.7	---	1.23
0.150000	52.99	---	66.00	13.01	L1	29.7	23.29	---
0.386000	31.65	---	58.15	26.50	N	29.7	1.95	---
0.454000	---	30.67	46.80	16.14	L1	29.7	---	0.97
1.918000	26.00	---	56.00	30.00	L1	29.7	-3.7	---
1.946000	---	19.29	46.00	26.71	L1	29.7	---	-10.41
3.570000	---	25.83	46.00	20.17	N	29.8	---	-3.97
4.198000	34.67	---	56.00	21.33	N	29.8	4.87	---
11.126000	35.90	---	60.00	24.10	L1	29.9	6	---
11.154000	---	28.97	50.00	21.03	L1	29.9	---	-0.93
12.558000	25.94	---	60.00	34.06	N	29.9	-3.96	---
13.106000	---	19.91	50.00	30.09	L1	29.9	---	-9.99

2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
22.7°C	41.2%	100.8kPa

Test Setup:




Figure 3

Test Procedure:

EUT+Charger:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT should work in idle mode. The function of FM has been open for standby without connect. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: $f > 1\text{GHz}$

EUT+Laptop:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and was charged. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained. The test set-up and the test methods are performed according to ANSI C63.4:2014

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing.

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Sample calculation: $(32.61 \text{ dB}\mu\text{V/m}) = (53.71 \text{ dB}\mu\text{V}) + (-21.1 \text{ dB})$, the corresponding frequency is 30.242500MHz.

Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB μ V/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54
	Peak	74

Test result:

EUT1+ charger:

Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV)	Polarity
30.242500	32.61	-21.1	53.71	V
43.046500	22.90	-17.8	40.70	V
64.823000	20.32	-20.0	40.32	V
86.939000	14.11	-21.6	35.71	V
190.001500	22.18	-19.2	41.38	V
957.562500	24.29	-0.8	25.09	V

EUT1+Laptop:

Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV)	Polarity
167.982500	27.74	-20.8	48.54	V
215.997500	27.44	-18.0	45.44	V
311.979000	27.04	-14.7	41.74	V
359.994000	32.78	-13.1	45.88	V
591.387500	34.03	-6.8	40.83	V
998.739000	37.21	-0.4	37.61	V


EUT2+ charger:

Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV)	Polarity
31.212500	34.25	-20.8	55.05	V
42.610000	17.79	-17.8	35.59	V
66.326500	17.97	-20.5	38.47	V
168.516000	23.69	-20.7	44.39	V
187.140000	28.04	-19.4	47.44	V
940.636000	25.02	-1.0	26.02	V

EUT2+Laptop:


Frequency(MHz)	Result(dBuV/m)	A _{Rpl} (dB)	P _{mea} (dBuV)	Polarity
167.982500	22.64	-20.8	43.44	V
215.997500	27.19	-18.0	45.19	V
264.012500	27.73	-16.1	43.83	V
359.994000	32.78	-13.1	45.88	V
503.990500	27.73	-9.2	36.93	V
998.399500	37.97	-0.4	38.37	V

EUT1+ charger: refer to Pic4,Pic5 and Pic6




Pic4. Radiated emission (30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic5. Radiated emission (1GHz –6GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic6. Radiated emission (6GHz –18GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical

EUT1+Laptop: refer to Pic7,Pic8 and Pic9




Pic7. Radiated emission(30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic8. Radiated emission (1GHz –6GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic9. Radiated emission (6GHz –18GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical

EUT2+ charger: refer to Pic10,Pic11 and Pic12



Pic10. Radiated emission (30MHz – 1GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical



Comment

Pic11. Radiated emission (1GHz –6GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic12. Radiated emission (6GHz –18GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical

EUT2+Laptop: refer to Pic13,Pic14 and Pic15




Pic13. Radiated emission (30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic14. Radiated emission (1GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic15. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mS emi-AnechoicChamber	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
2	ESW EMI test receiver	R&S	101574	20th Aug. 2020	20th Aug. 2019
3	CMW500 Mobile Station Tester	R&S	160132	20th Aug. 2020	20th Aug. 2019
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
5	ESIB7 EMI test receiver	R&S	100280	20th Aug. 2020	20th Aug. 2019
6	VULB 9163Ultra log test antenna	R&S	867	20th Aug. 2020	20th Aug. 2019
7	ENV216 AMN	R&S	3560.6550. 12	20th Aug. 2020	20th Aug. 2019
8	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	20th Aug. 2020	20th Aug. 2019
9	PS2000 Turn Table	FRANKONIA	-----	-----	-----
10	MA260 Antenna Master	FRANKONIA	-----	-----	-----
11	EMC32EMI test software	R&S	-----	-----	-----

-----The end-----