

# TEST REPORT FOR GSM TESTING

---

Report No.: SRTC2019-9004(F)-19011703(A)

Product Name: Mobile Phone

Product Model: HLTE215E

Applicant: Hisense International Co., Ltd.

Manufacturer: Hisense Communications Co., Ltd.

Specification: FCC Part 24E, Part 22H, Part 2 (2019)

FCC ID: 2ADOBHLTE215E

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

## CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>2</b>
1.1 NOTES OF THE TEST REPORT .....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY .....	2
1.3 APPLICANT’S DETAILS .....	2
1.4 MANUFACTURER’S DETAILS .....	2
1.5 TEST ENVIRONMENT .....	3
<b>2 DESCRIPTION OF THE DEVICE UNDER TEST .....</b>	<b>4</b>
2.1 FINAL EQUIPMENT BUILD STATUS .....	4
2.2 SUPPORT EQUIPMENT .....	5
2.3 CONDUCTED MEASUREMENT PATH LOSS .....	5
2.4 SUMMARY TABLE .....	5
<b>3 REFERENCE SPECIFICATION .....</b>	<b>6</b>
<b>4 KEY TO NOTES AND RESULT CODES .....</b>	<b>7</b>
<b>5 RESULT SUMMARY .....</b>	<b>8</b>
<b>6 TEST RESULT .....</b>	<b>9</b>
6.1 RF POWER OUTPUT-FCC PART 2.1046 .....	9
6.2 EFFECTIVE RADIATED POWER-FCC PART 22.913(A)/PART 24.232(c) .....	10
6.3 OCCUPIED BANDWIDTH-FCC PART 2.1049 .....	12
6.4 EMISSION BANDWIDTH-FCC PART 22.917(B)/PART 24.238(B) .....	13
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINAL-FCC PART 2.1051/ 22.917(A) /PART 24.238(A) .....	14
6.6 BAND EDGES COMPLIANCE- FCC PART 2.1051/ 22.917(A) /PART 24.238(A) .....	15
6.7 FREQUENCY STABILITY- FCC PART 2.1055/22.355 /PART 24.235 .....	16
6.8 RADIATED SPURIOUS EMISSIONS-FCC PART 2.1053/ 22.917(A)/PART 24.238(A) .....	17
6.9 PEAK-AVERAGE RATIO -FCC PART 24.232(d) .....	21
<b>7 MEASUREMENT UNCERTAINTIES .....</b>	<b>22</b>
<b>8 TEST EQUIPMENTS .....</b>	<b>23</b>
<b>APPENDIX A – TEST DATA OF CONDUCTED EMISSION .....</b>	<b>24</b>
<b>APPENDIX B – TEST DATA OF RADIATED EMISSION .....</b>	<b>49</b>

## 1. GENERAL INFORMATION

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### 1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

### 1.3 Applicant's details

Company:	Hisense International Co., Ltd.
Address:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City:	Qingdao
Country or Region:	China
Contacted person:	Geng Ruifeng
Tel:	+86-532-80877742
Fax:	---
Email:	gengruifeng@hisense.com

### 1.4 Manufacturer's details

Company:	Hisense Communications Co., Ltd.
Address:	218 Qianwangang Road, Qingdao Economic & Technological Development Zone, Qingdao, China
City:	Qingdao
Country or Region:	China
Contacted person:	Zhang chuanzhu
Tel:	+86-532-55756010
Fax:	---
Email:	zhangchuanzhu@hisense.com

## 1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-01-17
Testing Start Date:	2019-01-17
Testing End Date:	2019-03-06

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30
Maximum Extreme	35	---
Minimum Extreme	0	---

Normal Supply Voltage (V d.c.):	3.85
Maximum Extreme Supply Voltage (V d.c.):	4.40
Minimum Extreme Supply Voltage (V d.c.):	3.50

## 2 DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status

Frequency Range	GSM850: Tx:824~849MHz Rx:869~894MHz PCS1900: Tx:1850~1910MHz Rx:1930~1990MHz
Modulation Type	GSM/GPRS:GMSK EDGE: GMSK/8PSK
Emission Designator	300KGXW/300KG7W
Duplex Mode	FDD
Duplex Spacing	GSM850:45MHz PCS1900:80MHz
Antenna Type	PIFA Antenna
Antenna Information	Main Ant(Down-Ant) support GSM850/1900 DIV Ant(Up-Ant) support GSM850/1900
Power Supply	Battery/Charger
HW Version	V1.00
SW Version	L1592.6.01.05.MX05
IMEI	002101541913327

## 2.2 Support Equipment

The following support equipment was used to exercise the DUT during testing:

Equipment	Battery
Manufacturer	Huizhou Highpower Technology Co., Ltd.
Model Number	LPN385300A
Serial Number	---

Equipment	Charger
Manufacturer	JIANGSU CHENYANG ELECTRON CO.,LTD
Model Number	CC10-050200U
Serial Number	---

Equipment	Headset
Manufacturer	NEW LEADER INDUSTRY CO.,LTD
Model Number	NLD-EM116T-046S
Serial Number	---

Equipment	USB Cable
Manufacturer	SHENZHEN FKY-QY HARDWARE ELECTRONIC CO.,LTD
Model Number	FKYM1-2428L10WHR-C1
Serial Number	---

## 2.3 Conducted measurement Path Loss

GSM850 Offset 6.5dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.3dB

PCS1900 Offset 6.8dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

## 2.4 Summary table.

FCC Rule Part	Mode	Frequency Range(MHz)	Conducted (Average)、(dBm)	ERP/ EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
22H	GSM850	824.2-848.8	32.28	0.259	0.020	247KGXW
22H	EDGE850	824.2-848.8	32.26	0.258	0.018	250KG7W
24E	GSM1900	1850.2-1909.8	29.18	0.208	0.019	246KGXW
24E	EDGE1900	1850.2-1909.8	29.12	0.205	0.033	243KG7W

### **3 REFERENCE SPECIFICATION**

Specification	Version	Title
2.1046	2019	Measurements required: RF power output.
2.1049	2019	Measurements required: Occupied bandwidth.
2.1051	2019	Measurements required: Spurious emissions at antenna terminals.
2.1053	2019	Measurements required: Field strength of spurious radiation.
2.1055	2019	Measurements required: Frequency stability.
22.355	2019	Frequency tolerance.
22.913	2019	Effective radiated power limits.
22.917	2019	Emission limitations for cellular equipment.
24.232	2019	Power and antenna height limits.
24.235	2019	Frequency stability.
24.238	2019	Emission limitations for Broadband PCS equipment.
ANSI C63.26	2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
KDB 971168 D01	April 9, 2018	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

#### **4 KEY TO NOTES AND RESULT CODES**




The following are the definition of the test result.

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTC	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature



## 5 RESULT SUMMARY

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power and Effective Isotropic Radiated Power	22.913(a)/24.232(c)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Emission Bandwidth	22.917(b)/24.238(b)	Pass
5	Spurious Emissions at antenna terminals	2.1051/22.917(a)/24.238(a)	Pass
6	Band Edges Compliance	2.1051/22.917(a)/24.238(a)	Pass
7	Frequency Stability	2.1055/22.355/24.235	Pass
8	Radiated Spurious Emissions	2.1053/22.917(a)/24.238(a)	Pass
9	Peak-Average Ratio	24.232(d)	Pass

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. He Dengshun 	Issued date:  20190307


## **6 TEST RESULT**

### **6.1 RF Power Output-FCC Part 2.1046**

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits	≤33.0dBm
--------	----------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits	≤30.0dBm
--------	----------

Test result:


The test results are shown in Appendix A.

## 6.2 Effective Radiated Power-FCC Part 22.913(a)/Part 24.232(c)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

$$\text{Power (EIRP)} = P_{\text{mea}} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$ .

The measurement will be done at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits:

Operation Mode	Power Step	E.R.P. (dBm)
GSM	5	≤38.45
GPRS	3	≤38.45
EDGE	6	≤38.45

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

$$\text{Power (EIRP)} = P_{\text{mea}} + G_a$$

The measurement will be done at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits:

Operation Mode	Power Step	E.I.R.P. (dBm)
GSM	0	≤33
GPRS	3	≤33
EDGE	5	≤33

Test result:


The test results are shown in Appendix A.

### 6.3 Occupied Bandwidth-FCC Part 2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


The test results are shown in Appendix A.

### 6.4 Emission Bandwidth-FCC Part 22.917(b)/Part 24.238(b)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific emission bandwidth requirements in part 22.917(b)

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific emission bandwidth requirements in part 24.238(b)

Test result:


The test results are shown in Appendix A.

### 6.5 Spurious Emissions at antenna terminal-FCC Part 2.1051/ 22.917(a) /Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10<sup>th</sup> harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

The measurement will be conducted at one channel No189 (middle channel of GSM850 band)

Limits	≤-13dBm
--------	---------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10<sup>th</sup> harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

The measurement will be conducted at one channel No661 (middle channel of PCS1900 band)

Limits	≤-13dBm
--------	---------

Test result:


The test results are shown in Appendix A.

### 6.6 Band Edges Compliance- FCC Part 2.1051/ 22.917(a) /Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.

The measurement will be conducted at two channels No128 and No251 (Bottom and top channels of GSM850 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.

The measurement will be conducted at two channels No512 and No810 (Bottom and top channels of PCS1900 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------

Test result:

The test results are shown in Appendix A.




## 6.7 Frequency Stability- FCC Part 2.1055/22.355 /Part 24.235

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test setup:



### GSM850

Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from LV to HV. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 22.355.

### PCS1900

Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from LV to HV. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 24.235.

Test result:


The test results are shown in Appendix A.

### 6.8 Radiated Spurious Emissions-FCC Part2.1053/ 22.917(a)/Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



---

## GSM850

### Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10<sup>th</sup> harmonic of the highest frequency generated within the equipment.

### Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10<sup>th</sup> harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

### Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power ( $P_{mea}$ ) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna ( $P_{ca}$ ) and the Substitution Antenna Gain ( $G_a$ ).

### Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{mea} + P_{ca} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15 \text{ (dB)}$ .

Assumed the power of signal source record is -20dBm. A cable loss of -30dB, and an antenna gain of 11dB are added.

$$P=P_{\text{mea}}+P_{\text{ca}}+G_{\text{a}}=(-20\text{dBm})+(-30\text{dB})+(11\text{dB})=-39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 128), middle (Channel 189) and top (Channel 251) channels of the GSM 850 band.

PCS1900

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10<sup>th</sup> harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10<sup>th</sup> harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power ( $P_{\text{mea}}$ ) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_{\text{r}}$ ). The power of signal source ( $P_{\text{mea}}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna ( $P_{\text{ca}}$ ) and the Substitution Antenna Gain ( $G_{\text{a}}$ ).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{\text{mea}} + P_{\text{ca}} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$ .

Assumed the power of signal source record is -20dBm. A cable loss of -30dB and an antenna gain of 11dB are added.

$$P = P_{\text{mea}} + P_{\text{ca}} + G_a = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 512), middle (Channel 661) and top (Channel 810) channels of PCS 1900 band.

Test result:


The test results are shown in Appendix B.

**6.9 Peak-Average Ratio -FCC Part 24.232(d)**

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The Peak-Average Ratio is measured using spectrum analyzer. RBW is set to 30kHz on spectrum analyzer. The Peak-Average Ratio can be read on spectrum analyzer.

Limits: the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test result:

The test results are shown in Appendix A

## 7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

## **8 TEST EQUIPMENTS**

No.	Name/Model	Manufacturer	S/N	Calibration Date	Calibration Due Date
1	E5515C(8960) Mobile Station Tester	Agilent	MY50266302	2018.08.20	2019.08.19
2	N9020A Spectrum Analyzer	Agilent	MY48010771	2018.08.20	2019.08.19
3	6007 Power Divider	Weinschel	6007-GJ-1	2018.08.20	2019.08.19
4	DC Power Supply E3645A	Agilent	MY40000741	2019.03.01	2020.02.28
5	Temperature chamber SH241	ESPEC	92013758	2018.08.20	2019.08.19
6	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	----	----	----
7	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----	----
8	Turn table Diameter:1m	FRANKONIA	----	----	----
9	Turn table Diameter:5m	FRANKONIA	----	----	----
10	Antenna master FAC(MA4.0)	MATURO	----	----	----
11	Antenna master SAC(MA4.0)	MATURO	----	----	----
12	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----	----
13	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2018.08.20	2019.08.19
14	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100513	2018.08.20	2019.08.19
15	HL562 Ultra log antenna	R&S	100016	2018.08.20	2019.08.19
16	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2018.08.20	2019.08.19
17	ESI 40 EMI test receiver	R&S	100015	2018.08.20	2019.08.19
18	ESCS30 EMI test receiver	R&S	100029	2018.08.20	2019.08.19
19	HL562 Receive antenna	R&S	100167	2018.08.20	2019.08.19
20	ENV216 AMN	R&S	3560.6550.12	2018.08.20	2019.08.19

### **APPENDIX A – TEST DATA OF CONDUCTED EMISSION**

Please refer to the attachment.

### **APPENDIX B – TEST DATA OF RADIATED EMISSION**

Please refer to the attachment.



## APPENDIX A – TEST DATA OF CONDUCTED EMISSION

### RF Power Output-FCC Part2.1046

Main ANT and DIV ANT are TX diversity switching.

GSM850

Main Antenna Gain=-6.0dBi

DIV Antenna Gain=-7.0dBi

GSM Measured Power:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	Main Ant ERP (W)	DIV Ant ERP (W)
824.2	128	32.19	0.254	0.201
836.4	189	32.26	0.258	0.205
848.8	251	32.20	0.254	0.202

GPRS Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant ERP (W)	DIV Ant ERP (W)
824.2	128	4Downlink1uplink	32.20	0.254	0.202
836.4	189		32.28	0.259	0.206
848.8	251		32.21	0.255	0.202
824.2	128	3Downlink2uplink	30.68	0.179	0.142
836.4	189		30.72	0.181	0.144
848.8	251		30.75	0.182	0.145
824.2	128	2Downlink3uplink	29.02	0.122	0.097
836.4	189		29.14	0.126	0.100
848.8	251		28.92	0.119	0.095
824.2	128	1Downlink4uplink	27.34	0.083	0.066
836.4	189		27.32	0.083	0.066
848.8	251		27.46	0.085	0.068

EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant ERP (W)	DIV Ant ERP (W)
824.2	128	GMSK 4Downlink1uplink	32.17	0.252	0.200
836.4	189		32.26	0.258	0.205
848.8	251		32.21	0.255	0.202
824.2	128	GMSK 3Downlink2uplink	30.65	0.178	0.141
836.4	189		30.69	0.179	0.143
848.8	251		30.70	0.180	0.143
824.2	128	GMSK 2Downlink3uplink	29.07	0.124	0.098
836.4	189		29.12	0.125	0.099
848.8	251		28.97	0.121	0.096
824.2	128	GMSK 1Downlink4uplink	27.32	0.083	0.066
836.4	189		27.40	0.084	0.067
848.8	251		27.38	0.084	0.067

**EGPRS (8DPSK) Measured Power:**

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant ERP (W)	DIV Ant ERP (W)
824.2	128	8DPSK 4Downlink1uplink	26.48	0.068	0.054
836.4	189		26.16	0.063	0.050
848.8	251		26.35	0.066	0.052
824.2	128	8DPSK 3Downlink2uplink	25.07	0.049	0.039
836.4	189		25.12	0.050	0.040
848.8	251		25.14	0.050	0.040
824.2	128	8DPSK 2Downlink3uplink	23.48	0.034	0.027
836.4	189		23.45	0.034	0.027
848.8	251		23.36	0.033	0.026
824.2	128	8DPSK 1Downlink4uplink	21.78	0.023	0.018
836.4	189		21.82	0.023	0.018
848.8	251		21.65	0.022	0.018

**PCS1900**

Main Antenna Gain=-9.5dBi

DIV Antenna Gain=-6.0dBi

**GSM Measured Power:**

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	Main Ant EIRP (W)	DIV Ant EIRP (W)
1850.2	512	28.98	0.089	0.199
1880.0	661	29.14	0.092	0.206
1909.8	810	28.90	0.087	0.195

**GPRS Measured Power:**

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant EIRP (W)	DIV Ant EIRP (W)
1850.2	512	4Downlink1uplink	29.01	0.089	0.200
1880.0	661		29.18	0.093	0.208
1909.8	810		28.94	0.088	0.197
1850.2	512	3Downlink2uplink	27.74	0.067	0.149
1880.0	661		27.46	0.063	0.140
1909.8	810		27.12	0.058	0.129
1850.2	512	2Downlink3uplink	25.98	0.044	0.100
1880.0	661		25.53	0.040	0.090
1909.8	810		25.54	0.040	0.090
1850.2	512	1Downlink4uplink	24.67	0.033	0.074
1880.0	661		24.55	0.032	0.072
1909.8	810		24.18	0.029	0.066

EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant EIRP (W)	DIV Ant EIRP (W)
1850.2	512	GMSK 4Downlink1uplink	28.92	0.087	0.196
1880.0	661		29.12	0.092	0.205
1909.8	810		28.98	0.089	0.199
1850.2	512	GMSK 3Downlink2uplink	27.75	0.067	0.150
1880.0	661		27.43	0.062	0.139
1909.8	810		27.15	0.058	0.130
1850.2	512	GMSK 2Downlink3uplink	25.98	0.044	0.100
1880.0	661		25.48	0.040	0.089
1909.8	810		25.52	0.040	0.090
1850.2	512	GMSK 1Downlink4uplink	24.56	0.032	0.072
1880.0	661		24.53	0.032	0.071
1909.8	810		24.12	0.029	0.065

EGPRS (8DPSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Main Ant EIRP (W)	DIV Ant EIRP (W)
1850.2	512	8DPSK 4Downlink1uplink	24.80	0.034	0.076
1880.0	661		24.23	0.030	0.067
1909.8	810		24.12	0.029	0.065
1850.2	512	8DPSK 3Downlink2uplink	23.78	0.027	0.060
1880.0	661		23.25	0.024	0.053
1909.8	810		22.98	0.022	0.050
1850.2	512	8DPSK 2Downlink3uplink	21.86	0.017	0.039
1880.0	661		21.45	0.016	0.035
1909.8	810		21.05	0.014	0.032
1850.2	512	8DPSK 1Downlink4uplink	20.92	0.014	0.031
1880.0	661		20.48	0.013	0.028
1909.8	810		20.14	0.012	0.026

## Occupied Bandwidth-FCC Part2.1049

### GSM850

#### GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	246.06
836.4	189	246.67
848.8	251	244.47

#### EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	244.96
836.4	189	249.64
848.8	251	245.68

### PCS1900

#### GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	245.76
1880.0	661	243.92
1909.8	810	241.21

#### EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	241.02
1880.0	661	243.09
1909.8	810	240.19

GSM850 Offset 6.5dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.3dB


PCS1900 Offset 6.8dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

GSM850


GSM/GPRS MODE:



Channel 128




Channel 189




Channel 251


EDGE (GMSK) MODE:



Channel 128




Channel 189




Channel 251

PCS1900

GSM/GPRS MODE:




Channel 512




Channel 661






Channel 810


EDGE (GMSK) MODE:



Channel 512



Channel 661



Channel 810

**Emission Bandwidth-FCC Part 22.917(b)/Part 24.238(b)**

GSM850

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	310.3
836.4	189	317.6
848.8	251	319.6

EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	317.2
836.4	189	317.6
848.8	251	318.5

PCS1900

GSM/GPRS MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	309.6
1880.0	661	311.9
1909.8	810	313.8

EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	313.3
1880.0	661	314.1
1909.8	810	312.6

### Spurious Emissions at antenna terminal- FCC Part 2.1051/ 22.917(a) /Part 24.238(a) GSM850

GSM/GPRS MODE:




Channel 189, 30MHz~824MHz




Channel 189, 824MHz~849MHz

Note: The signal beyond the limit is the signal transmitted by EUT.




Channel 189, 849MHz~9GHz

EDGE (GMSK) MODE:




Channel 189, 30MHz~824MHz



Channel 189, 824MHz~849MHz


Note: The signal beyond the limit is the signal transmitted by EUT.




Channel 189, 849MHz~9GHz

PCS1900

GSM/GPRS MODE:




Channel 661, 30MHz~1850MHz




Channel 661, 1850MHz~1910MHz

Note: The signal beyond the limit is the signal transmitted by EUT.




Channel 661, 1910MHz~20GHz

EDGE (GMSK) MODE:




Channel 661, 30MHz~1850MHz





Channel 661, 1850MHz~1910MHz

Note: The signal beyond the limit is the signal transmitted by EUT.




Channel 661, 1910MHz~20GHz


**Band Edges Compliance- FCC Part 2.1051/ 22.917(a) /Part 24.238(a)**

GSM850

GSM/GPRS MODE:




Channel 128




Channel 251

EDGE (GMSK) MODE:




Channel 128




Channel 251

PCS1900

GSM/GPRS MODE:




Channel 512




Channel 810

EDGE (GMSK) MODE:



Channel 512



Channel 810

## Frequency Stability- FCC Part 2.1055/22.355 /Part 24.235

GSM850

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 128	Channel 189	Channel 251
0	-0.005	0.017	0.001
+10	0.018	0.014	0.016
+20	0.004	-0.005	0.020
+30	0.017	0.020	0.018
+35	0.016	0.020	-0.013

Voltage	Test Result (ppm)@NT		
	Channel 128	Channel 189	Channel 251
LV	0.007	0.005	0.009
HV	0.013	0.008	0.012

EDGE (GMSK) MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 128	Channel 189	Channel 251
0	-0.013	0.007	0.016
+10	-0.016	-0.006	0.017
+20	0.002	0.005	-0.008
+30	0.019	0.018	0.015
+35	-0.003	0.010	0.013

Voltage	Test Result (ppm)@NT		
	Channel 128	Channel 189	Channel 251
LV	0.011	0.013	0.012
HV	0.010	0.017	0.008

PCS1900

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 512	Channel 661	Channel 810
0	0.011	0.019	0.011
+10	0.012	0.016	-0.001
+20	-0.007	-0.012	0.007
+30	0.012	0.011	0.018
+35	0.001	-0.008	0.013

Voltage	Test Result (ppm)@NT		
	Channel 512	Channel 661	Channel 810
LV	0.011	0.016	0.011
HV	0.014	0.008	0.014

EDGE (GMSK) MODE:


Temperature(°C)	Test Result (ppm)@NV		
	Channel 512	Channel 661	Channel 810
0	-0.020	0.010	0.018
+10	0.013	-0.002	0.009
+20	0.007	0.014	-0.012
+30	0.004	0.003	0.019
+35	-0.018	0.010	-0.017

Voltage	Test Result (ppm)@NT		
	Channel 512	Channel 661	Channel 810
LV	0.022	0.033	0.015
HV	0.017	0.024	0.016


**Peak-Average Ratio -FCC Part 24.232(d)**

PCS1900

GSM/GPRS MODE:




EDGE (GMSK) MODE:






GSM850

GSM/GPRS MODE:



EDGE (GMSK) MODE:



## **APPENDIX B – TEST DATA OF RADIATED EMISSION**

### **GSM850 Test result:**

We chose Main Ant to perform the test for the worst case.

GSM/GPRS MODE Channel 128:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1650.87	-48.92	-13	Vertical
1665.45	-46.90	-13	Vertical
2535.90	-40.72	-13	Vertical
2576.31	-41.39	-13	Vertical
8966.80	-37.56	-13	Vertical
9967.52	-34.49	-13	Vertical

EDGE (GMSK) MODE Channel 128:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1649.54	-48.27	-13	Vertical
1668.32	-47.51	-13	Vertical
2536.16	-40.60	-13	Vertical
2575.65	-41.17	-13	Vertical
8966.79	-37.91	-13	Vertical
9970.34	-34.05	-13	Vertical

GSM/GPRS MODE Channel 189:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1649.45	-48.94	-13	Vertical
1667.81	-47.74	-13	Vertical
2533.39	-40.67	-13	Vertical
2576.50	-40.72	-13	Vertical
8960.42	-37.72	-13	Vertical
9969.82	-34.95	-13	Vertical

EDGE (GMSK) MODE Channel 189:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1648.80	-48.72	-13	Vertical
1669.04	-47.59	-13	Vertical
2536.80	-40.86	-13	Vertical
2576.37	-41.24	-13	Vertical
8960.85	-38.07	-13	Vertical
9972.07	-34.19	-13	Vertical

**GSM/GPRS MODE Channel 251:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1650.49	-48.35	-13	Vertical
1666.00	-47.25	-13	Vertical
2533.70	-41.10	-13	Vertical
2577.38	-41.17	-13	Vertical
8965.89	-37.97	-13	Vertical
9969.26	-33.92	-13	Vertical

**EDGE (GMSK) MODE Channel 251:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1648.97	-49.73	-13	Vertical
1665.67	-48.07	-13	Vertical
2535.80	-40.61	-13	Vertical
2576.49	-41.20	-13	Vertical
8961.50	-38.36	-13	Vertical
9969.76	-34.29	-13	Vertical

**GSM1900 Test result:**

We chose DIV Ant to perform the test for the worst case.

**GSM/GPRS MODE Channel 512**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2459.93	-48.88	-13	Vertical
2778.11	-48.05	-13	Vertical
3729.98	-40.48	-13	Vertical
6681.14	-40.06	-13	Vertical
9960.27	-37.05	-13	Vertical
17822.56	-34.49	-13	Vertical

**EDGE (GMSK) MODE Channel 512:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2458.12	-49.19	-13	Vertical
2775.31	-48.22	-13	Vertical
3727.72	-40.96	-13	Vertical
6679.88	-39.29	-13	Vertical
9963.21	-36.67	-13	Vertical
17819.50	-34.15	-13	Vertical

**GSM/GPRS MODE Channel 661:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2455.99	-49.44	-13	Vertical
2777.93	-47.52	-13	Vertical
3728.95	-41.15	-13	Vertical
6679.08	-39.77	-13	Vertical
9962.42	-37.67	-13	Vertical
17820.30	-34.40	-13	Vertical

**EDGE (GMSK) MODE Channel 661:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2459.38	-48.79	-13	Vertical
2781.14	-47.38	-13	Vertical
3727.08	-40.20	-13	Vertical
6677.01	-40.68	-13	Vertical
9960.46	-37.33	-13	Vertical
17822.95	-34.92	-13	Vertical

**GSM/GPRS MODE Channel 810:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2454.96	-49.54	-13	Vertical
2779.30	-48.09	-13	Vertical
3725.83	-40.53	-13	Vertical
6677.18	-39.42	-13	Vertical
9961.11	-37.51	-13	Vertical
17821.95	-33.95	-13	Vertical

**EDGE (GMSK) MODE Channel 810:**

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2457.76	-48.97	-13	Vertical
2778.78	-47.81	-13	Vertical
3728.55	-40.53	-13	Vertical
6677.73	-39.65	-13	Vertical
9960.37	-36.85	-13	Vertical
17823.22	-34.43	-13	Vertical

---End of Test Report---