

Report No.: ZR/2019/B002401

Page: 1 of 27

## **FCC TEST REPORT**

**Application No:** ZR/2019/B0024

Applicant: Hisense International Co., Ltd.

Address of Applicant Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China

Manufacturer: Hisense Communications Co., Ltd.

Address of Manufacturer: No.218 Qianwangang Road, Economic & Technological Development

Zone, Qingdao, China

Factory: Qingdao Intelligent & Precise Electronics Co., Ltd.

Address of Factory: No.218 Qianwangang Road, Economic & Technological Development

Zone, Qingdao, China

EUT Description: Smartphone
Model No.: HLTE226E
Trade Mark: Hisense

FCC ID: 2ADOBHLTE226E Standards: 47 CFR Part 2

> 47 CFR Part 22 subpart H 47 CFR Part 24 subpart E 47 CFR Part 27 subpart C

Test Method: FCC KDB 971168 D01 Power Meas License Digital Systems V03r01

C63.26 (2015)

**Date of Receipt:** 2019/11/25

**Date of Test:** 2019/11/26 to 2019/12/10

**Date of Issue:** 2019/12/10

Test Result: PASS \*

Authorized Signature:

Derole yang

Derek Yang

Wireless Laboratory Manager



<sup>\*</sup> In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Page: 2 of 27

## Version

	Revision Record					
Version	Chapter	Date	Modifier	Remark		
00		2019/12/10		Original		

Mike Mu	
	2019/12/10
(Mike Hu) /Project Engineer	Date
David Chen	
	2019/12/10
(David Chen) /Reviewer	Date
	David Chen





Report No.: ZR/2019/B002401

3 of 27 Page:

## Content

1	VER	SION	2
2	TES	T SUMMARY	5
	2.1	GSM850/UMTS BAND 5 & LTE BAND 5	5
	2.2	GSM 1900/UMTS BAND 2 /LTE BAND 2	5
	2.3	LTE BAND 4	6
	2.4	LTE BAND 7	6
	2.5	LTE BAND 12	7
3	GEN	IERAL INFORMATION	8
	3.1	CLIENT INFORMATION	8
	3.2	TEST LOCATION	8
	3.3	TEST FACILITY	8
	3.4	GENERAL DESCRIPTION OF EUT	9
	3.5	TEST MODE	9
	3.6	TEST ENVIRONMENT	9
	3.7	TECHNICAL SPECIFICATION	10
	3.8	TEST FREQUENCIES	12
4	DES	CRIPTION OF TESTS	16
	4.1	CONDUCTED OUTPUT POWER	16
	4.2	EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	16
	4.3	Occupied Bandwidth	16
	4.4	BAND EDGE AT ANTENNA TERMINALS	17
	4.5	Spurious And Harmonic Emissions at Antenna Terminal	18
	4.6	PEAK-AVERAGE RATIO	18
	4.7	FIELD STRENGTH OF SPURIOUS RADIATION	19
	4.8	FREQUENCY STABILITY / TEMPERATURE VARIATION	20
	4.9	TEST SETUPS	21
	4.9.	1 Test Setup 1	21
	4.9.2	2 Test Setup 2	21
	4.9.3	3 Test Setup 3	22
	4.9.4	4 Test Setup 4	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issue defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention. To check the authenticity of testing /inspection report a certificate, please contact us at telephone: (86-755) 83071443, \*\*Certificate\*\*

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

sgs.china@sgs.com



Report No.: ZR/2019/B002401

Page: 4 of 27

	4.10	TEST CONDITIONS	23
5	MAII	N TEST INSTRUMENTS	25
6	MEA	ASUREMENT UNCERTAINTY	27
7	ΔPP	PENDIXES	27



Page: 5 of 27

## 2 Test Summary

### 2.1 GSM850/UMTS Band 5 & LTE Band 5

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W	Section 1 of Appendix B	Pass
Peak-Average Ratio		Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Section 8 of Appendix B	Pass
Remark: For the verd	ict, the "N/A" denot	es "not applicable", the "N/T" denotes "not te	sted".	

### 2.2 GSM 1900/UMTS Band 2 /LTE Band 2

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§2.1046, §24.232	Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤ -13 dBm/1 MHz, from 9 kHz to 10 <sup>th</sup> harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §24.235	≤ ±2.5 ppm.	Section 8 of Appendix B	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.appx.and">http://www.sgs.com/en/Terms-and-Conditions.appx.and</a> cornel format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 tt(86-755) 26012053 ft(86-755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技园中区M-10栋一号厂房 邮编: 518057 tt(86-755) 26012053 ft(86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2019/B002401

Page: 6 of 27

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	
Remark: For the verd	Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".				

### 2.3 LTE Band 4

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP ≤ 1 W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§2.1046, §27.50(d)	Limit≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §27.53(h)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	≤ -13 dBm/1 MHz, from 9 kHz to 10 <sup>th</sup> harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(h)	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §27.54	≤ ±2.5 ppm.	Section 8 of Appendix B	Pass
Remark: For the verd	lict, the "N/A" denote	es "not applicable", the "N/T" denotes "not	tested".	

## 2.4 LTE Band 7

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Section 1 of Appendix B	Pass
Peak-Average Ratio	§27.50(a)	≤13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge,	Section 5 of Appendix B	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.appx.and">http://www.sgs.com/en/Terms-and-Conditions.appx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.appx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.appx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contactus at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2019/B002401

Page: 7 of 27

Test Item	FCC Rule No.	Requirements	Test Result	Verdict
		where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.		
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	Channel Edge  -25dBm/ 1 MHz 4 MHz 1	Section 6 of Appendix B	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	Channel Edge  -25dBm/ 1 MHz 1 MHz 1 MHz 9 kHz 9 s MHz X MHz 10 <sup>th</sup> harmonics X=Max {6MHz, EBW}	Section 7 of Appendix B	Pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Section 8 of Appendix B	Pass
Remark: For the verd	ict, the "N/A" denot	es "not applicable", the "N/T" denotes "not	tested".	

### 2.5 LTE Band 12

FCC Rule No	Requirements	Test Result	Verdict
§27.50(c)	FCC: ERP ≤ 3 W.	Section 1 of Appendix B	Pass
§2.1046, §27.50(c)	Limit≤13 dB	Section 2 of Appendix B	Pass
§2.1047	Digital modulation	Section 3 of Appendix B	Pass
§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass
§2.1051, §2.7.53(g)	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
§2.1051, §2.7.53(g)	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 <sup>th</sup> harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass
§2.1053, §2 7.53(g)	FCC: ≤ -13 dBm/100 kHz.	Section 7 of Appendix B	Pass
§2.1055, §27.54	≤ ±2.5ppm.	Section 8 of Appendix B	Pass
	\$27.50(c) \$2.1046, \$27.50(c) \$2.1047 \$2.1049 \$2.1051, \$2.7.53(g) \$2.1053, \$2.7.53(g) \$2.1053, \$2.1053, \$2.1053,	\$27.50(c)  \$2.1046, \$27.50(c)  \$2.1047  Digital modulation  \$2.1049  \$2.1049  \$2.1051, \$2.7.53(g)  \$2.1051, \$2.7.53(g)  \$2.1051, \$2.7.53(g)  \$2.1053, \$2.7.53(g)  \$2.1053, \$2.7.53(g)  \$2.1055,  \$2.1055,  \$2.1055,	§27.50(c)       FCC: ERP ≤ 3 W.       Section 1 of Appendix B         §2.1046, §27.50(c)       Limit≤13 dB       Section 2 of Appendix B         §2.1047       Digital modulation       Section 3 of Appendix B         §2.1049       OBW: No limit. EBW: No limit. EBW: No limit. Appendix B       Section 4 of Appendix B         §2.1051, §27.53(g)       ≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block. Appendix B       Section 5 of Appendix B         §2.1051, §27.53(g)       FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges. Appendix B       Section 6 of Appendix B         §2.1053, §27.53(g)       FCC: ≤ -13 dBm/100 kHz. Section 7 of Appendix B         §2.1055, Section 8 of



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.spx.and">http://www.sgs.com/en/Terms-and-Conditions.spx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳•科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Page: 8 of 27

## 3 General Information

#### 3.1 Client Information

Applicant:	Hisense International Co., Ltd.
Address of Applicant:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
Manufacturer:	Hisense Communications Co., Ltd.
Address of Manufacturer:	No.218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, China
Factory:	Qingdao Intelligent & Precise Electronics Co., Ltd.
Address of Factory:	No.218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, China

#### 3.2 Test Location

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
E-mail:	ee.shenzhen@sgs.com

## 3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

#### • Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issue defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention. To check the authenticity of testing /inspection report a certificate, please contact us at telephone: (86-755) 8307 1443, or email. \*\*The Proceduced Records\*\*.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Page: 9 of 27

## 3.4 General Description of EUT

EUT Description::	Smartphone	
Model No.:	HLTE226E	
Trade Mark:	Hisense	
Hardware Version:	V1.00	
Software Version:	L1703.6.01.01.MX02	
Sample Type:	□ Portable Device, □ Module	
Antenna Type:	☐ External, ☑ Integrated	
	GSM850: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	GSM1900: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	WCDMA Band II: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	WCDMA Band IV: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
Antenna Gain:	WCDMA Band V: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
Antenna Gam.	LTE Band 2: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	LTE Band 4: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	LTE Band 5: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	LTE Band 7: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	
	LTE Band 12: 0.5dBi (Main Ant); 0.5dBi (Second Ant);	

### 3.5 Test Mode

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS, GMSK modulation
GSM/TM2	GSM system, EGPRS, 8PSK modulation
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
UMTS/TM2	UMTS system, WCDMA, 16QAM modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation

Remark: The test mode(s) are selected according to relevant radio technology specifications.

### 3.6 Test Environment

Environment Parameter	Selected Values During Tests		
Relative Humidity	52%		
Atmospheric Pressure:	101.32 KPa		
Temperature	NT 25 °C		
	LV 3.55V		
Voltage:	NV	3.85V	
	HV	4.4V	

Remark: LV= lower extreme test voltage; NV= nominal voltage HV= upper extreme test voltage; NT= normal temperature



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention. To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND poccheck-processors.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Page: 10 of 27

## 3.7 Technical Specification

Characteristics	Description				
	⊠ GSM				
Radio System Type	□ UMTS     □				
	□ LTE				
	Band	TX	RX		
	GSM850	824 to 849 MHz	869 to 894 MHz		
	GSM1900	1850 to 1910 MHz	1930 to 1990 MHz		
	UMTS Band II	1850 to 1910 MHz	1930 to 1990 MHz		
0	UMTS Band IV	1710 to 1755 MHz	2110 to 2155 MHz		
Supported Frequency Range	UMTS Band V	824 to 849 MHz	869 to 894 MHz		
rango	LTE Band 2	1850 to 1910 MHz	1930 to 1990 MHz		
	LTE Band 4	1710 to 1755 MHz	2110 to 2155 MHz		
	LTE Band 5	824 to 849 MHz	869 to 894 MHz		
	LTE Band 7	2500 to 2570 MHz	2620 to 2690 MHz		
	LTE Band 12	699 to 716 MHz	729 to 746 MHz		
Target TX Output Power	GSM850:33.00 dBm GSM1900: 30.50dBm UMTS Band II: 23.50dBm UMTS Band IV: 23.50dBm UMTS Band V: 24.00dBm LTE Band 2: 23.50dBm LTE Band 4: 23.50dBm LTE Band 5: 24.00dBm LTE Band 7: 23.50dBm LTE Band 12: 23.50dBm				
	GSM system:	⊠0.2 MHz			
Companied Channel	UMTS system: LTE Band 2	∑5 MHz   ∑1.4 MHz;∑3 MHz; ∑5 MHz; ∑10 MHz;   ∑15 MHz, ∑20 MHz			
Supported Channel Bandwidth	LTE Band 4	☐ 13 MHz, ☐ 20 MHz; ☐ 5 MHz; ☐ 10 MHz; ☐ 15 MHz, ☐ 20 MHz			
	LTE Band 5 LTE Band 7				
	LTE Band 12	\( \sqrt{3} \) MHz, \( \sqrt{1} \) MHz, \( \sqrt{2} \) MHz; \( \sqrt{3} \) MHz; \( \sqrt{3} \) MHz; \( \sqrt{1} \) MHz; \( \sqrt{1} \) MHz; \( \sqrt{1} \)			
Characteristics	Description				
Designation of	GSM850	247KGXW; 252KG7W			
Emissions	GSM1900	247KGXW; 260KG7W			
(Remark: the necessary	UMTS Band II	4M17F9W;			
bandwidth of which is	UMTS Band IV UMTS Band V	4M17F9W; 4M15F9W;			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contactus at telephone: (85-755) 83071443,

or small: CM. Doccheck@sgs\_com Mo. Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・科技園中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.china@sgs.com



Report No.: ZR/2019/B002401

11 of 27 Page:

the worst value from		1M09G7D;1M09W7D;
the measured occupied		2M69G7D;2M68W7D;
bandwidths for each	LTE Band 2	4M49G7D;4M49W7D;
		8M99G7D;9M01W7D;
type of channel		13M7G7D;13M7W7D;
bandwidth		18M1G7D;18M1W7D;
configuration.)		1M09G7D;1M09W7D;
		2M69G7D;2M69W7D;
	LTE David 4	4M50G7D;4M50W7D;
	LTE Band 4	9M01G7D;8M97W7D;
		13M7G7D;13M7W7D;
		18M2G7D;18M2W7D;
	LTE Band 5	1M09G7D;1M09W7D;
		2M69G7D;2M69W7D;
		4M49G7D;4M51W7D;
		9M00G7D;9M01W7D;
		4M49G7D;4M50W7D;
		8M97G7D;8M99W7D;
	LTE Band 7	13M6G7D;13M7W7D;
		18M2G7D;18M1W7D;
		1M09G7D;1M09W7D;
	LTE David 40	2M69G7D;2M68W7D;
	LTE Band 12	4M50G7D;4M50W7D;
		8M97G7D;8M99W7D;





Report No.: ZR/2019/B002401

12 of 27 Page:

## 3.8 Test Frequencies

Toot Mode	TV / DV	RF Channel		
Test Mode	TX / RX	Low (L)	Middle (M)	High (H)
	TX RX	Channel 128	Channel 190	Channel 251
GSM850		824.2MHz	836.6 MHz	848.8 MHz
		Channel 128	Channel 190	Channel 251
		869.2 MHz	881.6 MHz	893.8 MHz

Test Mode	TX / RX	RF Channel		
i est ivioue		Low (L)	Middle (M)	High (H)
GSM1900	TX RX	Channel 512	Channel 661	Channel 810
		1850.2MHz	1880.0 MHz	1909.8 MHz
		Channel 512	Channel 661	Channel 810
		1930.2 MHz	1960.0 MHz	1989.8 MHz

Test Mode	TX / RX	RF Channel		
rest Mode	IA/KA	Low (L)	Middle (M)	High (H)
	TX	Channel 9262	Channel 9400	Channel 9538
WCDMA Band II	IA	1852.4 MHz	1880.0 MHz	1907.6 MHz
	RX	Channel 9662	Channel 9800	Channel 9938
		1932.4 MHz	1960.0 MHz	1987.6 MHz

Test Mode	TX / RX	RF Channel		
i est iviode	IA/KA	Low (L)	Middle (M)	High (H)
	TX	Channel 1312	Channel 1413	Channel 1513
WCDMA Band IV		1712.4MHz	1732.6 MHz	1752.6 MHz
	RX	Channel 1537	Channel 1638	Channel 1738
		2112.4 MHz	2132.6 MHz	2152.6 MHz

Test Mode	TV / DV	RF Channel		
i est iviode	TX / RX	Low (L)	Middle (M)	High (H)
	TX	Channel 4132	Channel 4182	Channel 4233
WCDMA Band V		826.4MHz	836.4 MHz	846.6 MHz
	RX	Channel 4357	Channel 4407	Channel 4458
		871.4 MHz	881.4 MHz	891.6 MHz





Report No.: ZR/2019/B002401

13 of 27 Page:

Toot Mode	Bandwidth	TX / RX		RF Channel	
Test Mode	Danuwidin	17/87	Low (L)	Middle (M)	High (H)
		TV	Channel 18607	Channel 18900	Channel 19193
	1.4MHz	TX	1850.7 MHz	1880 MHz	1909.3 MHz
	1.4IVITZ	RX	Channel 607	Channel 900	Channel 1193
		NA.	1930.7 MHz	1960 MHz	1989.3 MHz
		TX	Channel 18615	Channel 18900	Channel 19185
	3MHz	1.	1851.5 MHz	1880 MHz	1908.5 MHz
	SIVITZ	RX	Channel 615	Channel 900	Channel 1185
		NA.	1931.5 MHz	1960 MHz	1988.5 MHz
		TX	Channel 18625	Channel 18900	Channel 19175
	5MHz	1.X	1852.5 MHz	1880 MHz	1907.5 MHz
		RX	Channel 625	Channel 900	Channel1175
LTE Band 2			1932.5 MHz	1960 MHz	1987.5 MHz
LIE Dallu Z		TX	Channel 18650	Channel 18900	Channel 19150
	10MHz		1855 MHz	1880 MHz	1905 MHz
	TOME	RX	Channel 650	Channel 900	Channel 1150
			1935 MHz	1960 MHz	1985 MHz
		TX	Channel 18675	Channel 18900	Channel 19125
	15MHz		1857.5 MHz	1880 MHz	1902.5 MHz
	ISIVITZ	RX	Channel 675	Channel 900	Channel 1125
		NA.	1937.5 MHz	1960 MHz	1982.5 MHz
		TX	Channel 18700	Channel 18900	Channel 19100
	20MHz	1.	1860 MHz	1880 MHz	1900 MHz
	ZUIVITZ	RX	Channel 700	Channel 900	Channel 1100
		ΓΛ	1940 MHz	1960 MHz	1980 MHz

Test Mode	Bandwidth	TV / DV		RF Channel														
rest wode	Dandwidth	TX / RX	Low (L)	Middle (M)	High (H)													
		TV	Channel 19957	Channel 20175	Channel 20393													
	1 4141	TX	1710.7 MHz	1732.5 MHz	1754.3 MHz													
	1.4MHz	RX	Channel 1975	Channel 2175	Channel 2375													
		r.x	2112.5 MHz	2132.5MHz	2152.5 MHz													
		TX	Channel 19965	Channel 20175	Channel 20385													
	3MHz	1.	1711.5 MHz	1732.5 MHz	1753.5 MHz													
		DV	Channel 2000	Channel 2175	Channel 2350													
		RX	2115 MHz	2132.5MHz	2150 MHz													
	d 4 5MHz	TX	Channel 19975	Channel 20175	Channel 20375													
		1.	1712.5 MHz	1732.5 MHz	1752.5 MHz													
LTE Band 4		RX	Channel 1975	Channel 2175	Channel 2375													
			2112.5 MHz	2132.5MHz	2152.5 MHz													
		TX	Channel 20000	Channel 20175	Channel 20350													
	10MH=	10MH-	10MH-	10MU=	10MH=	101/1⊔~	10MU <del>-</del>	10MH=	10MH-	10MU=	10MH=	10MU~	10M⊔→	10MHz	1.	1715 MHz	1732.5 MHz	1750 MHz
	TUIVITZ	RX	Channel 2000	Channel 2175	Channel 2350													
		NA.	2115 MHz	2132.5MHz	2150 MHz													
	15MHz	TX	Channel 20025	Channel 20175	Channel 20325													
		1.	1717.5 MHz	1732.5 MHz	1747.5 MHz													
		RX	Channel 2025	Channel 2175	Channel 2325													
			2117.5 MHz	2132.5MHz	2147.5 MHz													
	20MHz	TX	Channel 20050	Channel 20175	Channel 20300													



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.spx.and">http://www.sgs.com/en/Terms-and-Conditions.spx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



Report No.: ZR/2019/B002401

14 of 27 Page:

	1720 MHz	1732.5 MHz	1745 MHz
DV	Channel 2050	Channel 2175	Channel 2300
RX	2120 MHz	2132.5MHz	2145 MHz

To at Marila	D	TV / DV		RF Channel			
Test Mode	Bandwidth TX / R		Low (L)	Middle (M)	High (H)		
	1.4MHz	TX	Channel 20407	Channel 20525	Channel 20643		
		1.	824.7 MHz	836.5 MHz	848.3 MHz		
		DV	Channel 2407	Channel 2525	Channel 2643		
		RX	869.7 MHz	881.5 MHz	893.3 MHz		
		TX	Channel 20415	Channel 20525	Channel 20635		
	3MHz	1.7	825.5 MHz	836.5 MHz	847.5 MHz		
		RX	Channel 2415	Channel 2525	Channel 2635		
LTE Band 5			870.5 MHz	881.5 MHz	892.5 MHz		
LIE Danu 5		TV	Channel 20425	Channel 20525	Channel 20625		
	TX	1.	826.5 MHz	836.5 MHz	846.5 MHz		
	SIVITZ	5MHz	Channel 2425	Channel 2525	Channel 2625		
				RX	871.5 MHz	881.5 MHz	891.5 MHz
		TX	Channel 20450	Channel 20525	Channel 20600		
	400411-	1.	829 MHz	836.5 MHz	844 MHz		
	10MHz	DV	Channel 2450	Channel 2525	Channel 2600		
	RX	874 MHz	881.5 MHz	889 MHz			

Toot Made	Donaluidth	TV / DV		RF Channel		
Test Mode	Bandwidth	TX / RX	Low (L)	Middle (M)	High (H)	
		TX	Channel 20775	Channel 21100	Channel 21425	
	5N1U-7	1.	2502.5 MHz	2535 MHz	2567.5 MHz	
	5MHz	RX	Channel 2775	Channel 3100	Channel 5825	
		NA.	2622.5 MHz	2655 MHz	2687.5 MHz	
		TX	Channel 20800	Channel 21100	Channel 21400	
	10MHz	1.	2505 MHz	2535 MHz	2565 MHz	
		RX	Channel 2800	Channel 3100	Channel 3400	
LTE Band 7			2625 MHz	2655 MHz	2685 MHz	
LIE Dallu I		TX	Channel 20825	Channel 21100	Channel 21375	
		15MU-	15MHz	1.	2507.5 MHz	2535 MHz
	ISIVITZ	RX	Channel 2825	Channel 3100	Channel 3375	
		NA.	2627.5 MHz	2655 MHz	2682.5 MHz	
		TX	Channel 20850	Channel 21100	Channel 21350	
	20MH-	1.	2510 MHz	2535 MHz	2560 MHz	
	20MHz	DV	Channel 2850	Channel 3100	Channel 3350	
	RX		2630 MHz	2655 MHz	2680 MHz	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.spx.and">http://www.sgs.com/en/Terms-and-Conditions.spx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

sgs.china@sgs.com



Report No.: ZR/2019/B002401

15 of 27 Page:

Toot Mode	Danduidth	TV / DV	RF Channel		
Test Mode	Bandwidth	TX / RX	Low (L)	Middle (M)	High (H)
			Channel 23017	Channel 23095	Channel 23173
	1.4MHz	TX	699.7 MHz	707.5 MHz	715.3 MHz
	1.4IVITZ	RX	Channel 5017	Channel 5095	Channel 5173
		NA.	729.7 MHz	737.5 MHz	745.3 MHz
		TX	Channel 23025	Channel 23095	Channel 23165
	3MHz	'^	700.5 MHz	707.5 MHz	714.5 MHz
	SIVITZ	RX	Channel 5025	Channel 5095	Channel 5165
LTE Pand12	LTE Band12		730.5 MHz	737.5 MHz	744.5 MHz
LIE Dallu 12		TX	Channel 23035	Channel 23095	Channel 23155
	5MHz	1.	701.5 MHz	707.5 MHz	713.5 MHz
	SIVITZ	RX	Channel 5035	Channel 5095	Channel 5155
			731.5 MHz	737.5 MHz	743.5 MHz
		TX	Channel 23060	Channel 23095	Channel 23130
	10MHz	1.	704 MHz	707.5 MHz	711 MHz
	TOWINZ	RX	Channel 5060	Channel 5095	Channel 5130
		ĽΛ	734 MHz	737.5 MHz	741 MHz



Page: 16 of 27

#### **Description of Tests** 4

## 4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Remark: Reference test setup 1

## 4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01; C63.26 (2015)

Calculate power in dBm by the following formula:

ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd)

EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP=ERP+2.15dB

## 4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Remark: Reference test setup 1



Page: 17 of 27

#### **Test Settings**

- 1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- Sweep = auto couple
- The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within
  - 1 5% of the 99% occupied bandwidth observed in Step 7

## 4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold

#### Remark: Reference test setup 1

#### Test Settings

- Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW > 1% of the emission bandwidth
- VBW ≥ 3 x RBW
- Detector = RMS
- Number of sweep points ≥ 2 x Span/RBW
- Trace mode = trace average for continuous emissions, max hold for pulse emissions
- Sweep time = auto couple
- 9. The trace was allowed to stabilize



Page: 18 of 27

## 4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

#### Remark: Reference test setup 1

#### Test Settings

- Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental frequency (separated into at least two plots per channel)
- Detector = RMS
- Trace mode = trace average for continuous emissions, max hold for pulse emissions
- Sweep time = auto couple
- The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

## 4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.1

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Remark: Reference test setup 1



Page: 19 of 27

#### Test Settings

- The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

## 4.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01

#### Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

#### Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] - cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log10(Power [Watts]).

#### Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber



Page: 20 of 27

2) Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) – cable loss (dB) + antenna gain (dBi) EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete

Remark: Reference test setup 3

## 4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; ANSI/C63.26 (2015)

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm ) of the center frequency.

#### **Time Period and Procedure:**

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Remark: Reference test setup 4




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

Report No.: ZR/2019/B002401

21 of 27 Page:

## 4.9 Test Setups

## 4.9.1 Test Setup 1



**Ground Reference Plane** 

### 4.9.2 Test Setup 2




Figure 1. 30MHz to 1GHz




Figure 2. above 1GHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.agpx.and">http://www.sgs.com/en/Terms-and-Conditions.agpx.and</a>, for electronic format document, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /imspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

www.sgsgroup.com.cn sgs.china@sgs.com

Report No.: ZR/2019/B002401

22 of 27 Page:

### 4.9.3 Test Setup 3




Figure 1. Below 30MHz





Figure 2. 30MHz to 1GHz

Figure 3. above 1GHz

### 4.9.4 Test Setup 4



Ground Reference Plane



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issue defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and his document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention. To check the authenticity of testing /inspection report 2 certificate, please contact us at telephone: (86-755) 8307 1443, \*\* \*\*Exercity\*\* \*\*Testing\*\* \*\*Testing\*\*

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn

中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

sgs.china@sgs.com

Report No.: ZR/2019/B002401

Page: 23 of 27

### 4.10 Test Conditions

Test Case		Test Conditions			
		Test Environment	Ambient Climate & Rated Voltage		
	Average	Test Setup	Test Setup 1		
	Power,	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
Transmit Output		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		
Power		Test Environment	Ambient Climate & Rated Voltage		
Data	Average Power,	Test Setup	Test Setup 1		
	Spectral Density (if	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
	required)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Tool Wood	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Peak-to-Average Ratio (if required)		Test Setup	Test Setup 1		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Tool Wood	UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Modulation		Test Setup	Test Setup 1		
Characteris	tics	RF Channels (TX)	M (M= middle channel )		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
	Occupied Bandwidth	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
Bandwidth		Tool Wood	UMTS/TM2; LTE/TM1;LTE/TM2		
Emission Bandwidth		Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
	(if	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)		
	required)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.spx.and">http://www.sgs.com/en/Terms-and-Conditions.spx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳•科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2019/B002401

Page: 24 of 27

	Test Environment	Ambient Climate & Rated Voltage
Day 4 Eduar	Test Setup	Test Setup 1
Band Edges Compliance	RF Channels (TX)	L, H (L= low channel, H= high channel )
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
	rest Mode	UMTS/TM2; LTE/TM1;LTE/TM2
	Test Environment	Ambient Climate & Rated Voltage
Spurious Emission at	Test Setup	Test Setup 1
Spurious Emission at Antenna Terminals	RF Channels (TX)	L,M, H
,	Tri Orialineis (TX)	(L= low channel, M= middle channel, H= high channel)
	Test Mode	GSM/TM1;UMTS/TM1;LTE/TM1
	Test Environment	Ambient Climate & Rated Voltage
	Test Setup	Test Setup 2
Field Strength of		GSM/TM1;GSM/TM2;UMTS/TM1;UMTS/TM2; LTE/TM1;LTE/TM2;
Spurious Radiation	Test Mode	Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
	Test Environment	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) VL, VN and VH of Rated Voltage at Ambient Climate.
Frequency Stability	Test Setup	Test Setup 4
Frequency Stability	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
	1 SOL IVIOGO	UMTS/TM2; LTE/TM1;LTE/TM2



Report No.: ZR/2019/B002401

25 of 27 Page:

#### **Main Test Instruments** 5

RE in Chamber							
Took Equipment	Manufacturer	Model No.	Inventory No	Cal. date	Cal.Due date		
Test Equipment	Manufacturer	Wiodel No.	Inventory No.	(yyyy-mm-dd)	(yyyy-mm-dd)		
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12		
Spectrum Analyzer (20Hz-43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2019/3/2	2020/3/1		
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26		
Horn Antenna (800MHz-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/413	2021/412		
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16		
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2019/7/14	2020/7/14		
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2019/7/14	2020/7/14		
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	EMC2063	2019/9/20	2020/9/19		
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2019/3/2	2020/3/1		
Band filter	N/A	N/A	N/A	N/A	N/A		
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A		
Coaxial Cable	SGS	N/A	SEM026-01	2019/6/12	2020/6/11		
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2019/4/3	2020/4/3		
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/1/13	2020/1/12		

	RF conducted t	est			
				Cal. date	Cal.Due date
Test Equipment	Manufacturer	Model No.	Inventory No.	(yyyy-mm-dd)	(yyyy-mm-dd)
Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	2019/10/22	2020/10/21
Signal Analyzer	Rohde & Schwarz	FSV	W005-02	2019/3/2	2020/3/1
Coaxial Cable	SGS	N/A	SEM031-01	2019/6/12	2020/6/11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019/10/22	2020/10/21
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	HTC-1	W006-17	2019/10/22	2020/10/21
Temperature Chamber	GIANT FORCE	ICT-150-40-CP-AR	W027-03	2019/10/22	2020/10/21
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2019/3/2	2020/3/1
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/10/22	2020/10/21





Report No.: ZR/2019/B002401

Page: 26 of 27

				Cal. Date	Cal. Due
Test Equipment	Manufacturer	Model No.	Inventory No.	(yyyy-mm-	date (yyyy-
				dd)	mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2019/4/3	2020/4/3
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/1/13	2020/1/12
EXA Signal Analyzer (10Hz-26.5GHz)	Agilent Technologies Inc	N9010A	SEM004-09	2019/3/13	2020/3/12
Spectrum Analyzer (20Hz-43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2019/3/2	2020/3/1
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26
Horn Antenna (800MHz-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2019/7/25	2020/7/24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019/7/25	2020/7/24
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2019/3/2	2020/3/1
Band filter	N/A	N/A	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019/6/12	2020/6/11
Tunable Notch Filter	WAINRIGHT Instruments	N/A	N/A	N/A	N/A
WRCD1700/2000-0.2/40-10EEK	GMBH	IN/A	IN/A	IN/A	IN/A
Tunable Notch Filter	WAINRIGHT Instruments	N/A	N/A	N/A	N/A
WRCD800/960-0.2/40-10EEK HighPass Filter	GMBH WAINRIGHT Instruments				
WHK1.2/15G-10SS	GMBH	N/A	N/A	N/A	N/A
HighPass Filter	WAINRIGHT Instruments				21/2
WHKX10-2700-3000-18000-40SS	GMBH	N/A	N/A	N/A	N/A
HighPass Filter	WAINRIGHT Instruments	N/A	N/A	N/A	N/A
WHKX7.0/26.5G-6SS	GMBH	IN/A	IN/A	IN/A	14/74
Band Reject Filter	WAINRIGHT Instruments	N/A	N/A	N/A	N/A
WRCG 824/849-814/859-40/8SS	GMBH WAINRIGHT Instruments				
Band Reject Filter WRCG 1850/1910-1835/1925-40/8SS	GMBH	N/A	N/A	N/A	N/A
Measurement Software	AUDIX	e3 V8.2014- 6-27	N/A	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.spx.and">http://www.sgs.com/en/Terms-and-Conditions.spx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing imspection report a certificate, please contact us at telephone: (85-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·科技园中区M-10栋一号厂房

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Page: 27 of 27

#### **Measurement Uncertainty** 6

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data
Transmit Output Power Data	Power [dBm]	U =±0.37 dB
Bandwidth	Magnitude [%]	U =± 0.2%
Band Edge Compliance	Disturbance Power [dBm]	U = ±2.0 dB
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = ±2.0 dB
		For 3 m Chamber:
		U = ±4.5 dB (30 MHz to 1GHz)
Field Strength of Spurious	ERP[dBm]/EIRP [dBm]	U = ±3.3 dB (above 1 GHz)
Radiation	ERF[dBIII]/EIRF [dBIII]	For 10 m Chamber:
		U = ±4.5 dB (30 MHz to 1GHz)
		U = ±3.2 dB (above 1 GHz)
Frequency Stability	Frequency Accuracy [ppm]	U = ±0.24 ppm

## **Appendixes**

Appendix A	Photographs of Set-up for ZR/2019/B0024.	
Appendix B.1	GSM 850 & 1900	
Appendix B.2	WCDMA Band II & IV & V	
Appendix B.3	LTE Band 2	
Appendix B.4	LTE Band 4	
Appendix B.5	LTE Band 5	
Appendix B.6	LTE Band 7	
Appendix B.7	LTE Band 12	

The End

