



FCC SAR TEST REPORT

Report No: STS1512175H01

Issued for

Global Distribution FZE

508/509, The Business Centre Building, Al Hamriya – Bur
Dubai, Po Box 126963, U.A.E.

Product Name:	Quad-core Smartphone
Brand Name:	i.onik
Model No.:	i544
Series Model:	N/A
FCC ID:	2ADPL-I544
Test Standard:	ANSI/IEEE Std. C95.1
	FCC 47 CFR Part 2 (2.1093)
	IEEE 1528: 2013
Max. Reported SAR (1g):	Head:0.792 W/kg
	Body:1.293 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





Test Report Certification

Applicant's name : Global Distribution FZE
Address : 508/509, The Business Centre Building, Al Hamriya – Bur Dubai, Po Box 126963, U.A.E.

Manufacturer's Name : Hong Kong Umedia Limited
Address : Room402, Bld.7, F518 idea land, Baoyuan Road, Bao'an District, Shenzhen, Guangdong, P.R.C

Product description

Product name : Quad-core Smartphone

Trademark : i.onik

Model and/or type reference : i544

Series Model : N/A

Standards : ANSI/IEEE Std. C95.1-1992
FCC 47 CFR Part 2 (2.1093)
IEEE 1528: 2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test

Date (s) of performance of tests : 08 Jan. 2016~11 Jan. 2016

Date of Issue : 12 Jan. 2016

Test Result : **Pass**

Testing Engineer :

Allen Chen

(Allen Chen)

Technical Manager :

John Zou

(John Zou)



Authorized Signatory :

Bovey Yang

(Bovey Yang)



TABLE OF CONTENTS

1. General Information	4
1.1 EUT Description	4
1.2 Test Environment	6
1.3 Test Factory	6
2. Test Standards And Limits	7
3. SAR Measurement System	8
3.1 Definition Of Specific Absorption Rate (SAR)	8
3.2 SAR System	8
3.2.1 Probe	9
3.2.2 Phantom	10
3.2.3 Device Holder	10
4. Tissue Simulating Liquids	11
4.1 Simulating Liquids Parameter Check	11
5. SAR System Validation	13
5.1 Validation System	13
5.2 Validation Result	13
6. SAR Evaluation Procedures	14
7. EUT Antenna Location Sketch	15
7.1 SAR TEST EXCLUSION CONSIDER TABLE	16
8. EUT Test Position	18
8.1 Define Two Imaginary Lines On The Handset	18
8.2 Hotspot mode exposure position condition	19
9. Uncertainty	20
9.1 Measurement Uncertainty	20
9.2 System validation Uncertainty	22
10. Conducted Power Measurement	24
11. EUT And Test Setup Photo	28
11.1 EUT Photo	28
11.2 Setup Photo	31
12. SAR Result Summary	40
12.1 Head SAR	40
12.2 Body-worn SAR	41
12.3 Body SAR And Hotspot	42
12.4 repeated SAR measurement	43
13. Equipment List	46
Appendix A. System Validation Plots	47
Appendix B. SAR Test Plots	63
Appendix C. Probe Calibration And Dipole Calibration Report	75



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Equipment	Quad-core Smartphone				
Brand Name	i.onik				
Model No.	i544				
Series Model	N/A				
FCC ID	2ADPL-I544				
Model Difference	N/A				
Adapter	Input: AC100-240V, 0.35A, 50/60 Hz Output: DC 5V, 700mA				
Battery	Rated Voltage: 3.7V Charge Limit: 4.2V Capacity: 1800mAh				
Device Category	Portable				
Product stage	Production unit				
RF Exposure Environment	General Population / Uncontrolled				
IMEI	135790246811222				
Hardware Version	N/A				
Software Version	N/A				
Frequency Range	GSM 850:824.2 ~ 848.8 MHz PCS1900:1850.2 ~ 1909.8 MHz WCDMA II:1852.4~1907.6 MHz WCDMA IV:1712.4~1752.6 MHz WCDMA V:826.4~846.6 MHz WLAN 802.11 b/g/n(HT20):2412~2462 MHz WLAN 802.11 b/g/n(HT40):2422~2452 MHz Bluetooth:2402~2480 MHz				
Transmit Power(Average):	GSM 850: 28.80dBm GSM 1900: 28.41dBm WCDMA II: 21.25dBm WCDMA IV: 20.71dBm WCDMA V: 22.03dBm		802.11b: 18.23dBm 802.11g: 15.26dBm 802.11 n(HT20): 15.26dBm 802.11 n(HT40): 12.13dBm Bluetooth: 5.268dBm		
Max. Reported SAR(1g):	Band	Mode	Head (W/kg)	Body-worn (W/kg)	Body-hotspot (W/kg)
	PCE	GSM 850	0.462	0.677	0.418
	PCE	GSM 1900	0.578	1.293	1.201
	PCE	WCDMA Band II	0.770	1.156	0.919
	PCE	WCDMA Band IV	0.792	0.755	0.553
	PCE	WCDMA Band V	0.462	0.504	0.269
	DTS	WIFI	0.107	0.160	0.093
	DSS	Bluetooth	0.149 ^{Note}	0.075 ^{Note}	0.075 ^{Note}
1-g Sum SAR(W/kg)		0.941	1.453	1.294	
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS)				



Operating Mode:	GSM: GSM Voice, GPRS, EGPRS Class 12; WCDMA: RMC, HSDPA, HSUPA Release 6; WLAN: 802.11 b/g/n; Bluetooth: V4.0 + EDR (GFSK +π/4DQPSK+8DPSK)
Antenna Specification:	GSM/WCDMA: PIFA Antenna BT/WIFI: PIFA Antenna
Hotspot Mode:	Support
DTM Mode:	Not Support
<p>Note:</p> <ol style="list-style-type: none">1. Bluetooth SAR was estimated2. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active)3. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests.4. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power	





1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required	Actual
Temperature (°C)	18-25	22~23
Humidity (%RH)	30-70	55~65

1.3 Test Factory

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F, Building B, Zhuoke Science Park, No.190, Chongqing Road, Fuyong, Baoan District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649

FCC Registration No.: 842334;

IC Registration No.: 12108A-1





2. Test Standards And Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1999	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 447498 D02 v02r01	SAR measurement procedures for USB dongle transmitters
6	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
7	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
8	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
9	FCC KDB 941225 D06 Hotspot Mode v02r01	SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. According to 1999/519/EC the limit for General Population/Uncontrolled exposure should be applied for this device, it is 2.0 W/kg as averaged over any 10 gram of tissue.

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.4 8.0 20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.08 1.6 4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 10 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

3. SAR Measurement System

3.1 Definition Of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

SATIMO SAR System Diagram:



Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 17/14 EP221 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter :5 mm
- Distance between probe tip and sensor center: 2.7mm
- Distance between sensor center and the inner phantom surface: 4 mm (repeatability better than +/- 1mm)
- Probe linearity: < 0.25 dB
- Axial Isotropy: < 0.25 dB
- Spherical Isotropy: < 0.25 dB
- Calibration range: 450MHz to 2600MHz for head & body simulating liquid. Angle between probe axis (evaluation axis) and surface normal line:less than 30°



Figure 1 – Satimo COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

SN 32/14 SAM115



SN 32/14 SAM116



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Frequency (MHz)	Bactericide	DGBE	HEC	NaCl	Sucrose	X100	Water	Conductivity	Permittivity
	%	%	%	%	%	%	%	σ	ϵ_r
835	0.10	/	1.00	1.45	57.00	/	40.45	0.90	41.6
900	0.10	/	1.00	1.48	56.50	/	40.92	0.98	41.2
1800	/	44.92	/	0.18	/	/	54.9	1.40	40.4
1900	/	44.92	/	0.18	/	/	54.9	1.42	39.9
2100	/	50.0	/	/	/	/	50.0	1.51	36.8
2450	/	7.99	/	0.16	/	/	50.0	1.88	40.3

Tissue dielectric parameters for head and body phantoms				
Frequency	ϵ_r		σ S/m	
	Head	Body	Head	Body
300	45.3	58.2	0.87	0.92
450	43.5	58.7	0.87	0.94
900	41.5	55.0	0.97	1.05
1450	40.5	54.0	1.20	1.30
1800	40.0	53.3	1.40	1.52
2450	39.2	52.7	1.80	1.95
3000	38.5	52.0	2.40	2.73
5800	35.3	48.2	5.27	6.00



LIQUID MEASUREMENT RESULTS

Date: January.08, 2016 Ambient condition: Temperature 22.0°C Relative humidity: 49%

Head Simulating Liquid		Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]					
835 MHz	21.5	Permitivity:	41.5	41.19	-0.75	±5
		Conductivity:	0.9	0.89	-1.11	± 5
1800 MHz	21.5	Permitivity:	40.10	40.2	0.25	±5
		Conductivity:	1.37	1.31	-4.38	± 5
1900 MHz	21.5	Permitivity:	40.0	39.44	-1.40	± 5
		Conductivity:	1.4	1.42	1.43	± 5
2450 MHz	21.5	Permitivity:	39.2	39.38	0.46	± 5
		Conductivity:	1.8	1.77	-1.67	± 5


Body Simulating Liquid		Parameters	Target	Measured	Deviation[%]	Limited[%]
Frequency	Temp. [°C]					
835 MHz	21.5	Permitivity:	55.2	54.262	-1.70	± 5
		Conductivity:	0.97	0.99	2.06	± 5
1800 MHz	21.5	Permitivity:	53.40	52.6	-1.50	± 5
		Conductivity:	1.49	1.38	-7.38	± 5
1900 MHz	21.5	Permitivity:	53.3	52.78	-0.98	± 5
		Conductivity:	1.52	1.55	1.97	± 5
2450 MHz	21.5	Permitivity:	52.7	52.41	-0.55	± 5
		Conductivity:	1.95	1.93	-1.03	± 5

5. SAR System Validation

5.1 Validation System

Each SATIMO system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the SATIMO software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



5.2 Validation Result

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %.

Ambient condition: Temperature 22.7°C

Relative humidity: 49%

Freq.(MHz)	Power(mW)	Tested Value (W/Kg)	Normalized SAR (W/kg)	Target(W/Kg)	Tolerance(%)	Date
835 Head	100	0.928	9.28	9.56	3.02	2016-01-08
835 Body	100	0.988	9.88	9.56	-3.24	2016-01-08
1800 Head	100	3.76	37.6	38.4	-2.08	2016-01-11
1800 Body	100	3.88	38.8	38.4	1.04	2016-01-11
1900 Head	100	4.124	41.24	39.7	-3.49	2016-01-09
1900 Body	100	5.156	51.56	52.4	1.63	2016-01-09
2450 Head	100	5.156	51.56	52.4	1.63	2016-01-11
2450 Body	100	5.108	51.08	52.4	2.58	2016-01-11

Note: The tolerance limit of System validation $\pm 10\%$.

6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Quad-core Smartphone, support GSM mode and WCDMA mode.



WWAN Antenna

WIFI/BT Antenna



7.1 SAR TEST EXCLUSION CONSIDER TABLE

According with FCC KDB 447498 D01, appendix A, <SAR test exclusion thresholds for 100MHz~6GHz and $\leq 50\text{mm}$ >table, this device SAR test configurations consider as following:

Band	Test position configurations					
	Front	Back	Left edge	Right edge	Top edge	Bottom edge
GSM850	<5mm	<5mm	<5mm	29mm	<5mm	118mm
	Yes	Yes	Yes	No	Yes	No
GSM1900	<5mm	<5mm	<5mm	29mm	<5mm	118mm
	Yes	Yes	Yes	No	Yes	No
WCDMA Band2	<5mm	<5mm	<5mm	29mm	<5mm	118mm
	Yes	Yes	Yes	No	Yes	No
WCDMA Band4	<5mm	<5mm	<5mm	29mm	<5mm	118mm
	Yes	Yes	Yes	No	Yes	No
WCDMA Band5	<5mm	<5mm	<5mm	29mm	<5mm	118mm
	Yes	Yes	Yes	No	Yes	No
WLAN	<5mm	<5mm	<5mm	58mm	26mm	96mm
	Yes	Yes	Yes	No	No	No
Bluetooth	<5mm	<5mm	<5mm	58mm	26mm	96mm
	Yes	Yes	Yes	No	No	No

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <5mm, 5mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance $\leq 50\text{mm}$ are determined by:

$[(\text{max.power of channel, including tune-up tolerance, Mw}) / (\text{min. test separation distance, mm})]^*[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

For $<50\text{mm}$ distance, we just calculate mW of the exclusion threshold value(3.0)to do compare per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances $>50\text{mm}$, the SAR test exclusion threshold is determined according to the following

a)[threshold at 50mm in step 1]+(test separation distance -50mm)*(f (MHz)/150)]Mw, at 100 MHz to 1500 MHz



b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at >1500MHz and ≤ 6GHz

6. Per KDB 447498 D02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA/DC-HSDPA output power is <0.25db higher than RMC 12.2Kbps, or reported SAR with RMC 12.2kbps setting is ≤1.2W/Kg, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded.

7. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band , testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode , thus the SAR can be excluded.



8. EUT Test Position


This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

8.1 Define Two Imaginary Lines On The Handset

(1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.

(2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.

(3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost



Title Position

(1) To position the device in the "cheek" position described above.

(2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to 5mm.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm(instead of 10mm)is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration(surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

NO	Source	Tol(%)	Prob. Dist.	Div. k	ci (1g)	ci (10g)	1gUi	10gUi	Veff
Measurement System									
1	Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
2	Axial isotropy	3.5	R	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.43	1.43	∞
3	Hemispherical isotropy	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
4	Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
5	Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
6	System Detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
7	Readout electronics	0.5	N	1	1	1	0.50	0.50	∞
8	Response time	0	R	$\sqrt{3}$	1	1	0	0	∞
9	Integration time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
10	Ambient noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
11	Ambient reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
12	Probe positioner mech. restrictions	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
13	Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
14	Max.SAR evaluation	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test sample related									
15	Device positioning	2.6	N	1	1	1	2.6	2.6	11
16	Device holder	3	N	1	1	1	3.0	3.0	7



17	Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Phantom and set-up									
18	Phantom uncertainty	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
19	Liquid conductivity (target)	2.5	N	1	0.78	0.71	1.95	1.78	5
20	Liquid conductivity (meas)	4	N	1	0.23	0.26	0.92	1.04	5
21	Liquid Permittivity (target)	2.5	N	1	0.78	0.71	1.95	1.78	∞
22	Liquid Permittivity (meas)	5.0	N	1	0.23	0.26	1.15	1.30	∞
Combined standard		RSS	$U_c = \sqrt{\sum_{i=1}^n C_i^2 U_i^2}$				10.63%	10.54%	
Expanded uncertainty (P=95%)		$U = k U_c, k=2$				21.26%	21.08%		



9.2 System validation Uncertainty

NO	Source	Tol(%)	Prob. Dist.	Div. k	ci (1g)	ci (10g)	1gUi	10gUi	Veff
Measurement System									
1	Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
2	Axial isotropy	3.5	R	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.43	1.43	∞
3	Hemispherical isotropy	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
4	Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
5	Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
6	System Detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
7	Modulation response	0	N	1	1	1	0	0	∞
8	Readout electronics	0.5	N	1	1	1	0.50	0.50	∞
9	Response time	0	R	$\sqrt{3}$	1	1	0	0	∞
10	Integration time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
11	Ambient noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
12	Ambient reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
13	Probe positioner mech. restrictions	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
14	Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
15	Max.SAR evaluation	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Dipole									
16	Deviation of experimental source from	4	N	1	1	1	4.00	4.00	∞
17	Input power and SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞



18	Dipole Axis to liquid Distance	2	R	$\sqrt{3}$	1	1			∞
Phantom and set-up									
19	Phantom uncertainty	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
20	Uncertainty in SAR correction for deviation(in	2.0	N	1	1	0.84	2	1.68	∞
21	Liquid conductivity (target)	2	N	1	1	0.84	2.00	1.68	∞
22	Liquid conductivity (temperature uncertainty)	2.5	N	1	0.78	0.71	1.95	1.78	5
23	Liquid conductivity (meas)	4	N	1	0.23	0.26	0.92	1.04	5
24	Liquid Permittivity (target)	2.5	N	1	0.78	0.71	1.95	1.78	∞
25	Liquid Permittivity (temperature uncertainty)	2.5	N	1	0.78	0.71	1.95	1.78	5
26	Liquid Permittivity (meas)	5.0	N	1	0.23	0.26	1.15	1.30	∞
Combined standard			RSS	$U_c = \sqrt{\sum_{i=1}^n C_i^2 U_i^2}$			10.15%	10.05%	
Expanded uncertainty (P=95%)		$U = k U_c, k=2$					20.29%	20.10%	



10. Conducted Power Measurement

Test Result:

Maximum Burst-Averaged Output Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	28.54	28.66	28.35	28.41	28.32	28.21
GPRS (GMSK, 1-Slot)	28.44	28.53	28.33	28.38	28.17	28.17
GPRS (GMSK, 2-Slot)	27.64	27.84	27.50	27.48	27.41	27.23
GPRS (GMSK, 3-Slot)	26.03	26.16	25.85	25.73	25.68	25.59
GPRS (GMSK, 4-Slot)	24.73	24.86	24.59	24.46	24.29	24.27
EGPRS (8PSK, 1-Slot)	28.31	28.42	28.15	28.26	28.07	27.99
EGPRS (8PSK, 2-Slot)	27.49	27.47	27.25	27.45	27.17	27.11
EGPRS (8PSK, 3-Slot)	25.81	25.78	25.46	25.79	25.46	25.47
EGPRS (8PSK, 4-Slot)	24.44	24.43	24.15	24.52	24.11	24.11

Remark: GPRS, CS4 coding scheme.
 Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link
 Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link
 Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

Maximum Frame-Averaged Output Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	19.51	19.63	19.32	19.38	19.29	19.18
GPRS (GMSK, 1-Slot)	19.41	19.50	19.30	19.35	19.14	19.14
GPRS (GMSK, 2-Slot)	21.62	21.82	21.48	21.46	21.39	21.21
GPRS (GMSK, 3-Slot)	21.77	21.90	21.59	21.47	21.42	21.33
GPRS (GMSK, 4-Slot)	21.72	21.85	21.58	21.45	21.28	21.26
EGPRS (8PSK, 1-Slot)	19.28	19.39	19.12	19.23	19.04	18.96
EGPRS (8PSK, 2-Slot)	21.47	21.45	21.23	21.43	21.15	21.09
EGPRS (8PSK, 3-Slot)	21.55	21.52	21.20	21.53	21.20	21.21
EGPRS (8PSK, 4-Slot)	21.43	21.42	21.14	21.51	21.10	21.10

Remark :

1. SAR testing was performed on the maximum frame-averaged power mode.
2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = Burst averaged power (1 Tx Slot) - 9.03 dB

Frame-averaged power = Burst averaged power (2 Tx Slots) - 6.02 dB

Frame-averaged power = Burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Burst averaged power (4 Tx Slots) - 3.01 dB

Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4183	4233	9263	9400	9538	1313	1450	1512
Frequency (MHz)	826.4	836.6	846.6	1852.4	1880.0	1907.6	1712.6	1740.0	1752.4
RMC 12.2Kbps	22.03	21.89	21.95	21.18	21.22	21.25	20.71	20.41	20.59
HSDPA Subtest-1	21.60	21.44	21.52	20.70	20.76	20.84	20.22	20.00	20.14
HSDPA Subtest-2	21.17	20.90	21.03	20.35	20.24	20.40	19.82	19.59	19.63
HSDPA Subtest-3	20.71	20.45	20.58	19.90	19.81	19.98	19.33	19.10	19.15
HSDPA Subtest-4	20.07	19.86	19.93	19.37	19.19	19.30	18.81	18.46	18.46
HSUPA Subtest-1	21.12	20.97	21.12	20.25	20.34	20.42	19.78	19.50	19.69
HSUPA Subtest-2	20.77	20.44	20.71	19.84	19.93	20.04	19.36	19.07	19.22
HSUPA Subtest-3	20.30	19.99	20.25	19.34	19.44	19.55	18.88	18.58	18.79
HSUPA Subtest-4	19.61	19.45	19.56	18.74	18.83	18.98	18.32	17.94	18.11
HSUPA Subtest-5	19.03	18.85	18.98	18.19	18.23	18.40	17.65	17.43	17.57

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	MAX(CM-1,0)
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device. The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



WIFI

Mode	Channel Number	Frequency (MHz)	Peak Power (dBm)
802.11b	1	2412	17.96
	6	2437	18.04
	11	2462	18.23
802.11g	1	2412	14.31
	6	2437	15.26
	11	2462	15.24
802.11n(HT-20)	1	2412	14.27
	6	2437	15.26
	11	2462	15.24
802.11n(HT-40)	3	2422	10.91
	6	2437	11.96
	9	2452	12.13

Justification for test configurations for WLAN per KDB publication 248227 D01:

1. Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
2. For transmission modes with the same maximum output power specification, power were measured for the largest Channel bandwidth, lowest order modulation and lowest data rate.
3. For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
4. For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
5. The bolded data rate and channel above were tested for SAR.

Bluetooth

Mode	Channel Number	Frequency (MHz)	Peak Power (dBm)
GFSK(1M)	0	2402	4.566
	39	2441	4.420
	78	2480	5.268
$\pi/4$ -DQPSK(2bps)	0	2402	4.188
	39	2441	4.057
	78	2480	4.792
8-DPSK(3Mbps)	0	2402	4.294
	39	2441	4.192
	78	2480	4.971

BT 4.0

Mode	Channel Number	Frequency (MHz)	Peak Power (dBm)
GFSK(1Mbps)	CH01	2402	-2.263
	CH20	2422	-2.647
	CH40	2442	-2.062



Turn Power

Mode	GSM850(AVG)	GSM1900(AVG)
GSM/PCS	27.7±1dBm	27.5±1dBm
GPRS (1 Slot)	27.6±1dBm	27.5±1dBm
GPRS (2 Slot)	27.0±1dBm	26.5±1dBm
GPRS (3 Slot)	25.2±1dBm	25.0±1dBm
GPRS (4 Slot)	24.0±1dBm	23.5±1dBm
EGPRS (1 Slot)	27.5±1dBm	27.5±1dBm
EGPRS (2 Slot)	26.5±1dBm	26.5±1dBm
EGPRS (3 Slot)	25.0±1dBm	25.0±1dBm
EGPRS (4 Slot)	23.5±1dBm	24.0±1dBm

Mode	WCDMA Band V(AVG)	WCDMA Band II(AVG)	WCDMA Band IV(AVG)
RMC	21.1±1dBm	20.3±1dBm	20.0±1dBm
HSDPA Subtest-1	21.0±1dBm	20.0±1dBm	19.5±1dBm
HSDPA Subtest-2	20.2±1dBm	19.5±1dBm	19.0±1dBm
HSDPA Subtest-3	20.0±1dBm	19.0±1dBm	18.5±1dBm
HSDPA Subtest-4	19.1±1dBm	18.5±1dBm	18.0±1dBm
HSUPA Subtest-1	20.2±1dBm	19.5±1dBm	19.0±1dBm
HSUPA Subtest-2	20.0±1dBm	19.1±1dBm	18.5±1dBm
HSUPA Subtest-3	19.5±1dBm	19.0±1dBm	18.0±1dBm
HSUPA Subtest-4	19.0±1dBm	18.0±1dBm	17.5±1dBm
HSUPA Subtest-5	18.1±1dBm	17.5±1dBm	17.0±1dBm

Mode	WIFI(PEAK)
IEEE 802.11b	18±1dBm
IEEE 802.11g	15±1dBm
IEEE 802.11n HT20	15±1dBm
IEEE 802.11n HT40	11.5±1dBm

Mode	BT(PEAK)
GFSK	4.5±1dBm
$\pi/4$ -DQPSK	4±1dBm
8DPSK	4±1dBm

Mode	BT4.0(PEAK)
GFSK	-2±1dBm

11. EUT And Test Setup Photo

11.1 EUT Photo

Front side



Back side



Top side



Bottom side



Left side




Right side




11.2 Setup Photo


Right Touch



Right Tilt




Left Touch




Left Tilt



Body Front side(separation distance is 5mm)




Body Back side(separation distance is 5mm)




Body Front side(separation distance is 10mm)



Body Back side(separation distance is 10mm)



Body Left side(separation distance is 10mm)




Body Top side(separation distance is 10mm)



835 Head Liquid depth (15 cm)



835 Body Liquid depth (15 cm)



1800 Head Liquid depth (15 cm)



1800 Body depth (15 cm)



1900 Head Liquid depth (15 cm)



1900 Body depth (15 cm)



2450 Head Liquid depth (15 cm)



2450 Body Liquid depth (15 cm)





12. SAR Result Summary

12.1 Head SAR

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	Voice	Right Cheek	CH 190	0.458	3.82	28.7	28.66	0.462	1
		Right Tilt	CH 190	0.341	-2.42	28.7	28.66	0.344	/
		Left Cheek	CH 190	0.335	-3.53	28.7	28.66	0.338	/
		Left Tilt	CH 190	0.262	3.92	28.7	28.66	0.264	/
GSM1900	Voice	Right Cheek	CH 512	0.534	-4.81	28.5	28.41	0.545	/
		Right Tilt	CH 512	0.566	-2.68	28.5	28.41	0.578	3
		Left Cheek	CH 512	0.252	-0.85	28.5	28.41	0.257	/
		Left Tilt	CH 512	0.327	1.09	28.5	28.41	0.334	/
WCDMA II	RMC	Right Cheek	CH 9538	0.761	-2.16	21.3	21.25	0.770	5
		Right Tilt	CH 9538	0.647	0.34	21.3	21.25	0.654	/
		Left Cheek	CH 9538	0.419	-0.03	21.3	21.25	0.424	/
		Left Tilt	CH 9538	0.379	-2.55	21.3	21.25	0.383	/
WCDMA IV	RMC	Right Cheek	CH 1313	0.427	-1.41	21	20.71	0.456	/
		Right Tilt	CH 1313	0.741	-0.30	21	20.71	0.792	7
		Left Cheek	CH 1313	0.409	-0.74	21	20.71	0.437	/
		Left Tilt	CH 1313	0.409	-2.54	21	20.71	0.437	/
WCDMA V	RMC	Right Cheek	CH4132	0.455	-0.64	22.1	22.03	0.462	9
		Right Tilt	CH4132	0.332	0.17	22.1	22.03	0.337	/
		Left Cheek	CH4132	0.295	-1.09	22.1	22.03	0.300	/
		Left Tilt	CH4132	0.247	-1.00	22.1	22.03	0.251	/

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
WIFI	802.11b	Right Cheek	CH11	0.090	-0.01	19	18.23	100	0.107	11
		Right Tilt	CH11	0.085	-0.04	19	18.23	100	0.101	/
		Left Cheek	CH11	0.071	0.22	19	18.23	100	0.085	/
		Left Tilt	CH11	0.070	3.23	19	18.23	100	0.084	/

Note: 1. Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg

2. Per KDB 248227 D01- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.054** W/Kg for Head)



12.2 Body-worn SAR

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-3 Slot	Front side	CH 190	0.385	-0.18	26.2	26.16	0.389	/
		Back side	CH 190	0.671	2.19	26.2	26.16	0.677	2
GSM 1900	EGPRS Data-3 Slot	Front side	CH 512	0.540	-3.68	26	25.79	0.567	/
		Back side	CH 512	1.232	-0.51	26	25.79	1.293	4
		Back side	CH 661	1.248	-1.25	26	25.79	1.310	/
		Back side	CH 810	1.169	3.70	26	25.46	1.324	/
WCDMA II	RMC	Front side	CH 9538	0.493	0.30	21.3	21.25	0.499	/
		Back side	CH 9263	0.905	-1.91	21.3	21.18	0.930	/
		Back side	CH 9400	1.135	-0.02	21.3	21.22	1.156	6
		Back side	CH 9538	0.864	-0.42	21.3	21.25	0.874	/
WCDMA IV	RMC	Front side	CH 1313	0.558	-0.50	21	20.71	0.597	/
		Back side	CH 1313	0.706	1.68	21	20.71	0.755	8
WCDMA V	RMC	Front side	CH4132	0.238	-3.01	22.1	22.03	0.242	/
		Back side	CH4132	0.496	-2.64	22.1	22.03	0.504	10

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
WIFI	802.11b	Front side	CH11	0.086	-1.07	19	18.23	100	0.103	/
		Back side	CH11	0.134	-0.19	19	18.23	100	0.160	12

Note: 1. The test separation of all above table is 5mm.

2. Per KDB 248227 D01- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.081** W/Kg for Body-worn)



12.3 Body SAR And Hotspot

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-3 Slot (hotspot)	Front side	CH 190	0.320	1.62	26.2	26.16	0.323	/
		Back side	CH 190	0.414	0.21	26.2	26.16	0.418	/
		Left side	CH 190	0.299	-0.92	26.2	26.16	0.302	/
		Top side	CH 190	0.154	-0.44	26.2	26.16	0.155	/
GSM 1900	EGPRS Data-3 Slot (hotspot)	Front side	CH 512	0.307	-3.90	26	25.79	0.322	/
		Back side	CH 512	1.144	-0.24	26	25.79	1.201	/
		Back side	CH 661	1.055	-3.76	26	25.79	1.107	/
		Back side	CH 810	1.013	-0.71	26	25.46	1.147	/
		Left side	CH 512	0.333	0.24	26	25.47	0.376	/
		Top side	CH 512	0.461	-1.03	26	25.79	0.484	/
WCDMA II	RMC (body-worn and hotspot)	Front side	CH 9538	0.240	0.60	21.3	21.25	0.243	/
		Back side	CH 9263	0.787	-1.89	21.3	21.18	0.809	/
		Back side	CH 9400	0.902	-3.74	21.3	21.22	0.919	/
		Back side	CH 9538	0.698	-2.12	21.3	21.25	0.706	/
		Left side	CH 9538	0.148	1.15	21.3	21.25	0.150	/
		Top side	CH 9538	0.449	1.81	21.3	21.25	0.454	/
WCDMA IV	RMC (body-worn and hotspot)	Front side	CH 1313	0.158	-3.95	21	20.71	0.169	/
		Back side	CH 1313	0.517	1.73	21	20.71	0.553	/
		Left side	CH 1313	0.151	0.30	21	20.71	0.161	/
		Top side	CH 1313	0.336	-1.49	21	20.71	0.359	/
WCDMA V	RMC (body-worn and hotspot)	Front side	CH4132	0.179	-4.19	22.1	22.03	0.182	/
		Back side	CH4132	0.265	-1.86	22.1	22.03	0.269	/
		Left side	CH4132	0.180	-3.57	22.1	22.03	0.183	/
		Top side	CH4132	0.095	-0.25	22.1	22.03	0.097	/

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
WIFI	802.11b	Front side	CH11	0.059	-1.07	19	18.23	100	0.070	/
		Back side	CH11	0.078	-0.19	19	18.23	100	0.093	/
		Left side	CH11	0.066	3.99	19	18.23	100	0.079	/

Note:

1. The test separation of all above table is 10mm.
2. Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.047** W/Kg for Body/Hotspot)
3. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

**Repeated SAR**

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM1900	EGPRS Data-3 Slot	Back side	CH 512	1.227	-0.34	26	25.79	1.288	/
WCDMA II	RMC (hotspot)	Back side	CH 9400	1.116	0.06	21.3	21.22	1.137	/

Note: 1.The test separation of all above table is 5mm

Band	Mode	Test Position	Channel	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM1900	EGPRS Data-3 Slot (hotspot)	Back side	CH 512	1.184	-2.78	26	25.79	1.243	/
WCDMA II	RMC (hotspot)	Back side	CH 9400	0.901	-1.98	21.3	21.22	0.918	/

Note: 1.The test separation of all above table is 10mm.

12.4 repeated SAR measurement

Band	Mode	Test Position	Channel	Original Measured SAR 1g(mW/g)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(mW/g)	2nd Repeated SAR 1g	Ratio
GSM1900	GPRS Data-3 Slot (worn)	Back side	CH 512	1.232	1.227	1.00	-	-	-
	GPRS Data-3 Slot (hotspot)			1.144	1.184	1.03	-	-	-
WCDMA II	RMC (worn)	Back side	CH 9400	1.135	1.116	1.02	-	-	-
	RMC (hotspot)			0.902	0.901	1.00	-	-	-

Note:

1. Per KDB 865664 D01V01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$
4. The ratio is the difference in percentage between original and repeated measured SAR.

**Simultaneous Multi-band Transmission Evaluation:**

Application Simultaneous Transmission information:

Position	Simultaneous state
Head	1. GSM + WIFI
	2. GSM + Bluetooth
	3. WCDMA + WIFI
	4. WCDMA + Bluetooth
Body	1. GSM + WIFI
	2. GSM + Bluetooth
	3. WCDMA + WIFI
	4. WCDMA + Bluetooth

NOTE:

1. Bluetooth and WIFI can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. Based upon KDB 447498 D01, BT SAR is excluded as below table.
4. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
5. For minimum test separation distance \leq 50mm, Bluetooth standalone SAR is excluded according to $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f} (\text{GHz}) / x] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
6. The reported SAR summation is calculated based on the same configuration and test position.
7. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f} (\text{GHz}) / x \leq 5$ W/kg for test separation distances ≤ 50 mm;
Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is >50 mm.

Estimated SAR		Maximum Average Power		Antenna to user(mm)	Frequency(GHz)	Stand alone SAR(1g) [W/kg]		
		dBm	mW					
BT	Head	5.5	3.548	5	2.480	0.149		
	Body			5	2.480	0.149		
				10	2.480	0.075		



Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + WIFI	Head	GSM Voice	0.578	0.685
		WIFI	0.107	
	Body-worn	GSM DATA	1.293	1.453
		WIFI	0.160	
	Body-hotspot	GSM DATA	1.201	1.294
		WIFI	0.093	
GSM + Bluetooth	Head	GSM Voice	0.578	0.627
		Bluetooth	0.149	
	Body-worn	GSM DATA	1.293	1.442
		Bluetooth	0.149	
	Body-hotspot	GSM DATA	1.201	1.276
		Bluetooth	0.075	
WCDMA RMC+ WIFI	Head	WCDMA RMC	0.792	0.899
		WIFI	0.107	
	Body-worn	WCDMA RMC	1.156	1.316
		WIFI	0.160	
	Body-hotspot	WCDMA RMC	0.919	1.012
		WIFI	0.093	
WCDMA RMC+ Bluetooth	Head	WCDMA RMC	0.792	0.941
		Bluetooth	0.149	
	Body-worn	WCDMA RMC	1.156	1.305
		Bluetooth	0.149	
	Body-hotspot	WCDMA RMC	0.919	0.994
		Bluetooth	0.075	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
835MHz Dipole	SATIMO	SID835	SN 30/14 DIP0G835-332	2014.09.01	2017.08.31
1900MHz Dipole	SATIMO	SID1900	SN 30/14 DIP1G900-333	2014.09.01	2017.08.31
2450 MHz Dipole	SATIMO	SID2450	SN 30/14 DIP2G450-335	2014.09.01	2017.08.31
E-Field Probe	SATIMO	SSE5	SN 17/14 EP221	2015.09.01	2016.08.31
Antenna	SATIMO	ANTA3	SN 07/13 ZNTA52	2014.09.01	2017.08.31
Waveguide	SATIMO	SWG5500	SN 13/14 WGA32	2014.09.01	2017.08.31
Phantom1	SATIMO	SAM	SN 32/14 SAM115	N/A	N/A
Phantom2	SATIMO	SAM	SN 32/14 SAM116	N/A	N/A
SAR TEST BENCH	SATIMO	MOBILE PHONE POSITIONNING SYSTEM	SN 32/14 MSH97	N/A	N/A
SAR TEST BENCH	SATIMO	LAPTOP POSITIONNING SYSTEM	SN 32/14 LSH29	N/A	N/A
Dielectric Probe Kit	SATIMO	SCLMP	SN 32/14 OCPG52	2015.09.01	2016.08.31
Multi Meter	Keithley	Multi Meter 2000	4050073	2015.11.20	2016.11.19
Signal Generator	Agilent	N5182A	MY50140530	2015.11.18	2016.11.17
Power Meter	R&S	NRP	100510	2015.10.25	2016.10.24
Power Sensor	R&S	NRP-Z11	101919	2015.10.24	2016.10.23
Power Sensor	Anritsu	MA2411B	1027253	2015.10.10	2016.10.09
Power Sensor	R&S	NRP-Z21	103971	2015.12.12	2016.12.11
Network Analyzer	Agilent	5071C	EMY46103472	2015.12.12	2016.12.11
Attenuator 1	PE	PE7005-10	N/A	2015.10.25	2016.10.24
Attenuator 2	PE	PE7005-3	N/A	2015.10.24	2016.10.23
Attenuator 3	Woken	WK0602-XX	N/A	2015.12.12	2016.12.11
Dual Directional Coupler	Agilent	778D	50783	2015.10.24	2016.10.23

Appendix A. System Validation Plots

System Performance Check Data (835MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-08

Measurement duration: 13 minutes 27 seconds

Experimental conditions

Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity (real part)	41.19
Relative permittivity	18.72
Conductivity (S/m)	0.89
Power drift (%)	0.45
Ambient Temperature:	22.7°C
Liquid Temperature:	22.3°C
ConvF:	4.83
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00

SAR Peak: 1.46 W/kg

SAR 10g (W/Kg)	0.612584
SAR 1g (W/Kg)	0.928356

Z Axis Scan



System Performance Check Data (835MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-08

Measurement duration: 14 minutes 13 seconds

Experimental conditions.

Probe	
Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity (real part)	54.26
Relative permittivity	21.408187
Conductivity (S/m)	0.99
Power drift (%)	0.090000
Ambient Temperature:	22.7°C
Liquid Temperature:	22.3°C
ConvF:	5.02
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00

SAR Peak: 1.48 W/kg

SAR 10g (W/Kg)	0.695261
SAR 1g (W/Kg)	0.987695

Z Axis Scan



System Performance Check Data(1800MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-11

Measurement duration: 14 minutes 10 seconds

Experimental conditions.


Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity (real part)	40.102364
Relative permittivity	14.096855
Conductivity (S/m)	1.368491
Power drift (%)	-1.390000
Ambient Temperature	22.7°C
Liquid Temperature	22.3°C
Probe	SN 17/14 EP221
ConvF	4.25
Crest factor:	1:1



Maximum location: X=7.00, Y=-1.00

SAR 10g (W/Kg)	1.613545
SAR 1g (W/Kg)	3.831264

Z Axis Scan



System Performance Check Data(1800MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-11

Measurement duration: 14 minutes 11 seconds

Experimental conditions.


Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity (real part)	50.102364
Relative permittivity	14.096855
Conductivity (S/m)	1.438491
Power drift (%)	-1.390000
Ambient Temperature	22.7°C
Liquid Temperature	22.3°C
Probe	SN 17/14 EP221
ConvF	4.34
Crest factor:	1:1



Maximum location: X=3.00, Y=0.00

SAR 10g (W/Kg)	1.956348
SAR 1g (W/Kg)	3.861233

Z Axis Scan



System Performance Check Data (1900MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-09

Measurement duration: 14 minutes 12 seconds

Experimental conditions.

Phantom	Validation plane
Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900MHz
Relative permittivity (real part)	39.44
Relative permittivity	13.26
Conductivity (S/m)	1.42
Power drift (%)	0.47
Ambient Temperature:	22.7°C
Liquid Temperature:	22.3°C
Probe	SN 17/14 EP221
ConvF:	4.71
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00

SAR Peak: 5.39 W/kg

SAR 10g (W/Kg)	1.975658
SAR 1g (W/Kg)	3.892354

Z Axis Scan



System Performance Check Data (1900MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2016-01-09

Measurement duration: 14 minutes 46 seconds

Experimental conditions.

Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900
Relative permittivity (real part)	52.78
Relative permittivity	12.87531
Conductivity (S/m)	1.55
Power drift (%)	0.37
Ambient Temperature:	22.7°C
Liquid Temperature:	22.3°C
Probe	SN 17/14 EP221
ConvF:	4.85
Crest factor:	1:1




Maximum location: X=2.00, Y=2.00

SAR Peak: 5.27 W/kg

SAR 10g (W/Kg)	2.135625
SAR 1g (W/Kg)	4.123621

Z Axis Scan



System Performance Check Data (2450MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=5mm, dy=6mm, dz=4mm

Date of measurement: 2016-01-11

Measurement duration: 13 minutes 51seconds

Experimental conditions.


Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity (real part)	39.38
Relative permittivity	12.930000
Conductivity (S/m)	1.77
Power drift (%)	-1.200000
Ambient Temperature	22.7°C
Liquid Temperature	22.3°C
Probe	SN 17/14 EP221
ConvF	4.11
Crest factor:	1:1



Maximum location: X=7.00, Y=6.00

SAR 10g (W/Kg)	2.635821
SAR 1g (W/Kg)	5.156285

Z Axis Scan



System Performance Check Data (2450MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=5mm, dy=6mm, dz=4mm

Date of measurement: 2016-01-11

Measurement duration: 14 minutes 23 seconds

Experimental conditions.


Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity (real part)	52.41
Relative permittivity	12.930000
Conductivity (S/m)	1.93
Power drift (%)	-1.200000
Ambient Temperature	22.7°C
Liquid Temperature	22.3°C
Probe	SN 17/14 EP221
ConvF	4.25
Crest factor:	1:1



Maximum location: X=3.00, Y=1.00

SAR 10g (W/Kg)	2.536281
SAR 1g (W/Kg)	5.108165

Z Axis Scan



Appendix B. SAR Test Plots


Plot 1: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-08
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.83
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 8.32)
Frequency (MHz)	836.6
Relative permittivity (real part)	42.27
Conductivity (S/m)	0.91
Variation (%)	3.82

Maximum location: X=-31.00, Y=1.00

SAR Peak: 0.65 W/kg

SAR 10g (W/Kg)	0.308581
SAR 1g (W/Kg)	0.458345




Plot 2: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-08
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	5.02
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	GPRS 850
Channels	Middle
Signal	Duty Cycle:1.2.66 (Crest factor:2.66)
Frequency (MHz)	836.6
Relative permittivity (real part)	42.27
Conductivity (S/m)	0.91
Variation (%)	2.19

Maximum location: X=22.00, Y=49.00
 SAR Peak:1.17 W/kg

SAR 10g (W/Kg)	0.384671
SAR 1g (W/Kg)	0.670815




Plot 3: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-09
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.71
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Tilt
Band	GSM1900
Channels	Middle
Signal	TDMA (Crest factor: 8.32)
Frequency (MHz)	1880.0
Relative permittivity (real part)	39.57
Conductivity (S/m)	1.43
Variation (%)	-2.68

Maximum location: X=-7.00, Y=24.00
SAR Peak: 1.01 W/kg

SAR 10g (W/Kg)	0.269655
SAR 1g (W/Kg)	0.565534




Plot 4: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-09
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.85
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	EGPRS 1900
Channels	Low
Signal	Duty Cycle:1.2.66 (Crest factor:2.66)
Frequency (MHz)	1850.2
Relative permittivity (real part)	51.68
Conductivity (S/m)	1.51
Variation (%)	-0.51

Maximum location: X=-15.00, Y=-24.00

SAR Peak: 1.95 W/kg

SAR 10g (W/Kg)	0.738428
SAR 1g (W/Kg)	1.232183




Plot 5: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-09
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.71
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA II
Channels	High
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1907.6
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	-2.16

Maximum location: X=-8.00, Y=21.00

SAR Peak: 1.32 W/kg

SAR 10g (W/Kg)	0.375686
SAR 1g (W/Kg)	0.761266




Plot 6: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-09
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.85
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA II
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1880.0
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	-0.02

Maximum location: X=-7.00, Y=-21.00
 SAR Peak: 1.79 W/kg

SAR 10g (W/Kg)	0.642721
SAR 1g (W/Kg)	1.349245




Plot 7: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-11
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.83
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Tilt
Band	WCDMA IV
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1712.6
Relative permittivity (real part)	42.27
Conductivity (S/m)	0.91
Variation (%)	-0.30

Maximum location: X=-9.00, Y=23.00
SAR Peak: 1.25 W/kg

SAR 10g (W/Kg)	0.370669
SAR 1g (W/Kg)	0.741016




Plot 8: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-11
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	5.02
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA IV
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1712.6
Relative permittivity (real part)	55.5
Conductivity (S/m)	0.96
Variation (%)	1.68

Maximum location: X=-13.00, Y=-23.00

SAR Peak: 1.20 W/kg

SAR 10g (W/Kg)	0.394628
SAR 1g (W/Kg)	0.706118




Plot 9: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-08
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.83
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA V
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	826.4
Relative permittivity (real part)	42.27
Conductivity (S/m)	0.91
Variation (%)	-0.64

Maximum location: X=-24.00, Y=8.00
SAR Peak: 0.68 W/kg

SAR 10g (W/Kg)	0.295653
SAR 1g (W/Kg)	0.454771




Plot 10: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-08
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	5.02
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	WCDMA V
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	826.4
Relative permittivity (real part)	55.5
Conductivity (S/m)	0.96
Variation (%)	-2.64

Maximum location: X=8.00, Y=35.00
SAR Peak: 0.83 W/kg

SAR 10g (W/Kg)	0.268234
SAR 1g (W/Kg)	0.495615




Plot 11: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-11
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.11
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=5mm dy=5mm dz=4mm, Complete/ndx=5mm dy=5mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2462
Relative permittivity (real part)	37.8
Conductivity (S/m)	1.86
Variation (%)	-0.01

Maximum location: X=-16.00, Y=24.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.071834
SAR 1g (W/Kg)	0.090023




Plot 12: DUT: Quad-core Smartphone; EUT Model: i544

Test Data	2016-01-11
Ambient Temperature(°C)	22.70
Liquid Temperature(°C)	22.30
Probe	SN 17/14 EP221
ConvF	4.25
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=5mm dy=5mm dz=4mm, Complete/ndx=5mm dy=5mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Back
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2462
Relative permittivity (real part)	51.2
Conductivity (S/m)	1.95
Variation (%)	-0.19

Maximum location: X=-10.00, Y=-12.00
SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.076824
SAR 1g (W/Kg)	0.134268





Appendix C. Probe Calibration And Dipole Calibration Report

Refer the appendix Calibration Report.

*****END OF THE REPORT*****