

## FCC 47 CFR PART 15 SUBPART C

### CERTIFICATION TEST REPORT

*For*

Gateway

MODEL No.: Smart Bridge

FCC ID:2ADQ4-GW01

Trade Mark: Keen Home

REPORT NO.: ES150721263E

ISSUE DATE: August 21, 2015

*Prepared for*

Keen Home Inc.

320 W 37th St, 15th Fl, New York, NY 10018 USA

*Prepared by*

SHENZHEN EMTEK CO., LTD

Bldg 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

## TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION</b>	<b>3</b>
<b>2</b>	<b>EUT TECHNICAL DESCRIPTION</b>	<b>4</b>
<b>3</b>	<b>SUMMARY OF TEST RESULT</b>	<b>5</b>
<b>4</b>	<b>TEST METHODOLOGY</b>	<b>6</b>
4.1	General Description Of Applied Standards	6
4.2	Measurement Equipment Used	6
4.3	Description Of Test Modes	7
<b>5</b>	<b>FACILITIES AND ACCREDITATIONS</b>	<b>8</b>
5.1	Facilities	8
5.2	Laboratory Accreditations And Listings	8
<b>6</b>	<b>TEST SYSTEM UNCERTAINTY</b>	<b>9</b>
<b>7</b>	<b>SETUP OF EQUIPMENT UNDER TEST</b>	<b>10</b>
7.1	Radio Frequency Test Setup 1	10
7.2	Radio Frequency Test Setup 2	10
7.3	Conducted Emission Test Setup	10
7.4	Block Diagram Configuration Of Test System	13
7.5	Support Equipment	13
<b>8</b>	<b>TEST REQUIREMENTS</b>	<b>14</b>
8.1	DTS (6db) Bandwidth	14
8.2	Maximum Peak Conducted Output Power	17
8.3	Maximum Power Spectral Density	18
8.4	Unwanted Emissions In Non-Restricted Frequency Bands	21
8.5	Radiated Spurious Emission	28
8.6	Conducted Emissions Test	44
8.7	Antenna Application	47

## 1 TEST RESULT CERTIFICATION

Applicant: Keen Home Inc.  
320 W 37th St, 15th Fl, New York, NY 10018 USA

Manufacturer: Ryder Electronics (Shenzhen) Ltd.  
139 Da Bao Road, District 33, Bao An, China

EUT Description: Gateway

Model Number: Smart Bridge

File Number: ES150721263E

Date of Test: August 14, 2015 to August 21, 2015

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	PASS
FCC 47 CFR Part 15, Subpart C	

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2014) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 14, 2015 to August 21, 2015

Prepared by :



Joe Xia/Editor

Reviewer :



Jack Li/Supervisor

Approve & Authorized Signer :



Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Device Type:</b>	2.4G ISM Band
<b>Standards:</b>	IEEE802.15.4
<b>Modulation:</b>	O-QPSK
<b>Operating Frequency Range(s):</b>	2405-2480MHz
<b>Number of Channels:</b>	16 Channels
<b>Transmit Power Max:</b>	19.528 dBm
<b>Antenna Type :</b>	PCB Antenna
<b>Antenna Gain:</b>	2.75dBi;
<b>Power supply:</b>	<input checked="" type="checkbox"/> DC supply: DC 6V from adapter
	<input checked="" type="checkbox"/> AC supply: AC 120V/60Hz
	<input checked="" type="checkbox"/> Adapter Model: SN110-0618 Input: 100-120V~ 50/60Hz, 0.3A Output: DC 6.0V, 1.8A

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.247(b)	Antenna Application	PASS	

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ADQ4-GW01 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
 FCC 47 CFR Part 2, Subpart J  
 FCC 47 CFR Part 15, Subpart C  
 FCC KDB 558074 D01 DTS Meas Guidance v03r02  
 FCC KDB 662911 D01 Multiple Transmitter Output v02r01  
 FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/17/2015
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/17/2015
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/17/2015
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/17/2015
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/17/2015

#### 4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/17/2015
Pre-Amplifier	HP	8447D	2944A07999	05/17/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/17/2015
Loop Antenna	ARA	PLA-1030/B	1029	05/17/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/17/2015
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/17/2015
Cable	Schwarzbeck	AK9513	ACRX1	05/17/2015
Cable	Rosenberger	N/A	FP2RX2	05/17/2015
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2015
Cable	Schwarzbeck	AK9513	CRRX2	05/17/2015

#### 4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/17/2015
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2015
Power meter	Anritsu	ML2495A	0824006	05/17/2015
Power sensor	Anritsu	MA2411B	0738172	05/17/2015

**Remark:** Each piece of equipment is scheduled for calibration once a year.

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	7	2435	13	2465
2	2410	8	2440	14	2470
3	2415	9	2445	15	2475
4	2420	10	2450	16	2480
5	2425	11	2455		
6	2430	12	2460		

Test Frequency and Channel:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	8	2440	15	2475
				16	2480

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

EMC Lab. : Accredited by CNAS, 2013.10.28  
The certificate is valid until 2016.10.29  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)  
The Certificate Registration Number is L229

: Accredited by TUV Rheinland Shenzhen, 2010.5.25  
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

: Accredited by FCC, April 17, 2014  
The Certificate Registration Number is 406365.

: Accredited by FCC, February 28, 2013  
The Certificate Registration Number is 709623.

: Accredited by Industry Canada, May 24, 2008  
The Certificate Registration Number is 4480A.

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Power Density	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.4-2014 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.4-2014 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	N/A	N/A	N/A	N/A	N/A	

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 TEST REQUIREMENTS

### 8.1 DTS (6DB) BANDWIDTH

#### 8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r02

#### 8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

#### 8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.1.4 Test Procedure

The EUT was operating in O-QPSK mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.


#### 8.1.5 Test Results

Temperature :	28°C	Test Date :	August 18, 2015
Humidity :	65 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
O-QPSK	1	2405	1.611	500	PASS
	8	2440	1.611	500	PASS
	15	2475	1.590	500	PASS
	16	2480	1.603	500	PASS


Test Model

DTS (6dB) Bandwidth  
O-QPSK  
Channel 1: 2405MHz




Test Model

DTS (6dB) Bandwidth  
O-QPSK  
Channel 8: 2440MHz




Test Model

DTS (6dB) Bandwidth  
 O-QPSK  
 Channel 16: 2480MHz



Test Model

DTS (6dB) Bandwidth  
 O-QPSK  
 Channel 15: 2475MHz



## 8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r02

### 8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

### 8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.2.4 Test Procedure

#### ■ According to FCC Part15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The testing follows FCC public Notice DA 00-705 Measurement Guidelines.

The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

#### ■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain - 6)

### 8.2.5 Test Results

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
O-QPSK	1	2405	19.500	30	PASS
	8	2440	19.528	30	PASS
	15	2475	19.375	30	PASS
	16	2480	-41.175	30	PASS

### 8.3 MAXIMUM POWER SPECTRAL DENSITY

#### 8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r02

#### 8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain - 6)

#### 8.3.5 Test Results

Temperature :	28°C	Test Date :	August 18, 2015
Humidity :	65 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
O-QPSK	1	2405	4.431	8	PASS
	8	2440	3.943	8	PASS
	15	2475	4.760	8	PASS
	16	2480	-56.203	8	PASS

Test Model

Power Spectral Density  
O-QPSK  
Channel 1: 2405MHz



Test Model

Power Spectral Density  
O-QPSK  
Channel 8: 2440MHz




Test Model

Power Spectral Density  
O-QPSK  
Channel 16: 2480MHz



Test Model

Power Spectral Density  
O-QPSK  
Channel 15: 2475MHz



## 8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

### 8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r02

### 8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq 1.5$  times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

#### ■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

### 8.4.5 Test Results


Test Model

PSD(Power Spectral Density ) RBW=100kHz  
 O-QPSK  
 Channel 1: 2405MHz



Test Model

Unwanted Emissions in non-restricted frequency bands  
 O-QPSK  
 Channel 1: 2405MHz



Test Model

Band edge  
O-QPSK  
☒ Channel 1: 2405MHz



Test Model	PSD(Power Spectral Density ) RBW=100kHz O-QPSK <input checked="" type="checkbox"/> Channel 8: 2440MHz
------------	---



Test Model	Unwanted Emissions In Non-Restricted Frequency Bands O-QPSK <input checked="" type="checkbox"/> Channel 8: 2440MHz
------------	--



Test Model	PSD(Power Spectral Density ) RBW=100kHz O-QPSK <input checked="" type="checkbox"/> Channel 16: 2480MHz
------------	--



Test Model	Unwanted Emissions In Non-Restricted Frequency Bands O-QPSK <input checked="" type="checkbox"/> Channel 16: 2480MHz
------------	---



Test Model	Band edge O-QPSK <input checked="" type="checkbox"/> Channel 16: 2480MHz
------------	--



Test Model	PSD(Power Spectral Density ) RBW=100kHz O-QPSK <input checked="" type="checkbox"/> Channel 15: 2475MHz
------------	--




Test Model

Unwanted Emissions In Non-Restricted Frequency Bands  
 O-QPSK  
 Channel 15: 2475MHz



Test Model

Band edge  
 O-QPSK  
 Channel 15: 2475MHz



## 8.5 RADIATED SPURIOUS EMISSION

### 8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v03r02

### 8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	2400/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 8.5.5 Test Results

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24 °C	Test Date:	August 18, 2015
Humidity:	53 %	Test By:	King Kong
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance}/\text{test distance})(\text{ dB})$ ;

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 1: 2405MHz		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4808.82	V	53.32	40.27	74.00	54.00	-20.68	-13.73
7214.04	V	50.09	37.43	74.00	54.00	-23.91	-16.57
9621.21	V	50.43	36.36	74.00	54.00	-23.57	-17.64
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4809.05	H	54.37	40.49	74.00	54.00	-19.63	-13.51
7213.90	H	50.66	38.20	74.00	54.00	-23.34	-15.80
9621.65	H	46.00	32.72	74.00	54.00	-28.00	-21.28

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 8: 2440MHz		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4878.77	V	53.66	40.89	74.00	54.00	-20.34	-13.11
7321.65	V	51.35	38.00	74.00	54.00	-22.65	-16.00
9761.33	V	50.49	37.08	74.00	54.00	-23.51	-16.92
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4879.05	H	49.35	37.97	74.00	54.00	-24.65	-16.03
7321.81	H	50.48	36.94	74.00	54.00	-23.52	-17.06
9761.81	H	47.96	37.18	74.00	54.00	-26.04	-16.82

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 1: 2480MHz		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4961.93	V	54.46	40.97	74.00	54.00	-19.54	-13.03
7439.52	V	51.40	38.22	74.00	54.00	-22.60	-15.78
9918.96	V	50.39	37.13	74.00	54.00	-23.61	-16.87
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4961.07	H	53.77	40.45	74.00	54.00	-20.23	-13.55
7438.86	H	47.71	36.22	74.00	54.00	-26.29	-17.78
9918.62	H	45.03	30.50	74.00	54.00	-28.97	-23.50

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 1: 2405MHz		

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.520	H	64.00	74.00	50.69	54.00
2389.520	V	58.80	74.00	44.02	54.00

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 16: 2480MHz		


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.550	H	62.30	74.00	49.40	54.00
2483.500	V	58.72	74.00	44.97	54.00

Temperature :	28°C	Test Date :	August 18, 2015		
Humidity :	65 %	Test By:	King Kong		
Test mode:	O-QPSK	Frequency:	Channel 15: 2475MHz		


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.780	H	62.97	74.00	44.13	54.00
2483.747	V	59.77	74.00	44.52	54.00

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	O-QPSK	<input checked="" type="checkbox"/> Channel 1: 2405MHz	<input type="checkbox"/> Channel 16: 2480MHz
		Polarity: H	Test By: King Kong
VBW=3MHz			




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	O-QPSK	<input checked="" type="checkbox"/> Channel 1: 2405MHz	<input type="checkbox"/> Channel 16: 2480MHz
		Polarity: H	Test By: King Kong
VBW=10Hz			




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	O-QPSK	<input checked="" type="checkbox"/> Channel 1: 2405MHz	<input type="checkbox"/> Channel 16: 2480MHz
	VBW=3MHz		Polarity: V
	Test By: King Kong		




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	O-QPSK	<input checked="" type="checkbox"/> Channel 1: 2405MHz	<input type="checkbox"/> Channel 16: 2480MHz
	Polarity: V	VBW=10Hz	Test By: King Kong




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	O-QPSK	<input type="checkbox"/> Channel 1: 2405MHz	<input checked="" type="checkbox"/> Channel 16: 2480MHz   Polarity: H
	VBW=3MHz		Test By: King Kong




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	O-QPSK	<input type="checkbox"/> Channel 1: 2405MHz	<input checked="" type="checkbox"/> Channel 16: 2480MHz   Polarity: H
	VBW=10Hz		Test By: King Kong




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	O-QPSK	<input type="checkbox"/> Channel 1: 2405MHz	<input checked="" type="checkbox"/> Channel 16: 2480MHz   Polarity: V
	VBW=3MHz		Test By: King Kong




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	O-QPSK	<input type="checkbox"/> Channel 1: 2405MHz	<input checked="" type="checkbox"/> Channel 16: 2480MHz   Polarity: V
	VBW=10Hz		Test By: King Kong




Test Model Spurious Emission in Restricted Band 2483.5-2500MHz  
O-QPSK  
 Channel 1: 2405MHz       Channel 15: 2475MHz      Polarity: H  
VBW=3MHz      Test By: King Kong




Test Model Spurious Emission in Restricted Band 2483.5-2500MHz  
O-QPSK  
 Channel 1: 2405MHz       Channel 15: 2475MHz      Polarity: H  
VBW=10Hz      Test By: King Kong




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz O-QPSK <input type="checkbox"/> Channel 1: 2405MHz <input checked="" type="checkbox"/> Channel 15: 2475MHz      Polarity: V VBW=3MHz      Test By: King Kong
------------	---



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	O-QPSK	<input type="checkbox"/> Channel 1: 2405MHz	<input checked="" type="checkbox"/> Channel 15: 2475MHz   Polarity: V
	VBW=10Hz		Test By: King Kong




■ Spurious Emission below 1GHz (30MHz to 1GHz)



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment				Height	Degree	Comment
			MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		42.0066	37.51	-12.95	24.56	40.00	-15.44	QP			
2	*	74.9191	47.13	-19.49	27.64	40.00	-12.36	QP			
3		144.8418	40.65	-17.94	22.71	43.50	-20.79	QP			
4		287.9904	44.35	-13.07	31.28	46.00	-14.72	QP			
5		394.8545	37.38	-9.15	28.23	46.00	-17.77	QP			
6		501.1790	41.30	-7.80	33.50	46.00	-12.50	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: FW



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		31.3992	49.48	-15.98	33.50	40.00	-6.50	QP		
2	*	41.5670	50.83	-12.93	37.90	40.00	-2.10	QP		
3	!	61.1316	51.27	-15.85	35.42	40.00	-4.58	QP		
4	!	63.5356	50.73	-16.58	34.15	40.00	-5.85	QP		
5		71.8320	52.33	-18.87	33.46	40.00	-6.54	QP		
6	!	74.9191	55.74	-19.49	36.25	40.00	-3.75	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: FW



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		41.5670	38.04	-12.93	25.11	40.00	-14.89	QP		
2		60.7044	40.81	-15.73	25.08	40.00	-14.92	QP		
3	*	74.9191	46.17	-19.49	26.68	40.00	-13.32	QP		
4		123.6985	36.84	-16.67	20.17	43.50	-23.33	QP		
5		144.3348	40.12	-17.92	22.20	43.50	-21.30	QP		
6		416.1791	29.40	-9.33	20.07	46.00	-25.93	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: FW



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1 !		31.5095	52.40	-15.95	36.45	40.00	-3.55	QP		
2 *		41.2765	50.10	-12.91	37.19	40.00	-2.81	QP		
3 !		60.7044	52.12	-15.73	36.39	40.00	-3.61	QP		
4 !		63.3132	52.97	-16.51	36.46	40.00	-3.54	QP		
5 !		71.5806	54.01	-18.83	35.18	40.00	-4.82	QP		
6 !		74.9191	54.17	-19.49	34.68	40.00	-5.32	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: FW



Site 3m Chamber #3

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15.247

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Gateway

M/N: GW01-001-DV-1.0


Mode: TX 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height		Table Degree						
								MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	*	41.5670	38.40	-12.93	25.47	40.00	-14.53	QP								
2		60.2801	40.30	-15.60	24.70	40.00	-15.30	QP								
3		74.9191	44.62	-19.49	25.13	40.00	-14.87	QP								
4		127.2176	41.75	-17.01	24.74	43.50	-18.76	QP								
5		143.8295	38.80	-17.90	20.90	43.50	-22.60	QP								
6		271.3245	34.19	-12.68	21.51	46.00	-24.49	QP								

\*:Maximum data    x:Over limit    !:over margin

Operator: FW



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1 !		31.7313	53.03	-15.88	37.15	40.00	-2.85	QP		
2 *		41.5670	51.35	-12.93	38.42	40.00	-1.58	QP		
3 !		60.4920	51.87	-15.67	36.20	40.00	-3.80	QP		
4 !		63.0916	52.69	-16.44	36.25	40.00	-3.75	QP		
5 !		71.3300	55.42	-18.77	36.65	40.00	-3.35	QP		
6 !		74.9191	56.93	-19.49	37.44	40.00	-2.56	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: FW

## 8.6 CONDUCTED EMISSIONS TEST

### 8.6.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.6.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

### 8.6.4 Test Procedure


The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

### 8.6.5 Test Results

Pass



Site Conduction #2

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Gaterway

M/N: GW01-001-DV-1.0

Mode: ON

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2050	41.46	0.00	41.46	63.41	-21.95	QP	
2		0.2050	20.14	0.00	20.14	53.41	-33.27	AVG	
3		0.4050	43.92	0.00	43.92	57.75	-13.83	QP	
4		0.4050	20.20	0.00	20.20	47.75	-27.55	AVG	
5		0.5900	46.75	0.00	46.75	56.00	-9.25	QP	
6		0.5900	24.65	0.00	24.65	46.00	-21.35	AVG	
7	*	1.0300	47.01	0.00	47.01	56.00	-8.99	QP	
8		1.0300	21.29	0.00	21.29	46.00	-24.71	AVG	
9		1.2050	43.51	0.00	43.51	56.00	-12.49	QP	
10		1.2050	18.86	0.00	18.86	46.00	-27.14	AVG	
11		14.4250	31.29	0.00	31.29	60.00	-28.71	QP	
12		14.4250	14.47	0.00	14.47	50.00	-35.53	AVG	


\*:Maximum data

x:Over limit

!:over margin

Comment: Factor build in receiver.

Operator: CSL



Site Conduction #2

Phase: **N**

Temperature: 26

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Gaterway

M/N: GW01-001-DV-1.0

Mode: ON

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2000	41.18	0.00	41.18	63.61	-22.43	QP	
2		0.2000	20.88	0.00	20.88	53.61	-32.73	AVG	
3		0.4750	43.30	0.00	43.30	56.43	-13.13	QP	
4		0.4750	22.20	0.00	22.20	46.43	-24.23	AVG	
5	*	0.6100	47.58	0.00	47.58	56.00	-8.42	QP	
6		0.6100	24.41	0.00	24.41	46.00	-21.59	AVG	
7		0.7900	46.62	0.00	46.62	56.00	-9.38	QP	
8		0.7900	25.33	0.00	25.33	46.00	-20.67	AVG	
9		1.0150	46.16	0.00	46.16	56.00	-9.84	QP	
10		1.0150	23.17	0.00	23.17	46.00	-22.83	AVG	
11		15.6250	28.70	0.00	28.70	60.00	-31.30	QP	
12		15.6250	17.43	0.00	17.43	50.00	-32.57	AVG	

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.    Operator: CSL

## 8.7 ANTENNA APPLICATION

### 8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.7.2 Result

PASS.

The EUT has 1 antenna: a PCB Antenna for 2.4G, the gain is 2.75 dBi;

Note:  Antenna use a permanently attached antenna which is not replaceable.  
 Not using a standard antenna jack or electrical connector for antenna replacement  
 The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.