

Otodata Wireless Network, Inc.

MPE CALCULATIONS REPORT

SCOPE OF WORK

MPE Calculations on Propane Monitoring Device, Model C033

REPORT NUMBER

105128961BOX-001b.1

ISSUE DATE

May 17, 2023

[REVISED DATE]

July 24, 2023

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. October 2022

© 2022 INTERTEK



MPE CALCULATIONS REPORT

(FULL COMPLIANCE)

Report Number: 105128961BOX-001b.1**Project Number:** G105128961**Report Issue Date:** May 17, 2023**Report Revision Date:** July 24, 2023**Model(s) Tested:** C033**Model(s) Partially Tested:** None**Model(s) Not Tested but declared equivalent by the client:** None**Standards:** FCC Part 1.1310 (05/23)

FCC KDB Publication 447498 D01 v06

ISED RSS-102 Issue 5; March 19, 2015

Tested by:

Intertek Testing Services NA, Inc.

70 Codman Hill Road

Boxborough, MA 01719

USA

Client:

Otodata Wireless Network, Inc.

1180 De Louvain Street

West Montreal, QC H4N 1G5

Canada

Report prepared by



Kouma Sinn / Senior Staff Engineer

Report reviewed by



Vathana Ven / Senior Staff Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Table of Contents

1	<i>Introduction and Conclusion</i>	<i>4</i>
2	<i>Test Summary.....</i>	<i>4</i>
3	<i>Maximum Permissive Exposure (MPE).....</i>	<i>5</i>
4	<i>Revision History.....</i>	<i>8</i>

1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

2 Test Summary

Section	Test full name	Result
3	Maximum Permissible Exposure (MPE) FCC Part 1.1310 (05/23) ISED RSS-102 Issue 5; March 19, 2015	Pass
4	Revision History	--

3 Maximum Permissible Exposure (MPE)

FCC Limits for Maximum Permissible Exposure

§ 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

RSS-102 Issue 5 Maximum Permissible Exposure

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Test Procedure

An MPE evaluation for was performed in order to show that the device was compliant with §2.1091. The maximum power density was calculated for each transmitter at a separation distance of 20cm.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{ConductedPower(dBm)/10}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$

Evaluation Results:

Numeric gain = $10^{(2.31/10)}$

Power Density = $[2.661\text{mW} * 1.702] / [4\pi * (20\text{cm})^2]$ or 0.000867 mW/cm²

Note: The maximum conducted power of 4.25 dBm or 2.661 mW at 2.480 GHz was taken from Intertek Report # 105128961BOX-001.1.

FCC MPE

Conducted Power (mW)	Numeric Gain	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Results
2.661	1.702	0.000901	1	Compliant

Notes: MPE limit at 2480 MHz is 1 mW/cm²

RSS-102 MPE

Conducted Power (mW)	Numeric Gain	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Results
2.661	1.702	0.000901	0.547	Compliant

Notes: MPE limit at 2480 MHz is $0.02619f^{0.6834}$ or $0.02619 * 2480^{0.6834}$ or 5.469 W/m² or 0.547 mW/cm²

The calculated maximum power density at 20 cm distance is less than the limit for general population / Uncontrolled Environment.

4 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	05/17/2023	105128961BOX-001b	KPS <i>KPS</i>	VFV <i>VFV</i>	Original Issue
1	07/24/2023	105128961BOX-001b.1	KPS <i>KPS</i>	VFV <i>VFV</i>	Removed SAR Exclusion Test calculation