

Produkte  
Products

**Prüfbericht - Nr.: 14037544 001**

Test Report No.:

Seite 1 von 11

Page 1 of 11

**Auftraggeber:** Wachsmuth & Kroemann, Inc  
Client: 621 IL Rt. 83, Ste. 202, Bensenville  
Illionis, USA

**Gegenstand der Prüfung:** Short Range Device - 433MHz Transmitter  
Test Item:

**Bezeichnung:** FB6200-S **Serien-Nr.:** Engineering sample  
Identification: Serial No.:

**Wareneingangs-Nr.:** A000149783-001 **Eingangsdatum:** 30.12.2014  
Receipt No.: A000149783-002 Date of Receipt:

**Zustand des Prüfgegenstandes bei Anlieferung:** Test sample(s) is/are not damaged and  
Condition of test item at delivery: suitable for testing.

**Prüfort:** Global United Technology Services Co., Ltd.  
Testing Location: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District,  
Shenzhen, China

**Prüfgrundlage:** FCC Part 15 Subpart C  
Test Specification: ANSI C63.4-2003

**Prüfergebnis:** Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben  
Test Results: genannter Prüfgrundlage.  
The above mentioned product was tested and **passed**.

**Prüflaboratorium:** TÜV Rheinland Hong Kong Ltd.  
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay,  
Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

27.01.2015	Benny Lau Project Manager		27.01.2015	Sharon Li Department Manager	
Datum Date	Name/Stellung Name/Position	Unterschrift Signature	Datum Date	Name/Stellung Name/Position	Unterschrift Signature

**Sonstiges:** FCC ID: 2ADQUFB6200  
Other Aspects

**Abkürzungen:** P(pass) = entspricht Prüfgrundlage  
F(fail) = entspricht nicht Prüfgrundlage  
N/A = nicht anwendbar  
N/T = nicht getestet

**Abbreviations:** P(pass) = passed  
F(fail) = failed  
N/A = not applicable  
N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

## Table of Content

	Page
<b>Cover Page .....</b>	<b>1</b>
<b>Table of Content .....</b>	<b>2</b>
<b>Test Summary .....</b>	<b>4</b>
<b>Product information.....</b>	<b>5</b>
1.    Manufacturers declarations .....	5
2.    Product function and intended use.....	5
3.    Submitted documents.....	5
4.    Independent Operation Modes .....	5
5.    Related Submittal(s) Grants .....	5
6.    Remark .....	5
<b>Test Set-up and Operation Mode.....</b>	<b>6</b>
7.    Principle of Configuration Selection .....	6
8.    Test Operation and Test Software.....	6
9.    Special Accessories and Auxiliary Equipment.....	6
10.    Countermeasures to achieve EMC Compliance.....	6
<b>Test Methodology .....</b>	<b>7</b>
11.    Radiated Emission .....	7
12.    Field Strength Calculation.....	7
<b>List of Test and Measurement Instruments.....</b>	<b>8</b>
<b>Results FCC Part 15 – Subpart C .....</b>	<b>9</b>
Subclause 15.203 – Antenna Information .....	Pass.....
Subclause 15.207 – Conducted Emission on AC Mains.....	N/A.....
Subclause 15.231 (c) – 20 dB Bandwidth.....	Pass.....
Subclause 15.231 (e) – Radiated Emission (Fundamental and Harmonics).....	Pass.....
Subclause 15.205 – Spurious Radiated Emissions .....	Pass.....
Subclause 15.231 (e) – Transmission Timing Requirement .....	Pass.....
Appendix 1 – Test Results.....	6 pages
Appendix 2 – Test Setup Photos.....	3 pages
Appendix 3 – EUT External Photos.....	3 pages
Appendix 4 – EUT Internal Photos .....	3 pages

**Appendix 5 – Label, Operational Description, Block, Schematics and User Manual..... 17 pages**

**Appendix 6 – RF Exposure Information..... 2 pages**

## Test Summary

### Conducted Emissions

*Result: N/A*

### 20dB bandwidth

*Result: Pass*

### Radiated Emission of Carrier Frequency

*Result: Pass*

### Spurious Radiated Emissions

*Result: Pass*

### Transmission duration and silent period

*Result: Pass*

## Product information

### 1. Manufacturers declarations

	<b>Transmitter</b>
Operating frequency range	433.92 MHz
Type of modulation	ASK
Number of channels	1
Type of antenna	Integral PCB Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	V <sub>nor</sub> : 3.0Vdc (2 x 1.5V "AAA" battery)

### 2. Product function and intended use

The equipment under test (EUT) is a transmitter operating at 433.92MHz. And it is powered by 3.0Vdc (2 x 1.5V "AAA" battery).

FCC ID: **2ADQUFB6200**

Models	Product description
<b>FB6200-S</b>	BBQ thermometer

### 3. Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 User manual  
 Rating Label

### 4. Independent Operation Modes

The basic operation modes are:

- Transmitting Bluetooth signal .

For further information refer to User Manual

### 5. Related Submittal(s) Grants

This is a single application for certification of the transmitter.

### 6. Remark

- None.

## Test Set-up and Operation Mode

### 7. Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 8. Test Operation and Test Software

Test operation should refer to test methodology.

- No testing software is provided by the applicant.

### 9. Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### 10. Countermeasures to achieve EMC Compliance

- none

## Test Methodology

### 11. Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### 12. Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dB<sub>uV/m</sub> at 3 meters.  
R = Reading of Spectrum Analyzer in dB<sub>uV</sub>.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

## List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (Registration number: 600491)

### Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal. Due date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	---	05 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	---	N/A
ESU EMI Test Receiver	R&S	ESU26	---	27 Jun 2015
Loop Antenna	Zhinan	ZN30900A	---	27 Jun 2015
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	---	08 Mar 2015
Double-ridged horn antenna	SCHWARZBECK	9120D	---	08 Mar 2015
RF Amplifier	HP	8347A	---	27 Jun 2015
RF Amplifier	HP	8349B	---	27 Jun 2015
EMI Test Software	AUDIX	E3	---	N/A
Coaxial cable	GTS	N/A	---	27 Jun 2015
Coaxial Cable	GTS	N/A	---	27 Jun 2015
Thermo meter	N/A	N/A	---	27 Jun 2015
FSP 30 Spectrum Analyzer	Rohde & Schwarz	FSP 30	100007	03 Dec 2014

## Results FCC Part 15 – Subpart C

<b>Subclause 15.203 – Antenna Information</b>	<b>Pass</b>	
<b>Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device		
<b>Results:</b> Permanent attached antenna		
<b>Verdict:</b> Pass		
<b>Subclause 15.207 – Conducted Emission on AC Mains</b>	<b>N/A</b>	
There is no AC power input or output ports on the EUT.		
<b>Subclause 15.231 (c) – 20 dB Bandwidth</b>	<b>Pass</b>	
Requirement: The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.		
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100kHz/300kHz Supply voltage : 3.0VDC Temperature : 23°C Humidity : 50%		
<b>Results:</b> Pass		
Frequency (MHz)	20 dB Bandwidth (kHz)	Limit (kHz)
433.92	620.00	<1084

Subclause 15.231 (e) – Radiated Emission (Fundamental and Harmonics)			Pass
Test Specification	:	ANSI C63.4 – 2003	
Mode of operation	:	Tx mode	
Port of testing	:	Enclosure	
RBW/VBW	:	120 kHz for $f < 1$ GHz 1 MHz / 3 MHz for $f > 1$ GHz	
Supply voltage	:	3.0VDC	
Frequency range	:	9kHz to tenth harmonic	
Temperature	:	23°C	
Humidity	:	50%	
Requirement:	The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.		
<b>Results:</b>	Pass		
Fundamental Frequency		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
433.913	38.0	72.9 / AV	
Fundamental Frequency		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
433.913	43.2	72.9 / AV	
Harmonics		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
No peak found	---	52.9 / AV	
Harmonics		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
No peak found	---	52.9 / AV	

<b>Subclause 15.205 – Spurious Radiated Emissions</b>		<b>Pass</b>
Test Specification	: ANSI C63.4 - 2003	
Mode of operation	: Tx mode	
Port of testing	: Enclosure	
Detector	: Peak	
RBW/VBW	: 120 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Supply voltage	: 3.0VDC	
Frequency range	: 9kHz to tenth harmonic	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	The field strength of emissions appearing within the restricted frequency bands shall not exceed the limits shown in §15.209.	
<b>Results:</b>	Pass	
Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	---
Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	---

<b>Subclause 15.231 (e) – Transmission Timing Requirement</b>		<b>Pass</b>
Requirement: Devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.		
<b>Results:</b>	Pass	
Freq MHz	Transmission Duration Sec	Limit Sec
433.88	0.161	<1
<b>Results:</b>	Pass	
Freq MHz	Silent Period Sec	Limit Sec
433.88	12.88	>10