



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20201101331E-02  
**Applicant:** BRYDGE GLOBAL  
**Address of Applicant:** 1912 Sidewinder Dr#104, Park City, Utah ,United States, 84060  
**Equipment Under Test (EUT):**  
**EUT Name:** Wireless desktop trackpad  
**Model No.:** BRY230N  
**Brand Name:** BRYDGE  
**FCC ID:** 2ADRG-BRY230N  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-11-05  
**Date of Test:** 2020-11-05 to 2020-11-25  
**Date of Issue:** 2020-11-25  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

*Tiny You*

(Tiny You)

**Reviewed By:**

*Sheek Luo*

(Sheek Luo)

**Approved By:**

*Jack Ai*

(Jack Ai)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20201101331E-02	Rev.01	Initial report	2020-11-25

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	BRYDGE GLOBAL
Address of Applicant:	1912 Sidewinder Dr#104, Park City, Utah ,United States, 84060
Manufacturer:	BRYDGE GLOBAL
Address of Manufacturer:	1912 Sidewinder Dr#104, Park City, Utah ,United States, 84060
Factory:	DONGGUAN MAE TAY ELECTRONIC CO., LTD.
Address of Factory:	Beihuan Road Industrial Area , Changping Town , Dongguan City, Guangdong Province , China

#### 3.2 General Description of EUT

Product Name:	Wireless desktop trackpad
Model No.:	BRY230N
Trade Mark:	BRYDGE
Hardware Version:	V2.1
Software Version:	V00. 02
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps, 2Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Direct Test Mode Tool (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	1.87dBi
EUT Power Supply:	lithium battery:DC 3.7V, 1200mAh, Charge by DC 5.0V

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

##### 1) For BLE

##### Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.59	2.5±1	3.5	2.239
Middle(2440MHz)	2.14	2.5±1	3.5	2.239
Highest(2480MHz)	2.81	2.5±1	3.5	2.239
GFSK(2Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.62	2.5±1	3.5	2.239
Middle(2440MHz)	2.16	2.5±1	3.5	2.239
Highest(2480MHz)	2.83	2.5±1	3.5	2.239

Worst case: GFSK(2Mbps)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.62	2.5±1	3.5	2.239	0.694	3.0
Middle (2440MHz)	2.16	2.5±1	3.5	2.239	0.700	
Highest (2480MHz)	2.83	2.5±1	3.5	2.239	0.705	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20201101331E-01

--THE END--