

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Bluetooth keyboard
Model Name	BRY7301
FCC ID	2ADRG-BRY7301

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\left[\sqrt{f(GHz)}\right] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

P_t=-6.612dBm=0.22mW

The value of the Maximum output power Pt is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation SAR=(0.22mW /5mm) .[$\sqrt{2.402(GHz)}$]= 0.07<3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.