



Klik Sleeve

REV. 2019-02-08

LIGHT	3 High-brightness full color RGB LED
Material	ABS Plastic casing Vinyl Sleeve Nylon Lanyard with metal clips
Colors	Translucent white Casing Clear Sleeve
Dimensions	A7 version: 154mm x 118mm x 15mm 6" x 4.75" x .5" A6 Version: 226mm x 118mm x 15mm 9" x 4.75" x .5"
Powered by	Replaceable 1 x CR2450 coin battery
Activation	Remove Pull-tab
Battery Life	3 to 5 days including klik interactions and light show
Control	BLE enabled / klik button
Weight	A7 version: 34g / 1.2 oz A6 version: 47g / 1.7 oz
Shipment Dim.	A7 Version - Box of 250 units - Dimensions: 39 x 38 x 31.7cm 15,3" x 15" x 12" - Gross weight : 11Kg / 24 lbs - Net weight: 9Kg / 20 lbs A6 Version - Box of 250 units - Dimensions: 61 x 42 x 27 cm 24" x 16.5" x 10.6" - Gross weight : 13Kg / 28.6 lbs - Net weight: 11Kg / 24 lbs
Operating Temp.	0° to 40° C / 32° to 104° F
Branding	- Option to print logo on top button - Option to apply sticker on top button for removable branding solution - Option to print on cardstock around button - Option to print on cardstock in A6 or A7 - Option to print on Lanyard
Reusable	- Possibility to rent and return or recuperate
Second life	- Works with Spark app on smartphone for personal lightshow
Certification	CE, ROHS2, WEEE, FCC, RCM

This device complies with part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Specific Absorption Rate (SAR) information:

This Badge 3 meets the government's requirements for exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

FCC RF Exposure Information and Statement The SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. Device types: 101-00050 (FCC ID: 2ADS4101-00050) has also been tested against this SAR limit. The highest SAR value reported under this standard during product certification for properly worn on the body is 0.032W/kg. This device was tested for typical body-worn operations with the back of the handset kept 0mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain a 0mm separation distance between the user's body and the back of the handset. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with FCC RF exposure requirements, and should be avoided.

Body-worn Operation

This device was tested for typical body-worn operations. To comply with RF exposure requirements, a minimum separation distance of 0mm must be maintained between the user's body and the handset, including the antenna. Third-party belt-clips, holsters, and similar accessories used by this device should not contain any metallic components. Body-worn accessories that do not meet these requirements may not comply with RF exposure requirements and should be avoided. Use only the supplied or an approved antenna.

IC Caution:

- English:

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) This device may not cause interference, and (2) This device must accept any interference, including interference that may cause undesired operation of the device.

- French:

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

(1) l'appareil ne doit pas produire de brouillage, et

(2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This device meets RSS-102 Issue 5 requirements for exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

ISED RF Exposure Information and Statement The SAR limit of ISED is 1.6 W/kg averaged over one gram of tissue. Device types: 101-00050 (IC: 7254A-10100050) has also been tested against this SAR limit. The highest SAR value reported under this standard during product certification for properly worn on the body is 0.032/kg. This device was tested for typical body-worn operations with the back of the handset kept 0mm from the body. To maintain compliance with ISED RF exposure requirements, use accessories that

maintain a 0mm separation distance between the user's body. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with ISED RF exposure requirements, and should be avoided.