



# TEST REPORT

## FCC PART 15 SUBPART C 15.247

### RSS-247 ISSUE 2

Test report  
On Behalf of  
Poly-Control ApS  
For  
Electronic door lock V3  
Model No.: V3-BTZBE  
FCC ID: 2ADSH-V3BTZBE  
IC ID: 12588A-V3BTZBE

Prepared for : Poly-Control ApS  
Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

Date of Test: Jan. 22, 2019 ~ Jan. 28, 2019  
Date of Report: Jan. 28, 2019  
Report Number: HK1811301755E

**TEST RESULT CERTIFICATION****Applicant's name** ..... Poly-Control ApS

Address ..... Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark

**Manufacture's Name** ..... Poly-Control ApS

Address ..... Gammel Stillingvej 427C, DK-8462 Harlev J, Denmark

**Factory** ..... Xiamen CMM CO. , LTD.

Address ..... NO. 136 Xin Guang Road, Haicang District | Xiamen city, Fujian Province, P.R. China

**Product description**

Trade Mark: ..... danalock

Product name ..... Electronic door lock V3

Model and/or type reference ... V3-BTZBE

**47 CFR FCC Part 15 Subpart C 15.247****Standards** ..... **RSS-247 issue 2**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :

Date (s) of performance of tests ..... : Jan. 22, 2019 ~ Jan. 28, 2019

Date of Issue ..... : Jan. 28, 2019

Test Result ..... : **Pass**

Testing Engineer

(Gary Qian)

Technical Manager

(Eden Hu)

Authorized Signatory

(Jason Zhou)



## TABLE OF CONTENTS

<b>1. SUMMARY .....</b>	<b>4</b>
1.1 TEST STANDARDS .....	4
1.2 TEST DESCRIPTION .....	4
1.3 TEST FACILITY .....	5
1.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	5
<b>2. GENERAL INFORMATION.....</b>	<b>6</b>
2.1 ENVIRONMENTAL CONDITIONS .....	6
2.2 GENERAL DESCRIPTION OF EUT.....	6
2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	6
2.4 DESCRIPTION OF TEST SETUP.....	7
2.5 RELATED SUBMITTAL(S) / GRANT (S).....	7
2.6 MODIFICATIONS .....	7
2.7 EQUIPMENT USED.....	8
<b>3. PEAK OUTPUT POWER.....</b>	<b>9</b>
3.1. MEASUREMENT PROCEDURE .....	9
3.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
3.3. LIMITS AND MEASUREMENT RESULT .....	10
<b>4. 6 DB BANDWIDTH.....</b>	<b>14</b>
4.1. MEASUREMENT PROCEDURE .....	14
4.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
4.3. LIMITS AND MEASUREMENT RESULTS .....	15
<b>5. CONDUCTED SPURIOUS EMISSION .....</b>	<b>19</b>
5.1. MEASUREMENT PROCEDURE .....	19
5.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
5.3. MEASUREMENT EQUIPMENT USED .....	19
5.4. LIMITS AND MEASUREMENT RESULT .....	19
<b>6. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b>	<b>26</b>
6.1 MEASUREMENT PROCEDURE .....	26
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	26
6.3 MEASUREMENT EQUIPMENT USED .....	26
6.4 LIMITS AND MEASUREMENT RESULT .....	27
<b>7. RADIATED EMISSION .....</b>	<b>31</b>
7.1. MEASUREMENT PROCEDURE .....	31
7.2. TEST SETUP .....	32
7.3. LIMITS AND MEASUREMENT RESULT .....	33
7.4. TEST RESULT .....	33
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....</b>	<b>45</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>46</b>



## 1. SUMMARY

### 1.1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[RSS-247-Issue 2](#): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus

[ANSI C63.10:2013](#) : American National Standard for Testing Unlicensed Wireless Devices

### 1.2 TEST DESCRIPTION

FCC PART 15.247 & RSS 247	DESCRIPTION OF TEST	RESULT
	Peak Output Power	Compliant
	6 dB Bandwidth	Compliant
	Conducted Spurious Emission and Band Edges	Compliant
	Maximum Conducted Output Power Density	Compliant
	Radiated Emission	Compliant
	Line Conduction Emission	NA



### 1.3 TEST FACILITY

#### 1.3.1 ADDRESS OF THE TEST LABORATORY

Shenzhen HUAK Testing Technology Co., Ltd.

Address: 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

#### 1.3.2 LABORATORY ACCREDITATION

The test facility is recognized, certified, or accredited by the following organizations:

##### **IC Registration No.: 21210**

The 3m alternate test site of Shenzhen HUAK Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 21210 on May 24, 2016.

##### **FCC Registration No.: CN1229**

Test Firm Registration Number : 616276

### 1.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen HUAK Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for HUAK laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance 0.15~30MHz	±3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## 2.GENERAL INFORMATION

### 2.1 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2 GENERAL DESCRIPTION OF EUT

Product Name:	Electronic door lock V3
Model/Type reference:	V3-BTZBE
Power supply:	DC 12V by Battery
Modulation:	OQPSK
Operation frequency:	2405MHz~2480MHz
Channel number:	16
Channel separation:	5MHz
Antenna type:	Chip Antenna
Antenna gain:	-3.44dBi
Hardware Version:	101-025_D1+101-029-E1
Software Version:	0x10020000

Note: For more details, refer to the user's manual of the EUT.

### 2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY

Frequency Band	Channel Number	Frequency
2400~2483.5MHz	11	2405MHz
	12	2410MHz
	:	:
	25	2475MHz
	26	2480MHz

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX 2475MHz
4	High channel TX 2480MHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacturer.



## 2.4 DESCRIPTION OF TEST SETUP

Configure :



Item	Equipment	Model No.	ID or Specification	Remark
1	Electronic door lock V3	V3-BTZBE	FCC ID: 2ADSH-V3BTZBE IC ID: 12588A-V3BTZBE	EUT

## 2.5 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and RSS-247.

## 2.6 MODIFICATIONS

No modifications were implemented to meet testing criteria.

**2.7 EQUIPMENT USED**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Horn Antenna	Schwarzbeck	BBHA 9170	HKE-090	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 27, 2018	N/A
14.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2018	3 Year

The calibration interval was one year

### 3. PEAK OUTPUT POWER

#### 3.1. MEASUREMENT PROCEDURE


For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2.  $RBW \geq DTS$  bandwidth
3.  $VBW \geq 3 \times RBW$ .
4.  $SPAN \geq VBW$ .
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### 3.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

##### PEAK POWER TEST SETUP






### 3.3. LIMITS AND MEASUREMENT RESULT

PEAK OUTPUT POWER MEASUREMENT RESULT FOR OQPSK MODULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.405(CH11)	12.133	30	Pass
2.425(CH15)	12.212	30	Pass
2.440(CH18)	12.265	30	Pass
2.445(CH19)	12.274	30	Pass
2.450(CH20)	12.288	30	Pass
2.475(CH25)	12.192	30	Pass
2.480(CH26)	7.960	30	Pass


Note: The CH15, 19, 20 and 25 had been tested which is required by US customer.

CH11






## CH15




## CH18






## CH19




## CH20






## CH25



## CH26





## 4. 6 DB BANDWIDTH

### 4.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW  $\geq 3 \times$  RBW.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

### 4.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.




#### 4.3. LIMITS AND MEASUREMENT RESULTS

LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Applicable Limits		
	Frequency (GHz)	Test Data (MHz)	Criteria
>500KHZ	2.405(CH11)	1.639	PASS
	2.425(CH15)	1.636	PASS
	2.440(CH18)	1.642	PASS
	2.445(CH19)	1.628	PASS
	2.450(CH20)	1.638	PASS
	2.475(CH25)	1.636	PASS
	2.480(CH26)	1.638	PASS


Note: The CH15, 19, 20 and 25 had been tested which is required by US customer.

CH11






## CH15



## CH18






## CH19




## CH20






## CH25



## CH26





## 5. CONDUCTED SPURIOUS EMISSION

### 5.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

### 5.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

### 5.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.


### 5.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS PASS




# TEST RESULT FOR ENTIRE FREQUENCY RANGE

## OQPSK MODULATION IN LOW CHANNEL






## OQPSK MODULATION IN MIDDLE CHANNEL






## OQPSK MODULATION IN HIGH CHANNEL 2475MHz






## OQPSK MODULATION IN HIGH CHANNEL 2480MHz




Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit.



### TEST RESULT FOR BAND EDGE OQPSK MODULATION IN LOW CHANNEL



### OQPSK MODULATION IN HIGH CHANNEL 2475MHz





## OQPSK MODULATION IN HIGH CHANNEL 2480MHz





## **6. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

### **6.1 MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

### **6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer To Section 7.2.

### **6.3 MEASUREMENT EQUIPMENT USED**


Refer To Section 6.



#### 6.4 LIMITS AND MEASUREMENT RESULT


Frequency (GHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
2.405(CH11)	-3.393	8	Pass
2.425(CH15)	-3.091	8	Pass
2.440(CH18)	-2.709	8	Pass
2.445(CH19)	-4.147	8	Pass
2.450(CH20)	-2.795	8	Pass
2.475(CH25)	-2.849	8	Pass
2.480(CH26)	-7.724	8	Pass

Note: The CH15, 19, 20 and 25 had been tested which is required by US customer.






## CH15




## CH18






## CH19



## CH20






## CH25



## CH26






## 7. RADIATED EMISSION

### 7.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 7.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





### 7.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.


### 7.4. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

**RADIATED EMISSION BELOW 1GHZ**


<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal



<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	58.1300	19.67	13.69	40.00	20.33	100	70	Horizontal
2	120.2100	18.60	12.91	43.50	24.90	100	10	Horizontal
3	161.9200	21.13	14.07	43.50	22.37	150	230	Horizontal
4	275.4100	21.24	14.98	46.00	24.76	150	10	Horizontal
5	405.3900	24.15	18.79	46.00	21.85	100	250	Horizontal
6	606.1800	31.18	23.02	46.00	14.82	100	360	Horizontal

**RESULT: PASS**

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Vertical



Suspected Data List								
NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.7900	22.98	13.89	40.00	17.02	150	130	Vertical
2	47.4600	21.34	14.42	40.00	18.66	200	150	Vertical
3	64.9200	29.52	12.70	40.00	10.48	200	10	Vertical
4	119.2400	19.19	12.82	43.50	24.31	200	120	Vertical
5	276.3800	20.73	15.06	46.00	25.27	100	50	Vertical
6	534.4000	27.30	21.61	46.00	18.70	100	80	Vertical

## RESULT: PASS

### Note:

- Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- All test modes had been tested. The mode 1 is the worst case and recorded in the report.



## RADIATED EMISSION ABOVE 1GHZ

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4810.011	46.74	7.12	53.86	74	-20.14	peak
4810.011	40.52	7.12	47.64	54	-6.36	AVG
7215.022	42.12	9.84	51.96	74	-22.04	peak
7215.022	37.75	9.84	47.59	54	-6.41	AVG

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4810.011	45.48	7.12	52.6	74	-21.4	
4810.011	41.17	7.12	48.29	54	-5.71	AVG
7215.022	43.25	9.84	53.09	74	-20.91	peak
7215.022	37.63	9.84	47.47	54	-6.53	AVG



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 2	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4880.005	45.87	7.12	52.99	74	-21.01	peak
4880.005	42.34	7.12	49.46	54	-4.54	AVG
7320.140	43.46	9.84	53.3	74	-20.7	peak
7320.140	37.39	9.84	47.23	54	-6.77	AVG

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 2	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4880.050	45.11	7.12	52.23	74	-21.77	peak
4880.050	39.74	7.12	46.86	54	-7.14	AVG
7320.080	44.03	9.84	53.87	74	-20.13	peak
7320.080	36.82	9.84	46.66	54	-7.34	AVG



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4960.012	46.68	7.12	53.8	74	-20.2	peak
4960.012	41.71	7.12	48.83	54	-5.17	AVG
7440.027	43.65	9.84	53.49	74	-20.51	peak
7440.027	37.58	9.84	47.42	54	-6.58	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Value Type
4960.013	44.35	7.12	51.47	74	-22.53	peak
4960.013	41.08	7.12	48.2	54	-5.8	AVG
7440.027	42.31	9.84	52.15	74	-21.85	peak
7440.027	38.62	9.84	48.46	54	-5.54	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

**RESULT: PASS****Note:**

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The "Factor" value can be calculated automatically by software of measurement system.



## TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

PK



AV



RESULT: PASS



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Vertical

PK



AV

**RESULT: PASS**



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 4	<b>Antenna</b>	Horizontal

PK



AV

**RESULT: PASS**



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 4	<b>Antenna</b>	Vertical

PK



AV

**RESULT: PASS**



<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Horizontal

PK



AV

**RESULT: PASS**

<b>EUT</b>	Electronic door lock V3	<b>Model Name</b>	V3-BTZBE
<b>Temperature</b>	25° C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 3	<b>Antenna</b>	Vertical

**PK**


**AV**


## RESULT: PASS

**Note:** The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB( $\mu$ V) to represent the Amplitude. Use the F dB( $\mu$ V/m) to represent the Field Strength. So A=F.

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### RADIATED EMISSION TEST SETUP BELOW 1GHZ




### RADIATED EMISSION TEST SETUP ABOVE 1GHZ






## APPENDIX B: PHOTOGRAPHS OF EUT

### TOP VIEW OF EUT




### BOTTOM VIEW OF EUT






FRONT VIEW OF EUT




BACK VIEW OF EUT






LEFT VIEW OF EUT




RIGHT VIEW OF EUT






OPEN VIEW OF EUT




OPEN VIEW OF EUT-2






INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2






INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4






INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6





INTERNAL VIEW OF EUT-7



----END OF REPORT----