

Report No.: SHEM200500380402

Page: 1 of 9

### **Cover Page**

### RF MPE REPORT

SHEM2005003804CR Application No.: FCC ID: 2ADTD-2DE2204IW IC: 20199-2DE2204IW

**Applicant:** Hangzhou Hikvision Digital Technology Co., Ltd

Address of Applicant: No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Hangzhou Hikvision Digital Technology Co., Ltd Manufacturer:

**Address of Manufacturer:** No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

1. Hangzhou Hikvision Technology Co., Ltd. Factory: 2. Hangzhou Hikvision Electronics Co., Ltd.

3. Chongqing Hikvision technology Co., Ltd. Address of Factory: 1.No.700,Dongliu Road,Binjiang District,Hangzhou Ctiy,Zhejiang,310052,China

2.No.299,Qiushi Road,Tonglu Economic Development Zone,Tonglu

County, Hangzhou, Zhejiang, 310052, China.

3. No. 118, Haikang Road, Area C, Jiangiao Industrial Park, Dadukou District,

Chongqing, 401325, China

**Equipment Under Test (EUT):** 

**EUT Name:** MINI PTZ CAMERA Model No.: DS-2DE2204IW-DE3/W

Add Model No.: Refer Page 2 Trade mark: **HIKVISION** 

FCC Rules 47 CFR §2.1091 Standard(s):

KDB447498 D01 General RF Exposure Guidance v06

RSS-102 Issue 5 (March 2015)

2020-05-25 **Date of Receipt:** 

2020-05-25 to 2020-06-04 Date of Test:

2020-06-10 Date of Issue:

Pass\* **Test Result:** 

Parlam Zhan

**E&E Section Manager** 

检验检测专用章 nspection & Testing Services

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction is suses defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sas.com

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612

t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com 中国・上海・松江区金都西路588号 邮编: 201612

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



# SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

Report No.: SHEM200500380402

Page: 2 of 9

For FCC Model No:DS-2DE2204IW-DE3/W,DS-2DE2402IW-DE3/W,DS-2DE2ABCDE-UVW/XYZ (The

"A","B" ,"C" ,"D" ,"E" ,"U" "V" "W" "X" "Y" and "Z" in the model name mean: A=0-9,A-Z or blank; B=0-9,A-Z or blank; C=0-9,A-Z or blank; C=0-9,A-Zblank; U= 0-9,A-Z or blank; V= 0-9,A-Z or blank; W= 0-9,A-Z or blank; X=0-9,A-Z or blank; Y=0-9,A-Z or blank; Z=0-9,A-Z or blank or "-" or "\*" or "/")

For IC Model No: DS-2DE2204IW-DE3/W, DS-2DE2402IW-DE3/W



Report No.: SHEM200500380402

Page: 3 of 9

Revision Record					
Version	Description	Date	Remark		
00	Original	2020-06-10	/		

Authorized for issue by:		
	Michael Nil	
	Micheal Niu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan / Reviewer	



Report No.: SHEM200500380402

Page: 4 of 9

#### 2 Contents

		Pa	age
1	COV	/ER PAGE	<b></b> 1
2	CON	NTENTS	4
3	GEN	IERAL INFORMATION	5
	3.1	GENERAL DESCRIPTION OF E.U.T.	5
	3.2	TECHNICAL SPECIFICATIONS	5
	3.3	TEST LOCATION	<i>6</i>
	3.4	TEST FACILITY	<i>6</i>
4	TES	T STANDARDS AND LIMITS	7
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	7
	4.2	IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	7
5	MEA	ASUREMENT AND CALCULATION	8
	5.1	MAXIMUM TRANSMIT POWER	8
	5.2	MPE CALCULATION	(



Report No.: SHEM200500380402

Page: 5 of 9

#### 3 General Information

#### 3.1 General Description of E.U.T.

Power supply:	DC 12V or PoE(802.3af,DC 36-57V) 0.35A		
Serial Number:	E09120063		
Firmware Version:	IPD_R7_EN_STD_5.6.15_200402		

### 3.2 Technical Specifications

Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK)		
	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)		
Number of Channels:	802.11b/g/n(HT20):11		
	802.11n(HT40):7		
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz		
	802.11n(HT40): 2422MHz to 2452MHz		
Antenna Gain:	1.28dBi		
Antenna Type:	Integral Antenna		
Channel Spacing:	5MHz		



Report No.: SHEM200500380402

Page: 6 of 9

#### 3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

#### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC (Designation Number: CN1172)

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

ISED (CAB identifier: CN0072)

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.

• VCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.



Report No.: SHEM200500380402

Page: 7 of 9

#### 4 Test Standards and Limits

#### 4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	

#### 4.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W



Report No.: SHEM200500380402

Page: 8 of 9

### 5 Measurement and Calculation

#### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200500380401

Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]
11B	2412	Ant1	16.69	46.67
11B	2437	Ant1	17.28	53.46
11B	2462	Ant1	17.57	57.15
11G	2412	Ant1	17.55	56.89
11G	2437	Ant1	17.98	62.81
11G	2462	Ant1	18.13	65.01
11N20SISO	2412	Ant1	16.20	41.69
11N20SISO	2437	Ant1	16.30	42.66
11N20SISO	2462	Ant1	16.41	43.75
11N40SISO	2422	Ant1	14.41	27.61
11N40SISO	2437	Ant1	14.45	27.86
11N40SISO	2452	Ant1	14.88	30.76



Report No.: SHEM200500380402

Page: 9 of 9

#### 5.2 MPE Calculation

For FCC:

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm<sup>2</sup>

The max. antenna gain is

1.28 dBi

Max. Conducted Power	Gain in Linear Scale	Operation Distance	Power Density	Limit (mW/cm <sup>2</sup> )	Result
P(mW)	G	R(cm)	(mW/cm <sup>2</sup> )	(11177701117)	
65.01	1.343	20	0.01737	1	Pass

For IC:

E.I.R.P.= P\*G= 0.06501×1.343=0.0873W < 2.68W

So the device is exclusion from SAR test.

-- End of the Report--